



ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR SINGLE SUPERHETERODYNE RECEIVER

Test report file number : E03OR-017

Applicant : OMRON AUTOMOTIVE ELECTRONICS KOREA CO., LTD.
Address : 481-2, Kasan-Dong, Kumchun-Ku, Seoul, 153-023, Korea

Manufacturer : OMRON AUTOMOTIVE ELECTRONICS KOREA CO., LTD.
Address : 481-2, Kasan-Dong, Kumchun-Ku, Seoul, 153-023, Korea

Type of Equipment : REMOTE CONTROL SECURITY RECEIVER

FCC ID : OSLOKA-620R

Model Name : OKA-620R

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 10 pages (including this page)

Date of Incoming : September 16, 2003

Date of Issuing : October 10, 2003

SUMMARY

The equipment complies with the requirements of FCC CFR 47 PART 15 SUBPART B, SECTION 15.101.

This test report contains only the results of a single test of the sample supplied for the examination. It is not a general valid assessment of the features of the respective products of the mass-production.

Prepared by: G. W. Lee
G. W. Lee/ Chief Engineer
EMC Div.
ONETECH Corp.

Reviewed by: Y. K. Kwon
Y. K. Kwon/ Director
EMC Div.
ONETECH Corp.



CONTENTS

	Page
1. VERIFICATION OF COMPLIANCE	3
2. GENERAL INFORMATION	4
2.1 PRODUCT DESCRIPTION	4
2.2 MODEL DIFFERENCES:	4
2.3 RELATED SUBMITTAL(S) / GRANT(S)	4
2.4 TEST SYSTEM DETAILS	5
2.5 TEST METHODOLOGY	5
2.6 TEST FACILITY	5
3. SYSTEM TEST CONFIGURATION	6
3.1 JUSTIFICATION	6
3.2 EUT EXERCISE SOFTWARE	6
3.3 EQUIPMENT MODIFICATIONS	6
3.4 CONFIGURATION OF TEST SYSTEM	6
4. PRELIMINARY TEST	7
4.1 AC POWER LINE CONDUCTED EMISSIONS TESTS	7
4.2 RADIATED EMISSIONS TESTS	7
5. FINAL RESULT OF MEASUREMENT	8
5.1 RADIATED EMISSION TEST	8
6. FIELD STRENGTH CALCULATION	9
7. LIST OF TEST EQUIPMENT	ERROR! BOOKMARK NOT DEFINED.



1. VERIFICATION OF COMPLIANCE

- APPLICANT : OMRON AUTOMOTIVE ELECTRONICS KOREA CO., LTD.
- ADDRESS : 481-2, Kasan-Dong, Kumchun-Ku, Seoul, 153-023, Korea
- CONTACT PERSON : Mr. Youngje, Seo / Section Manager
- TELEPHONE NO : 82-2-850-5743
- FCC ID : OSLOKA-620R
- MODEL NO/NAME : OKA-620R
- SERIAL NUMBER : N/A
- DATE : October 10, 2003

DEVICE TYPE	UNINTENTIONAL RADIATOR
E.U.T. DESCRIPTION	REMOTE CONTROL SECURITY RECEIVER - SINGLE SUPERHETERODYNE RECEIVER
THIS REPORT CONCERNS	ORIGINAL GRANT
MEASUREMENT PROCEDURES	ANSI C63.4/1992
TYPE OF EQUIPMENT TESTED	PRE-PRODUCTION
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	CERTIFICATION
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15, SECTION 15.101
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 METER OPEN AREA TEST SITE

The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.



2. GENERAL INFORMATION

2.1 Product Description

The OMRON AUTOMOTIVE ELECTRONICS KOREA CO., LTD., Model OKA-620R (referred to as the EUT in this report) is a receiver that is fixed inside the vehicle and receives the signal from the transmitter, Model: OKA-620T, FCC ID: OSLOKA-620T, which was manufactured by above applicant and then decide locking and unlocking the door and the alarm horn. The product specification described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE		Plastic
RECEIVING FREQUENCY		313.85 MHz
RF RECEIVER MODULE	TYPE	G8X-28RXIAM26 by Mitsumi Elec.
	LOCAL CLOCK FREQ.	313.85 MHz
	FREQUENCY GENERATION	Crystal Resonator
	MODULATION SCHEME	FM (Single Superheterodyne)
	CARRIER DETECT SENSITIVITY	11 dBuVemf
USED CPU		uPD789104AMC by NEC
LIST OF EACH OSC. OR CRY. FREQ. (FREQ.>=1MHz)		4.19 MHz on Main Board
OPERATING VOLTAGE/CURRENT		DC12V, 50mA from battery of vehicle
NUMBER OF LAYERS		2 Layers

2.2 Model Differences:

The difference(s) compared to the EUT is as follows: none

2.3 Related Submittal(s) / Grant(s)

Original submittal only



2.4 Test System Details

The EUT was tested with the following all equipment used in the tested systems are:

Model	Manufacturer	FCC ID	Description	Connected to
OKA-620R	OMRON AUTOMOTIVE ELECTRONICS KOREA CO., LTD.	OSLOKA-620R	RECEIVER	BATTERY
N/A	OMRON AUTOMOTIVE ELECTRONICS KOREA CO., LTD.	N/A	Door Unlock Check Unit with a battery	EUT
8657A	HP	N/A	Signal Generator	N/A

2.5 Test Methodology

Radiated testing was performed according to the procedures in ANSI C63.4/1992. Radiated testing was performed at a distance of 3 meters from EUT to the antenna.

2.6 Test Facility

The open area test site and conducted measurement facilities are located on at 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-080 Korea. Description details of test facilities were submitted to the Commission on January 18, 2002. (Registration Number: 92819)



3. SYSTEM TEST CONFIGURATION

3.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
MAIN BOARD	OMRON AUTOMOTIVE ELECTRONICS KOREA CO., LTD.	LD-CAR RECEIVER	N/A

3.2 EUT exercise Software

Set the signal generator to transmit at 313.85MHz and then the EUT receives the signal.

Used battery for the EUT was fully charged.

3.3 Equipment Modifications

- None

3.4 Configuration of Test System

Line Conducted Emission Test:

It is not need to test this requirement, because the power of the EUT supplies from a car battery.

Radiated Emission Test:

Preliminary radiated emissions tests were conducted using the procedure in ANSI C63.4/1992, 8.3.1.1 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meters open area test site.

Coherent Test:

During Radiated Emission Tests, H.P. signal generator model no: 8657A was used to radiate an frequency modulated signal to EUT at 313.85 MHz in order to cohere the individual components of the characteristic broadband emissions from EUT.

Antenna Power Conduction Test:

The antenna of this equipment was permanently installed on P.C.B. inside the EUT, so the radiated emission measurement was performed with the antenna installed.



4. PRELIMINARY TEST

4.1 AC Power line Conducted Emissions Tests

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
N/A	N/A
It is not need to test this requirement, because the power of the EUT is supplied from a car battery.	

4.2 Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated

Operation Mode	The Worse operating condition (Please check one only)
RX mode	X



5. FINAL RESULT OF MEASUREMENT

Preliminary test was done in normal operation mode. And the final measurement was selected for the maximized emission level

5.1 Radiated Emission Test

The following table shows the highest levels of radiated emission on both polarizations of horizontal and vertical.


Humidity Level : 49 % Temperature : 19 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART B, SECTION 15.109 (a)
 Type of Test : Unintentional Radiator
 Result : PASSED BY -15.69 dB at 823.83 MHz

EUT : REMOTE CONTROL SECURITY RECEIVER Date: October 02, 2003
 Operating Condition : RX mode
 Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)
 Frequency Range : 30 MHz ~ 2 GHz
 Distance : 3 Meter

Radiated Emission		Ant	Correction Factors		Total	FCC LIMIT	
Freq. (MHz)	Amp. (dBuV)	Pol.	Ant. (dBuV/m)	Cable (dB)	Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
353.07	9.20	H	14.78	0.67	24.65	46.02	-21.37
392.30	8.70	H	15.43	0.75	24.88	46.02	-21.14
470.76	7.80	H	16.56	0.77	25.13	46.02	-20.89
549.22	6.90	H	18.30	0.87	26.07	46.02	-19.95
627.68	9.10	H	19.43	0.95	29.48	46.02	-16.54
823.83	8.20	H	21.33	0.80	30.33	46.02	-15.69

There was not observed any emission from 1 GHz to 2GHz..

Radiated Emission Tabulated Data



Tested by: In-Sub, Youn / Test Engineer



6. FIELD STRENGTH CALCULATION

Meter readings are compared to the specification limit correcting for antenna and cable losses

+ Meter reading (dBuV)

+ Cable Loss (dB)

+ Antenna Factor (Loss) (dB/meter)

= Corrected Reading (dBuV/meter)

- Specification Limit (dBuV/meter)

= dB Relative to Spec (+/- dB)



7. LIST OF TEST EQUIPMENT

No.	EQUIPMENTS	MFR.	MODEL	SER. NO.	LAST CAL	DUE CAL	USE
1.	Test receiver	R/S	ESVS 10	827864/005	NOV/02	12MONTH	■
2.	Test receiver	R/S	ESHS 10	834467/007	APR/03	12MONTH	■
3.	Spectrum analyzer	HP	8564E	3650A00756	JUN/03	12MONTH	
4.	Spectrum analyzer	HP	8568B	3109A05456	MAY/03	12MONTH	■
5.	RF preselector	HP	85685A	3107A01264	MAY/03	12MONTH	■
6.	Quasi-Peak Adapter	HP	85650A	3107A01542	MAY/03	12MONTH	■
7.	TRILOG Broadband Antenna	Schwarzbeck	VULB9163	VULB9163 166	FEB/03	12MONTH	■
8.	Biconical antenna	EMCO	3104C	9109-4443	MAY/03	12MONTH	■
				9109-4444	JUL/03		
				91031852	AUG/02		
9.	Log Periodic antenna	EMCO	3146	9109-3213	AUG/02	12MONTH	■
				9109-3214	JUL/03		
				9109-3217	MAY/03		
		Schwarzbeck	9108-A(494)	62281001	AUG/02		
10.	LISN	EMCO	3825/2	9109-1867	AUG/03	12MONTH	
				9109-1869	OCT/02		
11.	Position Controller	EMCO	1090	9107-1038	N/A	N/A	■
12.	Turn Table	EMCO	1080-1.21	9109-1576	N/A	N/A	■
13.	Antenna Master	EMCO	1070-1	9109-1624	N/A	N/A	■