



Engineering analysis of a low power DSSS spread spectrum Transceiver,

**Equipment description: 2.4GHz WLAN USB device
Brand name: Intersil
Model number: ISL37300XU
FCC ID: OSZ37300XU**

According to requirements of :

FCC part 15.247 (b) (4),

FCC OET Bulletin 65 “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields “ and supplements A, B and C.

Date: October 18, 2001
Author: D.S. Sariredjo, Intersil Corp. The Netherlands
Rev: 1.0

Introduction

This engineering analysis was done according to FCC part 15.247 (b) (4) as part of the FCC certification requirements for spread spectrum devices.

The measured EIRP values for the lowest, middle and highest TX channel were used for the MPE calculations based on FCC OET Bulletin 65 and supplements A, B, and C. These calculations were done in worst case mode, assuming 100% reflection of incoming radiation, resulting in a potential doubling of predicted field strength and a four-fold increase in (far-field equivalent) power density (S).

$$S = \frac{EIRP}{4\pi R^2} \quad (\text{power density without reflection})$$

$$S = \frac{(2)^2 EIRP}{4\pi R^2} \quad (\text{worst case power density with 100\% reflection})$$

with R = 20 cm (8 inches)

Calculation results

Table 1 below shows the Power density (S) results for the lowest, middle and highest TX channel:

Measured EIRP (mW) Including antenna gain			Calculated worst case Power Density S (mW/cm ²)		
Ch 1	Ch 6	Ch 11	Ch 1	Ch 6	Ch 11
105.0	107.4	91.4	0.084	0.085	0.073

Table 1: Power density (S) calculations

Conclusion

Based on these calculations and using the limits of the general population / uncontrolled environment (which is 1.0 mW/cm² at 2.4 GHz), the Intersil low power spread spectrum transceiver does not exceed the MPE requirements set forth in documents above, with a minimum safe distance between antenna and operator of 20 centimeters (8 inches).

The equipment therefore fulfills the requirements on power density for general population / uncontrolled exposure and therefore complies with the requirements of FCC Part 15.247(b)(4) and FCC OET Bulletin 65 incl. supplements A, B, and C.