



TEST REPORT NUMBER: (8522)307-0201(C)

TEST REPORT

Applicant:	Jakks Pacific (HK) Ltd.	Fax:	---
		E-mail:	---
Address :	12/F., Wharf T&T Centre, 7 Canton Road. Tsim Sha Tsui Hongkong		
Test Date :	2022-11-14 to 2022-11-23		

Manufacturer or Supplier :	Jakks Pacific, Inc.
Address :	22619 PCH Malibu CA 90265 United States Of America (Excluding The States Of Alaska)
Sample Description:	Super Mario Rumble RC
Model number:	41822RX
Additional Model :	N/A
Rated Voltage:	DC9.0V (AA*6)
FCC ID :	OTA41822RX
IC :	7783A-41822RX

The submitted sample of the above equipment has been tested according to following standard(s)

47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

RSS-102 Issue 5 March 2015

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Assistant Manager

Name: Nick Lung

Date: NOV 30,2022



TEST REPORT NUMBER: (8522)307-0201(C)

1 Contents

	Page
TEST REPORT	1
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
3 SAR EVALUATION	4
3.1 IC RF EXPOSURE COMPLIANCE REQUIREMENT	4
3.1.1 <i>Standard Requirement</i>	4
3.1.2 <i>Limits</i>	4
3.1.3 <i>EUT RF Exposure</i>	6



TEST REPORT NUMBER: (8522)307-0201(C)

2 General Information

2.1 Client Information

Applicant:	Jakks Pacific (HK) Ltd.
Address of Applicant:	12/F., Wharf T&T Centre, 7 Canton Road. Tsim Sha Tsui Hongkong
Manufacturer:	Jakks Pacific, Inc.
Address of Manufacturer:	22619 PCH Malibu CA 90265 United States Of America (Excluding The States Of Alaska)
Factory:	Dongguan L C Technology Co.,Ltd
Address of Factory:	No. 408, Changhuang Road, Changping Town, Dongguan, Guangdong

2.2 General Description of EUT

Name:	Super Mario Rumble RC
Tset Model No.:	41822RX
Trade Mark :	N/A
Serial No :	--
Software Version:	0x5326_V05
Hardware Version:	H2121-RC
Frequency Range:	2420-2462MHz
Modulation Type:	GFSK
Number of Channels:	21
Sample Type:	Portable product
Antenna Type:	PCB antenna
Antenna Gain:	4dBi
Power Supply:	DC9.0V (AA*6)

Tested By: *Timo Le*

Reviewed By: *lewis zhou*

Date: November 23,2022



TEST REPORT NUMBER: (8522)307-0201(C)

3 SAR Evaluation

3.1 IC RF Exposure Compliance Requirement

3.1.1 Standard Requirement

IC: According to RSS-102 Issue 5 March 2015

2.5.1 Exemption Limits for Routine Evaluation – SAR Evaluation

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1.

FCC:

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

3.1.2 Limits

FCC:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

TEST REPORT NUMBER: (8522)307-0201(C)

IC:

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance^{4,5}

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤ 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤ 300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥ 50 mm
≤ 300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

Remakr: If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required.

TEST REPORT NUMBER: (8522)307-0201(C)

3.1.3 EUT RF Exposure

Measurement Data

IC:

$$e_{\text{irp}} = p_{\text{t}} \times g_{\text{t}} = (E \times d)^2 / 30$$

where:

p_{t} = transmitter output power in watts,

g_{t} = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, $10^{((\text{dB}\mu\text{V/m})/20)/10^6}$,

d = measurement distance in meters (m)---3m,

$$\text{So } p_{\text{t}} = (E \times d)^2 / 30 / g_{\text{t}}$$

The worst case refer to report (8522)307-0201(B) is below:

Antenna polarization: Horizontal		
Frequency (MHz)	Level (dB μ V/m)	Value
2.420	90.53	Peak

For 2420MHz:

Field strength = 90.53dB μ V/m @3m

Ant. gain 4dBi; so Ant numeric gain=2.512

$$\text{So } p_{\text{t}} = \{ [10^{(90.53/20)/10^6} \times 3]^2 / 30 / 2.512 \} \times 1000 \text{mW} = 0.1350 \text{mW}$$

$$0.1350 \text{mW} < 4.0 \text{mW}$$

So the SAR test is not required.



TEST REPORT NUMBER: (8522)307-0201(C)

FCC:

The worst case refer to report (8522)307-0201(B) is below:

Antenna polarization: Horizontal		
Frequency (MHz)	Level (dB μ V/m)	Value
2.420	90.53	Peak

For 2420MHz:

Field strength = 90.53dB μ V/m @3m

Ant. gain 4dBi; so Ant numeric gain=2.512

So $P_t = \{ [10^{(90.53/20)} / 10^6 \times 3]^2 / 30 / 2.512 \} \times 1000 \text{mW} = 0.1350 \text{mW}$

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g

Calculated value = $0.1350 / 5 \cdot \sqrt{2.420} = 0.04 < 3$

So the SAR test is not required.