



TEST REPORT

Report No. : AG029719-001 Date : 2007 January 05

Application No. : LG225584(4)

Client : Jakks Pacific (HK) Ltd.
Room 718, 7/F., AIA Tower,
New World Centre,
20 Salisbury Road, Tsim Sha Tsui East,
Kowloon, Hong Kong

Sample Description : One(1) submitted sample(s) stated to be Mini XPV
of Model No. 74000
Radio Frequency : 49.860MHz Receiver
Rating : 3.7V rechargeable battery
No. of submitted sample : Two (2) piece(s) ***

Date Received : 2006 November 13

Test Period : 2006 November 14 – 2006 November 16

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart B.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____
Danny Chui
Deputy Manager - EL. Division

FCC ID: OTARC74000R49

Page 1 of 11



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

Table of Contents

| | | |
|-----|---|----|
| 1 | General Information | 3 |
| 1.1 | General Description | 3 |
| 1.2 | Location of the test site | 4 |
| 1.3 | List of measuring equipment..... | 5 |
| 2 | Description of the radiated emission test | 6 |
| 2.1 | Test Procedure..... | 6 |
| 2.2 | Test Result..... | 6 |
| 2.3 | Radiated Emission Measurement Data | 7 |
| 3 | Description of the Line-conducted Test..... | 8 |
| 3.1 | Test Procedure..... | 8 |
| 3.2 | Test Result..... | 8 |
| 3.3 | Graph and Table of Conducted Emission Measurement Data | 8 |
| 4 | Photograph | 9 |
| 4.1 | Photographs of the Test Setup for Radiated Emission and Conduction Emission | 9 |
| 4.2 | Photographs of the External and Internal Configurations of the EUT..... | 9 |
| 5 | Supplementary document..... | 10 |
| 5.1 | Bandwidth | 10 |
| 5.2 | Duty cycle | 10 |
| 5.3 | Transmission time | 10 |
| 6 | Appendices..... | 11 |



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

1 General Information

1.1 General Description

The equipment under test (EUT) is a superregenerative receiver for Mini XPV. It operates at 49.860MHz which is controlled by a LRC circuit. The EUT is powered by a 3.7V rechargeable battery. When received a forward, turn left or turn right signal, it will fly to corresponding direction.

The brief circuit description is listed as follows:

- Q1 and associated circuit act as a RF demodulator.
- U1 and associated circuit act as a decoder.
- Q2, Q3 and associated circuit act as a voltage regulator.
- Q4, Q5 and associated circuit act as a motor driver for M1.
- Q6, Q7 and associated circuit act as a motor driver for M2.
- U2, U3, Q10 and associated circuit act as a charge protect circuit.



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

1.3 List of measuring equipment

| Equipment | Manufacturer | Model No. | Serial No. | Calibration Due Day |
|-------------------|--------------|-----------|------------|---------------------|
| EMI Test Receiver | R&S | ESCI | 100152 | 2007 September 30 |
| Broadband Antenna | Schaffner | CBL6112B | 2718 | 2008 May 24 |
| Signal Generator | IFR | 2023B | 202302/938 | 2006 December 28 |



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

2.2 Test Result

All other measurements are well below the limit. Thus, those highest emissions were presented in next page.

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

| Frequency (MHz) | Polarity (H/V) | Reading at 3m (dB μ V/m) | Antenna and Cable factor (dB) | Field Strength (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|-----------------|----------------|------------------------------|-------------------------------|-------------------------------|----------------------------|-------------|
| 48.681 | V | 13.6 | 10.6 | 24.2 | 40.0 | -15.8 |
| 49.061 | V | 15.1 | 10.6 | 25.7 | 40.0 | -14.3 |
| 49.465 | V | 16.5 | 10.6 | 27.1 | 40.0 | -12.9 |
| 50.253 | V | 18.2 | 8.4 | 26.6 | 40.0 | -13.4 |
| 50.645 | V | 14.0 | 8.4 | 22.4 | 40.0 | -17.6 |
| 52.639 | V | 12.4 | 8.4 | 20.8 | 40.0 | -19.2 |
| 98.282 | V | 9.8 | 9.5 | 19.3 | 43.5 | -24.2 |
| 100.161 | V | 8.4 | 11.1 | 19.5 | 43.5 | -24.0 |
| 148.851 | V | 9.3 | 12.0 | 21.3 | 43.5 | -22.2 |
| 150.041 | V | 8.5 | 12.0 | 20.5 | 43.5 | -23.0 |



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

| Document | Filename |
|-------------------------|-----------------|
| ID Label/Location | LabelSmp.jpg |
| Block Diagram | BlkDia.pdf |
| Schematic Diagram | Schem.pdf |
| Users Manual | UserMan.pdf |
| Operational Description | OpDes.pdf |

5.1 Bandwidth

N/A

5.2 Duty cycle

N/A

5.3 Transmission time

N/A



TEST REPORT

Report No. : AG029719-001

Date : 2007 January 05

6 Appendices

| | | | |
|-----|--|---|-------|
| A1. | Photos of the set-up of Radiated Emissions | 1 | page |
| A2. | Photos of External Configurations | 1 | page |
| A3. | Photos of Internal Configurations | 1 | page |
| A4. | ID Label/Location | 1 | page |
| A5. | Block Diagram | 1 | page |
| A6. | Schematics Diagram | 1 | page |
| A7. | User Manual | 2 | pages |
| A8. | Operation Description | 1 | page |

***** End of Report *****