

# Analysis Report

The Equipment Under Test (EUT), is a portable 27.14560MHz Transmitter (Controller Unit) for a RC car. The EUT is powered by 1 X 9.0V alkaline battery.

After switch on the EUT, model: 84011, 84331, the car will be moved forward or backward, turned left or right based on the joystick control in the controller.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

**Antenna Type: Dedicated antenna**

**Antenna Gain: 0dBi**

**Nominal rated field strength is 75.2 dB $\mu$ V/m at 3m**

**Maximum allowed production tolerance: +/- 3dB**

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 78.2dB $\mu$ V/m at 3m in frequency 27.146MHz, thus;

The EIRP =  $[(FS * D)^2 * 1000 / 30] = 0.02mW$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.02mW.

The SAR Exclusion Threshold Level:

=  $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 * 5 / \text{sqrt}(0.027) \text{ mW}$

= 91.3 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.