

廠商會檢定中心

TEST REPORT

Report No.	:	AY0031037(3)	Date:	14 Jun, 2019

Application No. : LY014803(5)

Client : Kidztech Toys Manufacturing Limited

Room 1201, 12/F., Inter-Continental Plaza, 94 Granville Road, Tsim Sha Tsui East,

Kowloon, Hong Kong

Sample Description : One(1) item of submitted sample stated to be:

Sample Description	Model number
1/6 R/C Yamaha Raptor 700R,	
1/6 RC Yamaha Raptor 700R,	84052, 5F633E3, 84056
1/6 RC Yamaha Raptor ATV	

Radio Frequency : 49.860MHz
Rating : 1 x 9V battery
No. of submitted sample : One (1) piece (s)
Sample registration No. : RY008983-001

Date Received : 17 May 2019

Test Period : 17 May 2019 – 31 May 2019

Test Requested : FCC 47CFR Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-18 Edition)

ANSI C63.10 - 2013

Test Result : See attached sheet(s) from page 2 to 16.

Conclusion : The submitted sample was found to comply with requirement of FCC 47CFR Part

15 Subpart C.

For and on behalf of

CMA Industrial Development Foundation Limited

Authorized Signature : _____ Page 1 of 16

Mr. WONG Lap-pong Andrew

Manager

FCC ID: OTM-8405219-49MTX

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatesting.org. This document shall not be reproduced except in full or with written approval by CMA Testing.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatesting.org Web Site: http://www.cmatesting.org



廠商會檢定中心

TEST REPORT

Report No. : AY0031037(3) Date : 14 Jun, 2019

Remark : Manufacturer declare that all **Three** models are the same cosmetics, materials, PCB

layout, electrical, mechanical, physical design, including software/firmware; therefore model <u>84052</u> was provided to be the representative of the test sample.

The difference between the tested sample and declared model(s) are non-

conductive outer casing only.

For and on behalf of CMA Industrial Development Foundation Limited

Authorized Signature : ______ Page 2 of 16

Mr. WONG Lap-pong Andrew

Manager

FCC ID: OTM-8405219-49MTX

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatesting.org. This document shall not be reproduced except in full or with written approval by CMA Testing.



廠商會檢定中心

TEST REPORT

Report No. : AY0029193(2) Date : May 31, 2019

Table of Contents

1		neral Information	4
	1.1	General Description	4
	1.2	Location of the test site	5
	1.3	List of measuring equipment	6
	1.4	Measurement Uncertainty	
	1.5	Test Summary	7
2	Des	cription of the radiated emission test	8
		Test Procedure	
	2.2	Test Setup	9
		Test Result	
	3.1	Test Procedure	13
	3.2	Test Result	13
	3.3	Test Setup	13
		Graph and Table of Conducted Emission Measurement Data	
4		plementary document	
	4.1	Bandwidth	
5	App	pendices	15

FCC ID: FCC ID: OTM-8405219-49MTX

Page 3 of 16



Report No. : AY0029193(2) Date : May 31, 2019

1 General Information

1.1 General Description

The equipment under test (EUT) model 84052 is a remote controlled toys. It operates at frequency band 49.86MHz for transmitter. The oscillation of radio control is generated by a 49.860MHz crystal (IC1) and modulated by encoder 977. The EUT is powered by one 9V battery. The EUT contains two control levers to control moving direction and a ON/OFF switch (K1).

The extendable antenna is used in EUT and the radio output power is unable to adjust.

Manufacturer declare that 84052, 5F633E3, 84056 are identical in cosmetics, material PCB layout, electrical, mechanical and physical design, including software/firmware and they are difference in non-conductive outer casing of receiver only.

Therefore, only model 84052 is selected for testing only.

The brief circuit description is listed as follows:

- SW1,SW2,SW3,SW4 and K1	and its associated circuit act as switch and control lever.
- IC1	and its associated circuit act as Encoder.
- TX1	and its associated circuit act as oscillation clock.
- Q1	and its associated circuit act as modulator.
- Q2	and its associated circuit act as RF amplifier.
- C6, C7, C8, T1, L3	and its associated circuit act as Filter and Antenna matching.
- ZD1	and its associated circuit act as Regulator circuit

FCC ID: FCC ID: OTM-8405219-49MTX

Page 4 of 16



Report No. : AY0029193(2) Date : May 31, 2019

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2014. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2014. A shielded room is located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

FCC Accredited Lab (Designation Number: HK0004) Conformity Assessment Body Identifier (CABID: HK0002)

FCC ID: FCC ID: OTM-8405219-49MTX

Page 5 of 16



廠商會檢定中心

TEST REPORT

Report No. AY0029193(2) Date: May 31, 2019

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EMI Test Receiver	Rohde & Schwarz	ESCI 100152		31 May 2020	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100964	11 Sep 2019	1Year
Loop Antenna	EMCO	6502	00056620	29 Oct 2020	2Years
Biconical Antenna	Rohde & Schwarz	HK116	837414/00	08 Oct 2020	2Years
Log Periodic Antenna	TESEQ	UPA6109	43666	08 Oct 2019	2Years
Coaxial Cable	Humber+Suhner	RG 213/U	N/A	08 May 2020	1Year
Coaxial Cable	Humber+Suhner	RG 214/U	N/A	08 May 2020	1Year

FCC ID: FCC ID: OTM-8405219-49MTX

Page 6 of 16



廠商會檢定中心

TEST REPORT

Report No. : AY0029193(2) Date : May 31, 2019

1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U _{lab})		
30MHz ~ 200MHz (Horizontal)	4.59dB		
30MHz ~ 200MHz (Vertical)	4.49dB		
200MHz ~1000MHz (Horizontal)	4.94dB		
200MHz ~1000MHz (Vertical)	4.97dB		
1GHz ~ 6GHz	4.52dB		

1.5 Test Summary

TEST ITEM	FCC REFERANCE	RESULT	
Fundamental emission	15.235(a)	Comply	
Out-band emission	15.235(b)	Comply	
Bandwidth	15.215(c)	Comply	

FCC ID: FCC ID: OTM-8405219-49MTX

Page 7 of 16



Report No. : AY0029193(2) Date : May 31, 2019

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.10 - 2013.

A non-conductive turntable with dimensions of 1.5m x 0.4m x 0.8m (L x W x H) placed above the reference ground plane. The equipment under test (EUT) was placed at 0.8m height for below 1GHz measurement and 1.5m height for above 1GHz measurement. The test distance is 3m between EUT and receiving antenna. A broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated. Additional absorbing material will be placed between the EUT and receiving antenna for above 1GHz measurement.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

FCC ID: FCC ID: OTM-8405219-49MTX

Page 8 of 16





廠商會檢定中心

TEST REPORT

Report No. : AY0029193(2) Date : May 31, 2019

2.2 Test Setup





30MHz - 1GHz

FCC ID: FCC ID: OTM-8405219-49MTX

Page 9 of 16




廠商會檢定中心

TEST REPORT

Report No. : AY0029193(2) Date : May 31, 2019

2.2 Test Setup



Above 1GHz

FCC ID: FCC ID: OTM-8405219-49MTX

Page 10 of 16



Report No. : AY0029193(2) Date : May 31, 2019

2.3 Test Result

Peak Detector data was measured unless otherwise stated.

The radiated emissions are measured from 9kHz to 500MHz (the tenth harmonics)

The worst case configuration is shown on the worst case configuration of test setup photo.

The frequencies from fundamental up to tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next pages.

The EUT has been tested in Transmission mode and antenna is fully extended.

It was found that the EUT meet the FCC requirement.

The Receiver (CAR) for this Transmitter (Remove) is under Supplier's Declaration of Conformity procedure.

FCC ID: FCC ID: OTM-8405219-49MTX

Page 11 of 16



廠商會檢定中心

TEST REPORT

Report No. : AY0029193(2) Date : May 31, 2019

2.4 Radiated Emission Measurement Data

Radiated emission

Environmental conditions:

Parameter	Recorded value		
Ambient temperature:	23.2	° C	
Relative humidity:	61.2	%	

Polarization	Frequency (MHz)	Reading at 3m (dBµV)	Antenn a Factor and Cable Loss (dB/m)	Field Strength at 3m (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)	Detector Type
Н	49.860	52.9	11.3	64.2	80.0	-15.8	PK
Н	49.860	62.0	11.3	73.3	80.0	-6.7	PK
V	99.695	12.9	10.2	23.1	43.5	-20.4	QP
Н	149.849	9.7	13.5	23.2	43.5	-20.3	QP
V	199.388	7.5	15.3	22.8	43.5	-20.7	QP
Н	249.307	11.8	14.5	26.3	46.0	-19.7	QP
Н	299.114	13.3	14.5	27.8	46.0	-18.2	QP
Н	349.090	13.0	16.9	29.9	46.0	-16.1	QP
Н	398.826	14.9	16.9	31.8	46.0	-14.2	QP
Н	488.736	11.2	20.9	32.1	46.0	-13.9	QP
Н	498.662	11.5	20.9	32.4	46.0	-13.6	QP

Remark: All other emission below the limit more than 20dB are not reported in this report.

FCC ID: FCC ID: OTM-8405219-49MTX

Page 12 of 16



廠商會檢定中心

TEST REPORT

Report No. : AY0029193(2) Date : May 31, 2019


- 3 Description of the Line-conducted Test
- 3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.10 - 2013. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Test Setup



3.4 Graph and Table of Conducted Emission Measurement Data

Not Applicable

FCC ID: FCC ID: OTM-8405219-49MTX

Page 13 of 16



Report No. : AY0029193(2) Date : May 31, 2019

4 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename		
ID Label/Location	Label Artwork and Location.pdf		
Block Diagram	Block Diagram.pdf		
Schematic Diagram	Schematic.pdf		
Users Manual	User Manual.pdf		
Operational Description	Operation Description.pdf		

4.1 Bandwidth

Appendices A1 is shown the fundamental emission is confined in the specified band. 20dB bandwidth is 18.171kHz and 20dB bandwidth are within the assigned band. It shows that the EUT meets the FCC Part 15.215(c).

And the in-band emission is more than 26dBc within the band 49.81 - 49.91MHz. It shows that the EUT meets the FCC Part 15.235(b).

FCC ID: FCC ID: OTM-8405219-49MTX

Page 14 of 16



Report No. : AY0029193(2) Date : May 31, 2019

5 Appendices

A1. Bandwidth Plot 1 page(s)

FCC ID: FCC ID: OTM-8405219-49MTX

Page 15 of 16




廠商會檢定中心

TEST REPORT

Report No. : AY0029193(2) Date : May 31, 2019

A1. Bandwidth Plot



***** End of Report *****

FCC ID: FCC ID: OTM-8405219-49MTX

Page 16 of 16