

# Appendix 5

## RF Exposure Information

FCC ID: OTM-8405822-24GTX

**Maximum transmitter power:**

Frequency (MHz)	Maximum peak output power (dBm)	Output power (mW)
2420	-13.23	0.0475
2442	-13.33	0.0465
2465	-10.23	0.0949

Note: The maximum peak field strength was taken from table of "Subclause 15.249(a) – Field Strength of Fundamental and Harmonics".

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

**Result:**

$$(0.0475/5) \cdot \sqrt{2420} = 0.015 < 3.0$$

$$(0.0465/5) \cdot \sqrt{2442} = 0.015 < 3.0$$

$$(0.0949/5) \cdot \sqrt{2465} = 0.030 < 3.0$$

**Conclusion:**

No SAR is required.