

Appendix 5

RF Exposure Information

FCC ID: OTM-8437122-24GTX

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBm)	Output power (mW)
2410	2.87	1.94
2442	1.47	1.40
2473	-0.23	0.95

Note: The maximum peak field strength was taken from table of "Subclause 15.249(a) – Field Strength of Fundamental and Harmonics".

For FCC

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Result:

$$(1.94/5) \cdot \sqrt{2410} = 0.602 < 3.0$$

$$(1.40/5) \cdot \sqrt{2442} = 0.438 < 3.0$$

$$(0.95/5) \cdot \sqrt{2473} = 0.314 < 3.0$$

Conclusion:

No SAR is required.