



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7) Date : July 20, 2018

Application No. : LW018586(7)

Applicant : Kidztech Toys Manufacturing Limited
Room 1201, 12/F., Inter-Continental Plaza,
94 Granville Road, Tsim Sha Tsui East,
Kowloon, Hong Kong

Sample Description : One(1) item of submitted sample stated to be:

Sample Description	Model No.
1/6 R/C Ducati Rider	84471, 844711824G

Radio Frequency : 2410 – 2475MHz

Rating : 2 x 1.5V AAA size batteries

No. of submitted sample : One (1) set (s)

Sample registration No. : RW019658-001(8)

Date Received : 22 Jun 2018.

Test Period : 25 Jun 2018 to 19 July 2018

Test Requested : FCC 47CFR Part 15 Certification
ISED Certification for License-exempt Device

Test Method : 47 CFR Part 15 (10-1-17 Edition)
ANSI C63.10 – 2013
ANSI C63.4 – 2014
RSS-210 Issue 9
RSS-Gen Issue 4

Test Result : See attached sheet(s) from page 2 to 20.

Conclusion : The submitted sample was found to comply with requirement of FCC 47CFR Part 15 Subpart C, section 15.249 and ISED Canada Radio Standard Specification.

Remark : Model: 844711824G is identical to model: 84471 and only difference in model number for Canada version and US version respectively. Model 84471 is selected as representative model for testing.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____ Page 1 of 20

Mr. WONG Lap-pong, Andrew
Manager
Electrical Division

FCC ID: OTM-8447118-24GTX
IC: 20978-844711824G



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
1.4	Measurement Uncertainty.....	6
1.5	Test Summary	6
2	Description of the radiated emission test	7
2.1	Test Procedure	7
2.2	Test Setup	8
2.3	Test Result	10
3.1	Test Procedure	14
3.2	Test Result	14
3.3	Test Setup	14
3.4	Graph and Table of Conducted Emission Measurement Data	14
4	Supplementary document.....	15
4.1	Bandwidth.....	15
5	Appendices.....	16



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

1 General Information

1.1 General Description

The 12MHz crystal oscillator drives the base of IC final amplifier. The modulation provided by IC U1. The output of U1 has the matching network consisting C2 and L1 that limit the harmonic content and effect the proper coupling of the antenna to the output stage. 0.0dBi wire antenna is used.

Antenna, Ground and Power Source:

The antenna consists of an Internal wired integral antenna. There is no external ground connection. The ground is only that of the printed circuit board. Electric current is supplied by two 1.5V AAA primary batteries.

Operation Descriptions:

The Equipment Under Test (EUT) is a portable 2.4GHz Pure Transmitter (Receiver function is disable), The transmitter is a remote-control system. The transmission signal is frequency hopping with channel frequency range 2410.0.-2475.0MHz during normal use with channel spacing 1MHz, and total 66 channels. The EUT was set to fixed frequency test mode by application. The EUT is powered by two 1.5V AAA batteries, After switching on the EUT, the car can be controlled to move forward, backward, turning left/right direction.

The transmitter has one control wheel and one control lever to control the left and right turn and forward and backward movement respectively. The EUT continues to transmit while Power on. Modulation by IC with GFSK (FHSS - Frequency Hopping Spread Spectrum) modulation.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2014. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2014. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC Accredited Lab (Designation Number: HK0004)
ISED Wireless Test Site (ISED Assigned Code: 4093A)



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EMI Test Receiver	Rohde & Schwarz	ESCS30	100001	01 Feb 2019	1Year
EMI Test Receiver	Rohde & Schwarz	ESCI	100152	07 Dec 2018	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100964	08 Feb 2019	1Year
Broadband Antenna	Schaffner	CBL6112B	2692	28 Mar 2020	2Years
Loop Antenna	EMCO	6502	00056620	25 Jan 2020	2Years
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-531	21 Dec 2018	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9718	9718-119	21 Dec 2018	2Years
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170442	02 Aug 2018	2Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9719	9719-010	02 Aug 2018	2Years
Coaxial Cable	Schaffner	RG 213/U	N/A	17 May 2019	1Year
Coaxial Cable	Suhner	RG 214/U	N/A	17 May 2019	1Year
Coaxial Cable	Suhner	Sucoflex_104	N/A	21 Dec 2018	1Year
LISN	Rohde & Schwarz	ENV216	101323	16 Jan 2019	1Year
Coaxial Cable	Tyco Electronics	RG 58C/U	N/A	24 Oct 2018	1Year



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U_{lab})
30MHz ~ 200MHz (Horizontal)	4.59dB
30MHz ~ 200MHz (Vertical)	4.49dB
200MHz ~1000MHz (Horizontal)	4.94dB
200MHz ~1000MHz (Vertical)	4.97dB
1GHz ~ 6GHz	4.52dB

1.5 Test Summary

TEST ITEM	FCC REFERANCE	RSS REFERENCE	RESULT
Fundamental and harmonic emission	15.249(a)	RSS-210, Annex B.10(a)	Comply
Out-band emission	15.249(d)	RSS-210, Annex B.10(6)	Comply
Peak Limit	15.249(e)	RSS-Gen, 8.1	Comply
Bandwidth	15.215(c)	RSS-Gen, 6.7	Comply



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.10 – 2013.

A non-conductive turntable with dimensions of 1.5m x 0.4m x 0.8m (L x W x H) placed above the reference ground plane. The equipment under test (EUT) was placed at 0.8m height for below 1GHz measurement and 1.5m height for above 1GHz measurement. The test distance is 3m between EUT and receiving antenna. A broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated. Additional absorbing material will be placed between the EUT and receiving antenna for above 1GHz measurement.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AW0041256(7)

Date : July 20, 2018

2.2 Test Setup



Below 30MHz



30MHz – 1GHz



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

2.2 Test Setup



Above 1GHz



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

2.3 Test Result

Peak Detector data was measured unless otherwise stated.

The radiated emissions are measured from 9kHz to 26GHz (the tenth harmonics)

The worst case configuration is shown on the worst case configuration of test setup photo.

The frequencies from fundamental up to tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next pages.

The EUT has been tested in Transmission mode.

It was found that the EUT meet the FCC and RSS requirement.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

2.4 Radiated Emission Measurement Data

Radiated emission

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	23.2	° C
Relative humidity:	65.7	%

Channel: 2410MHz

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector Type
V	2410.232	99.1	-4.7	94.4	114.0	-19.6	Peak
V	2409.910	80.0	-4.7	75.3	94.0	-18.7	Average
H	2410.296	101.3	-4.7	96.6	114.0	-17.4	Peak
H	2409.910	82.2	-4.7	77.5	94.0	-16.5	Average
H	2400.000	59.2	-4.7	54.5	74.0	-19.5	Peak
H	2400.000	26.2	-4.7	21.5	54.0	-32.5	Average
V	4819.450	52.6	2.3	54.9	74.0	-19.1	Peak
V	4820.130	26.9	2.3	29.2	54.0	-24.8	Average
V	7230.770	49.7	9.6	59.3	74.0	-14.7	Peak
V	7230.090	23.9	9.6	33.5	54.0	-20.5	Average

Remark:



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

Channel: 2440 MHz

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector Type
V	2440.758	99.5	-4.7	94.8	114.0	-19.2	Peak
V	2440.090	80.4	-4.7	75.7	94.0	-18.3	Average
H	2439.702	100.7	-4.7	96.0	114.0	-18.0	Peak
H	2440.020	81.6	-4.7	76.9	94.0	-17.1	Average
V	4879.440	52.2	2.3	54.5	74.0	-19.5	Peak
V	4879.840	26.2	2.3	28.5	54.0	-25.5	Average
V	7320.770	51.6	9.6	61.2	74.0	-12.8	Peak
V	7319.310	24.6	9.6	34.2	54.0	-19.8	Average

Remark:



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

Channel: 2475MHz

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector Type
V	2475.344	100.4	-4.7	95.7	114.0	-18.3	Peak
V	2475.090	81.3	-4.7	76.6	94.0	-17.4	Average
H	2475.278	100.0	-4.7	95.3	114.0	-18.7	Peak
H	2475.760	80.9	-4.7	76.2	94.0	-17.8	Average
V	2483.500	53.2	-4.7	48.5	54.0	-5.5	Peak
V	4950.530	53.4	2.8	56.2	74.0	-17.8	Peak
V	4950.050	26.4	2.8	29.2	54.0	-24.8	Average
V	7425.810	52.5	9.6	62.1	74.0	-11.9	Peak
V	7424.770	25.0	9.6	34.6	54.0	-19.4	Average

Remark: 1) The peak value of emission 2483.5MHz is below the average limit, so no average measurement is performed.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

3 Description of the Line-conducted Test


3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.10 – 2013. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Test Setup



3.4 Graph and Table of Conducted Emission Measurement Data

Not Applicable



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

4 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	Label Artwork and Location.pdf
Block Diagram	Block Diagram.pdf
Schematic Diagram	Schematic.pdf
Users Manual	User Manual.pdf
Operational Description	Operation Description.pdf

4.1 Bandwidth

Appendices A1 and A2 show the fundamental emission is confined in the specified band. 20dB bandwidth is 5.32MHz and 99% bandwidth is 5.12MHz. Both bandwidth fall in the band of 2400 – 2483.5MHz. It also shows that the EUT met the requirement of FCC Part 15.215(c) and RSS-GEN.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

5 Appendices

A1.	20dB Bandwidth Plot	2	page(s)
A2.	99% Bandwidth Plot	2	Page(s)



CMA Testing and Certification Laboratories



廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018

A1. 20dB Bandwidth Plot






CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018



Channel: 2475MHz



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AW0041256(7)

Date : July 20, 2018

A2. 99% Bandwidth Plot



Channel: 2410MHz



Channel: 2440MHz




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AW0041256(7)

Date : July 20, 2018



Channel: 2475MHz

***** End of Report *****