

# Analysis Report

The Equipment Under Test (EUT) is a transmitter of a RC system, which is operating at 27.145MHz as dictated by a crystal. The EUT is powered by 1 x 3V size AA battery. The EUT has a power ON/OFF switch and control key.

After switching ON the EUT and the corresponding car(ie. Receiver), activating the control key on the EUT can control the car moving forward, backward, left and right.

Antenna Type: Integral, external  
Nominal field strength is 63.3dB $\mu$ V/m @ 3m  
Production Tolerance of field strength is 60.3 dB $\mu$ V/m to 66.3 dB $\mu$ V/m  
Antenna gain is 0dBi

Based on the Maximum allowed field strength of production tolerance was 66.3dB $\mu$ V/m at 3m in frequency 27.145MHz, thus;

The EIRP =  $[(FS \cdot D)^2 \cdot 1000 / 30] = 0.00128\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain  
So;

Conducted Power = 0.00128mW

The SAR Exclusion Threshold Level for 27.145MHz when the minimum test separation distance is < 50mm:  
=  $[474 \cdot (1 + \log_{10}(100/f(\text{MHz})))]/2$   
= 371.2mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.