

# Analysis Report

The Equipment Under Test (EUT) is a transmitter of a RC system, which is operating at 49.860MHz as dictated by a crystal. The EUT is powered by 3 x “AAA” size batteries. The EUT has control keys.

After switching ON the EUT and the corresponding car(ie. Receiver), activating the control key on the EUT can control the car moving forward, backward, left and right.

Antenna Type: Integral, external

Nominal field strength is 70.1dB $\mu$ V/m @ 3m

Production Tolerance of field strength is 67.1 dB $\mu$ V/m to 73.1 dB $\mu$ V/m

Antenna gain is 0dBi

Based on the Maximum allowed field strength of production tolerance was 73.1dB $\mu$ V/m at 3m in frequency 49MHz, thus;

The EIRP =  $[(FS \cdot D)^2 \cdot 1000 / 30] = 0.00613\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.00613mW

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

=  $[474 * (1 + \log_{10}(f(\text{MHz})))]/2$

= 308.6mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.