

# Analysis Report

Report No.: 15050510HKG-001

The Equipment Under Test (EUT) is a portable transmitter of a RC Car operating at 49.86 MHz as dictated by a crystal. The EUT is powered by a 9.0 V DC source (1 x 9.0V battery). The EUT has a left / right joystick and a forward / backward joystick.

After switching ON the EUT and the receiver of the RC Car, activating the joysticks on the EUT can control the receiver moving forward, backward left and right directions.

Antenna Type: External, telescope antenna with unique antenna connector

Antenna Gain: 0dBi

Nominal rated field strength: 68.5dB $\mu$ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 71.5dB $\mu$ V/m at 3m in frequency 49.860MHz, thus;

The EIRP =  $[(FS \cdot D)^2 \cdot 1000 / 30] = 0.00424\text{mW}$

Thus;

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.00424mW.

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

=  $[474 * (1 + \log_{10}(100/f(\text{MHz})))]/2$

= 308.6mW

Since the above conducted output power is well below the SAR Exclusion Threshold level, so the EUT is considered to comply with SAR requirement without testing.