

Analysis Report

Report No.: 16060572HKG-001

The Equipment Under Test (EUT) is a portable 2.4GHz Transmitter (Controller Unit) for a RC car operating at the frequency range of 2405-2475MHz with 1 MHz channel spacing.

The EUT is powered by 9V battery. After switch on the EUT and paired with car, the car can be controlled to move forward/backward and turn left/ right by the controller.

Antenna Type: Internal integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 90.8dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 93.8 dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = [(FS*D) ^2*1000 / 30] = 0.72mW

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.72mW.

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.475) mW

= 9.53 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.