

## Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transmitter (Controller Unit) for a RC Car. The sample supplied operated on 68 channels, normally at 2408 - 2475MHz. The channels are separated with 1MHz spacing.

The EUT is powered by 2 x 1.5V AA batteries. After switching on the EUT, the car will be moved forward or backward and turned left and right based on the switches pressed in the controller.

Antenna Type: Internal, Integral antenna  
Antenna Gain: 0dBi  
Nominal rated field strength is 95.5dB $\mu$ V/m at 3m  
Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the maximum average field strength of production tolerance was 98.5dB $\mu$ V/m at 3m in frequency 2.475GHz.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

The worst case of SAR Exclusion Threshold Level:  
=  $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$   
=  $3.0 * 5 / \text{sqrt}(2.483.5) \text{ mW}$   
= 9.52 mW

According to the KDB 412172 D01:  
EIRP =  $[(\text{FS} * \text{D}) ^2 * 1000 / 30]$

Calculated Field Strength for 9.52mW is 105dBuV/m @3m

Since maximum average field strength plus production tolerance  $\leq$  105dBuV/m @3m and antenna gain is  $\geq$  0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.