



International Electrical Certification Centre Ltd.

Address: Units 303-305, 3/F., 31 Lok Yip Road, On Lok Tsuen, Fanling, N.T., Hong Kong
Telephone: +852 23052570
Fax: +852 27564480
Email: info@iecc.com.hk

Report No.: 57737
Page: 1 of 19

FCC Test Report

Application No.: 57737

Applicant: KIDZTECH TOYS MANUFACTURING LTD

Address: Room 1201, Inter-Continental Plaza
94 Granville Road, Tsim Sha Tsui East, Kowloon
Hong Kong

Product Information:

Product Description: R/C Car

Model: 83021, 83031, 83041, 83051, 83061, 83071, 83081, 83901 ♣

♣

Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

Product Class : Low Power Communication Device – Transmitter (27 MHz)

FCC ID number: OTM83023456827

Requirement: CFR 47 FCC PART 15 SUBPART C, 2011
- Intentional Radiators.

Date of Receipt: July 12, 2012

Date of Test: July 18, 2012 to July 20, 2012

Date of Issue: August 10, 2012

| | |
|----------------------|--------------|
| Test Result : | PASS* |
|----------------------|--------------|

* In the configuration tested, the EUT complied with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.

Authorized Signature:

Stephen C.N. Wong
Technical Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of International Electrical Certification Centre Ltd. or testing done by International Electrical Certification Centre Ltd. in connection with, distribution or use of the product described in this report must be approved by International Electrical Certification Centre Ltd. in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Test Summary

| Test | Test Requirement | Test Method | Class / Severity | Result |
|---|---------------------------------|-----------------|------------------|-------------------|
| Conducted Emission (150KHz to 30MHz) | FCC PART 15, SUBPART C: 2011 | ANSI C63.4:2009 | Class B | N/A ¹⁾ |
| Radiated Emission below 30MHz | FCC PART 15, SUBPART C: 2011 | ANSI C63.4:2009 | Class B | PASS |
| Radiated Emission (30MHz to 1GHz) | FCC PART 15, SUBPART C: 2011 | ANSI C63.4:2009 | Class B | PASS |
| Radiated Emission above 1 GHz | FCC PART 15, SUBPART B: 2011 | ANSI C63.4:2009 | Class B | N/A ¹⁾ |

Remark :

1) Please refer to section 6.1 & 6.4 of this report for explanation

♣ **Item no.:** 83021, 83031, 83041, 83051, 83061, 83071, 83081, 83901

According to the confirmation from the applicant, the above models are identical in all electrical aspects in relating to the circuit design, PCB layout, electrical components used, internal wiring and function. The differences are only the color and model name.

The models are also stated to be identical to model 8004 which was tested and complied with CFR47 FCC PART 15 SUBPART C for Intentional Radiators. The results in this report are transferred from the test report 57557 issued on July 24, 2012 for model 8004.

3 Contents

| | Page |
|--|-----------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 2 |
| 3 CONTENTS | 3 |
| 4 GENERAL INFORMATION..... | 4 |
| 4.1 GENERAL DESCRIPTION OF EUT | 4 |
| 4.2 DETAILS OF EUT | 4 |
| 4.3 CONDITIONS OF EUT | 4 |
| 4.4 DESCRIPTION OF SUPPORT UNITS | 4 |
| 4.5 STANDARDS APPLICABLE FOR TESTING | 4 |
| 4.6 TEST LOCATION..... | 4 |
| 4.7 TEST FACILITY..... | 4 |
| 4.8 DEVIATION FROM STANDARDS | 5 |
| 4.9 ABNORMALITIES FROM STANDARD CONDITIONS..... | 5 |
| 4.10 DECLARATION OF FAMILY GROUPING | 5 |
| 4.11 ABBREVIATIONS..... | 5 |
| 5 EQUIPMENTS USED DURING TEST | 6 |
| 6 TEST RESULTS..... | 7 |
| 6.1 CONDUCTED EMISSIONS MAINS TERMINALS, 150kHz TO 30MHz | 7 |
| 6.2 RADIATED EMISSIONS BELOW 30MHz | 7 |
| 6.2.1 EUT Operation..... | 8 |
| 6.2.2 Test Setup and Procedure..... | 8 |
| 6.2.3 Measurement Data | 9 |
| 6.3 RADIATED EMISSIONS, 30MHz TO 1GHz..... | 13 |
| 6.3.1 EUT Operation..... | 13 |
| 6.3.2 Test Setup and Procedure..... | 14 |
| 6.3.3 Measurement Data | 15 |
| 6.4 RADIATED EMISSIONS ABOVE 1 GHz | 16 |
| 7 PHOTOGRAPHS..... | 17 |
| 7.1 RADIATED EMISSION TEST SETUP | 17 |
| 7.2 EUT CONSTRUCTIONAL DETAILS..... | 18 |

4 General Information

4.1 General Description of EUT

EUT Name: R/C Car
Model: 83021, 83031, 83041, 83051, 83061, 83071, 83081, 83901
Serial No.: --

4.2 Details of EUT

Power Supply: DC 6V (AA battery x4)
Power Cord: --
Antenna Length 36 cm (fully extended)

4.3 Conditions of EUT

The received sample was under good condition.

4.4 Description of Support Units

The EUT has been tested as an independent unit.

4.5 Standards Applicable for Testing

CFR 47, FCC Part 15, Oct 2011
ANSI C63.4:2009

4.6 Test Location

All tests were performed at: -

International Electrical Certification Centre Ltd. (wholly owned by SGS Group)
Units 303-305, 3/F., 31 Lok Yip Road, On Lok Tsuen, Fanling, N.T., Hong Kong
Tel: +852 2305 2570 Fax: +852 2756 4480.

No tests were sub-contracted.

4.7 Test Facility

Measurement facility located at Fanling (Hong Kong), placed on file with the FCC Pursuant to Section 2.948 of the FCC Rules (**FCC Registration No. : 97774**).

The test facility is recognized, certified, or accredited by the following organizations:

FCC – CAB Registration No.: 446297

Measurement facility located at Fanling (Hong Kong), accredited as a Conformity Assessment Body (CAB) and was designated by FCC to perform compliance testing on equipment subject to Declaration Of Conformity (DOC) and Certification under Part 15 and 18 of the Commission's Rules.

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

4.10 Declaration of Family Grouping

None.

4.11 Abbreviations

N/A: Not Applicable

EUT: Equipment Under Test

5 Equipments Used during Test

| Radiated Emission | | | | |
|-------------------------------------|-----------------|---------------------|------------|---------------|
| Equipment | Manufacturer | Model / Serial No. | Cal. Date | Cal. Due Date |
| 3m Semi-Anechoic Chamber (pre-test) | -- | -- | -- | -- |
| 3m / 10m Open Area Test Site | -- | -- | 2012-02-24 | 2015-02-23 |
| Test Receiver | Rohde & Schwarz | ESCS 30 / 100388 | 2011-12-28 | 2012-12-27 |
| Spectrum Analyzer | Advantest | R3132 / 140101852 | 2011-08-09 | 2012-08-08 |
| Antenna (30-1000 MHz) | Schaffner | CBL6111C / 2791 | 2010-09-30 | 2012-09-29 |
| Loop Antenna | Rohde & Schwarz | HFH2-Z2 / 871336/48 | 2009-11-17 | 2012-11-16 |
| Coaxial Cable | -- | E167 | 2011-08-15 | 2012-08-14 |
| Antenna Mast System | Schwarzbeck | AM9104 / - | -- | -- |
| Turntable with Controller | Drehtisch | DT312 / - | -- | -- |

| General Use Equipment | | | | |
|------------------------------|--------------|--------------------|------------|---------------|
| Equipment | Manufacturer | Model / Serial No. | Cal. Date | Cal. Due Date |
| Digital Multimeter | Fluke | 189 / 83640020 | 2012-05-17 | 2013-05-16 |
| Temperature / Humidity meter | - | E160 | 2011-10-11 | 2012-10-10 |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

6 Test Results

6.1 Conducted Emissions Mains Terminals, 150kHz to 30MHz

Test Requirement: FCC Part15 B

Test Method: ANSI C63.4

Test Date: Not Applicable

Remark:

The product is battery operated and this test is not applicable.

6.2 Radiated Emissions below 30MHz

Test Requirement: FCC Part15 Subpart C Section 15.227 and 15.209

Test Method: ANSI C63.4

Test Date: July 19, 2012

Frequency Range: 9kHz to 30MHz

Measurement Distance: 3 m

Detector: Peak for pre-scan

(200Hz resolution bandwidth for measurement between 9kHz – 150kHz)

(9kHz resolution bandwidth for measurement between 150kHz – 30MHz)

Peak for final measurement within the operation band

Quasi-Peak for final measurement outside the operation band

Limits :

(a) Measurement within operation band :

Average detector : 10000µV/m (or 80 dB(µV/m)) at 3 m

Peak detector : 100 dB(µV/m) at 3m

(b) Measurement outside operation band :

| Frequency range (MHz) | Field strength limits (µV/m) | Measurement distance (m) |
|--|---------------------------------|-----------------------------|
| 0.009 to 0.490 | 2400/F(kHz) | 300 |
| 0.490 to 1.705 | 24000/F(kHz) | 30 |
| 1.705 to 30.0 | 30 | 30 |
| Note: At transitional frequencies the lower limit applies. | | |

6.2.1 EUT Operation

Operating Environment:

Temperature: 25°C

Humidity: 62%

Atmospheric Pressure: 1005mbar


EUT Operation: Pre-test with Peak detector with the following mode(s):

1. Control for different directions / speed up

Final test with Peak detector with the following mode(s):

1. Control for moving forward

6.2.2 Test Setup and Procedure



1. The pre-test of the radiated emissions test was conducted in a semi-anechoic chamber and the final measurement was conducted in the open area test site.
2. The EUT was operated with new batteries. The EUT was placed upon a non-metallic table 0.8m above the floor.
3. A loop antenna for the frequency range 9kHz - 30MHz, connected with 10 meters coaxial cable to the test receiver was used for measurement. The center of the loop was 1 m above the floor, positioned with its plane vertical at the specified distance and rotated about its vertical axis and placed horizontal for maximum response at each azimuth about the EUT.

4. An initial pre-scan was performed to find out the maximum emission level of the sample placed at 3 orthogonal planes and with the turntable rotated 360°. Final measurement was then performed to record the data for fundamental emission within the operation band and spurious emissions outside the band under worst-case condition for combination of the antenna orientation and turntable position.
5. Emission at the fundamental frequency for this pulse modulated device was measured with the peak detector function of the test receiver and was properly adjusted for the duty cycle correction factor as pulse desensitization to calculate the average emission value.

6.2.3 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. The EUT was measured by loop antenna with 3 orthogonal polarities. Final measurement was conducted in the open area test site with data as follows:

(a) Measurement within operation band :

| Frequency (MHz) | Antenna Polarity | Test Results (dBμV/m) | | FCC Limit (dBμV/m) | |
|-----------------|------------------|-----------------------|-----------|--------------------|---------|
| | | Peak | Average * | Peak | Average |
| 27.145 | Horizontal | 54.0 | 49.6 | 100 | 80 |
| | Vertical | 80.5 | 76.1 | 100 | 80 |

Note : (1) The above peak value is the maximum value of the measurement in the 3 orthogonal planes

(2) * Calculation for radiation (average) :

Formula :

$$\text{Duty cycle} = (N1L1 + N2L2 + \dots + Nn-1Ln-1 + NnLn) / 100 \text{ or } T$$

where

N1 is the number of type 1 pulse, L1 is length of type 1 pulse, etc.

T is the period of the pulse train (if less than 100ms)

According to the time domain plots shown on the next two pages :

$$\text{Duty cycle of the EUT} = (4 \times 1.67 + 10 \times 0.55) / 20.28 = 0.60$$

$$\text{Av correction factor} = 20 \times \log(0.60) \text{ dB}$$

$$= -4.44 \text{ dB}$$

$$\text{Radiation (average)} = \text{Radiation (peak)} + \text{Av correction factor}$$


$$\text{Radiation (average) of the EUT} = 54.0 - 4.44 \text{ dB}(\mu\text{V/m}) = 49.6 \text{ dB}(\mu\text{V/m}) \quad (\text{Horizontal ant.})$$

$$= 80.5 - 4.44 \text{ dB}(\mu\text{V/m}) = 76.1 \text{ dB}(\mu\text{V/m}) \quad (\text{Vertical ant.})$$

(b) Measurement outside operation band :


The spurious radiated emissions measured by the loop antenna was negligible (more than 20dB below limit).

Time Domain Plots (Fundamental frequency of Transmitter) :




Pulse cycle period = 20.28 ms

Time Domain Plots (Fundamental frequency of Transmitter) :



Pulse width = 1.67 ms (total no. of pulse : 4)




Pulse width = 0.55 ms (total no. of pulse : 10)

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Band Edges Plot :



The field strength of any emission within the operation band did not exceed 80 dB(μV/m) for average value or 100 dB(μV/m) for peak value.

6.3 Radiated Emissions, 30MHz to1GHz

Test Requirement: FCC Part15 Subpart C Section 15.209
Test Method: ANSI C63.4
Test Date: July 19, 2012
Frequency Range: 30MHz to 1GHz
Measurement Distance: 3m
Detector: Peak for pre-scan (120kHz resolution bandwidth)
Quasi-Peak if maximised peak within 6dB of limit
Class: Class B

| Frequency range MHz | Quasi-peak limits dB (µV/m) |
|--|--------------------------------|
| 30 to 88 | 40 |
| 88 to 216 | 43.5 |
| 216 to 960 | 46 |
| Above 960 | 54 |
| Note: At transitional frequencies the lower limit applies. | |

6.3.1 EUT Operation

Operating Environment:

Temperature: 25°C

Humidity: 62%

Atmospheric Pressure: 1005mbar


EUT Operation: Pre-test with Peak detector with the following mode(s):

1. Control for different directions / speed up
2. Charging the car (receiver)

Final test with Peak detector with the following mode(s):

1. Control for moving forward

6.3.2 Test Setup and Procedure



1. The pre-test of the radiated emissions test was conducted in a semi-anechoic chamber and the final measurement was conducted in the open area test site.
2. The EUT was operated with new batteries. The EUT was placed upon a non-metallic table 0.8m above the ground reference plane.
3. Bilog antenna was used for the frequency range from 30MHz to 1GHz
4. Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emissions spectrum plots of the EUT with located frequencies.
5. The actual frequencies of maximum emission were confirmed in the final radiated emissions measurement. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.

6.3.3 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. The EUT was measured by Bilog antenna with 2 orthogonal polarities and frequencies of peak emissions from the EUT were detected within 6dB of the limit line. Final measurement was conducted in the open area test site with data as follows:

Test results on operation with Control for Moving Forward mode :

| Frequency (MHz) | Antenna Polarization | Correction Factor (dB/m) | Receiver QP Reading (dBμV) | Emission Level (dBμV/m) | Limit (dBμV/m) | Over Limit (dB) |
|-----------------|----------------------|--------------------------|----------------------------|-------------------------|----------------|-----------------|
| 54.29 | V | 8.7 | 30.7 | 39.4 | 40.0 | -0.6 |
| 162.87 | H | 12.8 | 22.0 | 34.8 | 43.5 | -8.7 |
| 190.00 | H | 11.2 | 27.3 | 38.5 | 43.5 | -5.0 |
| 217.18 | H | 11.5 | 32.0 | 43.5 | 46.0 | -2.5 |
| 244.31 | H | 14.2 | 30.2 | 44.4 | 46.0 | -1.6 |
| 271.50 | H | 15.9 | 28.8 | 44.7 | 46.0 | -1.3 |

Note:

- 1) All readings are Quasi-Peak values.
- 2) Correction Factor = Antenna Factor + Cable Loss.
- 3) The above results were the worst case results with the EUT positioned in all 3 axis during the test. The EUT was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively and with its antenna fully extended.

6.4 Radiated Emissions above 1 GHz

Test Requirement: FCC Part15
Test Method: ANSI C63.4
Test Date: Not Applicable

Remark:

There is no need for Radiated Emissions (above 1G) test to be performed on this product in accordance with FCC Part 15: 2011 because the tenth harmonic of the highest fundamental frequency is less than 1 GHz.


For further details, please refer to Subpart A section 15.33 (a) (1) of FCC Part 15 which states:

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph:

(1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

7 Photographs

7.1 Radiatd Emission Test Setup



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

7.2 EUT Constructional Details



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



- END -

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.