



198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technological
Development District, Guangzhou, China 510663
Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM130500178601
Page: 1 of 47
FCC ID: OU9AW8001-LS

TEST REPORT

Application No.:	GZEM1305001786RF
Applicant:	Guangdong Transtek Medical Electronics Co., Ltd
FCC ID:	OU9AW8001-LS
Product Name:	Bluetooth Module
Product Description:	Wireless control Body Fat Analyzer with 2.4 GHz as carrier.
Model No.:	AW8001
Standards:	47 CFR PART 15 Subpart C: 2012 section 15.247
Date of Receipt:	2013-05-15
Date of Test:	2013-05-16 to 2012-05-29
Date of Issue:	2013-06-20
Test Result :	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 3 of this report for further detail.

Authorized Signature:

Richard Li
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2013-06-20		Original

Authorized for issue by:			
Tested By	 _____ (Storm Shu) /Signature	2013-05-16 to 2012-05-29 _____ Date	
Prepared By	 _____ (Storm Shu) /Signature	2013-06-07 _____ Date	
Checked By	 _____ (Jeffrey Chen) /Reviewer	2013-06-20 _____ Date	



3 Test Summary

Test	Test Requirement	Test method	Result
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
6 dB Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10: Clause 6.9.1	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	ANSI C63.10: Clause 6.10.3.1	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10: Clause 6.11.2.3	PASS
Conducted Spurious Emission (30MHz to 25GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.7	PASS
Radiated Spurious Emission 30 MHz to 25 GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.4, 6.5 and 6.6	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	ANSI C63.10: Clause 6.9.2	PASS

Remark:

N/A: not applicable. Refer to the relative section for the details.
EUT: In this whole report EUT means Equipment Under Test.
Tx: In this whole report Tx (or tx) means Transmitter.
Rx: In this whole report Rx (or rx) means Receiver.
RF: In this whole report RF means Radio Frequency.
ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.



4 Contents

1	COVER PAGE	1
2	VERSION.....	2
3	TEST SUMMARY	3
4	CONTENTS.....	4
5	GENERAL INFORMATION	5
5.1	Client Information	5
5.2	General Description of E.U.T.	5
5.3	Details of E.U.T.	5
5.4	Description of Support Units	5
5.5	Deviation from Standards	6
5.6	Abnormalities from Standard Conditions	6
5.7	Other Information Requested by the Customer	6
5.8	Test Location	6
5.9	Test Facility	7
6	EQUIPMENT USED DURING TEST.....	8
7	TEST RESULTS	9
7.1	E.U.T. test conditions.....	9
7.2	Antenna Requirement	11
7.3	6 dB Bandwidth.....	12
7.4	Maximum Peak Output Power.....	16
7.5	Peak Power Spectral Density	20
7.5	Conducted Spurious Emissions	24
7.6	Radiated Spurious Emissions	27
7.7	Band Edges Requirement	45

5 General Information

5.1 Client Information

Applicant: Guangdong Transtek Medical Electronics Co., Ltd
 Address of Applicant: Zone A, 5/F., Investment Building, No. 12 Huizhan East Rd., Torch Development District, Zhongshan, Guangdong, China 528437

5.2 General Description of E.U.T.


Product Name: Bluetooth Module
 Model No.: AW8001

5.3 Details of E.U.T.

Operating Frequency: 2402 MHz to 2480 MHz
 Type of Modulation: GFSK
 Number of Channels: 40 Channels
 Channel Separation: 2 MHz
 Antenna Type: PCB Layout
 Antenna gain: 0 dBi
 Function: Body Fat Analyzer with BT4.0 function to transmit signal.
 Power Supply: DC 5.0V supplied from host (Body Fat Analyzer)
 Power cord: N/A

5.4 Description of Support Units

The EUT should be put inside the host. During test the transferred board was used for finding the fixed frequency. The information of the support units is shown as below:





5.5 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

5.6 Abnormalities from Standard Conditions

None.

5.7 Other Information Requested by the Customer

None.

5.8 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.



5.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IEC 61010-1:2006-10 and Rules of procedure IEC 61010-2:2006-10, and the relevant IEC 61010-2 Scheme Operational documents.



6 Equipment Used during Test

RE in Chamber						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2014-08-30	2Y
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2014-05-06	1Y
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2014-03-04	1Y
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2014-05-09	1Y
EMC2025	Trilog Broadband Antenna 30-3000MHz	SCHWARZBECK MESS-ELEKTRONIK	VULB 9163	9163-450	2013-12-17	2Y
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2013-11-27	2Y
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2014-06-02	2Y
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	9120D-841	2013-11-28	2Y
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2014-07-01	2Y
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2014-03-04	1Y
EMC2065	Amplifier	HP	8447F	N/A	2013-11-7	1Y
EMC2063	1-26GHz Pre Amplifier	Compliance Direction System Inc.	PAP-1G26-48	6279.628	2013-07-29	1Y
EMC0075	310N Amplifier	Sonama	310N	272683	2014-03-04	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-04-07	2Y
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9170	9170-375	2014-06-01	3Y
EMC0530	10m Semi-Anechoic Chamber	ETS	N/A	N/A	2014-04-27	2Y

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date	Calibration Interval
					(YYYY-MM-DD)	
EMC0006	DMM	Fluke	73	70681569	2013-11-5	1Y
EMC0007	DMM	Fluke	73	70671122	2013-11-5	1Y

7 Test Results

7.1 E.U.T. test conditions

Test Voltage: DC6.0V
Temperature: 20.0 -25.0 °C
Humidity: 38-50 % RH
Atmospheric Pressure: 1000 -1010 mbar

Requirements: **15.31(e):** For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.
15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.

Test frequencies and frequency range:

According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified



EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	21	2442
2	2404	22	2444
3	2406	23	2446
4	2408	24	2448
5	2410	25	2450
6	2412	26	2452
7	2414	27	2454
8	2416	28	2456
9	2418	29	2458
10	2420	30	2460
11	2422	31	2462
12	2424	32	2464
13	2426	33	2466
14	2428	34	2468
15	2430	35	2470
16	2432	36	2472
17	2434	37	2474
18	2436	38	2476
19	2438	39	2478
20	2440	40	2480

Remark: Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2480 MHz

7.2 Antenna Requirement

Standard requirement

15.203 requirement:


For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna


The antenna is PCB Layout and no consideration of replacement. The best case gain of the antenna is 0dBi.



Test result: The unit does meet the FCC requirements.

7.3 6 dB Bandwidth

- Test Requirement: FCC Part 15 C section 15.247
 (a)(2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
- Test Method: ANSI C63.10: Clause 6.9.1
- Test Status: Enter test mode for the product. Test in Channel lowest (2402MHz), middle (2440MHz) and highest (2480MHz), keep in continuously transmitting status.
- Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss = 1.5dB) from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW=100KHz. VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Set span to encompass the entire emission bandwidth of the signal.
3. Mark the peak power frequency and -6dB (upper and lower) power frequency.
4. Repeat until all the test status is investigated.
5. Report the worse case.




Channel No.	Frequency (MHz)	Mode	Measured 6dB bandwidth (kHz)	Limit	Result
0	2402	GFSK	681.363	≥500KHz	Pass
20	2440		701.403		Pass
39	2480		661.323		Pass

Test result: The unit does meet the FCC requirements.




Result plot as follows:

Channel 0:2.402GHz:




Channel 20:2.440GHz:






Channel 39:2.480GHz:



7.4 Maximum Peak Output Power

- Test Requirement: FCC Part 15 C section 15.247
 (b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
 Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- Test Method: ANSI C63.10: Clause 6.10.3.1 (Method 1—spectral trace averaging).
- Test Status: Enter test mode for the product. Test in Channel lowest (2402MHz), middle (2440MHz) and highest (2480MHz), keep in continuously transmitting status.
- Test Configuration:





Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =2.5dB) from the antenna port to the spectrum.
2. Set span to encompass the entire emission bandwidth (EBW) of the signal.
3. Set RBW = 1 MHz.
4. Set VBW \geq 3 MHz.
5. Use sample detector mode if bin width (i.e., span/number of points in spectrum display) < 0.5 RBW. Otherwise use peak detector mode.
6. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep.
If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to "free run".
7. Trace average 100 traces in power averaging mode.
8. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer's band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.
9. Measure the channel power of the test frequency with special test status.
10. Repeat until all the test status is investigated.
11. Report the worse case.



Test result:


Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Channel Power (dBm)	Limit	Result
0	2402	GFSK	1Mbps	-2.72	1W(30dBm)	Pass
2	2440		1Mbps	-2.33		Pass
39	2480		1Mbps	-1.66		Pass

Remark: Level = Read Level + Cable Loss.


The unit does meet the FCC requirements.

Result plot as follows:


Channel 0:2.402GHz:



Channel 20:2.442GHz:



Channel 39:2.480GHz:




7.5 Peak Power Spectral Density

Test Requirement: FCC Part 15 C section 15.247
 (e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
 This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Method: ANSI C63.10: Clause 6.11.2.3

Test Status: Enter test mode for the product. Test in lowest Channel 2402MHz, middle Channel 2440MHz and highest Channel 2480MHz, keep in continuously transmitting status.

Test Configuration:





Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss =2.5dB) from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer:
 - a) Set CENTER FREQUENCY = Frequency from Power Spectral Density Test Matrix (see 6.10.2)
 - b) Set SPAN = 20 MHz (For devices with a nominal 40 MHz BW, 50 MHz span will be needed)
 - c) Set REFERENCE LEVEL = 20 dBm
 - d) Set ATTENUATION = 0 dB (add internal attenuation, if necessary)
 - e) Set SWEEP TIME = Coupled
 - f) Set RBW = 3 kHz
 - g) Set VBW = 10 kHz
 - h) Set DETECTOR = Peak
 - i) Set MKR = Center Frequency
 - j) Set TRACE = CLEAR WRITE

Place the radio in continuous transmit mode. Set the TRACE to MAX HOLD, and after the trace stabilizes, the TRACE to VIEW. Set the marker on the peak of the signal and then adjust the center frequency of the spectrum analyzer to the marker frequency.

After viewing the EUT waveform on the spectrum analyzer, perform the following spectrum analyzer functions to capture the trace:

Set SPAN = 300 kHz

Set SWEEP TIME = 100 s

Set TRACE = MAX HOLD

Set MKR = PEAK SEARCH

3. Measure the Power Spectral Density of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.




Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Peak Power Spectral Density (dBm/3KHz)	Limit	Result
0	2402	GFSK	1 Mbps	-11.69	8dBm/3KHz	Pass
20	2440		1 Mbps	-13.01		Pass
39	2480		1 Mbps	-13.39		Pass

Test result: Level = Read Level + Cable Loss.
The unit does meet the FCC requirements.


Result plot as follows:

Channel 0:2.402 GHz:






Channel 20:2.440 GHz:



Channel 39:2.480 GHz:



7.5 Conducted Spurious Emissions


Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10: Clause 6.7

Test Status: Enter test mode for the product. Test in lowest Channel 2402MHz, middle Channel 2440MHz and highest Channel 2480MHz, keep in continuously transmitting status.

Test Configuration:




Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.




Result plot as follows:

Channel 0: 2.402 GHz
30 MHz to 25GHz



Channel 20:2.440GHz


30 M to 25 GHz





Channel 39: 2.480 GHz

30 M to 25 GHz






7.6 Radiated Spurious Emissions


Test Requirement:	FCC Part 15 C section 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.
Test Method:	ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Enter test mode for the product. Test in lowest channel 2402 MHz and highest channel 2480 MHz, keep in continuously transmitting status with GFSK modulation.
Detector:	For PK value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW \geq RBW Sweep = auto Detector function = peak Trace = max hold For AV value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW = 10Hz Sweep = auto Detector function = peak Trace = max hold
15.209 Limit:	40.0 dB μ V/m between 30MHz & 88MHz 43.5 dB μ V/m between 88MHz & 216MHz 46.0 dB μ V/m between 216MHz & 960MHz 54.0 dB μ V/m above 960MHz

Test Configuration:

1) 30 MHz to 1 GHz emissions:



2) 1 GHz to 40 GHz emissions:





Test Procedure: The receiver scanned from the lowest frequency generated within the EUT to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

From 30MHz to 1GHz, read the Quasi-Peak field strength of the emissions with receiver QP detector RBW=120KHz.

Above 1GHz, read the Peak field strength and Average field strength.

Read the Peak field strength through RBW=1MHz, VBW=3MHz in spectrum analyzer setting;

Read the Average field strength through RBW=1MHz, VBW=10Hz in spectrum analyzer setting;

While maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the average field strength reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.

7.6.1 Harmonic and other spurious emissions

Test at Channel 0 (2.402 GHz) in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dB μ V/m)




Quasi-peak measurement

Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
MHz	dB μ V	dB/m	dB	dB	dB μ V/m	dB μ V/m	dB	
49.400	26.89	13.29	0.97	29.50	11.65	40.00	-28.35	QP
111.480	27.12	11.94	1.30	29.70	10.65	43.50	-32.85	QP
198.780	37.27	10.57	1.72	29.50	20.05	43.50	-23.45	QP
474.260	34.99	15.95	2.59	29.52	24.01	46.00	-21.99	QP
758.470	28.55	19.53	3.30	29.24	22.14	46.00	-23.86	QP
953.440	26.83	21.43	3.74	27.87	24.13	46.00	-21.87	QP



Horizontal:

Peak scan
 Level (dBμV/m)



Quasi-peak measurement

Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
44.550	26.79	13.55	0.90	29.50	11.74	40.00	-28.26	QP
99.840	26.14	13.16	1.22	29.70	10.82	43.50	-32.68	QP
193.930	29.12	10.56	1.70	29.52	11.86	43.50	-31.64	QP
288.990	33.71	12.84	2.03	29.59	18.99	46.00	-27.01	QP
455.830	37.36	15.58	2.53	29.54	25.93	46.00	-20.07	QP
778.840	30.51	19.82	3.35	29.22	24.46	46.00	-21.54	QP



1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4804.000	45.34	31.53	9.34	33.05	53.16	74.00	Vertical
7206.000	46.21	36.47	13.09	32.74	63.03	74.00	V
9608.000	41.32	38.08	13.23	34.06	58.57	74.00	V
4804.000	44.75	31.53	9.34	33.05	52.57	74.00	Horizontal
7206.000	45.56	36.47	13.09	32.74	62.38	74.00	H
9608.000	42.42	38.08	13.23	34.06	59.67	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4804.000	28.06	31.53	9.34	33.05	35.88	54.00	Vertical
7206.000	27.13	36.47	13.09	32.74	43.95	54.00	V
9608.000	26.19	38.08	13.23	34.06	43.44	54.00	V
4804.000	27.49	31.53	9.34	33.05	35.31	54.00	Horizontal
7206.000	27.61	36.47	13.09	32.74	44.43	54.00	H
9608.000	26.89	38.08	13.23	34.06	44.14	54.00	H



Test at Channel20 (2.440 GHz) in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dBμV/m)




Quasi-peak measurement

Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
32.910	28.04	12.31	0.72	29.50	11.57	40.00	-28.43	QP
98.870	25.11	13.10	1.21	29.70	9.73	43.50	-33.77	QP
265.710	26.88	12.26	1.96	29.57	11.52	46.00	-34.48	QP
461.650	30.31	15.65	2.55	29.53	18.98	46.00	-27.02	QP
781.750	27.59	19.82	3.37	29.22	21.57	46.00	-24.43	QP
947.620	27.26	21.40	3.73	27.90	24.49	46.00	-21.51	QP

Horizontal:

Peak scan

Level (dB μ V/m)



Quasi-peak measurement

Freq MHz	Read Level dB μ V	Antenna Factor dB/m	Cable Loss dB	Preamp Factor dB	Level dB μ V/m	Limit Line dB μ V/m	Over Limit dB	Remark
44.550	25.85	13.55	0.90	29.50	10.80	40.00	-29.20	QP
104.690	26.04	12.73	1.25	29.70	10.32	43.50	-33.18	QP
194.900	30.86	10.57	1.70	29.52	13.61	43.50	-29.89	QP
255.040	31.76	12.06	1.93	29.56	16.18	46.00	-29.82	QP
466.500	40.92	15.77	2.57	29.53	29.73	46.00	-16.27	QP
763.320	32.69	19.63	3.31	29.23	26.40	46.00	-19.60	QP



1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4884.000	44.33	31.58	9.33	32.86	52.38	74.00	Vertical
7326.000	42.48	36.50	13.11	32.60	59.49	74.00	V
9768.000	42.64	38.53	13.35	34.17	60.35	74.00	V
4884.000	44.37	31.58	9.33	32.86	52.42	74.00	Horizontal
7326.000	42.43	36.50	13.11	32.60	59.44	74.00	H
9768.000	41.89	38.53	13.35	34.17	59.60	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4884.000	28.14	31.58	9.33	32.86	36.19	54.00	Vertical
7326.000	27.23	36.50	13.11	32.60	44.24	54.00	V
9768.000	26.08	38.53	13.35	34.17	43.79	54.00	V
4884.000	27.98	31.58	9.33	32.86	36.03	54.00	Horizontal
7326.000	26.87	36.50	13.11	32.60	43.88	54.00	H
9768.000	26.79	38.53	13.35	34.17	44.50	54.00	H



Test at Channel39 (2.480 GHz) in transmitting status

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement


The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dBμV/m)




Quasi-peak measurement

Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
49.400	26.56	13.29	0.97	29.50	11.32	40.00	-28.68	QP
191.990	37.38	10.56	1.69	29.53	20.10	43.50	-23.40	QP
418.000	27.64	15.43	2.41	29.58	15.89	46.00	-30.11	QP
476.200	35.45	16.01	2.59	29.52	24.53	46.00	-21.47	QP
755.560	31.05	19.53	3.29	29.24	24.63	46.00	-21.37	QP
937.920	26.28	21.34	3.70	27.98	23.34	46.00	-22.66	QP



Horizontal:

Peak scan
 Level (dBμV/m)



Quasi-peak measurement

Freq MHz	Read Level dBuV	Antenna Factor dB/m	Cable Loss dB	Preamp Factor dB	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Remark
40.670	25.20	13.58	0.83	29.50	10.11	40.00	-29.89	QP
102.750	26.66	12.92	1.24	29.70	11.12	43.50	-32.38	QP
192.960	33.53	10.56	1.69	29.52	16.26	43.50	-27.24	QP
256.980	35.56	12.06	1.93	29.56	19.98	46.00	-26.02	QP
463.590	39.07	15.65	2.56	29.53	27.75	46.00	-18.25	QP
776.900	35.37	19.77	3.35	29.22	29.28	46.00	-16.72	QP



1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4960.000	43.12	31.70	9.31	32.67	51.46	74.00	Vertical
7440.000	41.37	36.60	13.14	32.46	58.65	74.00	V
9920.000	41.12	38.65	13.52	34.24	59.05	74.00	V
4960.000	42.42	31.70	9.31	32.67	50.76	74.00	Horizontal
7440.000	42.30	36.60	13.14	32.46	59.58	74.00	H
9920.000	41.39	38.65	13.52	34.24	59.32	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
4960.000	27.34	31.70	9.31	32.67	35.68	54.00	Vertical
7440.000	26.43	36.60	13.14	32.46	43.71	54.00	V
9920.000	26.21	38.65	13.52	34.24	44.14	54.00	V
4960.000	28.07	31.70	9.31	32.67	36.41	54.00	Horizontal
7440.000	27.19	36.60	13.14	32.46	44.47	54.00	H
9920.000	26.32	38.65	13.52	34.24	44.25	54.00	H

The field strength is calculated by adding the Antenna Factor. Cable Factor & Pre-amplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss – Pre-amplifier Factor.

As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.



Remark:

- 1) .For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonics of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 3rd harmonic.
- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.



7.6.2 Radiated Emissions which fall in the restricted bands

Test Requirement:	FCC Part 15 C section 15.247 (d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Enter test mode for the product. Test in lowest channel 2402 MHz and highest channel 2480 MHz, keep in continuously transmitting status with GFSK modulation.
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Limit:	40.0 dB μ V/m between 30MHz & 88MHz; 43.5 dB μ V/m between 88MHz & 216MHz; 46.0 dB μ V/m between 216MHz & 960MHz; 54.0 dB μ V/m above 960MHz.
Detector:	For PK value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW \geq RBW Sweep = auto Detector function = peak Trace = max hold For AV value: RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz VBW = 10Hz Sweep = auto Detector function = peak Trace = max hold



Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		



Test Result:

Test at Channel 0 (2.402 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	46.14	27.93	4.23	35.60	42.70	74.00	Vertical
2390.000	47.15	27.61	4.30	35.60	43.46	74.00	V
2483.500	46.34	27.55	4.40	35.60	42.69	74.00	V
2500.000	46.39	27.77	4.30	35.60	42.86	74.00	V
2310.000	46.52	27.93	4.23	35.60	43.08	74.00	Horizontal
2390.000	49.23	27.61	4.30	35.60	45.54	74.00	H
2483.500	46.21	27.55	4.40	35.60	42.56	74.00	H
2500.000	47.32	27.77	4.30	35.60	43.79	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	27.38	27.93	4.23	35.60	23.94	54.00	Vertical
2390.000	27.42	27.61	4.30	35.60	23.73	54.00	V
2483.500	27.31	27.55	4.40	35.60	23.66	54.00	V
2500.000	26.37	27.77	4.30	35.60	22.84	54.00	V
2310.000	27.54	27.93	4.23	35.60	24.10	54.00	Horizontal
2390.000	27.19	27.61	4.30	35.60	23.50	54.00	H
2483.500	27.32	27.55	4.40	35.60	23.67	54.00	H
2500.000	27.65	27.77	4.30	35.60	24.12	54.00	H



Test at Channel 20 (2.442 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	46.52	27.93	4.23	35.60	43.08	74.00	Vertical
2390.000	47.35	27.61	4.30	35.60	43.66	74.00	V
2483.500	45.31	27.55	4.40	35.60	41.66	74.00	V
2500.000	45.79	27.77	4.30	35.60	42.26	74.00	V
2310.000	46.04	27.93	4.23	35.60	42.60	74.00	Horizontal
2390.000	46.47	27.61	4.30	35.60	42.78	74.00	H
2483.500	46.37	27.55	4.40	35.60	42.72	74.00	H
2500.000	46.21	27.77	4.30	35.60	42.68	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dB μ V)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dB μ V/m)	Limit (dB μ V/m)	Antenna polarization
2310.000	27.87	27.93	4.23	35.60	24.43	54.00	Vertical
2390.000	27.65	27.61	4.30	35.60	23.96	54.00	V
2483.500	27.52	27.55	4.40	35.60	23.87	54.00	V
2500.000	27.63	27.77	4.30	35.60	24.10	54.00	V
2310.000	27.44	27.93	4.23	35.60	24.00	54.00	Horizontal
2390.000	27.52	27.61	4.30	35.60	23.83	54.00	H
2483.500	27.46	27.55	4.40	35.60	23.81	54.00	H
2500.000	27.29	27.77	4.30	35.60	23.76	54.00	H



Test at Channel 39 (2.480 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	47.21	27.93	4.23	35.60	43.77	74.00	Vertical
2390.000	46.69	27.61	4.30	35.60	43.00	74.00	V
2483.500	46.34	27.55	4.40	35.60	42.69	74.00	V
2500.000	46.72	27.77	4.30	35.60	43.19	74.00	V
2310.000	46.34	27.93	4.23	35.60	42.90	74.00	Horizontal
2390.000	46.27	27.61	4.30	35.60	42.58	74.00	H
2483.500	46.30	27.55	4.40	35.60	42.65	74.00	H
2500.000	46.12	27.77	4.30	35.60	42.59	74.00	H

Average Measurement:


Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	26.52	27.93	4.23	35.60	23.08	54.00	Vertical
2390.000	27.04	27.61	4.30	35.60	23.35	54.00	V
2483.500	26.37	27.55	4.40	35.60	22.72	54.00	V
2500.000	27.54	27.77	4.30	35.60	24.01	54.00	V
2310.000	27.25	27.93	4.23	35.60	23.81	54.00	Horizontal
2390.000	27.18	27.61	4.30	35.60	23.49	54.00	H
2483.500	27.27	27.55	4.40	35.60	23.62	54.00	H
2500.000	26.21	27.77	4.30	35.60	22.68	54.00	H

Remark: No any other emission which falls in restricted bands can be detected and be reported.

Test result: The unit does meet the FCC requirements.

7.7 Band Edges Requirement

Test Requirement:	FCC Part 15 C section 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.
Frequency Band:	2400 MHz to 2483.5 MHz
Test Method:	ANSI C63.10: Clause 6.9.2
Test Status:	Enter test mode for the product. Test in lowest channel 2402 MHz and highest channel 2480 MHz, keep in continuously transmitting status with GFSK modulation.
Test Configuration:	



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set RBW=100 kHz , VBW=300KHz ,suitable frequency span including 100 kHz bandwidth from band edge..
3. Measure the Conducted Spurious Emissions and Radiated Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse.



Test result with plots as follows:

The band edges was measured and recorded Result:


The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.




Result plot as follows:

Channel 0: 2.402 GHz



Channel 39: 2.480GHz



--End of Report--