

EMISSION TEST REPORT

Test Report No. : **21KE0071-YW-1**

Applicant: OMRON CORPORATION

Type of Equipment: Keyless Entry System (Transmitter)

Model No.: G8D-344H-A/ G8D-346H-A G8D-349H-A /
G8D-344H-A-NT

FCC ID OUCG8D-344H-A

Test standard: FCC Part 15 Subpart C
Section 15.231

Test Result: Complies

This report may not be reproduced in full, partial reproduction may only be made with the written consent of the laboratory.

The results in this report apply only to the sample tested.

Date of test: June 28, 2001

Tested by: 
Makoto Kosaka

Approved by: 
Kazutoyo Nakanishi
Section Manager of EMC section

Issued date: July 5, 2001

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Table of Contents	Page
1 GENERAL INFORMATION	3
1.1 Product Description	4
1.2 Test Specification	4
1.3 Methods & Procedures	4
1.4 Test Location	4
2 SYSTEM TEST CONFIGURATION	5
2.1 Operation Environment	5
2.2 Justification	5
2.3 EUT Exercise Software	5
2.4 Test Procedure	5
Figure 2.1 Configuration of Tested System	6
3 RADIATED EMISSION DATA	7
3.1 Field Strength Calculation	7
2.2 –20dB Bandwidth	7
3.3 Measurement Uncertainty	8
4 TEST EQUIPMENT USED	9
5 MEASUREMENT PHOTOS	10
Figure 5.1 Radiated Measurement Photos	10
APPENDIX	11
A:Test Data	A1 – A3

1 GENERAL INFORMATION

APPLICANT : OMRON CORPORATION

ADDRESS : 6368 Nenjo-Zaka, Okusa, Komaki-City,
Aichi 485-0802 Japan

Telephon Number : +81-568-78-6170
Facsimile Number : +81-568-78-6179

REGULATION(S) : FCC Part 15 Subpart C Section 15.231

MODEL NUMBER : G8D-344H-A/ G8D-346H-A/ G8D-349H-A
: G8D-344H-A-NT

FCC ID : OUCG8D-344H-A

SERIAL NUMBER : Sample No.1

CONDITION EUT : Engineering Prototype

KIND OF EQUIPMENT : Keyless Entry System (Transmitter)

TESTED DATE : June 28, 2001

RECEIPT DATE OF SAMPLE : June 28, 2001

REPORT FILE NUMBER : 21KE0071-YW-1

TEST SITE : A-PEX Yokowa No.3 Open Test Site

Test report**Our reference : 21KE0071-YW-1****Page : 4 of 11****Issued date : July 5, 2001****FCC ID : OUCG8D-344H-A****1.1 Product Description**

Model: G8D-344H-A, G8D-346H-A, G8D-349H-A and G8D-344H-A-NT (referred to as the EUT in this report) is a Keyless Entry System (Transmitter).

G8D-344H-A, G8D-346H-A, G8D-349H-A and G8D-344H-A-NT are deemed to be equal about the level of EMC since they have few differences as remarked below, therefore, G8D-344H-A which is a top-level model was measured as their representative.

Model No	PWB	Parts on PWB	Software (basic control)
G8D-344H-A	Origin	Origin(Loaded four SW) (LOCK,UNLOCK,TRUNK,PANIC)	Origin
G8D-346H-A	same as G8D-344H-A	Loaded three SW(LOCK,UNLOCK,TRUNK)	same as G8D-344H-A
G8D-349H-A	same as G8D-344H-A	Loaded two SW(LOCK,UNLOCK)	same as G8D-344H-A
G8D-344H-A-NT	same as G8D-344H-A	Loaded three SW(LOCK,UNLOCK,PANIC)	same as G8D-344H-A

The specification is as following :

Carrier Frequency : 313.85 MHz
 Modulation : FSK
 Other Clock Frequency : 5.00MHz
 Information antenna : Integral / P.C.B pattern antenna
 Operation Voltage : Lithium Battery DC 3.0V(CR2025)

1.2 Test Specification

Test Specification : FCC Part 15 Subpart C

Title : FCC 47CFR Part15 Radio Frequency Device

Subpart C Intentional Radiators

§ 15.231 Periodic operation in the band 40.66 – 40.70 MHz and above 70MHz

1.3 Methods & Procedures

No.	Item	Test Procedure	Specification	Remarks
1	Electric Field Strength of Fundamental Emission	ANSI C63.4:1992	§ 15.231	3m
2	Electric Field Strength of Spurious Emission	ANSI C63.4:1992	§ 15.205 § 15.209 § 15.231	3m
3	-20dB Bandwidth	ANSI C63.4:1992	§ 15.231	3m

1.4 Test Location

A-PEX International Co.,Ltd. Yokowa No.3 test site

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 Japan

Telephone number : +81-596-39-1485

Facsimile number : +81-596-39-0232

This site has been fully described in a report submitted to FCC office, and listed on September 12, 2000 (Registration number: 90412).

*NVLAP Lab. code : 200109-0

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

2 SYSTEM TEST CONFIGURATION

2.1 Operation Environment

Temperature : 24

Humidity : 42%

2.2 Justification

The system was configured in typical fashion (as a customer would normally use it) for testing.

2.3 EUT Exercise Software

The EUT exercise program used during radiated testing was designed to exercise the various system components in a manner similar to typical use.

The sequence is used:

Operation Mode : Transmitting

2.4 Test Procedure

Tabletop Equipment Radiated Emissions

EUT was placed on a platform of nominal size, 1m by 1m, raised 80cm above the conducting ground plane.


Test was made with the antenna positioned in both the horizontal and vertical planes of polarization.

The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.


The measurement distance was 3m.

Figure2.1 Configuration of Tested System

Front View



Top View



*Test data was taken under worse case conditions.

No.	Item	Model number	Serial number	Manufacturer	FCC ID
1	Keyless Entry System (Transmitter)	G8D-344H-A	Sample No.1	OMRON	OUCG8D-344H-A

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

3 RADIATED EMISSION DATA

The initial step in collecting radiated data was a spectrum analyzer peak scan of the measurement range (30MHz-3200MHz).

The final data was reported in the worst-case emissions.

The minimum margin to the limit is as follows :

No	Ant Pol	Freq [MHz]	Reading [dB μ V]	Antena Facter [dB]	Cable Loss [dB]	ATT [dB]	AMP Gain [dB]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Remark
1	H	313.88	77.8	14.4	3.6	5.8	27.6	74.0	75.6	1.6	Fundamental
2	H	2825.038	44.5	31.5	7.5	-	34.9	48.6	54.0	5.4	Spurious

Remark

Below 1GHz: Test Receiver Setting : QP Detect / IF Band width 120kHz

Above 1GHz: Spectrum Analyzer Setting : PK Detect / RBW 1MHz, VBW 1MHz

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, Cable Factor and Antenna Pad, and subtracting the Amplifier Gain from the measured reading. The sample calculation is as follows :

$$FS = RA + AF + CF + AT - AG$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Factor

AT = Antenna Pad

AG = Amplifier Gain

Assume a receiver reading of 77.8 dB μ V is obtained. The antenna Factor of 14.4 dB, Cable Factor of 3.6 dB and Antenna Pad of 5.8 dB is added. The Amplifier Gain of 27.6 dB is subtracted, giving a field strength of 74.0 dB μ V/m.

$$FS = 77.8 + 14.4 + 3.6 + 5.8 - 27.6 = 74.0 \text{ dB } \mu \text{ V/m}$$

3.2 -20dB Bandwidth

Bandwidth Limit: Fundamental Frequency 313.85MHz \times 0.25% = 784.625kHz

Bandwidth Limit	measurement data (20dB down) Center Freq: 313.85MHz	Result
Upper frequency Limit (314.2423125MHz:392.3125kHz)	314.073MHz(223kHz)	Pass
Lower frequency Limit (313.4576875MHz:392.3125kHz)	313.605MHz(245kHz)	Pass
-20dB Bandwidth (784.625kHz)	Uf + Lf = 468kHz	Pass

* See Appendix A2 and A3

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Test report

Our reference : 21KE0071-YW-1

Page : 8 of 11

Issued date : July 5, 2001

FCC ID : OUCG8D-344H-A

3.3 Measurement Uncertainty

Radiated Emission Test

The measurement uncertainty (with a 95% confidence level) for this test was $\pm 3.3\text{dB}$.

The data listed in this test report may exceed the test limit because it does not have enough margin (more than 3.3dB).

The data listed in this test report has enough margin, more than 3.3dB.

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Test report

Our reference : 21KE0071-YW-1

Page : 9 of 11

Issued date : July 5, 2001

FCC ID : OUCG8D-344H-A

4 Test EQUIPMENT USED

Instrument	Mfr.	Model No.	Control No.	Calibration Date / Interval
Pre Amplifier	Hewlett Packard	8447D	AF-01	March 31, 2001 / 1 year
Pre Amplifier	Hewlett Packard	8449B	AF-04	November 5, 2000 / 1 year
Attenuator	Anritsu	MP721B	AT-06	March 31, 2001 / 1 year
Biconical Antenna	Schwarzbeck	BBA9106	BA-03	May 1, 2001 / 1 year
Logperiodic Antenna	Schwarzbeck	UHALP9108-A	LA-06	May 1, 2001 / 1 year
Horn Antenna	A.H. Systems	SAS200/571	HA-01	May 20, 2001 / 1 year
Spectrum Analyzer	Hewlett Packard	8567A	SA-04	March 31, 2001 / 1 year
Spectrum Analyzer	Advantest	R3271	SA-05	February 1, 2001 / 1 year
Test Receiver	Rohde & Schwarz	ESVS10	TR-06	August 10, 2000 / 1 year
Test Receiver	Rohde & Schwarz	ESCS30	TR-07	August 8, 2000 / 1 year

*All measurement equipment is traceable to national standard.

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Test report

Our reference : 21KE0071-YW-1

Page : 10 of 11

Issued date : July 5, 2001

FCC ID : OUCG8D-344H-A

5 RADIATED MEASUREMENT PHOTOS

5.1 Radiated Measurement Photos



Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Test report

Our reference : 21KE0071-YW-1

Page : 11 of 11

Issued date : July 5, 2001

FCC ID : OUCG8D-344H-A

APPENDIX

A : Test Data

Radiated emissions and -20dB Bandwidth

A1 - A3

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

DATA OF RADIATION TEST

A-PEX INTERNATIONAL CO., LTD.
YOKOWA NO.3 OPEN SITE

COMPANY : OMRON Corporation
 TRADE NAME: OMRON
 EQUIPMENT : keyless Entry System (Transmitter)
 MODEL : G8D-344H-A (4SW type)
 POWER : DC3.0V(CR2025)
 Mode : Transmitting
 Serial No. : sample No.1
 Temperature : 24°C
 Humidity : 42%

REPORT NO : 21KE0071-YW-1
 REGULATION : FCC15.231(b) / 15.205
 TEST DISTANCE : 3m
 DATE : 2001/6/28
 FCC ID : OUCG8D-344H-A


 ENGINEER : Makoto Kosaka

Below 1GHz QP DETECT(Test Receiver: BW 120kHz)

Above 1GHz PK DETECT (Spectrum Analyzer : RBW 1MHz and VBW 1MHz)

No.	FREQ [MHz]	ANT TYPE	READING		ANT Factor [dB]	ATTEN [dB]	CABLE LOSS [dB]	AMP GAIN [dB]	RESULT		LIMIT [dB μ V/m]	MARGIN	
			HOR [dB μ V]	VER [dB μ V]					HOR [dB μ V/m]	VER [dB μ V/m]		HOR [dB]	VER [dB]
1	313.88	BB	77.8	56.2	14.4	5.8	3.6	27.6	74.0	52.4	75.6	1.6	23.2
2	627.79	BB	28.9	21.5	19.3	5.9	5.4	27.3	32.2	24.8	55.6	23.4	30.8
3	941.68	BB	27.6	23.2	22.8	5.9	7.1	26.7	36.7	32.3	55.6	18.9	23.3
4	1255.516	BB	47.1	45.6	25.9	0.0	4.8	35.1	42.7	41.2	55.6	12.9	14.4
5	1569.279	BB	47.2	47.3	27.8	0.0	5.4	34.7	45.7	45.8	54.0	8.3	8.2
6	1883.358	BB	43.3	42.0	29.6	0.0	6.1	34.5	44.5	43.2	55.6	11.1	12.4
7	2197.250	BB	43.1	43.1	30.8	0.0	6.7	34.4	46.2	46.2	55.6	9.4	9.4
8	2511.146	BB	45.6	44.1	31.6	0.0	7.2	34.5	49.9	48.4	55.6	5.7	7.2
9	2825.038	BB	44.5	42.6	31.5	0.0	7.5	34.9	48.6	46.7	54.0	5.4	7.3
10	3138.934	BB	43.1	43.2	31.6	0.0	7.9	34.9	47.7	47.8	55.6	7.9	7.8

REMARKS

ANTENNA TYPE: 30-300MHz Biconical / 300-1000MHz Logperiodic / 1-3.2GHz DRG Horn

CALCULATION(30MHz to 1000MHz) : READING + ANT Factor + ATTEN + Cable Loss - AMP Gain

CALCULATION(1.0GHz to 3.3GHz) : READING + ANT Factor + Cable Loss - AMP Gain


*Except for the above table : adequate margin data below the limits.

OMRON / G8D-344H-A / FCC ID: OUCG8D-344H-A
-20dB Bandwidth(Hor) 15.231(c) / Page A2
REF 80.0 dBuV ATTEN 10 dB

MAKER
313.8500 MHz
75.35 dBuV

MAKER
-245.0000 kHz
-20.20 dBuV

5 dB/



START 313.35 MHz
RES BW 100 kHz

VBW 10 kHz


STOP 314.35 MHz
SWP 20 msec

OMRON / G8D-344H-A / FCC ID: OUCG8D-344H-A
-20dB Bandwidth(Hor) 15.231(c) / Page A3
REF 80.0 dBuV ATTEN 10 dB

MAKER
313.8500 MHz
75.35 dBuV

MAKER
223.0000 kHz
-20.05 dBuV

5 dB/



START 313.35 MHz
RES BW 100 kHz

VBW 10 kHz

STOP 314.35 MHz
SWP 20 msec