



- NOTES:
- 1) J11 IS A 15 POS "D" CONNECTOR.
 - 2) J10 IS A 37 POS "D" CONNECTOR.
 - 3) ALL SINGLE WIRE IS 22 AWG UNLESS NOTED OTHERWISE.
 - 4) ALL SHIELDED WIRE IS BELDEN YR40143 UNLESS NOTED OTHERWISE.

CHANGED A7, A8, A9 TO 1159965 FROM 1555-1271 DUAL PEAK DETECTOR, REMOVED "MODULE". REV. A0 (CES)

AO	20084631	3/13/01	LRT
REV	ECN	DATE	APV

ITS CORPORATION

TITLE INTERCONNECT - METER PANEL - 5KW (1245-1400)

ADDED A18 (1245-1402) CHANGED A10 TO 1265-1309 OR 1265-1325 (AWG)	2	8/07/7/9/96	A7, A8, A9 WERE DUAL PEAK DETECTOR BD. NOTE 4: BELDEN S.M. BELDEN.	1	8/07/6/14/96	RE	APV	THIS PRINT IS THE PROPERTY OF ITS CORP. IT SHALL NOT BE COPIED WITHOUT PERMISSION.	DATE	REV
FINISH	REL	JAG	5/24/96	D	SCALE	---	SHEET	1 OF 1		

DWN	PJK	5/13/96	DWG. NO.	REV
CHK	JAG	5/24/96	1245-8400	A0
REL	JAG	5/24/96	D	SCALE