



EMC TEST REPORT FCC 47 CFR Part 15B Industry Canada ICES-003 Electromagnetic compatibility - Unintentional radiators	
Report Reference No.	G0M-1511-5232-EF0115B-V02
Testing Laboratory	Eurofins Product Service GmbH
Address	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	<div style="text-align: center;">   </div> <p>A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A</p>
Applicant's name	Kamstrup A/S
Address	Industrivej 28 8660 Skanderborg DENMARK
Test specification:	
Standard.....	47 CFR Part 15 Subpart B ICES-003, Issue 5:2012 ANSI C63.4:2014
Equipment under test (EUT):	
Product description	READy Converter for Australia
Model No.	READy Converter
Additional Models	None
Hardware version	5550 1413 A3
Firmware / Software version	50981118 D1 / 5514 1447 A1
Contains	FCC-ID: OUY-READYAMR2 IC: N/A
Test result	Passed

Possible test case verdicts:


- not applicable to test object: N/A
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)


Testing:

Date of receipt of test item: 2016-01-18

Date (s) of performance of tests: 2016-01-18 - 2016-01-19

Compiled by : Jens Marquardt

Tested by (+ signature)..... : Jens Marquardt 

Approved by (+ signature) : Jens Zimmermann 
Deputy Head of Lab

Date of issue : 2016-02-23

Total number of pages : 43

General remarks:

The test results presented in this report relate only to the object tested.
The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:

Version History

Version	Issue Date	Remarks	Revised by
V01	2016-02-17	Initial Release	
V02	2016-02-23	Diagrams were corrected.	J. Marquardt


REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Photos – Equipment external	6
1.2	Photos – Equipment internal	9
1.3	Photos – Test setup	12
1.4	Supporting Equipment Used During Testing	13
1.5	Input / Output Ports	13
1.6	Operating Modes and Configurations	14
1.7	Test Equipment Used During Testing	15
1.8	Sample emission level calculation	16
2	RESULT SUMMARY	17
3	TEST CONDITIONS AND RESULTS	18
3.1	Test Conditions and Results – Radiated emissions	18
3.2	Test Conditions and Results – AC power line conducted emissions	40

1 Equipment (Test item) Description

Description	READy Converter for Australia
Model	READy Converter
Additional Models	None
Serial number	None
Hardware version	5550 1413 A3
Software / Firmware version	50981118 D1 / 5514 1447 A1
Contains FCC-ID	OUY-READYAMR2
Contains IC	N/A
Power supply	24 VDC
AC/DC-Adaptor	None
Manufacturer	Kamstrup A/S Industrivej 28 8660 Skanderborg DENMARK
Highest emission frequency	Fmax[MHz]=925
Device classification	Class B
Equipment type	Tabletop
Number of tested samples	1

1.1 Photos – Equipment external




EUT ANTENNA CONNECTOR







EUT USB CONNECTOR





1.2 Photos – Equipment internal







ANTENNA VARIANT 2



1.3 Photos – Test setup



1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments (e.g. serial no.)
AE	Notebook	HP	Elitebook 8440p	Serial: CZC0506398
AE	Smartphone	Sony	Xperia	IMEI: 351710058229179
EUT	READY Converter AUS	Kamstrup	5550 1413 A3	Short range device to BT data bridge
EUT	External antenna 1	Laird technology / Nearson	S161AM-915	whip antenna RP SMA
EUT	External antenna 2	smarteq	6699467+ 6699466 with low loss cable	roof top antenna
None				
<p>*Note: Use the following abbreviations:</p> <p>AE : Auxiliary/Associated Equipment, or</p> <p>SIM : Simulator (Not Subjected to Test)</p> <p>CABL : Connecting cables</p>				

1.5 Input / Output Ports

Port #	Name	Type*	Max. Cable Length	Cable Shielded	Comments (e.g. Cat. of Cable)
1	USB-Cable	I/O	<3m	Yes	For charging
<p>*Note: Use the following abbreviations:</p> <p>AC : AC power port</p> <p>DC : DC power port</p> <p>N/E : Non electrical</p> <p>I/O : Signal input or output port</p> <p>TP : Telecommunication port</p>					

1.6 Operating Modes and Configurations

Mode #	Description
1	USB Cable connected for charging. Bluetooth connection to Smartphone

Configuration #	EUT Configuration
1	Charging with USB, SRD, roof top antenna Bluetooth connection (<u>inactive</u>) to Smartphone
2	Charging with USB, SRD, Walk by antenna Bluetooth connection (<u>active</u>) to Smartphone

1.7 Test Equipment Used During Testing

Measurement Software			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	2014.1.15

Radiated emissions – 3m Chamber					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Biconical Antenna	R&S	HK 116	EF00012	2013-02	2016-02
LPD-Antenne	R&S	HL 223	EF00187	2014-03	2017-03
Horn antenna	Schwarzbeck	BBHA 9120D	EF00018	2013-09	2016-09
EMI Test Receiver	R&S	ESU26	EF00887	2016-01	2017-01
RF Cable			-	System Cal.	System Cal
RF Cable			-	System Cal.	System Cal

Conducted emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH2-Z5	EF00182	2014-11	2016-11
EMI Test Receiver	R&S	ESR7	EF00943	2015-09	2016-09
Cable	-	RG58/U	-	System Cal.	System Cal.

1.8 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dB μ V. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dB μ V/m). The FCC limits are given in units of μ V/m. The following formula is used to convert the units of μ V/m to dB μ V/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 * \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

$$\begin{array}{rclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading} - \text{FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

2 Result Summary

FCC 47 CFR Part 15B, Industry Canada ICES-003				
Product Specific Standard	Requirement – Test	Reference Method	Result	Remarks
47 CFR 15.109 ICES-003 Item 6.2	Radiated emissions	ANSI C 63.4	PASS	
47 CFR 15.107 ICES-003 Item 6.1	AC power line conducted emissions	ANSI C63.4	PASS	
Remarks:				

3 Test Conditions and Results

3.1 Test Conditions and Results – Radiated emissions

Radiated emissions acc. FCC 47 CFR 15.109 / ICES-003				Verdict: PASS		
Laboratory Parameters:		Required prior to the test		During the test		
Ambient Temperature		15 to 35 °C		23°C		
Relative Humidity		30 to 60 %		41%		
Test according referenced standards		Reference Method				
		ANSI C63.4				
Sample is tested with respect to the requirements of the equipment class		Equipment class				
		Class B				
Test frequency range determined from highest emission frequency		Highest emission frequency				
		925 MHz				
Fully configured sample scanned over the following frequency range		Frequency range				
		30 MHz to 18 GHz				
Operating mode		1				
Configuration		1 & 2				
Limits and results Class B						
Frequency [MHz]	Quasi-Peak [dBµV/m]	Result	Average [dBµV/m]	Result	Peak [dBµV/m]	Result
30 – 88	40	PASS	-		-	-
88 – 216	43.5	PASS	-		-	-
216 – 960	46	PASS	-		-	-
960 – 1000	54	PASS	-		-	-
> 1000	-	-	54	PASS	74	PASS
Comments:						

Test Procedure:

The test site is in accordance with ANSI C63-4:2014 requirements and is listed by FCC.
The measurement procedure is as follows:

Exploratory measurement:

- The EUT was placed on a non-conductive table at a height of 0.8m.
- The EUT and support equipment, if needed, were set up to simulate typical usage.
- Cables, of type and length specified by the manufacturer, were connected to at least one port of each type and were terminated by a device or simulating load of actual usage.
- The antenna was placed at a distance of 3 or 10 m.
- The received signal was monitored at the measurement receiver.
 - Cables not bundled were manipulated within the range of likely arrangements to produce the highest emission amplitude
 - To maximize the suspected emissions the EUT is rotated 360 degrees. If the signal exceeds the previous amplitude, go back to the corresponding azimuth and manipulate the cables again for maximizing the emissions if possible.
 - Move the antenna from 1 to 4m to maximize the suspected highest amplitude signal.
- This procedure has to be performed in both antenna polarizations, horizontal and vertical.
- The arrangement of the equipment with the maximum emission level is shown on the setup picture at item 1.3.

Final measurement:


- The EUT was placed on a 0.8 m non-conductive table at a 3 m distance from the receive antenna. The antenna output was connected to the measurement receiver
- A biconical antenna was used for the frequency range 30 – 200 MHz, a logarithmic periodical antenna was used for the frequency range from 200 – 1000 MHz. Above one 1 GHz a Double Ridged Broadband Horn antenna was used. The antenna was placed on an adjustable height antenna mast
- The EUT and cable arrangement were based on the exploratory measurement results
- Emissions were maximized at each frequency by rotating the EUT and adjusting the receive antenna height and polarization. The maximum values were recorded.
- The test data of the worst-case conditions were recorded and shown on the next pages.

Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3m
Mode:	1
Test Date:	2016-01-19
Note:	

Index 21




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3m
Mode:	1
Test Date:	2016-01-19
Note:	

Index 20




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant: Kamstrup A/S
 EUT Name: READy Converter for Australia
 Model: READy Converter
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Marquardt
 Test Conditions: Tnom: 23°C, Unom: 5 VDC (via USB)
 Antenna: Rohde & Schwarz HL 223, Horizontal
 Measurement distance: 3m
 Mode: 1
 Test Date: 2016-01-19
 Note: Peak 6: SRD Carrier

Index 18



Peak Number	Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status	Angle	Height
1	854.642 MHz	43.7 dBµV/m	46 dBµV/m	-2.3 dB	Pass	0 Degree	1 m
2	854.036 MHz	39.68 dBµV/m	46 dBµV/m	-6.32 dB	Pass	0 Degree	1 m
3	855.944 MHz	35.97 dBµV/m	46 dBµV/m	-10.03 dB	Pass	0 Degree	1 m
4	857.564 MHz	33.95 dBµV/m	46 dBµV/m	-12.05 dB	Pass	0 Degree	1 m
5	858.68 MHz	40.65 dBµV/m	46 dBµV/m	-5.35 dB	Pass	0 Degree	1 m
6	924.8 MHz					0 Degree	1 m

Test Report No.: G0M-1511-5232-EF0115B-V02


Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant: Kamstrup A/S
 EUT Name: REAdy Converter for Australia
 Model: REAdy Converter
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Marquardt
 Test Conditions: Tnom: 23°C, Unom: 5 VDC (via USB)
 Antenna: Rohde & Schwarz HL 223, Vertical
 Measurement distance: 3m
 Mode: 1
 Test Date: 2016-01-19
 Note: Peak 6: SRD Carrier

Index 19




Peak Number	Frequency	Quasi-Peak	Quasi-Peak Limit	Quasi-Peak Difference	Quasi-Peak Status	Angle	Height
1	853.304 MHz	38.7 dBµV/m	46 dBµV/m	-7.3 dB	Pass	0 Degree	1 m
2	854.318 MHz	43.99 dBµV/m	46 dBµV/m	-2.01 dB	Pass	0 Degree	1 m
3	855.584 MHz	41.95 dBµV/m	46 dBµV/m	-4.05 dB	Pass	0 Degree	1 m
4	856.994 MHz	38.11 dBµV/m	46 dBµV/m	-7.89 dB	Pass	0 Degree	1 m
5	858.356 MHz	39.57 dBµV/m	46 dBµV/m	-6.43 dB	Pass	0 Degree	1 m
6	924.8 MHz					0 Degree	1 m

Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant: Kamstrup A/S
 EUT Name: READy Converter for Australia
 Model: READy Converter
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Marquardt
 Test Conditions: Tnom: 23°C, Unom: 5 VDC (via USB)
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3m
 Mode: 1
 Test Date: 2016-01-19
 Note: Peak 1: SRD 2nd Harmonic

Index 17




Peak Number	Frequency	Average	Average Limit	Average Difference	Average Status	Angle	Height
1	1.85 GHz	59.24 dBµV/m	54 dBµV/m	5.24 dB	Fail	0 Degree	1 m

Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	1
Test Date:	2016-01-19
Note:	

Index 16




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	1
Test Date:	2016-01-19
Note:	

Index 14




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	1
Test Date:	2016-01-19
Note:	

Index 15




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	1
Test Date:	2016-01-19
Note:	

Index 12




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	1
Test Date:	2016-01-19
Note:	

Index 13




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 1




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 2




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 5




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 3




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 7




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 8




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 10




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 9




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 13




Spurious emissions under normal conditions according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 5 VDC (via USB)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	2
Test Date:	2016-01-18
Note:	

Index 14



3.2 Test Conditions and Results – AC power line conducted emissions

Conducted emissions acc. FCC 47 CFR 15.107 / ICES-003			Verdict: PASS	
Laboratory Parameters:	Required prior to the test	During the test		
Ambient Temperature	15 to 35 °C	23°C		
Relative Humidity	30 to 60 %	41%		
Test according referenced standards	Reference Method			
	ANSI C63.4			
Fully configured sample scanned over the following frequency range	Frequency range			
	0.15 MHz to 30 MHz			
Sample is tested with respect to the requirements of the equipment class	Equipment class			
	Class B			
Points of Application	Application Interface			
AC Mains	LISN			
Operating mode	1			
Configuration	2			
Limits and results Class B				
Frequency [MHz]	Quasi-Peak [dBµV]	Result	Average [dBµV]	Result
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS
0.5 to 5	56	PASS	46	PASS
5 to 30	60	PASS	50	PASS
Limits and results Class A				
Frequency [MHz]	Quasi-Peak [dBµV]	Result	Average [dBµV]	Result
0.15 to 5	79	PASS	66	PASS
5 to 30	73	PASS	60	PASS
Comments:				
* Limit decreases linearly with the logarithm of the frequency.				

Test Procedure:

The test site is in accordance with ANSI C63-4:2014 requirements and is listed by FCC.
The measurement procedure is as follows:

Exploratory measurement:

- The EUT was placed on a non conductive table 0.8 m above the reference ground plane and 0.4 m away from the vertical conducting plane (ANSI C63.4: 2009 item 7.3.1)
- The power cord that is normally supplied or recommended by the manufacturer was connected to the LISN.
- The distance between the outer edge of the EUT and the LISN shall be set to 0.8 m. A longer power cord shall be bundled to this length (bundling shall not exceed 40 cm in length).
- The LISN measurement port was connected to a measurement receiver
- I/O cables were bundled not longer than 0.4 m
- Measurement was performed in the frequency range 0.15 – 30MHz on each current-carrying conductor
- To maximize the emissions the cable positions were manipulated
- The worst configuration of EUT and cables is shown on a test setup picture at item 1.3

Test Procedure:

Final measurement:


- The EUT was placed on a non conductive table 0.8 m above the reference ground plane and 0.4 m away from the vertical conducting plane (ANSI C63.4: 2009 item 7.3.1)
- The power cord that is normally supplied or recommended by the manufacturer was connected to the LISN.
- The distance between the outer edge of the EUT and the LISN shall be set to 0.8 m. A longer power cord shall be bundled to this length (bundling shall not exceed 40 cm in length).
- The LISN measurement port was connected to a measurement receiver
- The EUT and cable arrangement were based on the exploratory measurement results
- The test data of the worst-case conditions were recorded and shown on the next pages.

EMI voltage test in the ac-mains according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 120VAC / 5 VDC (via USB)
LISN:	ESH2-Z5 N
Mode:	1
Test Date:	2016-01-19
Note:	

Index 22



EMI voltage test in the ac-mains according to FCC Part 15 B

Project number: G0M-1512-5232

Applicant:	Kamstrup A/S
EUT Name:	READY Converter for Australia
Model:	READY Converter
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Marquardt
Test Conditions:	Tnom: 23°C, Unom: 120 VAC / 5 VDC (via USB)
LISN:	ESH2-Z5 L
Mode:	1
Test Date:	2016-01-19
Note:	

Index 23

