

Deere & Company / MA4M

Page: 1 of 6

# RF Exposure Report

Project Number: 4975321 Proposal: SUW-202108001433

Report Number: 4975321EMC13 Revision Level: 2

Client: Deere & Company

Equipment Under Test: JDLink™ M Modem - 4G

Model Number: MA4M

FCC ID: OV5-MA4M

Applicable Standards: 47 C.F.R. §§ 2.1091; FCC KDB 447498

**FCC OET Bulletin 65 Supplement** 

Report issued on: 19 December 2022

Test Result: Compliant



FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER: 3212.01
Report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

Prepared by:

Brandon Osborn, EMC/RF Project Engineer

Reviewed by:

Stephen Whalen, EMC/SAR Manager

Stote CWhal

Remarks: This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com//en/Terms-and-Conditions.aspx. And for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/terms-e-document.aspx.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for a maximum of 30 days only.



Deere & Company / MA4M

Page: 2 of 6

### **TABLE OF CONTENTS**

1	GEN	NERAL INFORMATION
	1.1	CLIENT INFORMATION
	1.2	TEST LABORATORY
	1.3	GENERAL INFORMATION OF EUT
	1.4	OPERATING MODES AND CONDITIONS
_		
2	RF	EXPOSURE2
	2.1	TEST RESULT
	2.2	TEST METHOD
	2.3	SINGLE TRANSMISSION RF EXPOSURE LEVELS
	2.4	SIMULTANEOUS TRANSMISSION RF EXPOSURE LEVELS
		VISION HISTORY
2	DEA	IIION HISTODY



Deere & Company / MA4M

Page: 3 of 6

### 1 General Information

### 1.1 Client Information

Name: Deere & Company dba John Deere Intelligent Solutions

Address: 9505 Northpark Drive

City, State, Zip, Country: Urbandale, IA 50131 USA

### 1.2 Test Laboratory

Name: SGS North America, Inc.

Address: 620 Old Peachtree Road NW, Suite 100

City, State, Zip, Country: Suwanee, GA 30024, USA

Accrediting Body: A2LA

Type of lab: Testing Laboratory

Certificate Number: 3212.01

#### 1.3 General Information of EUT

Product Description: JDLink™ M Modem - 4G

Model Number: MA4M

Serial Number: PCMA4MA101508

Modes of Operation: LTE Bands 2/4/5/7/12/13/26/38/41/66

WCDMA Bands II / IV / V

GSM 850 / 1900

802.11 b/g/nHT20/nHT40

BT GFSK/ Pi/4DQPSK/8DPSK/LE

Antenna Type: Internal Proprietary

IMEI: 351072640039594

Sample Received Date: 24 October 2022

Dates of testing: 5-14 November 2022

\*Data was not measured by SGS laboratory and therefore not responsible for accuracy. Data obtained via customer, specification sheet, previous regulatory filing or other.

## 1.4 Operating Modes and Conditions

For this assessment, the EUT's maximum power including the maximum tolerance was considered.

SGS North America Inc.



Deere & Company / MA4M

Page: 4 of 6

# 2 RF Exposure

### 2.1 Test Result

Test Description	Product Specific Standard	Test Result
RF Exposure	FCC Part 1.1310	Compliant

### 2.2 Test Method

Using the maximum power (including tune-up tolerances), the power density was calculated. Maximum antenna gain was assumed for this exercise.

### 2.3 Single transmission RF Exposure Levels

Band of Operation	Band of Operation		Antenna Gain	Cable Loss	Averag	e EIRP	Distance (R)	Power Density EIRP <sub>Avg</sub> /(4πR²)	FCC	% of Limit	Verdict
Type	MHz	dBm			dBm	mW	cm	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>		
LTE Band 2	1850-1910	23.4	3.2	0.0	26.6	454	20	0.090	1.00	9.03%	Pass
LTE Band 4	1710-1755	23.8	4.1	0.0	27.9	614	20	0.122	1.00	12.2%	Pass
LTE Band 5	824-849	23.3	0.0	0.0	23.3	213	20	0.042	0.55	7.72%	Pass
LTE Band 7	2500-2570	22.4	4.2	0.0	26.6	457	20	0.091	1.00	9.09%	Pass
LTE Band 12	699-716	23.3	0.0	0.0	23.3	212	20	0.042	0.47	9.06%	Pass
LTE Band 13	777-787	23.1	0.5	0.0	23.6	230	20	0.046	0.52	8.82%	Pass
LTE Band 26	814-849	23.3	0.0	0.0	23.3	216	20	0.043	0.54	7.91%	Pass
LTE Band 38	2570-2620	23.2	4.2	0.0	27.4	546	20	0.109	1.00	10.86%	Pass
LTE Band 41	2496-2620	23.4	4.2	0.0	27.6	579	20	0.115	1.00	11.53%	Pass
LTE Band 66	1710-1780	23.5	4.1	0.0	27.6	571	20	0.114	1.00	11.37%	Pass
WCDMA Band II	1850-1910	20.1	3.2	0.0	23.3	216	20	0.043	1.00	4.29%	Pass
WCDMA Band IV	1710-1755	20.4	4.1	0.0	24.5	284	20	0.056	1.00	5.65%	Pass
WCDMA Band V	824-849	19.9	0.0	0.0	19.9	98	20	0.020	0.55	3.56%	Pass
GSM 850	824-849	25.0	0.0	0.0	25.0	318	20	0.063	0.55	11.51%	Pass
GSM 1900	1850-1910	21.8	3.2	0.0	25.0	313	20	0.062	1.00	6.22%	Pass
WLAN 2.4	2400-2483.5	17.8	4.0	0.0	21.8	151	20	0.030	1.00	3.01%	Pass
Bluetooth	2400-2483.5	5.1	4.0	0.0	9.1	8	20	0.002	1.00	0.16%	Pass
Bluetooth LE	2400-2483.5	2.8	4.0	0.0	6.8	5	20	0.001	1.00	0.10%	Pass

SGS North America Inc.



Deere & Company / MA4M

Page: 5 of 6

# 2.4 Simultaneous transmission RF Exposure Levels

Simultaneous Transmissions - Percent of Limit						
	WLAN 2.4	Bluetooth	Bluetooth LE			
LTE Band 2	7.2%	6.3%	6.2%			
LTE Band 4	8.5%	7.6%	7.5%			
LTE Band 5	11.8%	10.9%	10.8%			
LTE Band 7	12.0%	11.1%	11.0%			
LTE Band 12	14.0%	13.1%	13.0%			
LTE Band 13	12.7%	11.8%	11.7%			
LTE Band 26	27.0%	26.1%	26.0%			
LTE Band 38	15.2%	14.3%	14.1%			
LTE Band 41	15.2%	14.3%	14.1%			
LTE Band 66	8.5%	7.6%	7.5%			
WCDMA Band II	6.0%	5.1%	4.9%			
WCDMA Band IV	7.0%	6.1%	5.9%			
WCDMA Band V	9.7%	8.7%	8.6%			
GSM 850	20.7%	19.8%	19.7%			
GSM 1900	6.7%	5.8%	5.7%			
WLAN 2.4	-	1.3%	1.1%			
Bluetooth	1.3%					
Bluetooth LE	1.1%					

Note: Highlighted value only indicates worst-case.



Deere & Company / MA4M

Page: 6 of 6

# 3 Revision History

Revision Level	Description of changes	Revision Date
0	Initial release	19 December 2022
1	Added trademark symbol to name JDLink™	18 January 2023
2	Removed 2.1093 and 802.11a per the TCB comments Updated company name and address in section 1.1	16 February 2023

SGS North America Inc.