

Telemetry & Remote SCADA Solutions

FCC Part 15.212 Requirement	Comment/Declaration
(i) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	The radio elements have their own shielding.
(ii) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	Complies.
(iii) The modular transmitter must have its own power supply regulation.	Complies. Internal 2.8V regulation.
(iv) The modular transmitter must comply with the antenna and transmission system requirements of §§15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of §15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	Complies. RPSMA connection and documented antenna requirements.
(v) The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i> , the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)).	Does not comply. The unit was tested as not a stand-alone device.



Telemetry & Remote SCADA Solutions

omplies. The modular transmitter has a label fixed to the top of RF shielding.
omplies.
omplies.
he module 100250 is submitted for Limited fodular Approval (LMA). In keeping with CC Part 15.212 Unlicensed Modular ransmitter Approval, this letter affirms that ontrol Microsystems Inc. operating as chneider Electric shall retain complete control wer the final installation of the module in an ind-product and ensure compliance of the ind-product to FCC regulations. The module in all only be installed into an end-product by perators trained by Control Microsystems Inc. perating as Schneider Electric. The module in all not be distributed, marketed or sold to the eneral public. It will only be available installed in a complete Accutech end-product. The complete Accutech end-product shall only it is sold by Schneider Electric directly or arough a Schneider Electric specified sales thannel to authorized resellers.
he e s