

FCC Class II Permissive Change

On

Dual-band CDMA 800/1900 PCMCIA Card

	FCC Part 22 & 24	IC RSS 129 & RSS 133		
ID:	OVFKWC-KPC650	3572A-KPC650		
Original Grant Date:	September 29, 2004	September 29, 2004		
MODEL:	KPC-650			

STATEMENT OF COMPLIANCE

Kyocera Wireless Corp declares under its sole responsibility that the product, FCC ID: OVFKWC-KPC650 to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines. It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices.

Any deviations from these standards, guidelines and recommended practices are noted: NONE.

Date of Test:	December 3-10, 2004	
Test performed by:	Kyocera Wireless Corp. 10300 Campus Point Drive San Diego, Ca 92121	
Report Prepared by:	Fernando Calimbahin, Engineer	
Report Reviewed by:	C. K. Li, Engineer, Senior Staff/Manager	



Table of Contents

Tal	ble of	f Contents	2
1	Tes	t Summary	3
2	Tran	nsmitter RF Power Output	2
		·	
2	2.1	Conducted Power	3
2	2.2	Radiated Power	1



1 Test Summary

	RSS RSS 129 133			Results		
FCC Rule			Description	N/A	Passed	Remarks
2.1046			TX Conducted Power			
22.913 24.232	7.1	6.2	TX Radiated Power		✓	*See Nemko Report
2.1049			Occupied Bandwidth	✓		
2.1051			Block Edge Compliance	✓		
2.1051			Spurious Emissions At Antenna Terminals	✓		
2.1053	6.3, 8	6.3	Transmitter Radiated Spurious Emissions		✓	*See Nemko Report
2.1055			Transmitter RF Carrier Frequency Stability	✓		
2.1091 2.1093	11	8	Exposure of Humans to RF Fields (SAR)		✓	*See KPC650 C2PC SAR Report
15	10	9	RX Radiated Emissions		✓	*See Nemko Report

Notes: N/A: Product performance and specifications are not affected by the changes.

2 Transmitter RF Power Output

2.1 Conducted Power

FCC: § 2.1046	IC: RSS-129 §7.1, RSS-133 §6.2					
Measurement Procedures:						

The RF output power was measured using a Giga-tronics 8541C Universal Power Meter and HP 8594E Spectrum Analyzer that has the CDMA personality option. Terminated to a resistive coaxial load of 50 ohms.

Mode	Frequency (MHz)	Channel	Measured Power (dBm)
	824.70	1013	24.17
CDMA 800	836.52	384	24.22
	848.31	777	24.12
	1851.25	25	23.98
CDMA 1900	1880.00	600	24.08
	1908.75	1175	23.80

^{*:} Both configurations A (D064937) and B (D064923) were tested. Only the worst case configuration (A) data is reported.



Model: KPC-650

2.2 Radiated Power

FCC: § 22.913, § 24.232 IC: RSS-129 §7.1 and §9.1, RSS-133 §6.2

Measurement Procedures:

The radiated power test was performed at Nemko in San Diego, California. The test report is attached in a separate attachment.

Mode	Frequency (MHz)	Channel	FCC Filed Max. Power (dBm)	Measured Max. Power (dBm)	Ref.
	824.70	1013		22.99	
CDMA 800	836.52	384	25.30	22.98	ERP
	848.31	777		24.75	
	1851.25	25		23.46	
CDMA 1900	1880.00	600	24.18	23.61	EIRP
	1908.75	1175		24.09	