

**SAR Test Report on  
Single-Band CDMA Cellular Phone With Bluetooth**

<b>FCC Part 24 Certification</b>	
FCC ID:	<b>OVFKWC-M1000-2J0</b>
MODEL:	<b>M1000-2J0</b>
DATE:	<b>May 23, 2007</b>

<b>STATEMENT OF COMPLIANCE</b>	
<p>Kyocera Wireless Corp declares under its sole responsibility that the product, FCC ID: OVFKWC-M1000-2J0 to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines. It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices.</p> <p>Any deviations from these standards, guidelines and recommended practices are noted: NONE.</p>	
<b>Date of Test:</b>	May 17 – May 19, 2007
<b>Test performed by:</b>	Kyocera Wireless Corp. 10300 Campus Point Drive San Diego, CA 92121
<b>Report Prepared by:</b>	Thuy To, Regulatory Engineer
<b>Report Reviewed by:</b>	C.K. Li, Principal Hardware Engineer

## Table of Contents

<b>1</b>	<b>INTRODUCTION</b> .....	<b>3</b>
<b>2</b>	<b>EQUIPMENT UNDER TEST (EUT)</b> .....	<b>3</b>
<b>3</b>	<b>PRODUCT DESCRIPTION</b> .....	<b>4</b>
<b>4</b>	<b>ACCESSORIES:</b> .....	<b>4</b>
<b>5</b>	<b>SAR TEST RESULT SUMMARY</b> .....	<b>5</b>
5.1	MAXIMUM RESULTS FOUND DURING SAR EVALUATION.....	5
5.2	HEAD CONFIGURATION.....	5
5.3	BODY WORN CONFIGURATION (WITH KWC BODY WORN ACCESSORIES) .....	5
5.4	MEASUREMENT UNCERTAINTY .....	5
<b>6</b>	<b>TEST CONDITIONS</b> .....	<b>6</b>
6.1	AMBIENT CONDITIONS .....	6
6.2	RF CHARACTERISTICS OF THE TEST SITE .....	6
6.3	TEST SIGNAL, FREQUENCIES AND OUTPUT POWER .....	6
6.3.1	CDMA2000 Test conditions .....	6
6.4	DEVICE TEST CONDITIONS .....	7
<b>7</b>	<b>DESCRIPTION OF THE TEST EQUIPMENT</b> .....	<b>8</b>
7.1	DOSIMETRIC SYSTEM .....	8
7.2	ADDITIONAL EQUIPMENT NEEDED IN VALIDATION .....	9
7.3	TISSUE STIMULANTS .....	9
7.4	PHANTOMS DESCRIPTION.....	9
7.5	ISOTROPIC E-FIELD PROBE.....	10
<b>8</b>	<b>SYSTEM VALIDATION</b> .....	<b>11</b>
<b>9</b>	<b>DESCRIPTION OF THE TEST PROCEDURE</b> .....	<b>12</b>
9.1	TEST POSITIONS .....	12
9.1.1	Initial Ear Position.....	12
9.1.2	Cheek Position.....	13
9.1.3	Tilt Position.....	13
9.1.4	Body Worn Configuration.....	14
9.2	SCAN PROCEDURES .....	14
9.3	SAR AVERAGING METHODS.....	14
<b>10</b>	<b>MEASUREMENT UNCERTAINTY</b> .....	<b>15</b>
<b>11</b>	<b>TEST DATA</b> .....	<b>16</b>
11.1	HEAD SAR TEST RESULTS.....	16
11.2	BODY WORN SAR TEST RESULT .....	17
<b>12</b>	<b>LIST OF APPENDIX</b> .....	<b>18</b>

**1 INTRODUCTION**

This test report describes an environmental evaluation measurement of specific absorption rate (SAR) distribution in simulated human head tissues exposed to radio frequency (RF) radiation from a wireless portable device manufactured by Kyocera Wireless Corp. (KWC). These measurements were performed for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC). The testing was performed in accordance with FCC OET Bulletin 65 Supplement C (01/01) and IEEE P1528/D1.2 issued on April 21, 2003.

**2 EQUIPMENT UNDER TEST (EUT)**

The wireless device is described as follows:

<b>FCC ID:</b>	OVFKWC-M1000-2J0		
<b>Product:</b>	Single-Band 1XRTT CDMA Cellular Phone with Bluetooth		
<b>Trade Name:</b>	Kyocera Wireless Corp.		
<b>Model Number:</b>	M1000-2J0		
<b>EUT S/N:</b>	FFMK0000001439		
<b>Type:</b>	[ X ] Identical Prototype, [ ] Pre-production		
<b>Device Category:</b>	Portable		
<b>RF Exposure Environment:</b>	General Population / Uncontrolled		
<b>Antenna Type:</b>	Internal	<b>Antenna Location:</b>	Top of back side
<b>Detachable Antenna:</b>	No	<b>Antenna Dimensions (mm):</b>	47(L), 23(W), 8(H)
<b>External Input:</b>	Audio/Digital Data		
<b>Quantity:</b>	Quantity production is planned		
<b>FCC Rule Parts:</b>	§24H		
<b>Modes:</b>	1900 CDMA		
<b>Multiple Access Scheme:</b>	CDMA		
<b>Duty Cycle:</b>	1:1		
<b>TX Frequency (MHz):</b>	1850 - 1910		
<b>Emission Designators:</b>	1M25F9W		
<b>Max. Output Power (W):</b>	0.309 EIRP		

**3 PRODUCT DESCRIPTION**

The phones OVFKWC-M1000-2J0 are Single-Band 1XRTT CDMA Cellular products with Bluetooth.

The phones have assisted GPS software feature enabled to meet the emergency location requirements of the FCC’s E911 Phase II mandate. The CDMA architecture is defined as 1900MHz (PCS CDMA).

The phone is designed in compliance with the technical specifications for compatibility of mobile and base stations in the Cellular Radio telephone service contained in “Cellular System Mobile Station -Land Station Compatibility Specification” as specified in OET Bulletin 53 and TIA Standards

The phone will support certain CDMA2000 radio-configurations (RC) as describes in Exhibit 1 (operation description).

**4 ACCESSORIES:**

KWC Battery Model: Standard: CV90-N3344-01 (3.7V, 900mAh)	Mini Universal Pouch Model: CV90-61344-03
 <p data-bbox="316 1207 511 1239">900mAh Battery</p>	

**5 SAR TEST RESULT SUMMARY**

This device has been tested for localised specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1 ~ 1992 and has been tested in accordance with the measurement procedures specified in IEEE P1528\_D1.2. Normal antenna operating positions were incorporated, with the device transmitting at frequencies consistent with normal usage of the device. The device has been shown capable of compliance for localised specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE std. C95.1-1992

**5.1 Maximum Results Found during SAR Evaluation**

The equipment is deemed to fulfil the requirements if the measured values are less than or equal to the limit.

**5.2 Head Configuration**

Mode	Ch/f(MHz)	Conducted Power (dBm)	Device Position	Flip Position	Measured (mW/g)	Result
CDMA-1900	25 (1851.25)	22.51	Right Cheek	Closed	1.46	<b>PASSED</b>

**5.3 Body Worn Configuration (with KWC body worn accessories)**

Mode	Ch/f(MHz)	Conducted Power (dBm)	Device Position	Flip Position	Measured (mW/g)	Result
CDMA-1900	600 (1880)	22.71	Waist level	Closed	0.718	<b>PASSED</b>

**5.4 Measurement Uncertainty**

<b>Combined Uncertainty (Assessment &amp; Source)</b>	<b>± 10.46</b>
<b>Extended Uncertainty (k=2)</b>	<b>± 21.22</b>

**6 TEST CONDITIONS**

**6.1 Ambient Conditions**

All tests were performed under the following environmental conditions:

<b>Ambient Temperature:</b>	22 ± 1 Degrees C
<b>Tissue simulating liquid temperature:</b>	22 ± 1 Degrees C
<b>Humidity:</b>	38 %
<b>Pressure:</b>	1015 mB

**6.2 RF characteristics of the test site**

All SAR measurements were performed inside a shielded room that provide isolation from external EM fields.

The E-field probes of the DASY 4 system are capable of detecting signals as low as 5µW/g in the liquid dielectric. External fields are minimising by the shielded room, leaving the phone as the dominant radiation source. Two 2-foot square ferrite panels are placed on the floor of the room beneath the phantom area of the DASY system to minimise reflected energy that would otherwise re-enter the phantom and combine constructively or destructively with the desired fields. These ferrite panels provide roughly 12 to 13 dB of attenuation in the frequency range of 900 MHz, and 7 to 8 dB of attenuation in the frequency range of 1.9 GHz.

**6.3 Test Signal, Frequencies and Output Power**

In all operating bands, the measurements were performed on low, mid and high channels. The phone was set to nominal maximum power level during all tests and at the beginning of the each test.

DASY4 system measures power drift during SAR testing by comparing E-field in the same location at the beginning and at the end of measurement. These records were used to monitor stability of power output.

**6.3.1 CDMA2000 Test conditions**

The device supports CDMA2000 in 1X (Phase I, Protocol revision 6) mode only. CDMA2000 1X includes TIA/EIA-95B as a subset and was approved for publishing in July 1999. It provides voice and data capabilities within a standard 1.25 MHz CDMA channel. This RF bandwidth is identical to the legacy IS-95 B system standard.

**6.3.1.1 Head SAR Measurements**

SAR for head exposure configurations was measured in RC3 with the EUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 was not required when the maximum average output of each channel was less than ¼ dB higher than that measured in RC3. Otherwise, SAR was measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

**6.3.1.2 Body SAR Measurements**

SAR for body exposure configurations was measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCH<sub>n</sub>) was not required when the maximum average output of each RF channel was less than ¼ dB higher than that measured with FCH only. Otherwise, SAR was measured on the maximum output channel (FCH + SCH<sub>n</sub>) with FCH at full rate and SCH<sub>0</sub> enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels were enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts.

Body SAR in RC1 was not required when the maximum average output of each channel was less than ¼ dB higher than that measured in RC3. Otherwise, SAR was measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that resulted in the highest SAR for that channel in RC3.

Table 6.3 below shows the maximum power level vs RCs

CONFIGURATION	CONDUCTED POWER (dBm)		
	CDMA 1900		
	Ch 25	Ch 600	Ch 1175
	Avg	Avg	Avg
SO2, RC1 Full Rate	22.43	22.78	22.85
SO2, RC3 Full Rate	22.50	22.82	22.88
SO55, RC1 Full Rate	22.49	22.81	22.86
<b>SO55, RC3 Full Rate</b>	<b>22.51</b>	<b>22.85</b>	<b>22.90</b>
TDSO SO32, RC3 (FCH +SCH) Full Rate	22.00	22.71	22.40
TDSO SO32, RC3 (FCH) Full Rate	22.50	22.78	22.11

Table 6.3 RC Configuration tested at “all up” power control bit.

**6.4 Device Test Conditions**

The EUT was tested with a fully charged battery as supplied with the handset. Conducted RF power measurements were performed before and after each SAR measurements to confirm the output power.

**7 DESCRIPTION OF THE TEST EQUIPMENT**

**7.1 Dosimetric System**

The measurements were performed with an automated near-field scanning system (as shown in Figure 7.1), DASY4, manufactured by Schmid & Partner Engineering AG (SPEAG) of Zurich, Switzerland. The system is comprised of high precision robot, robot controller, computer, near-field probe, probe alignment sensor and the SAM phantom containing brain or muscle equivalent material. The overall RSS uncertainty of the measurement system is  $\pm 10.46\%$  with an expanded uncertainty of  $\pm 21.22\%$  (K=2). The measurement uncertainty budget is given in section 10. Below is a list of the calibrated equipment used for the measurements:

Test Equipment	Serial Number	Cal. Due Date
DASY4 DAE3	493	11-07-07
E-field Probe ET3DV6	1664	06-22-07
Dipole Validation kit, D1900V2	5d003	03-21-08

*The calibration records of E-field probe and dipoles are attached in Appendix C and Appendix D respectively.*




Figure 7.1 DASY 4 System



**7.2 Additional equipment needed in validation**

Test Equipment	Serial Number	Cal. Due Date
Signal Generator, Agilent E4438C	MY44270167	9-27-08
Power meter, Giga-tronics 8541C	1832552	01-31-08
Power Sensor, Giga-tronics 80601A	1830275	07-20-07
Serial Network Analyzer, E5062A	MY44100250	02-22-08
Thermometer	186700	04-22-08
Dielectric Probe, HP 85070E	--	No cal required

**7.3 Tissue Stimulants**

All dielectric parameters of tissue stimulants were measured within 24 hours of SAR measurements. The depth of the tissue stimulant in the ear reference point and flat reference point of the phantom were at least 15 cm. during all the tests. The depth of the liquid is measured by running a program that brings the probe to the bottom surface of the phantom then raise it up 15 centimeters. The operator at this point performs a visual inspection and makes sure that the liquid level is at or above the probe tip.

The list of ingredients and the percent composition used for the Head and Muscle tissue simulates are listed in the table below:

Ingredient	1900 MHz	
	HEAD	MUSCLE
Water	54%	69.91%
Cellulose	--	--
Glycol monobutyl	44.91%	29.96%
Sugar	--	--
Preventol	--	--
Salt	0.21%	0.13%


*The ingredients above are adopted from Application Note: Recipes for Head/Muscle Tissue Simulating Liquid by SPEAG.*

**7.4 Phantoms Description**

SAM v4.0 phantom, manufactured by SPEAG, was used during the measurement. It has fiberglass shell integrated in a wooden table. The shape of the shell corresponds to the phantom defined in IEEE 1528/D1.2. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. Reference markings on the phantom allow the complete set-up of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

The thickness of phantom shell is 2mm except for the ear, where an integrated ear spacer provides 6mm spacing from the tissue boundary. Manufacturer reports tolerance in shell thickness to be ± 0.1mm.

7.5 Isotropic E-Field Probe

<p><b>Model:</b></p>	<ul style="list-style-type: none"> <li>ET3DV6</li> </ul> 
<p><b>Construction:</b></p>	<ul style="list-style-type: none"> <li>Symmetrical design with triangular core</li> <li>Built-in optical fiber for surface detection system</li> <li>Built-in shielding against static charges</li> <li>PEEK enclosure material (resistant to organic solvents, e.g., glycol)</li> </ul>
<p><b>Calibration:</b></p>	<ul style="list-style-type: none"> <li>Calibration certificate in Appendix C</li> </ul>
<p><b>Frequency:</b></p>	<ul style="list-style-type: none"> <li>10MHz to 3GHz (dosimetry); Linearity: <math>\pm 0.2\text{dB}</math> (30MHz to 3GHz)</li> </ul>
<p><b>Optical Surface:</b></p>	<ul style="list-style-type: none"> <li><math>\pm 0.2\text{mm}</math> repeatability in air and clear liquid over diffuse reflecting</li> </ul>
<p><b>Detection:</b></p>	<ul style="list-style-type: none"> <li>Surface</li> </ul>
<p><b>Directivity:</b></p>	<ul style="list-style-type: none"> <li><math>\pm 0.2\text{dB}</math> in HSL (rotation around probe axis)</li> <li><math>\pm 0.4\text{dB}</math> in HSL (rotation normal to probe axis)</li> </ul>
<p><b>Dynamic Range:</b></p>	<ul style="list-style-type: none"> <li>5 uW/g to &gt; 100 mW/g; Linearity: <math>\pm 0.2\text{dB}</math></li> </ul>
<p><b>Dimensions:</b></p>	<ul style="list-style-type: none"> <li>Overall length: 330mm</li> <li>Tip length: 16mm</li> <li>Body diameter: 12mm</li> <li>Tip diameter: 6.8mm</li> <li>Distance from probe tip to dipole centers: 2.7mm</li> </ul>
<p><b>Application:</b></p>	<ul style="list-style-type: none"> <li>General dosimetry up to 3GHz</li> <li>Compliance tests of mobile phones</li> <li>Fast automatic scanning in arbitrary phantoms.</li> </ul>

**8 SYSTEM VALIDATION**

The probes are calibrated annually by the manufacturer. Dielectric parameters of the stimulating liquids are measured with an automated Hewlett Packard 85070E dielectric probe in conjunction with an Agilent E5062A ENA serial network analyser.

The SAR measurements of the device were done within 24 hours of system accuracy verification, which was done using the dipole validation kit. Power level of 20dBm was supplied to a dipole antenna placed under the flat section of SAM phantom. The validation results are in the table below and printouts of the validation test are attached in Appendix A. All the measured parameters are within the specification.

The system validation with head tissues was used for the device testing in muscle. Based on OET 65 Supplement C EAB Part 24 SAR review Reminder Sheet 01/2002, this is a valid test.

	Freq. (MHz)	Description	Validation SAR (mW/g), 1g	Dielectric Parameters		Temp. (°C)	Test date	Comments Validation testing -
				$\epsilon_r$	$\sigma$ (S/m)			
Tissue	1900	Measured	3.88	40.4	1.444	22 ± 1	05-18-07	For device testing in Head
		SPEAG Reference	3.89	39.40	1.42	22 ±0.2	3-21-06	From Speag Certificate
		FCC Reference*	--	40.0	1.40	20-26	--	
	1900	Measured	3.94	53.20	1.47	22 ± 1	05-18-07	For device testing in Muscle
		Measured	3.99	54	1.46	22 ± 1	05-19-07	For device testing in Muscle
		SPEAG Reference	4.04	54.70	1.54	22 ±0.2	03-21-06	From Speag Certificate
		FCC Reference*	--	53.3	1.52	20-26	--	

*FCC reference values are adopted from OET Bulletin 65 (97-01) Supplement C (01-01).*

**9 DESCRIPTION OF THE TEST PROCEDURE**

Measurements were made on both left hand side and right hand side of the phantom.

The device was position against phantom according to OET Bulletin 65 (97-01) Supplement C (01-01). Definitions of terms used in aligning the device to a head phantom are available in IEEE Standard P1528/D1.2 “Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques”

**9.1 Test Positions**

The device was placed in the holder. The bottom of the device aligns with the bottom of the holder clamp to provide a standard positioning and ensure enough free space for antenna.

Device holder was provided by SPEAG together with DASY4.

**9.1.1 Initial Ear Position**

The device was initially positioned with the earpiece region pressed against the ear spacer of a head phantom parallel to the “Neck-Front” (N-F) line defined along the base of the ear spacer that contains the “Ear Reference Point” (ERP). The “test device reference point” (point A) is aligned to the ERP on the head phantom and the “vertical centerline” is aligned to the “phantom reference plane”.




Figure 7-1 – Handset vertical and horizontal reference lines.




Figure 7-2 - Close up side view of phantom showing the ear region.

**9.1.2 Cheek Position**

“Initial ear position” alignments are maintained and the device is brought toward the mouth of the head phantom by pivoting along the “Neck-Front” line until any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom or when any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.




Figure 7.3 - Phone position 1, “cheek” or “touch” position.

**9.1.3 Tilt Position**

In the “cheek position”, if the earpiece of the device is not in full contact with the phantom’s ear spacer and the peak SAR location for the “cheek position” is located at the ear spacer region or corresponds to the earpiece region of the handset, the device is returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer. Otherwise, the device is moved away from the cheek perpendicular to the line passes through both “ear reference points” for approximate 2-3cm. While it is in this position, the device is tilted away from the mouth with respect to the “test device reference point” by 15°. After the tilt, it is then moved back toward the head perpendicular to the line passes through both “ear reference point” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process is repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously.




Figure 7.3 - Phone position 2, “tilted” position.

#### 9.1.4 Body Worn Configuration

KWC body worn accessories were tested for the FCC RF exposure compliance. The device was positioned into the carrying case and placed below the flat phantom. Hands-free headset was connected during measurements.

The SAR levels were also measured with 15.0mm air space for the hands-free application, which allow user to use other body-worn holster that contains no metal and provides at least 15.0mm separation from the closest point of the handset to the body.

#### 9.2 Scan Procedures

First, coarse scans are used for a quick determination of the field distribution. Then an area scan measures all reachable points, it computes all of the field maxima found in the scanned area, within a range of 2dB as specified in IEEE P1528, (see the configuration below). For cases where multiple maxima were detected, the number of zoom scans could be increased accordingly.

Next a cube scan, 7x7x7 points (spacing between each point is 5x5x5mm), is performed around the highest E-field value to determine the averaged SAR-distribution over 1g. If two peaks are within 2dB of the highest one, two zoom scans are performed to provide the evaluations. A fine resolution volume scan determines the one-gram average SAR for both peaks.

#### 9.3 SAR Averaging Methods

The maximum SAR value is average over its volume using interpolation and extrapolation.

The interpolation of the points is done with a 3d-Spline. The 3d-Spline is composed of three one-dimensional splines with the "Not a knot" –condition [W. Gander, Computermathematik, p. 141-150] (x, y and z – directions) [numerical Recipes in C, Second Edition, p 123].

The extrapolation is based on least square algorithm [W. Gander, Computermathematik, p. 168-180]. Through the points in the first 30mm in all z-axis, polynomials of order four are calculated. This polynomial is then used to evaluate the points between the surface and the probe tip. The points, calculated from the surface, have a distance of 1mm from one another.

**10 MEASUREMENT UNCERTAINTY**

Description of individual measurement uncertainty

Uncertainty Description	Uncert. Value (± %)	Prob. Dist.	Div	C <sub>i</sub> <sup>1</sup> 1g	Stand. Uncert (1g) (±%)	V <sub>i</sub> <sup>2</sup> or V <sub>eff</sub>
<b>Measurement system</b>						
Probe calibration	4.8	N	1	1	4.8	∞
Axial isotropy	4.7	R	√3	0.7	1.9	∞
Hemispherical Isotropy	9.6	R	√3	0.7	3.9	∞
Boundary effects	1.0	R	√3	1	0.6	∞
Linearity	4.7	R	√3	1	1.0	∞
System Detection limit	1.0	R	√3	1	0.5	∞
Readout Electronics	1.0	N	1	1	1.0	∞
Response Time	0.8	R	√3	1	0.5	∞
Integration Time	2.6	R	√3	1	1.5	∞
RF ambient conditions	3.0	R	√3	1	1.7	∞
Mech. Constrains of robot	0.4	R	√3	1	0.2	∞
Probe positioning	2.9	R	√3	1	1.7	∞
Extrapolation, integration and Integration Algorithms for Max. SAR Evaluation	1.0	R	√3	1	0.6	∞
<b>Test Sample Related</b>						
Device positioning	3.0	N	1	1	3.0	∞
Device Holder	3.0	N	1	1	3.0	∞
Power drift	7.0	N	√3	1	4.0	∞
<b>Phantom and setup</b>						
Phantom uncertainty	4.0	R	√3	1	2.3	∞
Liquid conductivity (target)	5.0	R	√3	0.6	1.7	∞
Liquid conductivity (meas.)	5.0	N	1	0.6	3.0	∞
Liquid permittivity (target)	5.0	R	√3	0.6	1.7	∞
Liquid permittivity (meas.)	5.0	N	1	0.6	1.5	∞
<b>Combined Standard Uncertainty:</b>					<b>10.46</b>	
<b>Extended Standard Uncertainty (k=2):</b>					<b>21.22</b>	

N: Normal  
R: Rectangular

11 TEST DATA

11.1 Head SAR Test Results

The following tables list the SAR results in each configuration and operating mode. The channels tested for each configuration have similar SAR distributions. Highest SAR (bold blue color) plots for each configuration is provided in Appendix B.

M1000-2J0 CDMA 1900 HEAD		Channel:				
		25		600	1175	
		Frequency (MHz):				
		1851.25		1880	1908.75	
Configuration	Test Position	Flip Position	Antenna Position	SAR, 1g (W/kg)		
RC3-SO55	Left Cheek/Touch	Closed	Fixed	1.26	<b>1.30</b>	1.18
	Left Ear/Tilt	Closed	Fixed	0.762	0.882	<b>0.976</b>
	Right Cheek/Touch	Closed	Fixed	<b>1.46</b> /*1.41	1.42	1.14
	Right Ear/Tilt	Closed	Fixed	1.10	<b>1.32</b>	0.867

Note: If the SAR measured at the mid-channel is at least 3dB lower than the SAR limit, testing at the low and high channels were no longer performed.

Note 2: Phone operates at head position at closed configuration only.

\* Means the phone was tested with Bluetooth on.



**11.2 Body Worn SAR Test Result**

For each mode, corresponding SAR distribution printouts of maximum results per accessory (in blue below), i.e., the device was tested with a 15mm air gap and with a KWC universal pouch are shown in Appendix B. The rest of SAR distributions are substantially similar or equivalent to the plots submitted regardless of used channel.

**Waist Level SAR with KWC Body Worn Accessories**

<b>CDMA 1900 BODY</b>		Channel:			25	600	1175
		Frequency (MHz):			1851.25	1880	1908.75
Accessory	Configuration	Test Position	Flip Position	Phone Position	SAR, 1g (W/kg)		
<b>Air Gap - 15mm</b>	RC1 – SO55	Flat	Closed	Face Down			0.618
	RC3 – SO32 (FCH)	Flat	Closed	Face Down		0.712	
	RC3 – SO32 (FCH + SCH)	Flat	Closed	Face Down		<b>0.718</b> /0.639 *	

<b>CDMA 1900 BODY</b>		Channel:			25	600	1175
		Frequency (MHz):			1851.25	1880	1908.75
Accessory	Configuration	Test Position	Flip Position	Phone Position	SAR, 1g (W/kg)		
<b>Universal Pouch (CV90-61344-03)</b>	RC1 – SO55	Flat	Closed <sup>2)</sup>	Face Down			0.238
	RC3 – SO32 (FCH)	Flat	Closed <sup>2)</sup>	Face Down		0.266	
	RC3 – SO32 (FCH + SCH)	Flat	Closed <sup>2)</sup>	Face Down		<b>0.286</b>	

Note: If the SAR measured at the mid-channel is at least 3dB lower than the SAR limit, testing at the low and high channels were no longer performed.

Note 2: Phone operates at closed configuration only when in pouch.

\* Means the phone was tested with Bluetooth on.

## 12 LIST OF APPENDIX

Appendix	Description	Note
A	Validation Test Plots	<i>Please see separate attachment</i>
B	SAR Distribution Plots	<i>Please see separate attachment</i>
C	Probe Calibration Parameters	<i>Please see separate attachment</i>
D	Dipole Calibration Parameters	<i>Please see separate attachment</i>
E	EUT Setup Photos	<i>Please see separate attachment</i>