



No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM120700418803
Page: 1 of 27

FCC REPORT

Application No.:

SZEM1207004188RF

Applicant:

Million concept electronic (shenzhen) CO., LTD

Manufacturer:

Million concept electronic (shenzhen) CO., LTD

Factory:

Million concept electronic (shenzhen) CO., LTD

Product Name:

Hart Rate Monitor System

Model No.(EUT):

BELT

FCC ID:

OVJ-BELT

Standards:

47 CFR Part 15, Subpart C (2012)

Date of Receipt:

2012-07-26

Date of Test:

2012-11-19 to 2013-04-08

Date of Issue:

2013-06-09

Test Result:**PASS ***

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	N/A
Field Strength of the Fundamental Signal	47 CFR Part 15, Subpart C Section 15.249 (a)	ANSI C63.10 (2009)	PASS
Spurious Emissions	47 CFR Part 15, Subpart C Section 15.249 (a)/15.209	ANSI C63.10 (2009)	PASS
Band edge (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.249(a)/15.205	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.215 (c)	ANSI C63.10 (2009)	PASS

Remark:

N/A: In this while report not applicable

Note: Due to the EUT is powered by the battery only, the AC Power Line Conducted Emission is not applicable.

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST ENVIRONMENT AND MODE	5
4.4 DESCRIPTION OF SUPPORT UNITS	5
4.5 TEST LOCATION	5
4.6 TEST FACILITY	6
4.7 DEVIATION FROM STANDARDS	6
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
4.10 EQUIPMENT LIST	7
5 TEST RESULTS AND MEASUREMENT DATA	11
5.1 ANTENNA REQUIREMENT	11
5.2 RADIATED SPURIOUS EMISSIONS	12
5.2.1 <i>Field Strength Of The Fundamental Signal</i>	14
5.2.2 <i>Spurious Emissions</i>	15
5.3 BAND EDGE (RADIATED EMISSION)	19
5.4 20dB BANDWIDTH	25-27

4 General Information

4.1 Client Information

Applicant:	Million concept electronic (shenzhen) CO., LTD
Address of Applicant:	No. 98, Xiashanmen road, Songgan Town, Baoan District, Shenzhen City 518105, Guangdong, China
Manufacturer:	Million concept electronic (shenzhen) CO., LTD
Address of Manufacturer:	No. 98, Xiashanmen road, Songgan Town, Baoan District, Shenzhen City 518105, Guangdong, China
Factory:	Million concept electronic (shenzhen) CO., LTD
Address of Factory:	No. 98, Xiashanmen road, Songgan Town, Baoan District, Shenzhen City 518105, Guangdong, China

4.2 General Description of EUT

Product Name:	Hart Rate Monitor System
Model No.:	BELT
Trade Mark:	Myzone
Channels Frequencies:	2410MHz, 2457MHz, 2473MHz, 2479MHz
Modulation Type:	GFSK
Number of Channels:	4
Sample Type:	Portable production
Antenna Type:	PCB
Antenna Gain:	0dBi
Power Supply:	3.0V DC (3.0V x 1 "CR2032"Button cells)
Test Voltage:	3.0V DC
Remark:	New battery be used during all the measurement

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel(CH1)	2410MHz
The Middle channel(CH20)	2457MHz
The Highest channel(CH39)	2479MHz

4.3 Test Environment and Mode

Operating Environment:	
Temperature:	23.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1020mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode.

4.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Hart rate signal generator	Million concept electronic	V 1.1

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.



4.10 Equipment List

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2013-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2013-05-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2013-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2013-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2013-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2013-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2013-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2013-05-59
10	Coaxial cable	SGS	N/A	SEL0189	2013-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2013-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
13	Band filter	Amindeon	82346	SEL0094	2013-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2013-05-24
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2013-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2013-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2013-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2013-06-04

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2014-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2014-05-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2013-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2013-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2013-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2014-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2013-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2014-05-59
10	Coaxial cable	SGS	N/A	SEL0189	2014-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2014-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2014-05-29
13	Band filter	Amindeon	82346	SEL0094	2014-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2014-05-24
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2013-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2014-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2013-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2014-06-04

RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2013-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2013-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2013-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2013-05-24
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2013-05-16
8	Band filter	amideon	82346	SEL0094	2013-05-16
9	POWER METER	R & S	NRVS	SEL0144	2013-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2013-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2013-10-24




RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2013-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2013-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2014-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2014-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2014-05-24
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2014-05-16
8	Band filter	amideon	82346	SEL0094	2014-05-16
9	POWER METER	R & S	NRVS	SEL0144	2014-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2014-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2013-10-24

Note: The calibration interval is one year, all the instruments are valid.

5 Test results and Measurement Data


5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
EUT Antenna:	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



5.2 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.249 and 15.209				
Test Method:	ANSI C63.10: 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Spurious Emissions)	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	2400MHz-2483.5MHz	94.0		Average Value	
		114.0		Peak Value	



Test Procedure:	<ol style="list-style-type: none"> a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
-----------------	---

	g. Test the EUT in the lowest channel, the middle channel, the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report. i. Repeat above procedures until all frequencies measured was complete.
Instruments Used:	Refer to section 4.10 for details
Test Mode:	Transmitting mode
Test Results:	Pass

Measurement Data

5.2.1 Field Strength Of The Fundamental Signal

Peak value:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2410.100	2.99	32.54	39.86	98.88	94.55	114	-19.45	Horizontal
2410.100	2.99	32.54	39.86	99.88	95.55	114	-18.45	Vertical
2457.000	3.01	32.64	39.91	98.08	93.82	114	-20.18	Horizontal
2457.000	3.01	32.64	39.91	99.19	94.93	114	-19.07	Vertical
2478.950	3.03	32.67	39.92	98.89	94.67	114	-19.33	Horizontal
2478.950	3.03	32.67	39.92	101.75	97.53	114	-16.67	Vertical

Average value:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Average value (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2410.100	2.99	32.54	39.86	82.41	78.08	94	-15.92	Horizontal
2410.100	2.99	32.54	39.86	83.41	79.08	94	-14.92	Vertical
2457.000	3.01	32.64	39.91	81.61	77.35	94	-16.65	Horizontal
2457.000	3.01	32.64	39.91	82.72	78.46	94	-15.54	Vertical
2478.950	3.03	32.67	39.92	82.42	78.20	94	-15.80	Horizontal
2478.950	3.03	32.67	39.92	85.28	81.06	94	-12.94	Vertical


5.2.2 Spurious Emissions

30MHz~1GHz

Test mode: Transmitting mode


QP value:

Vertical:



Freq	Cable		Antenna	Preamp	Read	Limit	Line	Over
	Loss	Factor	Factor	Level	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	56.190	0.80	6.43	27.28	38.45	18.41	40.00	-21.59
2	118.270	1.25	7.63	27.08	42.68	24.47	43.50	-19.03
3	191.020	1.39	6.84	26.73	51.61	33.11	43.50	-10.39
4	269.590	1.77	8.90	26.48	42.64	26.82	46.00	-19.18
5	474.260	2.50	13.30	27.58	41.81	30.03	46.00	-15.97
6	935.980	3.64	20.63	26.61	38.64	36.30	46.00	-9.70

Horizontal:



Condition : 47 CFR PART 15 B 3m 3142C NEW HORIZONTAL

Job No. : 4188RF

Freq	Cable	Antenna	Preamp	Read	Limit	Over		
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	33.880	0.60	14.90	27.34	29.06	17.21	40.00	-22.79
2	159.980	1.34	9.50	26.86	41.58	25.56	43.50	-17.94
3	191.020	1.39	6.84	26.73	47.37	28.87	43.50	-14.63
4	257.950	1.71	8.90	26.51	54.07	38.18	46.00	-7.82
5	462.620	2.46	13.33	27.52	46.20	34.48	46.00	-11.52
6	749.740	3.06	17.30	27.35	39.37	32.38	46.00	-13.62



Above 1GHz								
Test mode:		Transmitting	Test channel:	2410MHz	Detector:		Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Average Limit (dBuV/m)	Over Limit (dB)	Polarization
1593.340	2.58	28.84	39.39	49.41	41.44	54	-12.56	Vertical
3367.661	3.62	33.26	40.58	45.79	42.09	54	-11.91	Vertical
4536.000	4.52	35.14	41.43	46.63	44.86	54	-9.14	Vertical
7063.693	5.60	35.83	40.00	47.69	49.12	54	-4.88	Vertical
8637.084	6.17	36.31	38.64	46.21	50.05	54	-3.95	Vertical
11872.880	6.44	38.78	38.22	45.12	52.12	54	-1.88	Vertical
1593.340	2.58	28.84	39.39	51.30	43.33	54	-10.67	Horizontal
3776.385	3.98	33.53	40.87	47.75	44.39	54	-9.61	Horizontal
5191.168	4.84	34.60	41.62	48.60	46.42	54	-7.58	Horizontal
7781.104	6.22	36.00	39.38	47.29	50.13	54	-3.87	Horizontal
9759.591	5.98	37.46	37.66	43.93	49.71	54	-4.29	Horizontal
11027.980	6.23	38.49	37.88	45.73	52.57	54	-1.43	Horizontal

Test mode:		Transmitting	Test channel:	2457MHz	Detector:		Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Average Limit (dBuV/m)	Over Limit (dB)	Polarization
1406.496	2.45	27.94	39.31	44.92	36.00	54	-18.00	Vertical
1963.180	2.81	31.55	39.55	45.61	40.42	54	-13.58	Vertical
3662.775	3.87	33.41	40.79	47.38	43.87	54	-10.13	Vertical
5776.922	5.05	35.34	41.12	48.25	47.52	54	-6.48	Vertical
7663.165	6.23	36.00	39.48	46.80	49.55	54	-4.45	Vertical
8814.774	6.16	36.45	38.49	44.93	49.05	54	-4.95	Vertical
1442.758	2.48	28.01	39.33	44.02	35.18	54	-18.82	Horizontal
1870.490	2.75	30.81	39.51	44.58	38.63	54	-15.37	Horizontal
3561.636	3.79	33.28	40.72	46.61	42.96	54	-11.04	Horizontal
5603.126	4.99	35.07	41.27	46.87	45.66	54	-8.34	Horizontal
7245.810	5.83	35.90	39.84	45.99	47.88	54	-6.12	Horizontal
10778.210	6.17	38.41	37.77	44.39	51.20	54	-2.80	Horizontal

Test mode:		Transmitting		Test channel:		2479MHz	Detector:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Average Limit (dBuV/m)	Over Limit (dB)	Polarization	
1593.340	2.58	28.84	39.39	55.36	47.39	54	-6.61	Vertical	
3176.155	3.46	33.33	40.44	48.31	44.66	54	-9.34	Vertical	
4582.422	4.55	35.06	41.47	48.17	46.31	54	-7.69	Vertical	
6347.466	5.22	36.12	40.63	48.08	48.79	54	-5.21	Vertical	
7880.772	6.21	36.00	39.29	47.62	50.54	54	-3.46	Vertical	
9960.375	5.98	37.67	37.48	46.25	52.42	54	-1.58	Vertical	
1593.340	2.58	28.84	39.39	50.80	42.83	54	-11.17	Horizontal	
2008.676	2.84	31.80	39.57	47.63	42.70	54	-11.30	Horizontal	
4478.633	4.48	35.15	41.39	47.20	45.44	54	-8.56	Horizontal	
6478.053	5.25	36.26	40.51	47.17	48.17	54	-5.83	Horizontal	
8042.903	6.20	36.01	39.15	47.36	50.42	54	-3.58	Horizontal	
11370.050	6.31	38.43	38.02	45.67	52.39	54	-1.61	Horizontal	

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) The disturbance range 9kHz~ 30MHz and 13GHz~25GHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 3) All of radiated spurious emission peak level under average limit, and peak limit- average limit =20dB, so all of average level should be passed.

5.3 Band edge (Radiated Emission)

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205																						
Test Method:	ANSI C63.10: 2009																						
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																						
Limit(band edge):	<p>Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.</p> <table border="1"> <thead> <tr> <th>Frequency</th> <th>Limit (dBuV/m @3m)</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-88MHz</td> <td>40.0</td> <td>Quasi-peak Value</td> </tr> <tr> <td>88MHz-216MHz</td> <td>43.5</td> <td>Quasi-peak Value</td> </tr> <tr> <td>216MHz-960MHz</td> <td>46.0</td> <td>Quasi-peak Value</td> </tr> <tr> <td>960MHz-1GHz</td> <td>54.0</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td> </tr> <tr> <td>74.0</td><td>Peak Value</td> </tr> </tbody> </table>			Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	74.0	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																					
30MHz-88MHz	40.0	Quasi-peak Value																					
88MHz-216MHz	43.5	Quasi-peak Value																					
216MHz-960MHz	46.0	Quasi-peak Value																					
960MHz-1GHz	54.0	Quasi-peak Value																					
Above 1GHz	54.0	Average Value																					
	74.0	Peak Value																					
Test Setup:																							
	<p>Figure 1. 30MHz to 1GHz</p>																						
	<p>Figure 2. Above 1 GHz</p>																						


Test Procedure:	<ul style="list-style-type: none">a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channelg. Test the EUT in the lowest channel , the Highest channelh. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.i. Repeat above procedures until all frequencies measured was complete.
Instruments Used:	Refer to section 4.10 for details
Test Mode:	Transmitting mode
Test Results:	Pass

Measurement Data

Band edge (Radiated Emission)

Test mode:	Transmitting	Test channel:	2410MHz	Remark:	Peak
------------	--------------	---------------	---------	---------	------

Vertical:



Condition : FCC PART15.249 2.4PK 3m VERTICAL


Job No. : 4188RF

Mode : 2410MHz

Freq	Cable		Antenna		Preamp		Read Level	Limit Line	Over Limit	Remark
	Loss	Factor	Factor	Factor	dB	dBuV				
MHz	dB	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dBuV/m	dB	dB
1	2400.000	2.98	32.51	39.86	57.97	53.60	74.00	-20.40	Peak	
2	2410.100	2.99	32.54	39.86	99.88	95.55	114.00	-18.45	Peak	

If radiated spurious emission peak level under average limit, and peak limit- average limit =20dB, so all of average level should be passed.


Horizontal:



If radiated spurious emission peak level under average limit, and peak limit- average limit =20dB, so all of average level should be passed.

Test mode:	Transmitting	Test channel:	2479MHz	Remark:	Peak
------------	--------------	---------------	---------	---------	------

Vertical:



Condition : FCC PART15.249 2.4PK 3m VERTICAL

Job No. : 4188RF


Mode : 2479MHz

	Freq	Cable		Antenna	Preamp	Read	Limit	Over	Remark
		Loss	Factor	Factor	Level	Level	Line	Limit	
	MHz	dB	dB/m		dB	dBuV	dBuV/m	dBuV/m	
1	2478.850	3.03	32.67	39.92	101.75	97.53	114.00	-16.47	Peak
2	2483.500	3.03	32.67	39.92	62.84	58.62	74.00	-15.38	Peak

Average:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Average value (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.500	2.98	32.51	39.86	46.37	42.15	54	-16.87	Vertical

Horizontal:



Condition : FCC PART15.249 2.4PK 3m HORIZONTAL

Job No. : 4188RF

Mode : 2479MHz

	Freq	Cable			Antenna	Preamp	Read	Limit	Over	Remark
		Loss	Factor	Factor	Level	Level	dBuV			
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		2478.950	3.03	32.67	39.92	98.89	94.67	114.00	-19.33	Peak
2	0	2483.500	3.03	32.67	39.92	60.25	56.03	74.00	-17.97	Peak

Average:


Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Average value (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.500	2.98	32.51	39.86	43.78	39.56	54	-16.87	Horizontal

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

5.4 20dB Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.215
Test Method:	ANSI C63.10:2009
Test Setup:	
Instruments Used:	Refer to section 4.7 for details
Test mode:	Transmitting mode
Limit:	N/A
Test Results:	Pass

Measurement Data


Test channel	20dB bandwidth (MHz)	Results
Lowest	1.080	Pass
Middle	1.100	Pass
Highest	1.010	Pass

Test plot as follows:

Test channel: Lowest



Test channel: Middle



***This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."**

Test channel:	Highest
---------------	---------

