



Subject.: Acknowledgment of FCC Modular approval requirements

FCC ID : OVNSE8

To Whom It May Concern:

This application is a RFID module at 125KHz, which cannot work without our reader (tested with)

| Modular Approval Requirement | Yes | No |
|---|------------|-----------|
| (i) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements. | X | |
| (ii) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation. | X | |
| (iii) The modular transmitter must have its own power supply regulation. | | X |
| (iv) The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler (at all connections between the module and the antenna, including the cable). The “professional installation” provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section. | X | |
| (v) The modular transmitter must be tested in a stand-alone configuration | | X |
| (vi) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. | X | |
| (vii) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. | X | |
| (viii) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration. | X | |



Justifications :

(iii) Power supply regulation is the same for the entire board

(v) It can't be run without the board

Regards,

A handwritten signature in blue ink, appearing to be 'SP', with a long horizontal line extending to the right.

Sylvain Poitrat
Technical Director