





SmoothTalker[®]

Maximum Power



Dual Band Mag Mount Antenna



Dual Band Glass Mount 15" Antenna



Dual Band Glass Mag Antenna



Dual Band Glass Mount 4" Antenna



Adapter Cables
(Order Separately)



AC/DC Power Supply
(Optional) Allows Use of
Booster in Home or Office

Specifications:

(Optional)

Model:BST11900

Frequency Range (Mhz)	Antenna Gain Only	
Uplink	1850-1910	824-849
Downlink	1930-1990	869-894
Output Power	max 2 Watt	N/A
Gain	Antenna Gain Only	
Uplink	+12dB	6dB max
Downlink	+12dB	6dB max
DC Input Power		
Stand By	DC 12V/0.2A Max	
In Use	DC12V/600mAh Max	
RFConnector	MCT-Male	
Weight	350g	
Dimensions	125 x 82 x 25mm	



SmoothTalker[®]

Maximum Power

User Instruction Manual

Model BST1900

Cellular Band Booster Amplifier

GSM /GPRS/EDGE/TDMA

MCT

Mobile Communication Technologies Inc.

Contact Us On The Internet At www.smoothtalker.com

User Instructions

Car Booster Instructions:

1) Place the Booster in a suitable location under the dashboard and plug in power cord to cigarette lighter socket of vehicle.

2) Instructions for mounting antenna to vehicle:

This device should be installed with the antenna supplied. It is required that the antenna is mounted in a suitable location which is a minimum distance of 20cm(8 inches)away from the user or nearby persons in order to comply with FCC rules concerning MPE (Maximum Permissible Exposure) safety limits

Magnetic Mount: Place centered, only on vehicle roof or 8 inches(20cm) away from any vehicle occupant or nearby persons.

Glass mount: The antenna base should be placed on the front or rear windshield and centered as close to the vehicle roof as possible. It should be positioned to provide a minimum distance of 8 inches (20 cm) from any of the vehicle occupants or nearby persons. Run the co-ax cable along the head liner or along the floor under the carpet and bring up to the position of the booster.

Connect co-ax cable to side of booster marked "Antenna".

Trunk mount: When mounting on trunk the antenna should be placed in the center of the trunk closest to the rear windshield of the vehicle. It should be positioned to provide a minimum distance of 8 inches (20 cm) from any of the vehicle occupants or nearby persons.

3) Connect the 100cm cable from cell phone to side of booster marked "Signal Adapter".

When using with Cell Phone; connect cell phone adapter cable from cell phone to 100cm cable.

When using with Car Kit: connect Car Kit antenna out, to 100cm cable.

4) Tighten all connections securely and move the switch located at the side of the booster to the "on" position. A green light will indicate that the unit is now ready for use.

PLEASE NOTE: It is normal for the booster to be quite warm while the phone is in use.

NOTE: This equipment has been tested and found to comply with the limits for a Class AB digital devices, pursuant to Part 24 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of more of the following measures:

Reorient or relocate the receiving antenna · Increase the separation between the equipment and receiver · Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. · Consult the dealer or an experienced radio/TV technician for help.

"Changes or modifications not expressly approved by MCT, Inc., the party responsible for compliance, could void the user's authority to operate the equipment."

www.smoothtalker.com

Typical Car Installation

