

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 5.85 mW/g, SAR (10g): 3.19 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)

1.1 cm Belt-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)

Spring Whip Antenna (KRE1011219/21)

NiMH Battery Intrinsically Safe (BKB191210/6)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.52 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C


Date Tested: June 19, 2003

Cube Scan to show Peak Scan Location

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)
1.1 cm Belt-Clip Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiMH Battery Intrinsically Safe (BKB191210/6)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.52 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 6.04 mW/g, SAR (10g): 3.18 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)

1.1 cm Belt-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)

Spring Whip Antenna (KRE1011219/21)

NiCd Battery Intrinsically Safe (BKB191210/5)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.55 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C


Date Tested: June 19, 2003

Cube Scan to show Peak Scan Location

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)
1.1 cm Belt-Clip Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Intrinsically Safe (BKB191210/5)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°,180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 6.67 mW/g, SAR (10g): 3.47 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)

1.1 cm Belt-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver

with Speaker-Microphone (KRY1011617/183R1A)

Spring Whip Antenna (KRE1011219/21)

NiMH Battery Non-Intrinsically Safe (BKB191210/4)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.54 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C


Date Tested: June 19, 2003

Cube Scan to show Peak Scan Location

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)
1.1 cm Belt-Clip Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.54 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 6.75 mW/g, SAR (10g): 3.52 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)

1.1 cm Belt-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
 with Speaker-Microphone (KRY1011617/183R1A)

Spring Whip Antenna (KRE1011219/21)

NiCd Battery Non-Intrinsically Safe (BKB191210/3)

Continuous Wave Mode

Mid Channel [155.00 MHz]


Conducted Power: 5.53 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C

Date Tested: June 19, 2003

Cube Scan to show Peak Scan Location

Primary Hotspot Evaluation



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 3.75 mW/g, SAR (10g): 2.75 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)

1.1 cm Belt-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
 with Speaker-Microphone (KRY1011617/183R1A)

Spring Whip Antenna (KRE1011219/21)

NiCd Battery Non-Intrinsically Safe (BKB191210/3)

Continuous Wave Mode


Mid Channel [155.00 MHz]

Conducted Power: 5.53 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C

Date Tested: June 19, 2003


Secondary Hotspot Evaluation



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)
1.1 cm Belt-Clip Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.53 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003


Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Z-Axis Extrapolation at Peak SAR Location

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)
1.1 cm Belt-Clip Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.53 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 4.10 mW/g, SAR (10g): 2.15 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)

1.1 cm Belt-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)

Helical Coil Antenna (KRE1011219/2)

NiMH Battery Intrinsically Safe (BKB191210/6)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.54 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C

Date Tested: June 19, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 4.01 mW/g, SAR (10g): 2.13 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)

1.1 cm Belt-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)

Helical Coil Antenna (KRE1011219/2)

NiCd Battery Intrinsically Safe (BKB191210/5)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.54 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C

Date Tested: June 19, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°,180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 4.24 mW/g, SAR (10g): 2.22 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)

1.1 cm Belt-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver

with Speaker-Microphone (KRY1011617/183R1A)

Helical Coil Antenna (KRE1011219/2)

NiMH Battery Non-Intrinsically Safe (BKB191210/4)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.57 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C


Date Tested: June 19, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°,180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 4.21 mW/g, SAR (10g): 2.29 mW/g

Body-Worn SAR with Metal Belt-Clip (KRY1011647/1)
1.1 cm Belt-Clip Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.57 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 2.88 mW/g, SAR (10g): 2.10 mW/g

Body-Worn SAR with Nylon T-Strap (KRY1011656/1)

1.6 cm Nylon T-Strap Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)

Spring Whip Antenna (KRE1011219/21)

NiMH Battery Intrinsically Safe (BKB191210/6)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.55 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C


Date Tested: June 19, 2003

Cube Scan to show Peak Scan Location

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiMH Battery Intrinsically Safe (BKB191210/6)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003


Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Time sweep

SAR VERSUS TIME (30 minutes)


Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiMH Battery Intrinsically Safe (BKB191210/6)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 3.32 mW/g, SAR (10g): 2.41 mW/g


Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Intrinsically Safe (BKB191210/5)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.58 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003

Cube Scan to show Peak Scan Location

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Intrinsically Safe (BKB191210/5)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.58 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 3.61 mW/g, SAR (10g): 2.57 mW/g

Body-Worn SAR with Nylon T-Strap (KRY1011656/1)

1.6 cm Nylon T-Strap Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
 with Speaker-Microphone (KRY1011617/183R1A)

Spring Whip Antenna (KRE1011219/21)

NiMH Battery Non-Intrinsically Safe (BKB191210/4)

Continuous Wave Mode


Mid Channel [155.00 MHz]

Conducted Power: 5.58 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C

Date Tested: June 19, 2003


Cube Scan to show Peak Scan Location



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.58 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 3.55 mW/g, SAR (10g): 2.57 mW/g

Body-Worn SAR with Nylon T-Strap (KRY1011656/1)

1.6 cm Nylon T-Strap Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)

Spring Whip Antenna (KRE1011219/21)

NiCd Battery Non-Intrinsically Safe (BKB191210/3)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.58 Watts

Ambient Temp. 23.9°C; Fluid Temp. 23.5°C


Date Tested: June 19, 2003

Cube Scan to show Peak Scan Location

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.82$ mho/m $\epsilon_r = 61.1$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0


Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.58 Watts
Ambient Temp. 23.9°C; Fluid Temp. 23.5°C
Date Tested: June 19, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 2.61 mW/g, SAR (10g): 1.93 mW/g

Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiMH Battery Intrinsically Safe (BKB191210/6)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.59 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 2.81 mW/g, SAR (10g): 2.06 mW/g

Body-Worn SAR with Nylon T-Strap (KRY1011656/1)

1.6 cm Nylon T-Strap Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)

Helical Coil Antenna (KRE1011219/2)

NiCd Battery Intrinsically Safe (BKB191210/5)


Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.60 Watts

Ambient Temp. 22.8°C; Fluid Temp. 23.4°C


Date Tested: June 20, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 2.14 mW/g, SAR (10g): 1.56 mW/g


Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.53 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 2.55 mW/g, SAR (10g): 1.86 mW/g


Body-Worn SAR with Nylon T-Strap (KRY1011656/1)
1.6 cm Nylon T-Strap Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.57 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 2.50 mW/g, SAR (10g): 1.86 mW/g


Body-Worn SAR with Leather Case (Belt-Loop type - KRY1011638/1)
1.7 cm Leather Case/Belt Loop Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Cube Scan to show Peak Scan Location

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0


Body-Worn SAR with Leather Case (Belt-Loop type - KRY1011638/1)
1.7 cm Leather Case/Belt Loop Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 2.31 mW/g, SAR (10g): 1.72 mW/g

Body-Worn SAR with Leather Case (Belt Loop type - KRY1011638/1)
1.7 cm Leather Case/Belt Loop Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.53 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003




M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
 150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
 Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
 Cube 5x5x7
 SAR (1g): 0.688 mW/g, SAR (10g): 0.534 mW/g

Body-Worn SAR with Leather Case, Belt-Loop & Swivel Mount (KRY1011639/1)
 4.5 cm Leather Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
 P7100(IP) Portable VHF PTT Radio Transceiver
 with Speaker-Microphone (KRY1011617/183R1A)
 Spring Whip Antenna (KRE1011219/21)
 NiCd Battery Non-Intrinsically Safe (BKB191210/3)
 Continuous Wave Mode
 Mid Channel [155.00 MHz]
 Conducted Power: 5.53 Watts
 Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
 Date Tested: June 20, 2003


Cube Scan to show Peak Scan Location



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Body-Worn SAR with Leather Case, Belt-Loop & Swivel Mount (KRY1011639/1)
4.5 cm Leather Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.53 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003


Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
 150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
 Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
 Cube 5x5x7
 SAR (1g): 1.17 mW/g, SAR (10g): 0.897 mW/g

Body-Worn SAR with Leather Case, Belt-Loop & Swivel Mount (KRY1011639/1)
 4.5 cm Leather Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
 P7100(IP) Portable VHF PTT Radio Transceiver
 with Speaker-Microphone (KRY1011617/183R1A)
 Helical Coil Antenna (KRE1011219/2)
 NiMH Battery Non-Intrinsically Safe (BKB191210/4)
 Continuous Wave Mode
 Mid Channel [155.00 MHz]
 Conducted Power: 5.55 Watts
 Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
 Date Tested: June 20, 2003

Primary Hotspot Evaluation




M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
 150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
 Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
 Cube 5x5x7
 SAR (1g): 1.18 mW/g, SAR (10g): 0.647 mW/g

Body-Worn SAR with Leather Case, Belt-Loop & Swivel Mount (KRY1011639/1)
 4.5 cm Leather Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
 P7100(IP) Portable VHF PTT Radio Transceiver
 with Speaker-Microphone (KRY1011617/183R1A)
 Helical Coil Antenna (KRE1011219/2)
 NiMH Battery Non-Intrinsically Safe (BKB191210/4)
 Continuous Wave Mode
 Mid Channel [155.00 MHz]
 Conducted Power: 5.55 Watts
 Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
 Date Tested: June 20, 2003

Secondary Hotspot Evaluation




M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
 150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
 Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
 Cube 5x5x7
 SAR (1g): 1.07 mW/g, SAR (10g): 0.575 mW/g

Body-Worn SAR with Leather Case, Belt-Loop & Swivel Mount (KRY1011639/1)
 4.5 cm Leather Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
 P7100(IP) Portable VHF PTT Radio Transceiver
 with Speaker-Microphone (KRY1011617/183R1A)
 Helical Coil Antenna (KRE1011219/2)
 NiMH Battery Non-Intrinsically Safe (BKB191210/4)
 Continuous Wave Mode
 Mid Channel [155.00 MHz]
 Conducted Power: 5.55 Watts
 Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
 Date Tested: June 20, 2003

Tertiary Hotspot Evaluation



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0


150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 1.02 mW/g, SAR (10g): 0.789 mW/g


Body-Worn SAR with Nylon Case, Belt-Loop & Swivel Mount (KRY1011648/1)
4.0 cm Nylon Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.54 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Cube Scan to show Peak Scan Location

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0


Body-Worn SAR with Nylon Case, Belt-Loop & Swivel Mount (KRY1011648/1)
4.0 cm Nylon Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.54 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 1.28 mW/g, SAR (10g): 0.969 mW/g


Body-Worn SAR with Nylon Case, Belt-Loop & Swivel Mount (KRY1011648/1)
4.0 cm Nylon Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Primary Hotspot Evaluation

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 0.565 mW/g, SAR (10g): 0.311 mW/g


Body-Worn SAR with Nylon Case, Belt-Loop & Swivel Mount (KRY1011648/1)
4.0 cm Nylon Case, Belt-Loop & Swivel Mount Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Secondary Hotspot Evaluation

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 1.69 mW/g, SAR (10g): 1.29 mW/g

Body-Worn SAR with Belt-Loop & Swivel (KRY1011609/1)
3.5 cm Belt-Loop & Swivel Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Cube Scan to show Peak Scan Location**Primary Hotspot Evaluation**

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0

150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0


Cube 5x5x7

SAR (1g): 0.722 mW/g, SAR (10g): 0.350 mW/g

Body-Worn SAR with Belt-Loop & Swivel (KRY1011609/1)
 3.5 cm Belt-Loop & Swivel Separation Distance to Planar Phantom
 P7100(IP) Portable VHF PTT Radio Transceiver
 with Speaker-Microphone (KRY1011617/183R1A)
 Spring Whip Antenna (KRE1011219/21)
 NiCd Battery Non-Intrinsically Safe (BKB191210/3)
 Continuous Wave Mode
 Mid Channel [155.00 MHz]
 Conducted Power: 5.55 Watts
 Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
 Date Tested: June 20, 2003

Coarse Scan to show SAR Distribution at Lower Section of Radio

Secondary Hotspot Evaluation



M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0


150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 0.800 mW/g, SAR (10g): 0.414 mW/g


Body-Worn SAR with Belt-Loop & Swivel (KRY1011609/1)
3.5 cm Belt-Loop & Swivel Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Spring Whip Antenna (KRE1011219/21)
NiCd Battery Non-Intrinsically Safe (BKB191210/3)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.55 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Tertiary Hotspot Evaluation

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 2.55 mW/g, SAR (10g): 1.95 mW/g


Body-Worn SAR with Belt-Loop & Swivel (KRY1011609/1)
3.5 cm Belt-Loop & Swivel Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.58 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Primary Hotspot Evaluation

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
Cube 5x5x7
SAR (1g): 1.88 mW/g, SAR (10g): 0.942 mW/g

Body-Worn SAR with Belt-Loop & Swivel (KRY1011609/1)
3.5 cm Belt-Loop & Swivel Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.58 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Secondary Hotspot Evaluation

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0


150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7

SAR (1g): 1.87 mW/g, SAR (10g): 1.05 mW/g

Body-Worn SAR with Belt-Loop & Swivel (KRY1011609/1)
3.5 cm Belt-Loop & Swivel Separation Distance to Planar Phantom
P7100(IP) Portable VHF PTT Radio Transceiver
with Speaker-Microphone (KRY1011617/183R1A)
Helical Coil Antenna (KRE1011219/2)
NiMH Battery Non-Intrinsically Safe (BKB191210/4)
Continuous Wave Mode
Mid Channel [155.00 MHz]
Conducted Power: 5.58 Watts
Ambient Temp. 22.8°C; Fluid Temp. 23.4°C
Date Tested: June 20, 2003

Tertiary Hotspot Evaluation

M/A-COM INC. FCC ID: OWDTR-0013-E

Small Planar Phantom; Flat Section; Position: (270°, 180°)
 Probe: ET3DV6 - SN1387; ConvF(8.80,8.80,8.80); Crest factor: 1.0
 150 MHz Muscle: $\sigma = 0.78$ mho/m $\epsilon_r = 61.2$ $\rho = 1.00$ g/cm³
 Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0
 Cube 5x5x7
 SAR (1g): 3.27 mW/g, SAR (10g): 2.09 mW/g

Body-Worn SAR with Speaker Microphone Antenna Version Plus (KRY1011617/184R1A)

1.3 cm Lapel-Clip Separation Distance to Planar Phantom

P7100(IP) Portable VHF PTT Radio Transceiver

Spring Whip Antenna (KRE1011219/21)

NiCd Battery Non-Intrinsically Safe (BKB191210/3)

Continuous Wave Mode

Mid Channel [155.00 MHz]

Conducted Power: 5.58 Watts

Ambient Temp. 22.8°C; Fluid Temp. 23.4°C

Date Tested: June 20, 2003

