



AN-025137-008  
antenna (top) and  
mount (inset)

## Yagi Antennas, 806-896 MHz, 10 dBd gain

The AN-025137-008 has been engineered to meet the requirements of a high gain, broadband, premium quality antenna. This antenna provides 10 dBd gain and operates in the 806-896 MHz range. The AN-025137-008 is manufactured using high strength 6061-T6 aluminum to withstand heavy ice, high wind and other harsh conditions. All elements are welded to the boom and the dipole design has an integral feed line welded to the boom for extra strength and electrical conductivity. This eliminates misalignment or fastener problems. The entire antenna is anodized for appearance and corrosion resistance. A heavy duty clamp is supplied which easily permits horizontal or vertical polarization.

### Features

- Elements and boom are manufactured from aircraft quality 6061-T6 aluminum for optimum strength
- Antenna is anodized for corrosion resistance
- Antenna is supplied with a 2' pigtail (RG213) and N female connector



### Technical Data

Maximum Power: 200 watts
Nominal Impedance: 50 ohms
Radiator Material: Aluminum 6061-T6
Cable Type: RG213
Cable Length: 2 ft
Connector Type: N female
Mounting Method: Includes mounting hardware BWC1001

### RF/Electrical Specifications

Model	Frequency Range	H-Plane Beamwidth	E-Plane Beamwidth	Front to Back Ratio	Nominal Gain
AN-025137-008	806-896 MHz	60°	46°	20 dB	10 dBd

### Mechanical Specifications

Model	Dimensions* (L x W)	Weight (Mass)	Cross Sectional Area	Lateral Thrust @ 100 mph	Rated Wind Velocity**
AN-025137-008	24" x 6.8"	2 lbs	0.24 ft <sup>2</sup>	6	125 mph

\* Dimension does not include antenna cable

\*\*120 mph with 1/2" radial ice (mph)