

# FCC PART 15.247

## TEST REPORT

For

### Kasda Digital Technology Co., Ltd.

B-31 Building, Tanglang Industry Zone, XiLi Nanshan, Shenzhen, China

**FCC ID: OWI-KW55293**

|                                                                                                                                                                                                                                                                                                                 |                                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| <b>Report Type:</b><br>Original Report                                                                                                                                                                                                                                                                          | <b>Product Type:</b><br>Wireless Router |
| <b>Test Engineer:</b> Haiguo Li                                                                                                                                                                                            |                                         |
| <b>Report Number:</b> RSZ140710001-00                                                                                                                                                                                                                                                                           |                                         |
| <b>Report Date:</b> 2014-08-04                                                                                                                                                                                                                                                                                  |                                         |
| Sula Huang                                                                                                                                                                                                                  |                                         |
| <b>Reviewed By:</b> RF Engineer                                                                                                                                                                                                                                                                                 |                                         |
| <b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>6/F, the 3rd Phase of WanLi Industrial Building<br>ShiHua Road, FuTian Free Trade Zone<br>Shenzhen, Guangdong, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                         |

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## **TABLE OF CONTENTS**

|                                                                                                     |           |
|-----------------------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                                                     | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                            | 4         |
| OBJECTIVE .....                                                                                     | 4         |
| RELATED SUBMITTAL(S)/GRANT(S).....                                                                  | 4         |
| TEST METHODOLOGY .....                                                                              | 4         |
| TEST FACILITY .....                                                                                 | 5         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                                               | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                                             | 6         |
| EUT EXERCISE SOFTWARE .....                                                                         | 6         |
| EQUIPMENT MODIFICATIONS .....                                                                       | 6         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                                            | 7         |
| EXTERNAL I/O CABLE.....                                                                             | 7         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                                   | 8         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                                | <b>9</b>  |
| <b>FCC §15.247 (i) &amp; §1.1307 (b) (1) &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b> | <b>10</b> |
| APPLICABLE STANDARD .....                                                                           | 10        |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                                                       | <b>11</b> |
| APPLICABLE STANDARD .....                                                                           | 11        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                                                | 11        |
| <b>FCC §15.207 (a) - CONDUCTED EMISSIONS .....</b>                                                  | <b>12</b> |
| APPLICABLE STANDARD .....                                                                           | 12        |
| MEASUREMENT UNCERTAINTY.....                                                                        | 12        |
| EUT SETUP.....                                                                                      | 12        |
| EMI TEST RECEIVER SETUP.....                                                                        | 13        |
| TEST PROCEDURE .....                                                                                | 13        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                                | 13        |
| TEST RESULTS SUMMARY .....                                                                          | 14        |
| TEST DATA .....                                                                                     | 14        |
| <b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>                              | <b>17</b> |
| APPLICABLE STANDARD .....                                                                           | 17        |
| MEASUREMENT UNCERTAINTY .....                                                                       | 17        |
| EUT SETUP .....                                                                                     | 17        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                                                   | 18        |
| TEST PROCEDURE .....                                                                                | 18        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                                | 19        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                                      | 20        |
| TEST RESULTS SUMMARY .....                                                                          | 20        |
| TEST DATA .....                                                                                     | 20        |
| <b>FCC §15.247(a) (2) – 6 dB BANDWIDTH TESTING.....</b>                                             | <b>41</b> |
| APPLICABLE STANDARD .....                                                                           | 41        |
| TEST PROCEDURE .....                                                                                | 41        |
| TEST EQUIPMENT LIST AND DETAILS.....                                                                | 41        |
| TEST DATA .....                                                                                     | 41        |

|                                                                               |           |
|-------------------------------------------------------------------------------|-----------|
| <b>FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER .....</b>                   | <b>55</b> |
| APPLICABLE STANDARD .....                                                     | 55        |
| TEST PROCEDURE .....                                                          | 55        |
| TEST EQUIPMENT LIST AND DETAILS.....                                          | 55        |
| TEST DATA .....                                                               | 55        |
| <b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>         | <b>57</b> |
| APPLICABLE STANDARD .....                                                     | 57        |
| TEST PROCEDURE .....                                                          | 57        |
| TEST EQUIPMENT LIST AND DETAILS.....                                          | 57        |
| TEST DATA .....                                                               | 58        |
| <b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>                          | <b>67</b> |
| APPLICABLE STANDARD .....                                                     | 67        |
| TEST PROCEDURE (KDB558074 D01 DTS MEAS GUIDANCE V03R02 SUB-CLAUSE 10.2) ..... | 67        |
| TEST EQUIPMENT LIST AND DETAILS.....                                          | 67        |
| TEST DATA .....                                                               | 67        |
| <b>PRODUCT SIMILARITY DECLARATION LETTER .....</b>                            | <b>81</b> |

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Kasda Digital Technology Co., Ltd.*'s product, model number: *KW55293 (FCC ID: OWI-KW55293)* or the "EUT" in this report was a *Wireless Router*, which was measured approximately: 14.7 cm (L) x 10.4 cm (W) x 3.4 cm (H), rated with input voltage: DC 5V from adapter.

Adapter information:

Switching Adapter

Model: DSA-6PFE-05 FUS 050100

Input: 100-240V~ 50/60 Hz, 0.2A

Output: DC 5.0V, 1A

*Note: The serial models KW55293 and GR55293NF share the same schematics, they are different in model names, the details was explained in the attached product similarity declaration letter provided and guaranteed by applicant. Model KW55293 was selected for testing.*

*\*All measurement and test data in this report was gathered from production sample serial number: KW5529300081 (Assigned by the applicant). The EUT supplied by the applicant was received on 2014-07-10.*

### Objective

This Type approval report is prepared on behalf of *Kasda Digital Technology Co., Ltd.* in accordance with Part 2- Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15-Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15B, submissions with ID: OWI-KW55293

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b, 802.11g mode and 802.11n-HT20, 11 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2412            | 7       | 2442            |
| 2       | 2417            | 8       | 2447            |
| 3       | 2422            | 9       | 2452            |
| 4       | 2427            | 10      | 2457            |
| 5       | 2432            | 11      | 2462            |
| 6       | 2437            | /       | /               |

EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, 7 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2422            | 6       | 2447            |
| 2       | 2427            | 7       | 2452            |
| 3       | 2432            | /       | /               |
| 4       | 2437            | /       | /               |
| 5       | 2442            | /       | /               |

EUT was tested with Channel 1, 4 and 7.

### EUT Exercise Software

Run CMD.exe and input specific command which was provided by the manufacturer.

802.11b: Rate 1Mbps, Power level: 45  
802.11g: Rate 6Mbps, Power level: 45  
802.11n-HT20: Rate MCS8, Power level: 43  
802.11n-HT40: Rate MCS8, Power level: 43

### Equipment Modifications

No modification was made to the EUT tested.


**Support Equipment List and Details**

| Manufacturer | Description | Model       | Serial Number            |
|--------------|-------------|-------------|--------------------------|
| DELL         | PC          | VOSTRO 220S | 127BP2X                  |
| DELL         | LCD Monitor | E178WFPC    | CN-OWY564-64180-7C4-2SQH |
| DELL         | Keyboard    | L100        | CNORH656658907BL05DC     |
| DELL         | Mouse       | MOC5UO      | G1900NKD                 |
| SAST         | Modem       | AEM-2100    | 0293                     |

**External I/O Cable**

| Cable Description                 | Length (m) | From/Port | To            |
|-----------------------------------|------------|-----------|---------------|
| Shielding Detachable USB Cable    | 1.5        | Host PC   | Mouse         |
| Shielding Detachable Serial Cable | 1.2        | Host PC   | Modem         |
| Shielding Detachable K/B Cable    | 1.5        | Host PC   | Keyboard      |
| Shielding Detachable VGA Cable    | 1.5        | Host PC   | LCD Monitor   |
| Unshielding Detachable DC Cable   | 1.2        | Modem     | Modem Adapter |
| Unshielding Detachable DC Cable   | 1.2        | EUT       | Adapter       |
| Unshielded Detachable RJ45 Cable  | 1.5        | EUT       | Host PC       |

## Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| FCC Rules                            | Description of Test                      | Result     |
|--------------------------------------|------------------------------------------|------------|
| §15.247 (i), §1.1307 (b)(1), §2.1091 | Maximum Permissible Exposure (MPE)       | Compliance |
| §15.203                              | Antenna Requirement                      | Compliance |
| §15.207 (a),                         | Conducted Emissions                      | Compliance |
| §15.247(d)                           | Spurious Emissions at Antenna Port       | Compliance |
| §15.205, §15.209, §15.247(d)         | Spurious Emissions                       | Compliance |
| §15.247 (a)(2)                       | 6 dB Bandwidth                           | Compliance |
| §15.247(b)(3)                        | Maximum Peak Output Power                | Compliance |
| §15.247(d)                           | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| §15.247(e)                           | Power Spectral Density                   | Compliance |

## FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz)                                   | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
| 0.3–1.34                                                | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30                                                 | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30–300                                                  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500                                                | /                             | /                             | f/1500                              | 30                       |
| 1500–100,000                                            | /                             | /                             | 1.0                                 | 30                       |

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

### Calculated Data:

| Mode         | Frequency (MHz) | Antenna Gain |           | Conducted Power |        | Evaluation Distance (cm) | Power Density (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) |
|--------------|-----------------|--------------|-----------|-----------------|--------|--------------------------|-------------------------------------|---------------------------------|
|              |                 | (dBi)        | (numeric) | (dBm)           | (mW)   |                          |                                     |                                 |
| 802.11b      | 2462            | 3.0          | 2.0       | 18.40           | 69.18  | 20                       | 0.0275                              | 1.0                             |
| 802.11g      | 2412            | 3.0          | 2.0       | 22.58           | 181.13 | 20                       | 0.0721                              | 1.0                             |
| 802.11n-HT20 | 2412            | 3.0          | 2.0       | 24.69           | 294.44 | 20                       | 0.1172                              | 1.0                             |
| 802.11n-HT40 | 2422            | 3.0          | 2.0       | 23.60           | 229.07 | 20                       | 0.0911                              | 1.0                             |

### Result: Compliance

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

This product has two integrated antenna with maximum gain 3.0 dBi which was soldered on PCB, fulfill the requirement of this section, and please refer to the EUT photo.

**Result:** Compliance.

## FCC §15.207 (a) - CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207


### Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements may be receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

| Port     | Expanded Measurement uncertainty       |
|----------|----------------------------------------|
| AC Mains | 3.26 dB (k=2, 95% level of confidence) |
| CAT 3    | 3.70 dB (k=2, 95% level of confidence) |
| CAT 5    | 3.86 dB (k=2, 95% level of confidence) |
| CAT 6    | 4.64 dB (k=2, 95% level of confidence) |

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN, and the other relevant equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Test Equipment List and Details

| Manufacturer    | Description       | Model   | Serial Number          | Calibration Date | Calibration Due Date |
|-----------------|-------------------|---------|------------------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCS30  | 100176                 | 2014-06-03       | 2015-06-03           |
| Rohde & Schwarz | LISN              | ESH2-Z5 | 892107/021             | 2014-06-09       | 2015-06-09           |
| Rohde & Schwarz | LISN              | ENV216  | 3560.6650.12-101613-Yb | 2014-06-09       | 2015-06-09           |
| Rohde & Schwarz | Transient Limitor | ESH3Z2  | DE25985                | 2014-05-14       | 2015-05-14           |
| Rohde & Schwarz | CE Test software  | EMC 32  | V8.53                  | --               | --                   |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, the worst margin reading as below:

**6.4 dB at 0.478770 MHz** in the **Neutral** conductor mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In our lab.,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.


## Test Data

### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 56 %      |
| ATM Pressure:      | 100.0 kPa |

*The testing was performed by Haiguo Li on 2014-07-23.*


*Test Mode: Transmitting*

**AC 120 V, 60 Hz, Line:****EMI Auto Test L**

| Frequency (MHz) | Corrected Amplitude (dBμV) | Correction Factor (dB) | Limit (dBμV) | Margin (dB) | Detector (PK/QP/Ave.) |
|-----------------|----------------------------|------------------------|--------------|-------------|-----------------------|
| 0.443430        | 37.7                       | 19.6                   | 57.0         | 19.3        | QP                    |
| 0.443430        | 29.9                       | 19.6                   | 47.0         | 17.1        | Ave.                  |
| 0.482650        | 39.6                       | 19.6                   | 56.3         | 16.7        | QP                    |
| 0.482650        | 29.3                       | 19.6                   | 46.3         | 17.0        | Ave.                  |
| 0.541750        | 36.3                       | 19.6                   | 56.0         | 19.7        | QP                    |
| 0.541750        | 26.5                       | 19.6                   | 46.0         | 19.5        | Ave.                  |
| 0.790150        | 38.4                       | 19.5                   | 56.0         | 17.6        | QP                    |
| 0.790150        | 27.0                       | 19.5                   | 46.0         | 19.0        | Ave.                  |
| 3.981910        | 32.3                       | 19.7                   | 56.0         | 23.8        | QP                    |
| 3.981910        | 22.7                       | 19.7                   | 46.0         | 23.3        | Ave.                  |
| 4.005430        | 32.4                       | 19.7                   | 56.0         | 23.6        | QP                    |
| 4.005430        | 22.5                       | 19.7                   | 46.0         | 23.5        | Ave.                  |

**AC 120V, 60 Hz, Neutral:**

## EMI Auto Test N



| Frequency (MHz) | Corrected Amplitude (dBμV) | Correction Factor (dB) | Limit (dBμV) | Margin (dB) | Detector (PK/QP/Ave.) |
|-----------------|----------------------------|------------------------|--------------|-------------|-----------------------|
| 0.470830        | 48.5                       | 19.6                   | 56.5         | 8.0         | QP                    |
| 0.470830        | 39.7                       | 19.6                   | 46.5         | 6.8         | Ave.                  |
| 0.478770        | 48.4                       | 19.6                   | 56.4         | 8.0         | QP                    |
| 0.478770        | 40.0                       | 19.6                   | 46.4         | 6.4         | Ave.                  |
| 0.589210        | 44.0                       | 19.6                   | 56.0         | 12.0        | QP                    |
| 0.589210        | 34.3                       | 19.6                   | 46.0         | 11.7        | Ave.                  |
| 0.707350        | 44.6                       | 19.6                   | 56.0         | 11.4        | QP                    |
| 0.707350        | 35.1                       | 19.6                   | 46.0         | 10.9        | Ave.                  |
| 0.746690        | 45.1                       | 19.6                   | 56.0         | 10.9        | QP                    |
| 0.746690        | 35.5                       | 19.6                   | 46.0         | 10.5        | Ave.                  |
| 0.821550        | 44.0                       | 19.6                   | 56.0         | 12.0        | QP                    |
| 0.821550        | 35.2                       | 19.6                   | 46.0         | 10.8        | Ave.                  |

**Note:**

- 1) Corrected Amplitude = Reading + Correction Factor
- 2) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss
- 3) Margin = Limit – Corrected Amplitude

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

### Measurement Uncertainty


All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report

| Frequency    | Polarity              | Measurement uncertainty                |
|--------------|-----------------------|----------------------------------------|
| 30MHz~200MHz | Horizontal            | 4.62 dB (k=2, 95% level of confidence) |
|              | Vertical              | 4.54 dB (k=2, 95% level of confidence) |
| 200MHz~1GHz  | Horizontal            | 4.84 dB (k=2, 95% level of confidence) |
|              | Vertical              | 5.91 dB (k=2, 95% level of confidence) |
| 1 GHz~6 GHz  | Horizontal / Vertical | 4.68 dB (k=2, 95% level of confidence) |
| Above 6 GHz  | Horizontal / Vertical | 4.92 dB (k=2, 95% level of confidence) |

### EUT Setup

Below 1 GHz:



**Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W | IF B/W  | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz   | 120 kHz | QP       |
| Above 1 GHz       | 1MHz    | 3 MHz     | /       | PK       |
|                   | 1MHz    | 10 Hz     | /       | Ave.     |

**Test Procedure**

During the radiated emission test, the adapter was connected to the outlet of the first LISN, and the other relevant equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz and peak and Average detection modes for frequencies above 1 GHz.

**Test Equipment List and Details**

| Manufacturer              | Description       | Model           | Serial Number | Calibration Date | Calibration Due Date |
|---------------------------|-------------------|-----------------|---------------|------------------|----------------------|
| HP                        | Amplifier         | 8447E           | 1937A01046    | 2014-05-06       | 2015-05-06           |
| Rohde & Schwarz           | EMI Test Receiver | ESCI            | 101122        | 2013-09-25       | 2014-09-25           |
| Sunol Sciences            | Broadband Antenna | JB1             | A040904-2     | 2011-11-28       | 2014-11-27           |
| Mini                      | Pre-amplifier     | ZVA-183-S+      | 5969001149    | 2014-04-23       | 2015-04-23           |
| Sunol Sciences            | Horn Antenna      | DRH-118         | A052304       | 2011-12-01       | 2014-11-30           |
| Rohde & Schwarz           | Signal Analyzer   | FSIQ26          | 8386001028    | 2013-11-12       | 2014-11-12           |
| DUCOMMUN                  | Pre-amplifier     | ALN-22093530-01 | 991373-01     | 2013-08-03       | 2014-08-03           |
| the electro-Mechanics Co. | Horn Antenna      | 3116            | 9510-2270     | 2013-10-14       | 2016-10-13           |
| TDK                       | Chamber           | Chamber A       | 2#            | 2012-10-15       | 2015-10-15           |
| TDK                       | Chamber           | Chamber B       | 1#            | 2011-07-23       | 2014-07-23           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, the worst margin reading as below:

**3.69 dB at 2488.09 MHz in the Horizontal polarization for 802.11g mode**

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{lim} + U_{cispr}$$

In our lab.,  $U_{(L_m)}$  is less than  $+U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

## Test Data

### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25~26 °C  |
| <b>Relative Humidity:</b> | 50~55 %   |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Haiguo Li from 2014-07-21 to 2014-07-22.*

*Test Mode: Transmitting*

Note: For 802.11b/g, test with two antenna ports transmit separately, the worst case is from ANT001; for 802.11n-HT20, 802.11n-HT40, test with two antenna ports transmit simultaneously, and the worst case as below:

**30 MHz-25 GHz****802.11b mode:**

| Frequency<br>(MHz)        | Receiver          |                          | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|---------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                           | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                     | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| Low Channel (2412 MHz)    |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                     | 43.25             | QP                       | 121                 | 1.3           | H              | -14.5                       | 28.75                              | 43.5                       | 14.75          |
| 2412.00                   | 89.68             | PK                       | 305                 | 1.1           | H              | 6.13                        | 95.81                              | /                          | /              |
| 2412.00                   | 84.17             | Ave.                     | 305                 | 1.1           | H              | 6.13                        | 90.30                              | /                          | /              |
| 2412.00                   | 99.91             | PK                       | 261                 | 1.5           | V              | 6.13                        | 106.04                             | /                          | /              |
| 2412.00                   | 96.00             | Ave.                     | 261                 | 1.5           | V              | 6.13                        | 102.13                             | /                          | /              |
| 2358.65                   | 40.64             | PK                       | 326                 | 1.3           | H              | 5.48                        | 46.12                              | 74                         | 27.88          |
| 2358.65                   | 27.91             | Ave.                     | 326                 | 1.3           | H              | 5.48                        | 33.39                              | 54                         | 20.61          |
| 2373.64                   | 46.38             | PK                       | 216                 | 1.7           | H              | 5.48                        | 51.86                              | 74                         | 22.14          |
| 2373.64                   | 30.88             | Ave.                     | 216                 | 1.7           | H              | 5.48                        | 36.36                              | 54                         | 17.64          |
| 2494.69                   | 42.87             | PK                       | 140                 | 1.7           | V              | 7.21                        | 50.08                              | 74                         | 23.92          |
| 2494.69                   | 28.32             | Ave.                     | 140                 | 1.7           | V              | 7.21                        | 35.53                              | 54                         | 18.47          |
| 4824.00                   | 38.47             | PK                       | 272                 | 2.1           | V              | 12.44                       | 50.91                              | 74                         | 23.09          |
| 4824.00                   | 29.54             | Ave.                     | 272                 | 2.1           | V              | 12.44                       | 41.98                              | 54                         | 12.02          |
| 7236.00                   | 36.95             | PK                       | 46                  | 1.2           | H              | 17.06                       | 54.01                              | 74                         | 19.99          |
| 7236.00                   | 20.35             | Ave.                     | 46                  | 1.2           | H              | 17.06                       | 37.41                              | 54                         | 16.59          |
| 9648.00                   | 38.86             | PK                       | 138                 | 1.5           | H              | 19.28                       | 58.14                              | 74                         | 15.86          |
| 9648.00                   | 22.92             | Ave.                     | 138                 | 1.5           | H              | 19.28                       | 42.2                               | 54                         | 11.80          |
| Middle Channel (2437 MHz) |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                     | 43.67             | QP                       | 115                 | 1.1           | H              | -14.5                       | 29.17                              | 43.5                       | 14.33          |
| 2437.00                   | 88.67             | PK                       | 69                  | 1.5           | H              | 6.13                        | 94.80                              | /                          | /              |
| 2437.00                   | 85.14             | Ave.                     | 69                  | 1.5           | H              | 6.13                        | 91.27                              | /                          | /              |
| 2437.00                   | 100.27            | PK                       | 305                 | 1.0           | V              | 6.13                        | 106.40                             | /                          | /              |
| 2437.00                   | 95.54             | Ave.                     | 305                 | 1.0           | V              | 6.13                        | 101.67                             | /                          | /              |
| 2365.36                   | 42.15             | PK                       | 44                  | 1.2           | H              | 5.48                        | 47.63                              | 74                         | 26.37          |
| 2365.36                   | 26.91             | Ave.                     | 44                  | 1.2           | H              | 5.48                        | 32.39                              | 54                         | 21.61          |
| 2389.82                   | 46.11             | PK                       | 343                 | 1.2           | H              | 5.48                        | 51.59                              | 74                         | 22.41          |
| 2389.82                   | 32.19             | Ave.                     | 343                 | 1.2           | H              | 5.48                        | 37.67                              | 54                         | 16.33          |
| 2498.82                   | 40.48             | PK                       | 349                 | 1.5           | V              | 7.21                        | 47.69                              | 74                         | 26.31          |
| 2498.82                   | 30.32             | Ave.                     | 349                 | 1.5           | V              | 7.21                        | 37.53                              | 54                         | 16.47          |
| 4874.00                   | 39.09             | PK                       | 145                 | 2.4           | V              | 12.4                        | 51.49                              | 74                         | 22.51          |
| 4874.00                   | 30.95             | Ave.                     | 145                 | 2.4           | V              | 12.4                        | 43.35                              | 54                         | 10.65          |
| 7311.00                   | 36.67             | PK                       | 354                 | 1.8           | V              | 16.62                       | 53.29                              | 74                         | 20.71          |
| 7311.00                   | 20.52             | Ave.                     | 354                 | 1.8           | V              | 16.62                       | 37.14                              | 54                         | 16.86          |
| 9748.00                   | 37.67             | PK                       | 55                  | 1.1           | H              | 19.4                        | 57.07                              | 74                         | 16.93          |
| 9748.00                   | 23.51             | Ave.                     | 55                  | 1.1           | H              | 19.4                        | 42.91                              | 54                         | 11.09          |

| Frequency<br>(MHz)      | Receiver          |                          | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|-------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                         | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                     | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| High Channel (2462 MHz) |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                   | 43.85             | QP                       | 101                 | 1.3           | H              | -14.5                       | 29.35                              | 43.5                       | 14.15          |
| 2462.00                 | 88.83             | PK                       | 177                 | 2.0           | H              | 6.13                        | 94.96                              | /                          | /              |
| 2462.00                 | 84.39             | Ave.                     | 177                 | 2.0           | H              | 6.13                        | 90.52                              | /                          | /              |
| 2462.00                 | 99.84             | PK                       | 137                 | 1.8           | V              | 6.13                        | 105.97                             | /                          | /              |
| 2462.00                 | 95.41             | Ave.                     | 137                 | 1.8           | V              | 6.13                        | 101.54                             | /                          | /              |
| 2385.74                 | 48.59             | PK                       | 145                 | 1.6           | H              | 5.48                        | 54.07                              | 74                         | 19.93          |
| 2385.74                 | 36.09             | Ave.                     | 145                 | 1.6           | H              | 5.48                        | 41.57                              | 54                         | 12.43          |
| 2489.60                 | 54.39             | PK                       | 27                  | 1.1           | H              | 7.21                        | 61.6                               | 74                         | 12.40          |
| 2489.60                 | 39.77             | Ave.                     | 27                  | 1.1           | H              | 7.21                        | 46.98                              | 54                         | 7.02           |
| 2494.59                 | 51.35             | PK                       | 130                 | 1.0           | V              | 7.21                        | 58.56                              | 74                         | 15.44          |
| 2494.59                 | 37.00             | Ave.                     | 130                 | 1.0           | V              | 7.21                        | 44.21                              | 54                         | 9.79           |
| 4924.00                 | 42.10             | PK                       | 74                  | 2.2           | V              | 12.46                       | 54.56                              | 74                         | 19.44          |
| 4924.00                 | 31.80             | Ave.                     | 74                  | 2.2           | V              | 12.46                       | 44.26                              | 54                         | 9.74           |
| 7386.00                 | 38.90             | PK                       | 43                  | 2.0           | V              | 15.91                       | 54.81                              | 74                         | 19.19          |
| 7386.00                 | 23.00             | Ave.                     | 43                  | 2.0           | V              | 15.91                       | 38.91                              | 54                         | 15.09          |
| 9848.00                 | 39.93             | PK                       | 50                  | 2.1           | V              | 19.29                       | 59.22                              | 74                         | 14.78          |
| 9848.00                 | 23.34             | Ave.                     | 50                  | 2.1           | V              | 19.29                       | 42.63                              | 54                         | 11.37          |

**802.11g Mode:**

| Frequency<br>(MHz)        | Receiver          |                          | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|---------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                           | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                     | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| Low Channel (2412 MHz)    |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                     | 43.08             | QP                       | 108                 | 1.3           | H              | -14.5                       | 28.58                              | 43.5                       | 14.92          |
| 2412.00                   | 92.23             | PK                       | 190                 | 1.3           | H              | 6.13                        | 98.36                              | /                          | /              |
| 2412.00                   | 82.67             | Ave.                     | 190                 | 1.3           | H              | 6.13                        | 88.80                              | /                          | /              |
| 2412.00                   | 101.47            | PK                       | 142                 | 1.3           | V              | 6.13                        | 107.60                             | /                          | /              |
| 2412.00                   | 90.28             | Ave.                     | 142                 | 1.3           | V              | 6.13                        | 96.41                              | /                          | /              |
| 2349.16                   | 52.82             | PK                       | 50                  | 1.3           | H              | 5.48                        | 58.30                              | 74                         | 15.70          |
| 2349.16                   | 35.80             | Ave.                     | 50                  | 1.3           | H              | 5.48                        | 41.28                              | 54                         | 12.72          |
| 2378.68                   | 57.03             | PK                       | 207                 | 1.1           | H              | 5.48                        | 62.51                              | 74                         | 11.49          |
| 2378.68                   | 38.33             | Ave.                     | 207                 | 1.1           | H              | 5.48                        | 43.81                              | 54                         | 10.19          |
| 2489.12                   | 45.67             | PK                       | 301                 | 1.4           | V              | 7.21                        | 52.88                              | 74                         | 21.12          |
| 2489.12                   | 35.92             | Ave.                     | 301                 | 1.4           | V              | 7.21                        | 43.13                              | 54                         | 10.87          |
| 4824.00                   | 41.81             | PK                       | 143                 | 1.5           | H              | 12.44                       | 54.25                              | 74                         | 19.75          |
| 4824.00                   | 31.25             | Ave.                     | 143                 | 1.5           | H              | 12.44                       | 43.69                              | 54                         | 10.31          |
| 7236.00                   | 38.55             | PK                       | 252                 | 1.6           | V              | 17.06                       | 55.61                              | 74                         | 18.39          |
| 7236.00                   | 22.08             | Ave.                     | 252                 | 1.6           | V              | 17.06                       | 39.14                              | 54                         | 14.86          |
| 9648.00                   | 38.64             | PK                       | 199                 | 2.0           | V              | 19.28                       | 57.92                              | 74                         | 16.08          |
| 9648.00                   | 24.48             | Ave.                     | 199                 | 2.0           | V              | 19.28                       | 43.76                              | 54                         | 10.24          |
| Middle Channel (2437 MHz) |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                     | 43.25             | QP                       | 121                 | 1.3           | H              | -14.5                       | 28.75                              | 43.5                       | 14.75          |
| 2437.00                   | 92.26             | PK                       | 352                 | 2.3           | H              | 6.13                        | 98.39                              | /                          | /              |
| 2437.00                   | 81.06             | Ave.                     | 352                 | 2.3           | H              | 6.13                        | 87.19                              | /                          | /              |
| 2437.00                   | 101.86            | PK                       | 297                 | 1.0           | V              | 6.13                        | 107.99                             | /                          | /              |
| 2437.00                   | 90.61             | Ave.                     | 297                 | 1.0           | V              | 6.13                        | 96.74                              | /                          | /              |
| 2346.34                   | 51.39             | PK                       | 210                 | 1.4           | H              | 5.48                        | 56.87                              | 74                         | 17.13          |
| 2346.34                   | 35.95             | Ave.                     | 210                 | 1.4           | H              | 5.48                        | 41.43                              | 54                         | 12.57          |
| 2381.00                   | 56.44             | PK                       | 296                 | 1.9           | H              | 5.48                        | 61.92                              | 74                         | 12.08          |
| 2381.00                   | 38.58             | Ave.                     | 296                 | 1.9           | H              | 5.48                        | 44.06                              | 54                         | 9.94           |
| 2497.58                   | 46.77             | PK                       | 183                 | 1.6           | V              | 7.21                        | 53.98                              | 74                         | 20.02          |
| 2497.58                   | 36.60             | Ave.                     | 183                 | 1.6           | V              | 7.21                        | 43.81                              | 54                         | 10.19          |
| 4874.00                   | 42.65             | PK                       | 216                 | 1.4           | H              | 12.4                        | 55.05                              | 74                         | 18.95          |
| 4874.00                   | 31.73             | Ave.                     | 216                 | 1.4           | H              | 12.4                        | 44.13                              | 54                         | 9.87           |
| 7311.00                   | 37.72             | PK                       | 26                  | 2.5           | H              | 16.62                       | 54.34                              | 74                         | 19.66          |
| 7311.00                   | 22.36             | Ave.                     | 26                  | 2.5           | H              | 16.62                       | 38.98                              | 54                         | 15.02          |
| 9748.00                   | 38.87             | PK                       | 114                 | 2.2           | H              | 19.4                        | 58.27                              | 74                         | 15.73          |
| 9748.00                   | 23.48             | Ave.                     | 114                 | 2.2           | H              | 19.4                        | 42.88                              | 54                         | 11.12          |

| Frequency<br>(MHz)      | Receiver          |                          | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|-------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                         | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                     | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| High Channel (2462 MHz) |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                   | 43.46             | QP                       | 115                 | 1.3           | H              | -14.5                       | 28.96                              | 43.5                       | 14.54          |
| 2462.00                 | 92.32             | PK                       | 178                 | 2.5           | H              | 6.13                        | 98.45                              | /                          | /              |
| 2462.00                 | 82.82             | Ave.                     | 178                 | 2.5           | H              | 6.13                        | 88.95                              | /                          | /              |
| 2462.00                 | 102.12            | PK                       | 270                 | 1.6           | V              | 6.13                        | 108.25                             | /                          | /              |
| 2462.00                 | 91.91             | Ave.                     | 270                 | 1.6           | V              | 6.13                        | 98.04                              | /                          | /              |
| 2364.29                 | 47.05             | PK                       | 101                 | 1.3           | H              | 5.48                        | 52.53                              | 74                         | 21.47          |
| 2364.29                 | 30.01             | Ave.                     | 101                 | 1.3           | H              | 5.48                        | 35.49                              | 54                         | 18.51          |
| 2488.09                 | 57.76             | PK                       | 344                 | 1.4           | H              | 7.21                        | 64.97                              | 74                         | 9.03           |
| 2488.09                 | 43.10             | Ave.                     | 344                 | 1.4           | H              | 7.21                        | 50.31                              | 54                         | 3.69           |
| 2494.12                 | 56.25             | PK                       | 212                 | 2.2           | V              | 7.21                        | 63.46                              | 74                         | 10.54          |
| 2494.12                 | 40.93             | Ave.                     | 212                 | 2.2           | V              | 7.21                        | 48.14                              | 54                         | 5.86           |
| 4924.00                 | 40.38             | PK                       | 267                 | 2.4           | H              | 12.46                       | 52.84                              | 74                         | 21.16          |
| 4924.00                 | 30.76             | Ave.                     | 267                 | 2.4           | H              | 12.46                       | 43.22                              | 54                         | 10.78          |
| 7386.00                 | 38.77             | PK                       | 251                 | 1.5           | V              | 15.91                       | 54.68                              | 74                         | 19.32          |
| 7386.00                 | 22.48             | Ave.                     | 251                 | 1.5           | V              | 15.91                       | 38.39                              | 54                         | 15.61          |
| 9848.00                 | 38.20             | PK                       | 330                 | 1.6           | H              | 19.29                       | 57.49                              | 74                         | 16.51          |
| 9848.00                 | 24.80             | Ave.                     | 330                 | 1.6           | H              | 19.29                       | 44.09                              | 54                         | 9.91           |

**802.11n-HT20 Mode:**

| Frequency<br>(MHz)        | Receiver          |                          | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|---------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                           | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                     | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| Low Channel (2412 MHz)    |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                     | 43.77             | QP                       | 104                 | 1.3           | H              | -14.5                       | 29.27                              | 43.5                       | 14.23          |
| 2412.00                   | 92.46             | PK                       | 248                 | 1.4           | H              | 6.13                        | 98.59                              | /                          | /              |
| 2412.00                   | 82.33             | Ave.                     | 248                 | 1.4           | H              | 6.13                        | 88.46                              | /                          | /              |
| 2412.00                   | 101.84            | PK                       | 272                 | 1.5           | V              | 6.13                        | 107.97                             | /                          | /              |
| 2412.00                   | 91.64             | Ave.                     | 272                 | 1.5           | V              | 6.13                        | 97.77                              | /                          | /              |
| 2353.25                   | 51.34             | PK                       | 210                 | 1.7           | H              | 5.48                        | 56.82                              | 74                         | 17.18          |
| 2353.25                   | 34.30             | Ave.                     | 210                 | 1.7           | H              | 5.48                        | 39.78                              | 54                         | 14.22          |
| 2380.36                   | 55.32             | PK                       | 104                 | 2.4           | H              | 5.48                        | 60.8                               | 74                         | 13.20          |
| 2380.36                   | 40.88             | Ave.                     | 104                 | 2.4           | H              | 5.48                        | 46.36                              | 54                         | 7.64           |
| 2485.89                   | 46.46             | PK                       | 280                 | 1.8           | V              | 7.21                        | 53.67                              | 74                         | 20.33          |
| 2485.89                   | 37.87             | Ave.                     | 280                 | 1.8           | V              | 7.21                        | 45.08                              | 54                         | 8.92           |
| 4824.00                   | 41.93             | PK                       | 171                 | 1.1           | H              | 12.44                       | 54.37                              | 74                         | 19.63          |
| 4824.00                   | 31.24             | Ave.                     | 171                 | 1.1           | H              | 12.44                       | 43.68                              | 54                         | 10.32          |
| 7236.00                   | 37.78             | PK                       | 13                  | 1.8           | H              | 17.06                       | 54.84                              | 74                         | 19.16          |
| 7236.00                   | 22.44             | Ave.                     | 13                  | 1.8           | H              | 17.06                       | 39.5                               | 54                         | 14.50          |
| 9648.00                   | 38.15             | PK                       | 261                 | 2.0           | V              | 19.28                       | 57.43                              | 74                         | 16.57          |
| 9648.00                   | 23.43             | Ave.                     | 261                 | 2.0           | V              | 19.28                       | 42.71                              | 54                         | 11.29          |
| Middle Channel (2437 MHz) |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                     | 43.52             | QP                       | 111                 | 1.3           | H              | -14.5                       | 29.02                              | 43.5                       | 14.48          |
| 2437.00                   | 92.30             | PK                       | 136                 | 1.3           | H              | 6.13                        | 98.43                              | /                          | /              |
| 2437.00                   | 82.18             | Ave.                     | 136                 | 1.3           | H              | 6.13                        | 88.31                              | /                          | /              |
| 2437.00                   | 101.43            | PK                       | 331                 | 1.1           | V              | 6.13                        | 107.56                             | /                          | /              |
| 2437.00                   | 91.94             | Ave.                     | 331                 | 1.1           | V              | 6.13                        | 98.07                              | /                          | /              |
| 2350.31                   | 50.19             | PK                       | 21                  | 1.8           | H              | 5.48                        | 55.67                              | 74                         | 18.33          |
| 2350.31                   | 35.17             | Ave.                     | 21                  | 1.8           | H              | 5.48                        | 40.65                              | 54                         | 13.35          |
| 2385.25                   | 55.18             | PK                       | 183                 | 2.2           | H              | 5.48                        | 60.66                              | 74                         | 13.34          |
| 2385.25                   | 38.24             | Ave.                     | 183                 | 2.2           | H              | 5.48                        | 43.72                              | 54                         | 10.28          |
| 2491.09                   | 45.94             | PK                       | 290                 | 2.5           | V              | 7.21                        | 53.15                              | 74                         | 20.85          |
| 2491.09                   | 35.48             | Ave.                     | 290                 | 2.5           | V              | 7.21                        | 42.69                              | 54                         | 11.31          |
| 4874.00                   | 40.66             | PK                       | 163                 | 1.2           | V              | 12.4                        | 53.06                              | 74                         | 20.94          |
| 4874.00                   | 32.63             | Ave.                     | 163                 | 1.2           | V              | 12.4                        | 45.03                              | 54                         | 8.97           |
| 7311.00                   | 38.91             | PK                       | 193                 | 1.8           | H              | 16.62                       | 55.53                              | 74                         | 18.47          |
| 7311.00                   | 23.67             | Ave.                     | 193                 | 1.8           | H              | 16.62                       | 40.29                              | 54                         | 13.71          |
| 9748.00                   | 38.31             | PK                       | 158                 | 1.5           | H              | 19.4                        | 57.71                              | 74                         | 16.29          |
| 9748.00                   | 24.29             | Ave.                     | 158                 | 1.5           | H              | 19.4                        | 43.69                              | 54                         | 10.31          |

| Frequency<br>(MHz)      | Receiver          |                          | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|-------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                         | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                     | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| High Channel (2462 MHz) |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                   | 43.64             | QP                       | 113                 | 1.3           | H              | -14.5                       | 29.14                              | 43.5                       | 14.36          |
| 2462.00                 | 92.38             | PK                       | 28                  | 2.3           | H              | 6.13                        | 98.51                              | /                          | /              |
| 2462.00                 | 83.54             | Ave.                     | 28                  | 2.3           | H              | 6.13                        | 89.67                              | /                          | /              |
| 2462.00                 | 101.93            | PK                       | 85                  | 1.5           | V              | 6.13                        | 108.06                             | /                          | /              |
| 2462.00                 | 92.28             | Ave.                     | 85                  | 1.5           | V              | 6.13                        | 98.41                              | /                          | /              |
| 2371.37                 | 46.16             | PK                       | 39                  | 2.3           | H              | 5.48                        | 51.64                              | 74                         | 22.36          |
| 2371.37                 | 29.87             | Ave.                     | 39                  | 2.3           | H              | 5.48                        | 35.35                              | 54                         | 18.65          |
| 2489.87                 | 57.86             | PK                       | 44                  | 2.2           | H              | 7.21                        | 65.07                              | 74                         | 8.93           |
| 2489.87                 | 42.76             | Ave.                     | 44                  | 2.2           | H              | 7.21                        | 49.97                              | 54                         | 4.03           |
| 2490.08                 | 55.97             | PK                       | 150                 | 2.1           | V              | 7.21                        | 63.18                              | 74                         | 10.82          |
| 2490.08                 | 40.59             | Ave.                     | 150                 | 2.1           | V              | 7.21                        | 47.8                               | 54                         | 6.20           |
| 4924.00                 | 41.10             | PK                       | 250                 | 2.3           | V              | 12.46                       | 53.56                              | 74                         | 20.44          |
| 4924.00                 | 32.20             | Ave.                     | 250                 | 2.3           | V              | 12.46                       | 44.66                              | 54                         | 9.34           |
| 7386.00                 | 37.06             | PK                       | 261                 | 1.7           | H              | 15.91                       | 52.97                              | 74                         | 21.03          |
| 7386.00                 | 23.85             | Ave.                     | 261                 | 1.7           | H              | 15.91                       | 39.76                              | 54                         | 14.24          |
| 9848.00                 | 38.48             | PK                       | 247                 | 1.5           | V              | 19.29                       | 57.77                              | 74                         | 16.23          |
| 9848.00                 | 23.93             | Ave.                     | 247                 | 1.5           | V              | 19.29                       | 43.22                              | 54                         | 10.78          |

**802.11n-HT40 Mode:**

| Frequency<br>(MHz)      | Receiver          |                          | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|-------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                         | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                     | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| Low Channel(2422MHz)    |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                   | 43.72             | QP                       | 114                 | 1.3           | H              | -14.5                       | 29.22                              | 43.5                       | 14.28          |
| 2422.00                 | 93.37             | PK                       | 327                 | 2.4           | H              | 6.13                        | 99.50                              | /                          | /              |
| 2422.00                 | 83.41             | Ave.                     | 327                 | 2.4           | H              | 6.13                        | 89.54                              | /                          | /              |
| 2422.00                 | 102.20            | PK                       | 203                 | 1.8           | V              | 6.13                        | 108.33                             | /                          | /              |
| 2422.00                 | 92.44             | Ave.                     | 203                 | 1.8           | V              | 6.13                        | 98.57                              | /                          | /              |
| 2355.27                 | 56.48             | PK                       | 241                 | 2.4           | H              | 5.48                        | 61.96                              | 74                         | 12.04          |
| 2355.27                 | 39.86             | Ave.                     | 241                 | 2.4           | H              | 5.48                        | 45.34                              | 54                         | 8.66           |
| 2388.03                 | 58.64             | PK                       | 214                 | 2.4           | H              | 5.48                        | 64.12                              | 74                         | 9.88           |
| 2388.03                 | 40.03             | Ave.                     | 214                 | 2.4           | H              | 5.48                        | 45.51                              | 54                         | 8.49           |
| 2495.77                 | 45.80             | PK                       | 205                 | 2.5           | V              | 7.21                        | 53.01                              | 74                         | 20.99          |
| 2495.77                 | 29.79             | Ave.                     | 205                 | 2.5           | V              | 7.21                        | 37                                 | 54                         | 17.00          |
| 4844.00                 | 42.42             | PK                       | 129                 | 2.2           | V              | 12.4                        | 54.82                              | 74                         | 19.18          |
| 4844.00                 | 30.92             | Ave.                     | 129                 | 2.2           | V              | 12.4                        | 43.32                              | 54                         | 10.68          |
| 7266.00                 | 38.79             | PK                       | 149                 | 1.7           | V              | 16.62                       | 55.41                              | 74                         | 18.59          |
| 7266.00                 | 23.87             | Ave.                     | 149                 | 1.7           | V              | 16.62                       | 40.49                              | 54                         | 13.51          |
| 9688.00                 | 38.89             | PK                       | 58                  | 1.8           | H              | 19.29                       | 58.18                              | 74                         | 15.82          |
| 9688.00                 | 23.73             | Ave.                     | 58                  | 1.8           | H              | 19.29                       | 43.02                              | 54                         | 10.98          |
| Middle Channel(2437MHz) |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                   | 43.27             | QP                       | 112                 | 1.3           | H              | -14.5                       | 28.77                              | 43.5                       | 14.73          |
| 2437.00                 | 92.33             | PK                       | 64                  | 2.3           | H              | 6.13                        | 98.46                              | /                          | /              |
| 2437.00                 | 81.99             | Ave.                     | 64                  | 2.3           | H              | 6.13                        | 88.12                              | /                          | /              |
| 2437.00                 | 102.06            | PK                       | 201                 | 1.2           | V              | 6.13                        | 108.19                             | /                          | /              |
| 2437.00                 | 91.95             | Ave.                     | 201                 | 1.2           | V              | 6.13                        | 98.08                              | /                          | /              |
| 2346.21                 | 49.51             | PK                       | 10                  | 1.6           | H              | 5.48                        | 54.99                              | 74                         | 19.01          |
| 2346.21                 | 35.38             | Ave.                     | 10                  | 1.6           | H              | 5.48                        | 40.86                              | 54                         | 13.14          |
| 2375.39                 | 54.17             | PK                       | 178                 | 1.2           | H              | 5.48                        | 59.65                              | 74                         | 14.35          |
| 2375.39                 | 37.26             | Ave.                     | 178                 | 1.2           | H              | 5.48                        | 42.74                              | 54                         | 11.26          |
| 2484.43                 | 42.58             | PK                       | 211                 | 2.4           | V              | 7.21                        | 49.79                              | 74                         | 24.21          |
| 2484.43                 | 23.82             | Ave.                     | 211                 | 2.4           | V              | 7.21                        | 31.03                              | 54                         | 22.97          |
| 4874.00                 | 40.48             | PK                       | 101                 | 1.2           | V              | 12.4                        | 52.88                              | 74                         | 21.12          |
| 4874.00                 | 30.10             | Ave.                     | 101                 | 1.2           | V              | 12.4                        | 42.5                               | 54                         | 11.50          |
| 7311.00                 | 37.10             | PK                       | 141                 | 1.7           | V              | 16.62                       | 53.72                              | 74                         | 20.28          |
| 7311.00                 | 22.54             | Ave.                     | 141                 | 1.7           | V              | 16.62                       | 39.16                              | 54                         | 14.84          |
| 9748.00                 | 39.80             | PK                       | 353                 | 1.8           | V              | 19.4                        | 59.2                               | 74                         | 14.80          |
| 9748.00                 | 23.41             | Ave.                     | 353                 | 1.8           | V              | 19.4                        | 42.81                              | 54                         | 11.19          |

| Frequency<br>(MHz)     | Receiver          |                          | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | FCC Part<br>15.247/205/209 |                |
|------------------------|-------------------|--------------------------|---------------------|---------------|----------------|-----------------------------|------------------------------------|----------------------------|----------------|
|                        | Reading<br>(dBμV) | Detector<br>(PK/QP/Ave.) |                     | Height<br>(m) | Polar<br>(H/V) |                             |                                    | Limit<br>(dBμV/m)          | Margin<br>(dB) |
| High Channel(2452 MHz) |                   |                          |                     |               |                |                             |                                    |                            |                |
| 146.2                  | 43.78             | QP                       | 100                 | 1.3           | H              | -14.5                       | 29.28                              | 43.5                       | 14.22          |
| 2452.00                | 92.48             | PK                       | 251                 | 1.9           | H              | 6.13                        | 98.61                              | /                          | /              |
| 2452.00                | 82.06             | Ave.                     | 251                 | 1.9           | H              | 6.13                        | 88.19                              | /                          | /              |
| 2452.00                | 103.12            | PK                       | 284                 | 1.9           | V              | 6.13                        | 109.25                             | /                          | /              |
| 2452.00                | 92.33             | Ave.                     | 284                 | 1.9           | V              | 6.13                        | 98.46                              | /                          | /              |
| 2384.31                | 44.69             | PK                       | 165                 | 2.0           | H              | 5.48                        | 50.17                              | 74                         | 23.83          |
| 2384.31                | 30.74             | Ave.                     | 165                 | 2.0           | H              | 5.48                        | 36.22                              | 54                         | 17.78          |
| 2488.27                | 59.85             | PK                       | 296                 | 2.3           | H              | 7.21                        | 67.06                              | 74                         | 6.94           |
| 2488.27                | 41.20             | Ave.                     | 296                 | 2.3           | H              | 7.21                        | 48.41                              | 54                         | 5.59           |
| 2496.46                | 54.82             | PK                       | 290                 | 1.6           | V              | 7.21                        | 62.03                              | 74                         | 11.97          |
| 2496.46                | 39.45             | Ave.                     | 290                 | 1.6           | V              | 7.21                        | 46.66                              | 54                         | 7.34           |
| 4904.00                | 40.61             | PK                       | 42                  | 1.9           | H              | 12.46                       | 53.07                              | 74                         | 20.93          |
| 4904.00                | 32.86             | Ave.                     | 42                  | 1.9           | H              | 12.46                       | 45.32                              | 54                         | 8.68           |
| 7356.00                | 37.76             | PK                       | 22                  | 2.3           | V              | 16.49                       | 54.25                              | 74                         | 19.75          |
| 7356.00                | 23.77             | Ave.                     | 22                  | 2.3           | V              | 16.49                       | 40.26                              | 54                         | 13.74          |
| 9808.00                | 38.22             | PK                       | 326                 | 2.4           | V              | 19.29                       | 57.51                              | 74                         | 16.49          |
| 9808.00                | 23.14             | Ave.                     | 326                 | 2.4           | V              | 19.29                       | 42.43                              | 54                         | 11.57          |

**Note:**


Corrected Amplitude = Corrected Factor + Reading

Corrected Factor=Antenna factor (RX) + Cable loss – Amplifier Factor


Margin = Limit - Corrected Amplitude

# Conducted Spurious Emissions at Antenna Port:


## 802.11b Low Channel, Antenna 0




## 802.11b Middle Channel, Antenna 0




### 802.11b High Channel, Antenna 0




### 802.11g Low Channel, Antenna 0




### 802.11g Middle Channel, Antenna 0




### 802.11g High Channel, Antenna 0




### 802.11n-HT20 Low Channel, Antenna 0




### 802.11n-HT20 Middle Channel, Antenna 0




### 802.11n-HT20 High Channel, Antenna 0




### 802.11n-HT40 Low Channel, Antenna 0




### 802.11n-HT40 Middle Channel, Antenna 0




### 802.11n-HT40 High Channel, Antenna 0




### 802.11b Low Channel, Antenna 1




### 802.11b Middle Channel, Antenna 1




### 802.11b High Channel, Antenna 1




### 802.11g Low Channel, Antenna 1




### 802.11g Middle Channel, Antenna 1




### 802.11g High Channel, Antenna 1




### 802.11n-HT20 Low Channel, Antenna 1




### 802.11n-HT20 Middle Channel, Antenna 1




### 802.11n-HT20 High Channel, Antenna 1




### 802.11n-HT40 Low Channel, Antenna 1



### 802.11n-HT40 Middle Channel, Antenna 1



### 802.11n-HT40 High Channel, Antenna 1



## FCC §15.247(a) (2) – 6 dB BANDWIDTH TESTING


### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Equipment List and Details

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 8386001028    | 2013-11-12       | 2014-11-12           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 50 %      |
| ATM Pressure:      | 101.0 kPa |

The testing was performed by Haiguo Li on 2014-07-21.


Test Mode: Transmitting

**Test Result:** Pass.


Please refer to the following tables and plots.

| Channel           | Frequency (MHz) | 6 dB Emission Bandwidth (MHz) |           | Limit (kHz) | Result |
|-------------------|-----------------|-------------------------------|-----------|-------------|--------|
|                   |                 | Antenna 0                     | Antenna 1 |             |        |
| 802.11b mode      |                 |                               |           |             |        |
| Low               | 2412            | 10.10                         | 10.10     | ≥500        | Pass   |
| Middle            | 2437            | 10.10                         | 10.10     | ≥500        | Pass   |
| High              | 2462            | 10.10                         | 10.10     | ≥500        | Pass   |
| 802.11g mode      |                 |                               |           |             |        |
| Low               | 2412            | 16.47                         | 16.47     | ≥500        | Pass   |
| Middle            | 2437            | 16.47                         | 16.47     | ≥500        | Pass   |
| High              | 2462            | 16.47                         | 16.47     | ≥500        | Pass   |
| 802.11n-HT20 mode |                 |                               |           |             |        |
| Low               | 2412            | 17.68                         | 17.68     | ≥500        | Pass   |
| Middle            | 2437            | 17.68                         | 17.68     | ≥500        | Pass   |
| High              | 2462            | 17.68                         | 17.68     | ≥500        | Pass   |
| 802.11n-HT40 mode |                 |                               |           |             |        |
| Low               | 2422            | 35.95                         | 35.95     | ≥500        | Pass   |
| Middle            | 2437            | 35.95                         | 35.95     | ≥500        | Pass   |
| High              | 2452            | 35.95                         | 35.95     | ≥500        | Pass   |


### 802.11b Low Channel, Antenna 0




### 802.11b Middle Channel, Antenna 0




## 802.11b High Channel, Antenna 0




## 802.11b Low Channel, Antenna 1




### 802.11b Middle Channel, Antenna 1




### 802.11b High Channel, Antenna 1




### 802.11g Low Channel, Antenna 0




### 802.11g Middle Channel, Antenna 0



## 802.11g High Channel, Antenna 0



## 802.11g Low Channel, Antenna 1



Ref Lvl 23.5 dBm Delta 1 [T1] -2.09 dB RBW 100 kHz RF Att 30 dB

23.5 20 10 0 -10 -20 -30 -40 -50 -60 -70 -76.5

3.5 dB Offset

D1 3.38 dBm D2 -2.62 dBm


1MAX

1 [T1] 2.45385371 GHz -2.09 dB 16.47294589 MHz


Center 2.462 GHz 3 MHz/ Span 30 MHz

Date: 21.JUL.2015 17:11:45

## 802.11n-HT20 Low Channel, Antenna 0



## 802.11n-HT20 Middle Channel, Antenna 0



Ref Lvl 23.5 dBm Delta 1 [T1] -2.13 dB RBW 100 kHz RF Att 30 dB  
 23.5 dB Offset 17.67535070 MHz VBW 300 kHz SWT 7.5 ms Unit dBm

3.5 dB Offset

D1 2.15 dBm D2 -3.85 dBm

1MAX 1MA

Center 2.462 GHz 3 MHz/ Span 30 MHz


2.45325251 GHz -2.13 dB 17.67535070 MHz

1 [T1] 1 [T1]


Delta 1 [T1] -2.23 dB  
 RBW 100 kHz RF Att 30 dB  
 VBW 300 kHz  
 Ref Lvl 23.5 dBm 17.67535070 MHz  
 SWT 7.5 ms Unit dBm

3.5 dB Offset  
 -D1 2.23 dBm  
 -D2 -3.77 dBm  
 1MAX  
 1A  
 2.40325251 GHz  
 -2.23 dB  
 17.67535070 MHz  
 Center 2.412 GHz 3 MHz/ Span 30 MHz  
 Date: 21. JUL 2014 17:14:06

### 802.11n-HT20 Middle Channel, Antenna 1



### 802.11n-HT20 High Channel, Antenna 1



Ref Lvl 23.5 dBm Delta 1 [T1] -2.45 dB RBW 100 kHz RF Att 30 dB  
 23.5 dBm 35.95190381 MHz SWT 15 ms Unit dBm

3.5 dB Offset

D1 -1.33 dBm  
 D2 -7.33 dBm

1 MAX

1 [T1] -2.45 dB  
 2.40414429 GHz -2.45 dB  
 35.95190381 MHz -2.45 dB

Center 2.422 GHz 6 MHz/ Span 60 MHz

Date: 21. JUL. 2014 19:58:52

Delta 1 [T1] -2.52 dB  
 Ref Lvl 23.5 dBm  
 35.95190381 MHz  
 RBW 100 kHz  
 VBW 300 kHz  
 SWT 15 ms  
 RF Att 30 dB  
 Unit dBm

3.5 dB Offset  
 D1 -1.56 dBm  
 D2 -7.56 dBm  
 1MAX  
 2.41914429 GHz  
 -2.52 dB  
 35.95190381 MHz  
 6 MHz/  
 Span 60 MHz  
 Center 2.437 GHz

Date: 21. JUL. 2014 20:00:29

Ref Lvl 23.5 dBm Delta 1 [T1] -2.65 dB RBW 100 kHz RF Att 30 dB  
 3.5 dB Offset 35.95190381 MHz VSWR 300 kHz Unit dBm

Center 2.452 GHz 6 MHz/ Span 60 MHz

Date: 21. JUL. 1998 20:03:02

Ref Lvl  
23.5 dBm

Delta 1 [T1]  
-2.04 dB

RBW 100 kHz  
VBW 300 kHz  
SWT 15 ms

RF Att 30 dB

Unit dBm

3.5 dB Offset

2.40414429 GHz  
-2.04 dB

35.95190381 MHz

D1 -1.53 dBm

D2 -7.53 dBm

1MAX


Center 2.422 GHz

6 MHz/


Span 60 MHz

Date: 21.JUL.1998 17:23:50

## 802.11n-HT40 Middle Channel, Antenna 1



## 802.11n-HT40 High Channel, Antenna 1



## FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER


### Applicable Standard

According to §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r02

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



### Test Equipment List and Details

| Manufacturer | Description  | Model    | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------|----------|---------------|------------------|----------------------|
| HP           | Power Meter  | EPM-441A | GB37481494    | 2013-11-24       | 2014-11-24           |
| HP           | Power Sensor | EPM-441A | GB37481494    | 2013-11-24       | 2014-11-24           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 50%       |
| ATM Pressure:      | 101.0 kPa |

The testing was performed by Haiguo Li on 2014-07-21.

*Test Mode: Transmitting*

| Channel           | Frequency<br>(MHz) | Max Peak Conducted Output Power (dBm) |           |                         | Limit<br>(dBm) |
|-------------------|--------------------|---------------------------------------|-----------|-------------------------|----------------|
|                   |                    | Antenna 0                             | Antenna 1 | Antenna 0<br>+Antenna 1 |                |
| 802.11b mode      |                    |                                       |           |                         |                |
| Low               | 2412               | 18.26                                 | 18.06     | \                       | 30             |
| Middle            | 2437               | 18.10                                 | 18.20     | \                       | 30             |
| High              | 2462               | 17.74                                 | 18.40     | \                       | 30             |
| 802.11g mode      |                    |                                       |           |                         |                |
| Low               | 2412               | 22.58                                 | 22.19     | \                       | 30             |
| Middle            | 2437               | 22.32                                 | 22.24     | \                       | 30             |
| High              | 2462               | 22.01                                 | 22.19     | \                       | 30             |
| 802.11n-HT20 mode |                    |                                       |           |                         |                |
| Low               | 2412               | 21.86                                 | 21.50     | 24.69                   | 30             |
| Middle            | 2437               | 21.36                                 | 21.42     | 24.40                   | 30             |
| High              | 2462               | 21.04                                 | 21.33     | 24.20                   | 30             |
| 802.11n-HT40 mode |                    |                                       |           |                         |                |
| Low               | 2422               | 20.83                                 | 20.33     | 23.60                   | 30             |
| Middle            | 2437               | 20.54                                 | 20.34     | 23.45                   | 30             |
| High              | 2452               | 20.48                                 | 20.17     | 23.34                   | 30             |


**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE****Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Procedure**

According to KDB 558074 D01 DTS Meas Guidance v03r02

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Equipment List and Details**

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 8386001028    | 2013-11-12       | 2014-11-12           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

# Test Data

## Environmental Conditions


|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 50 %      |
| ATM Pressure:      | 101.0 kPa |

The testing was performed by Haiguo Li on 2014-07-21.


Test Mode: Transmitting

**Test Result:** Compliance. Please refer to following plots.


## 802.11b: Band Edge, Left Side, Antenna 0




### 802.11b: Band Edge, Right Side, Antenna 0




### 802.11g: Band Edge, Left Side, Antenna 0




### 802.11g: Band Edge, Right Side, Antenna 0




### 802.11n-HT20: Band Edge, Left Side, Antenna 0




### 802.11n-HT20: Band Edge, Right Side, Antenna 0




### 802.11n-HT40: Band Edge, Left Side, Antenna 0





### 802.11n-HT40: Band Edge, Right Side, Antenna 0




### 802.11b: Band Edge, Left Side, Antenna 1






**802.11b: Band Edge, Right Side, Antenna 1****802.11g: Band Edge, Left Side, Antenna 1**

### 802.11g: Band Edge, Right Side, Antenna 1




### 802.11n-HT20: Band Edge, Left Side, Antenna 1



**802.11n-HT20: Band Edge, Right Side, Antenna 1****802.11n-HT40: Band Edge, Left Side, Antenna 1**

### 802.11n-HT40: Band Edge, Right Side, Antenna 1



## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure (KDB558074 D01 DTS Meas Guidance v03r02 sub-clause 10.2)

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### Test Equipment List and Details

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 8386001028    | 2013-11-12       | 2014-11-12           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


|                    |            |
|--------------------|------------|
| Temperature:       | 25 – 28 °C |
| Relative Humidity: | 50 – 57 %  |
| ATM Pressure:      | 101.0 kPa  |

The testing was performed by Haiguo Li from 2014-07-21 to 2014-07-31.


*Test Mode: Transmitting***Test Result: Pass**

| Channel           | Frequency<br>(MHz) | PSD(dBm/3kHz) |           |                         | Limit<br>(dBm/3kHz) |
|-------------------|--------------------|---------------|-----------|-------------------------|---------------------|
|                   |                    | Antenna 0     | Antenna 1 | Antenna 0<br>+Antenna 1 |                     |
| 802.11b mode      |                    |               |           |                         |                     |
| Low               | 2412               | -4.28         | -4.10     | \                       | ≤8                  |
| Middle            | 2437               | -5.46         | -5.53     | \                       | ≤8                  |
| High              | 2462               | -5.50         | -5.56     | \                       | ≤8                  |
| 802.11g mode      |                    |               |           |                         |                     |
| Low               | 2412               | -12.18        | -12.08    | \                       | ≤8                  |
| Middle            | 2437               | -12.80        | -12.57    | \                       | ≤8                  |
| High              | 2462               | -12.83        | -13.24    | \                       | ≤8                  |
| 802.11n-HT20 mode |                    |               |           |                         |                     |
| Low               | 2412               | -13.03        | -13.43    | -10.22                  | ≤8                  |
| Middle            | 2437               | -13.30        | -13.41    | -10.32                  | ≤8                  |
| High              | 2462               | -13.51        | -13.44    | -10.46                  | ≤8                  |
| 802.11n-HT40 mode |                    |               |           |                         |                     |
| Low               | 2422               | -14.85        | -16.10    | -12.37                  | ≤8                  |
| Middle            | 2437               | -16.39        | -16.55    | -13.47                  | ≤8                  |
| High              | 2452               | -16.18        | -16.69    | -13.47                  | ≤8                  |


## Power Spectral Density, 802.11b Low Channel, Antenna 0




## Power Spectral Density, 802.11b Middle Channel, Antenna 0




### Power Spectral Density, 802.11b High Channel, Antenna 0




### Power Spectral Density, 802.11b Low Channel, Antenna 1




### Power Spectral Density, 802.11b Middle Channel, Antenna 1




### Power Spectral Density, 802.11b High Channel, Antenna 1




### Power Spectral Density, 802.11g Low Channel, Antenna 0




### Power Spectral Density, 802.11g Middle Channel, Antenna 0




### Power Spectral Density, 802.11g High Channel, Antenna 0




### Power Spectral Density, 802.11g Low Channel, Antenna 1





### Power Spectral Density, 802.11g Middle Channel, Antenna 1




### Power Spectral Density, 802.11g High Channel, Antenna 1






**Power Spectral Density, 802.11n-HT20 Low Channel, Antenna 0****Power Spectral Density, 802.11n-HT20 Middle Channel, Antenna 0**

### Power Spectral Density, 802.11n-HT20 High Channel, Antenna 0




### Power Spectral Density, 802.11n-HT20 Low Channel, Antenna 1






**Power Spectral Density, 802.11n-HT20 Middle Channel, Antenna 1****Power Spectral Density, 802.11n-HT20 High Channel, Antenna 1**



### Power Spectral Density, 802.11n-HT40 Low Channel, Antenna 0



### Power Spectral Density, 802.11n-HT40 Middle Channel, Antenna 0



**Power Spectral Density, 802.11n-HT40 High Channel, Antenna 0****Power Spectral Density, 802.11n-HT40 Low Channel, Antenna 1**

**Power Spectral Density, 802.11n-HT40 Middle Channel, Antenna 1****Power Spectral Density, 802.11n-HT40 High Channel, Antenna 1**

## PRODUCT SIMILARITY DECLARATION LETTER



Kasda Digital Technology Co., Ltd.  
B-31 Building, Tanglang Industry Zone, Xili Nanshan, Shenzhen, China  
Tel: +86 755 8609 6689 Fax: +86 755 8610 6137

7/30/2014

### Product Similarity Declaration

To Whom It May Concern,

We, Kasda Digital Technology Co., Ltd., hereby declare that we have a product named as Wireless Router ( Model number: KW55293 ) was tested by BACL, meanwhile, for our marketing purpose, we would like to list a series models ( KW55293, GR55293NF ) on reports and certificate, all the models are identical schematics only named differently. We confirm that all information above is true, and we'll be responsible for all the consequences. Please contact me if you have any question.

Signature: *Xiong Ying*

Xiong, Ying

Purchasing Manager

\*\*\*\*\* END OF REPORT \*\*\*\*\*