



## Maximum Permissible Exposure

SSNT92-U2B;

Silver Spring Networks NIC 451

FCC, Part 15 §1.1310

Industry Canada RSS-Gen §3.2

### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4\pi d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10^{(G \text{ (dBi)}/10)}$$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm<sup>2</sup>

The calculations in the table below use highest gain antennas for the client EUT. Where the antenna gain exceeds 6dBi the transmitter power is reduced where necessary to meet the EIRP requirements. These calculations represent worst case in terms of the exposure levels.

Per FCC 1.1310 Power density Limit for device operating in frequency range 300 to 1500MHz = f/1500 (mW/cm<sup>2</sup>)

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 0.6mW/cm <sup>2</sup> Limit(cm)	Minimum Separation Distance (cm)
900 - 928	+1.2	1.32	29.674	927.7	12.8	20

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm <sup>2</sup> Limit(cm)	Minimum Separation Distance (cm)
2400 – 2483.5	+4.5	2.82	26.330	429.6	9.8	20

**Note:** for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Specification

#### Maximum Permissible Exposure Limits

**FCC §1.1310** Limit = 1mW / cm<sup>2</sup> from 1.310 Table 1

**RSS-Gen §3.2** The requirements in Radio Standards Specification RSS-102 shall be met.

### Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty	±1.33 dB
-------------------------	----------