RF Exposure (MPE) Calculations

Silver Spring Networks										
FCC ID: OWS-NIC514										
IC: 5975A- NIC514										
Utility Meter WLAN Transceiver			2.4 GHz			**Calculate mW/cm2 here. Enter frequency in MHz:**				
RF Hazard Distance Calculation						Calculation of Limits from 1.1310 Table 1				
									Controlled	Uncontrolled
									Ave 6 min	Ave 30 min
mW/cm2 from Table1:		1.00	(E: 61 V/m)			F(MHz)	**Actual F, MHz**		Occ, mW/c2	Gen, mW/cm2
						0.3-3	0.5		100.0	100.0
Max RF Power	TX Antenna	MPE distance	S, mW/cm@	Comment		*3.0 - 30.0*	*5*		*180.0*	*36.0*
P, dBm	G, dBi	cm	at 20 cm			**30.0-300**	**55**		**1.0**	**0.2**
						300-1500	*902*		*3.0*	*0.60*
21.7	**1.0**	**3.8**	**0.04**			1500-100000	5555		5.0	1.0
						Enter P(mW)	Equivalent dBm	**Enter dBm**	Equivalent Watts	
Basis of Calculations:						***64***	**18.1**	***18.1***	64.6	
E^2/3770 = S, mW/cm2										
E, V/m = (Pwatts*Ggain*30)^.5/d, meters										
d = ((Pwatts*G*30)/3770*S))^0.5			Pwatts*Ggain = 10^(PdBm-30+GdBi)/10)							
S@20cm = 20 log (MPE dist/20cm)										
NOTE: For mobile or fixed location transmitters, minimum separation distance is for FCC compliance is 20 cm,										
even if calculations indicate MPE distance is less										