

# MPE/RF EXPOSURE EVALUATION REPORT



Evaluation of: Itron Inc NIC 531-0601

to

To: FCC CFR 47 Part 15 RF Exposure requirements

Test Report Serial No.: ITRO18-U5 Rev A FCC MPE

This report supersedes: NONE

Applicant: Itron Networked Solutions, Inc.  
230 West Tasman Drive  
San Jose, California 95134  
USA

Product Function: Plug in radio device, mesh and  
HAN networks

Issue Date: 29th April 2019

## **This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**



**Title:** ITRON Inc. NIC 531-0601  
**To:** FCC CFR 47 Part 1.1310  
**Serial #:** ITRO18-U5 Rev A FCC MPE  
**Issue Date:** 29th April 2019  
**Page:** 2 of 4

## 1. MAXIMUM PERMISSABLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4*\pi*d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 \wedge (\text{G (dBi)}/10)$$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1 mW/cm<sup>2</sup>

These calculations represent worst case in terms of the exposure levels for the device.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit (mW/cm <sup>2</sup> )	Min Calculated safe distance for Limit (cm)
902- 928 (DSSS)	1.0	1.26	27.70	588.8	0.147	0.6	9.92
902- 928 (FHSS)	1.0	1.26	29.88	972.7	0.244	0.6	12.75
2400 - 2483.5	0.0	1.0	26.40	436.5	0.09	1.0	5.89

**Note:** for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Specification

#### Maximum Permissible Exposure Limits

FCC §1.1310 Table 1 (B) Limits for General Population/Uncontrolled Exposure

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** ITRON Inc. NIC 531-0601  
**To:** FCC CFR 47 Part 1.1310  
**Serial #:** ITRO18-U5 Rev A FCC MPE  
**Issue Date:** 29th April 2019  
**Page:** 3 of 4

### Specification - Maximum Permissible Exposure Limits

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500	--	--	f/300	6
1,500-100,000	--	--	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500	--	--	f/1500	30
1,500-100,000	--	--	1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)