

# RF EXPOSURE REPORT

Applicant	ARTS DIGITAL TECHNOLOGY (HK) LTD
Address	1704, 17/F, Fo Tan Industrial Centre, 26-28 Au Pui Wan St., Fo Tan, Hong Kong

Manufacturer or Supplier	ARTS DIGITAL TECHNOLOGY (HK) LTD	
Address	1704, 17/F, Fo Tan Industrial Centre, 26-28 Au Pui Wan St., Fo Tan, Hong Kong	
Product	Bluetooth Karaoke System w/7" TFT	
Brand Name	ADT, AKAI	
Model	KS800-BT	
Additional Model & Model Difference	KS808, KS800, KS808-BT, KS80X-BT, KS80X	
Date of tests	Jun. 03, 2016 ~ Jun. 23, 2016	

FCC Part 2 (Section 2.1091)

neerl

- **KDB 447498 D01**
- **⊠** IEEE C95.1

### $\textbf{CONCLUSION: The submitted sample was found to } \underline{\textbf{COMPLY}} \text{ with the test requirement}$

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Chris Chen Manager / EMC Department

Date: Jun. 23, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



## Test Report No.: FS160603N010

## **Table of Contents**

REL	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: <a href="mailto:customerservice.dg@cn.bureauveritas.com">customerservice.dg@cn.bureauveritas.com</a>



# **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS160603N010	Original release	Jun. 23, 2016

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: <u>customerservice.dg@cn.bureauveritas.com</u>

Page 3 of 6



## 1. CERTIFICATION

FCC ID:	OWT-KS800BT		
PRODUCT:	Bluetooth Karaoke System w/7" TFT		
BRAND NAME:	AME: ADT, AKAI		
MODEL NO.:	KS800-BT		
ADDITIONAL NO.:	KS808, KS800, KS808-BT, KS80X-BT, KS80X		
TEST SAMPLE:	E: Engineering Sample		
APPLICANT:	ARTS DIGITAL TECHNOLOGY (HK) LTD		
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01		
	IEEE C95.1		

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



## 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)			POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)		
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

### 3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: FS160603N010

## 5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type	
Chain 0	0	Integral PCB Antenna	

## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2402-2480	0.1355	0	20	0.00002696	1.0

--- END ---

Fax: +86 769 8593 1080

Tel: +86 769 8593 5656

Email: <u>customerservice.dg@cn.bureauveritas.com</u>

Page 6 of 6