## FCC §1.1307 (b) (1) & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE

## (MPE)

## **Applicable Standard**

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Report No.: RSZ181018003-00B

Limits for General Population/Uncontrolled Exposure										
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)						
0.3-1.34	614	1.63	*(100)	30						
1.34-30	824/f	2.19/f	$*(180/f^2)$	30						
30-300	27.5	0.073	0.2	30						
300-1500	/	/	f/1500	30						
1500-100,000	/	/	1.0	30						

f = frequency in MHz

## **MPE Calculated:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

FCC Part 20.21 Page 1 of 2

<sup>\* =</sup> Plane-wave equivalent power density

Tune-Up Power Including Tolerance:

Mode	Frequency band (MHz)	Antenna Gain		Max Tune-up Power	Cable	Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(dB)	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
uplink	698-716	8	6.31	23.5	4.97	20	0.090	0.465
	776-787	8	6.31	21.5	4.97	20	0.056	0.517
	824-849	8	6.31	22.0	5.17	20	0.061	0.549
	1710-1755	9	7.94	21.0	7.51	20	0.035	1.0
	1850-1915	9	7.94	20.0	7.51	20	0.028	1.0
downlink	728-746	5	3.16	14.0	4.97	20	0.005	0.485
	746-757	5	3.16	14.0	4.97	20	0.005	0.497
	869-894	5	3.16	14.0	5.17	20	0.005	0.579
	2110-2155	7	5.01	14.0	7.51	20	0.004	1.0
	1930-1995	7	5.01	14.0	7.51	20	0.004	1.0

Report No.: RSZ181018003-00B

Note: "3+"O czko wo "wpg/wr "qwr w'r qy gt "rkurgf "ku"GKTRO

\*4+"Vhis EUT contains FCC ID: 2AC7Z-ESP32WROVERB, and the power density is WkFk=0.1182'mW/cm<sup>2</sup>,

BLE=0.0007 mW/cm<sup>2</sup>, Bluetooth =0.0017 mW/cm<sup>2</sup>

According to the MPE of FCC ID: 2AC7Z-ESP32WROVERB, WIFI and Bluetooth can't transmitting simultaneously, so consider the booster and WIFI transmitting simultaneously is the worst case: The ratio= MPE/Limit<sub>Booster</sub>+ MPE/Limit<sub>WIFI</sub> = 0.005/0.485+0.1182/1=0.129<1.0

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20 cm from nearby persons.

**Result: Compliance** 

FCC Part 20.21 Page 2 of 2