

FCC §1.1307 & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (Minutes) |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | f/1500 | 30 |
| 1500-100,000 | / | / | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For worst case:

Uplink

| Frequency (MHz) | Max tune-up power | | Antenna Gain | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|-----------------|-------------------|--------|--------------|-----------|--------------------------|-------------------------------------|---------------------------------|
| | (dBm) | (mW) | (dBi) | (numeric) | | | |
| 824-849 | 21.00 | 125.89 | 7 | 5.01 | 30 | 0.056 | 0.56 |
| 1850-1910 | 21.00 | 125.89 | 7 | 5.01 | 30 | 0.056 | 1.00 |

Downlink

| Frequency (MHz) | Max tune-up power | | Antenna Gain | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|-----------------|-------------------|--------|--------------|-----------|--------------------------|-------------------------------------|---------------------------------|
| | (dBm) | (mW) | (dBi) | (numeric) | | | |
| 869-894 | 25.00 | 316.23 | 7 | 5.01 | 30 | 0.140 | 0.59 |
| 1930-1990 | 25.00 | 316.23 | 7 | 5.01 | 30 | 0.140 | 1.00 |

The Maximum indoor and outdoor Gain is 7.0 dBi

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 30cm from nearby persons.

Result: Compliance