


RADIO TEST REPORT

The device described below is tested by Dongguan Nore Testing Center Co., Ltd. to determine the maximum emission levels emanating from the device, the severe levels which the device can endure and E.U.T.'s performance criterion. The test results, data evaluation, test procedures, and equipment of configurations shown in this report were made in accordance with the procedures in ANSI C63.10(2013).

Applicant /Manufacturer : Targus International LLC
Address : 1211 North Miller Street, Anaheim, California, 92806, United States
Factory : Acrox Technologies Co., Ltd.
Address : Hsinmin Industrial, Changan Town, Dongguan City, Guangdong, China
E.U.T. : Wireless Receiver
Brand Name : Targus
Model No. : AMW572BR
FCC ID : OXM000069
Measurement Standard : FCC PART 15.249: 2016
Date of Receiver : December 06, 2016
Date of Test : December 06, 2016 to December 20, 2016
Date of Report : December 20, 2016

This Test Report is Issued Under the Authority of :

Prepared by



Rose Hu / Engineer

Approved & Authorized Signer



Iori Fan / Authorized Signatory

This test report is for the customer shown above and their specific product only. This report applies to above tested sample only and shall not be reproduced in part without written approval of Dongguan Nore Testing Center Co., Ltd.



Table of Contents

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	4
1.2 RELATED SUBMITTAL(S) / GRANT (S).....	6
1.3 TEST METHODOLOGY.....	6
1.4 EQUIPMENT MODIFICATIONS	6
1.5 SUPPORT DEVICE	6
1.6 TEST FACILITY AND LOCATION.....	7
1.7 SUMMARY OF TEST RESULTS.....	8
2. SYSTEM TEST CONFIGURATION.....	9
2.1 EUT CONFIGURATION	9
2.2 SPECIAL ACCESSORIES.....	9
2.3 DESCRIPTION OF TEST MODES	9
2.4 EUT EXERCISE	9
3. CONDUCTED EMISSIONS TEST	10
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	10
3.2 TEST CONDITION	10
3.3 MEASUREMENT RESULTS.....	10
4. RADIATED EMISSION TEST.....	13
4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	13
4.2 MEASUREMENT PROCEDURE	14
4.3 LIMIT.....	15
4.4 MEASUREMENT RESULTS	16
5. 20DB BANDWIDTH.....	20
5.1 MEASUREMENT PROCEDURE	20
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	20
5.3 MEASUREMENT RESULTS.....	20
6. BAND EDGE	23
6.1 MEASUREMENT PROCEDURE	23
6.2 LIMIT.....	23
6.3 MEASUREMENT RESULTS.....	23
7. ANTENNA REQUIREMENT	24
7.1 MEASUREMENT PROCEDURE	24
7.2 MEASUREMENT RESULTS.....	24
8. TEST EQUIPMENT LIST.....	25

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

This device is a 2.4G USB dongle, it's powered by DC 5V come from USB port. For more details features, please refer to User's Manual.

Product Name	: Wireless Receiver
Model Name	: AMW572BR
Model Difference Description	: None
Power Supply	: DC 5V come from USB port
Test Voltage	: AC 120V 60Hz PC input

Technical Specification:

2.4G Function:

Frequency Range	: 2404-2478MHz
Modulation Type	: GFSK
Number of Channel	: 75
Antenna Type	: PCB
Antenna Gain	: -1.0 dBi
Hardware version	: V1.13
Software version	: V1.0

Channel List:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	2404	26	2429	51	2454
2	2405	27	2430	52	2455
3	2406	28	2431	53	2456
4	2407	29	2432	54	2457
5	2408	30	2433	55	2458
6	2409	31	2434	56	2459
7	2410	32	2435	57	2460
8	2411	33	2436	58	2461
9	2412	34	2437	59	2462
10	2413	35	2438	60	2463
11	2414	36	2439	61	2464
12	2415	37	2440	62	2465
13	2416	38	2441	63	2466
14	2417	39	2442	64	2467
15	2418	40	2443	65	2468
16	2419	41	2444	66	2469
17	2420	42	2445	67	2470
18	2421	43	2446	68	2471
19	2422	44	2447	69	2472
20	2423	45	2448	70	2473
21	2424	46	2449	71	2474
22	2425	47	2450	72	2475
23	2426	48	2451	73	2476
24	2427	49	2452	74	2477
25	2428	50	2453	75	2478

Note: The Lowest, middle, and the Highest frequency of channel were selected to perform the test. The frequency selected see below:

The Lowest frequency: 2404MHz
The middle frequency: 2441MHz
The Highest frequency: 2478MHz

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: OXM000069 filing to comply with Section 15.249 of the FCC Part 15 (2016), Subpart C Rule.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

Notebook PC : Manufacturer: IBM Corporation
M/N: R50e
S/N: L3-HZNGO
P/N: 1834KDC
Adapter : Manufacturer: IBM Corporation
M/N: 08K8210
Input: AC100-240V 50/60Hz 0.5-1.0A
Output: DC 16V 4.5A

1.6 Test Facility and Location

Listed by CNAS, August 14, 2015

The certificate is valid until August 13, 2018

The Laboratory has been assessed and proved to be in compliance with CNAS/CL01

The Certificate Registration Number is L5795.

Listed by FCC, July 03, 2014

The Certificate Registration Number is 665078.

Listed by Industry Canada, June 18, 2014

The Certificate Registration Number is 46405-9743.

Dongguan NTC Co., Ltd.

(Full Name: Dongguan Nore Testing Center Co., Ltd.)

Building D, Gaosheng Science and Technology Park, Hongtu Road,

Nancheng District, Dongguan City, Guangdong, China

(Full Name: Building D, Gaosheng Science & Technology Park,

Zhouxi Longxi Road, Nancheng District, Dongguan, Guangdong, China.



1.7 Summary of Test Results

FCC Rules	Description Of Test	Uncertainty	Result
§15.207(a)	AC Power Conducted Emission	±1.06dB	Compliant
§15.249(a)/ 15.209	Radiated Emissions	±3.70dB	Compliant
§15.249(d)/ 15.205	Band Edge	±1.70dB	Compliant
§15.215(c)	20dB Bandwidth	±1.42 x10 ⁻⁴ %	Compliant
§15.203	Antenna Requirement	±0.60dB	Compliant

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories


Not available for this EUT intended for grant.

2.3 Description of test modes

The EUT has been tested under operating condition. The Lowest, middle and highest frequencies were chosen for testing.

2.4 EUT Exercise


The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.



Report No.: AMW572BR
 Test Standard: FCC PART 15_Class B_QP
 Test item: Conducted Emission Phase: L1
 Applicant: Targus Temp.()/Hum.(%): 24(C) / 58 %
 Product: Wireless Receiver Power Rating: AC 120V 60Hz(PC Input)
 Model No.: AMW572BR Test Engineer: Jess

Test Mode: TX
 Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1539	10.80	34.60	45.40	65.78	-20.38	QP	P	
2	0.1539	10.80	31.70	42.50	55.78	-13.28	AVG	P	
3	0.2300	10.80	17.80	28.60	62.45	-33.85	QP	P	
4	0.2300	10.80	10.50	21.30	52.45	-31.15	AVG	P	
5	0.5380	10.80	16.50	27.30	56.00	-28.70	QP	P	
6	0.5380	10.80	14.30	25.10	46.00	-20.90	AVG	P	
7	0.7700	10.80	16.10	26.90	56.00	-29.10	QP	P	
8	0.7700	10.80	14.40	25.20	46.00	-20.80	AVG	P	
9	1.0020	10.80	15.80	26.60	56.00	-29.40	QP	P	
10	1.0020	10.80	12.70	23.50	46.00	-22.50	AVG	P	
11	8.3860	10.80	18.30	29.10	60.00	-30.90	QP	P	
12	8.3860	10.80	12.00	22.80	50.00	-27.20	AVG	P	



Report No.: AMW572BR
 Test Standard: FCC PART 15_Class B_QP
 Test item: Conducted Emission
 Applicant: Targus
 Product: Wireless Receiver
 Model No.: AMW572BR
 Phase: N
 Temp.()/Hum.(%): 24(C) / 58 %
 Power Rating: AC 120V 60Hz(PC Input)
 Test Engineer: Jess

Test Mode: TX


Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1539	10.80	33.30	44.10	65.78	-21.68	QP	P	
2	0.1539	10.80	29.00	39.80	55.78	-15.98	AVG	P	
3	0.3060	10.80	15.90	26.70	60.08	-33.38	QP	P	
4	0.3060	10.80	12.50	23.30	50.08	-26.78	AVG	P	
5	0.5380	10.80	16.60	27.40	56.00	-28.60	QP	P	
6	0.5380	10.80	14.90	25.70	46.00	-20.30	AVG	P	
7	0.7700	10.80	17.00	27.80	56.00	-28.20	QP	P	
8	0.7700	10.80	14.80	25.60	46.00	-20.40	AVG	P	
9	2.1540	10.80	16.50	27.30	56.00	-28.70	QP	P	
10	2.1540	10.80	13.50	24.30	46.00	-21.70	AVG	P	
11	8.9220	10.80	20.00	30.80	60.00	-29.20	QP	P	
12	8.9220	10.80	15.10	25.90	50.00	-24.10	AVG	P	


4. Radiated Emission Test

4.1 Test SET-UP (Block Diagram of Configuration)

4.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz



4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



4.2 Measurement Procedure

- Blow 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- For the radiated emission test above 1GHz:
The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz


4.3 Limit

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)	
		μV/m	
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	
88 ~ 216	3	150	
216 ~ 960	3	200	
Above 960	3	500	
Frequency range MHz	Distance Meters	Field Strengths Limit (15.249)	
		mV/m (Field strength of fundamental)	μV/m (Field strength of Harmonics)
902 ~ 928	3	50	500
2400 ~ 2483.5	3	50	500
5725 ~ 5875	3	50	500
24000 ~ 2425000	3	250	2500

- Remark :
- (1) Emission level (dB)μV = 20 log Emission level μV/m
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

4.4 Measurement Results


Please refer to following the test plots of the worst case: High channel.



Report No.:	AMW572BR	Test Standard:	FCC Part 15_Class B_3M	Test Distance:	
Test item:	Radiation Emission	Ant. Polarization:	Horizontal	Temp.(C)/Hum.(%):	21(C) / 55 %
Applicant:	Targus	Power Rating:	AC 120V 60Hz(PC Input)	Test Engineer:	Lecdon
Product:	Wireless Receiver				
Model No.:	AMW572BR				
Test Mode:	TX				
Remark:					

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.0000	-16.57	32.70	16.13	40.00	-23.87	QP			P	
2	109.2788	-12.15	29.63	17.48	43.50	-26.02	QP			P	
3	298.9261	-10.49	33.21	22.72	46.00	-23.28	QP			P	
4	471.4743	-7.43	34.08	26.65	46.00	-19.35	QP			P	
5	595.8333	-5.11	32.34	27.23	46.00	-18.77	QP			P	
6	617.5959	-5.05	33.17	28.12	46.00	-17.88	QP			P	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.



Report No.:	AMW572BR	Test Standard:	FCC Part 15_Class B_3M	Test Distance:	
Test item:	Radiation Emission	Ant. Polarization:	Vertical	Temp.(C)/Hum.(%):	21(C) / 55 %
Applicant:	Targus	Power Rating:	AC 120V 60Hz(PC Input)	Test Engineer:	Lecdon
Product:	Wireless Receiver				
Model No.:	AMW572BR				
Test Mode:	TX				
Remark:					

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	43.9903	-13.97	28.18	14.21	40.00	-25.79	QP			P	
2	152.8044	-18.42	31.16	12.74	43.50	-30.76	QP			P	
3	298.9262	-12.49	31.83	19.34	46.00	-26.66	QP			P	
4	469.9198	-9.47	30.28	20.81	46.00	-25.19	QP			P	
5	619.1506	-7.05	30.26	23.21	46.00	-22.79	QP			P	
6	751.2819	-2.57	27.27	24.70	46.00	-21.30	QP			P	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.



Frequency Range: 1-25GHz Test Date : December 16, 2016
 Test Result: PASS Temperature : 21 °C
 Measured Distance: 3m Humidity : 55 %
 Test By: Sance

Freq. (MHz)	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)										
2404	V	81.35	71.64	8.15	89.50	79.79	114.00	94.00	-24.50	-14.21
4808	V	44.04	32.63	14.82	58.86	47.45	74.00	54.00	-15.14	-6.55
7212	V	39.65	28.06	20.85	60.50	48.91	74.00	54.00	-13.50	-5.09

2404	H	86.40	76.16	8.15	94.55	84.31	114.00	94.00	-19.45	-9.69
4808	H	44.07	32.61	14.82	58.89	47.43	74.00	54.00	-15.11	-6.57
7212	H	37.48	26.12	20.85	58.33	46.97	74.00	54.00	-15.67	-7.03

Operation Mode: TX Mode (Mid)										
2441	V	84.45	71.97	8.23	92.68	80.20	114.00	94.00	-21.32	-13.80
4882	V	40.26	28.22	14.95	55.21	43.17	74.00	54.00	-18.79	-10.83
7323	V	37.39	25.73	20.92	58.31	46.65	74.00	54.00	-15.69	-7.35

2441	H	82.36	72.37	8.23	90.59	80.60	114.00	94.00	-23.41	-13.40
4882	H	45.91	33.16	14.95	60.86	48.11	74.00	54.00	-13.14	-5.89
7323	H	37.24	25.58	20.92	58.16	46.50	74.00	54.00	-15.84	-7.50

Operation Mode: TX Mode (High)										
2478	V	81.25	69.47	8.20	89.45	77.67	114.00	94.00	-24.55	-16.33
4956	V	41.39	30.31	15.15	56.54	45.46	74.00	54.00	-17.46	-8.54
7434	V	36.92	25.54	21.02	57.94	46.56	74.00	54.00	-16.06	-7.44

2478	H	88.25	75.96	8.20	96.45	84.16	114.00	94.00	-17.55	-9.84
4956	H	41.61	29.60	15.15	56.76	44.75	74.00	54.00	-17.24	-9.25
7434	H	36.36	25.50	21.02	57.38	46.52	74.00	54.00	-16.62	-7.48

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level + Factor
 - (3) Factor= Antenna Gain + Cable Loss – Amplifier Gain
 - (4) Data of measurement within this frequency range shown “ ---” in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
 - (5) Measurement uncertainty : ±3.7dB.
 - (6) Horn antenna used for the emission over 1000MHz.


5. 20dB Bandwidth

5.1 Measurement Procedure

The 20dB bandwidth of the emission was contained within the frequency band designated which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered, FCC Rule 15.215(c):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

5.2 Test SET-UP (Block Diagram of Configuration)




5.3 Measurement Results

Refer to attached data chart.

RBW:	100KHz	VBW:	300KHz
Spectrum Detector:	PK	Temperature :	22 °C
Test By:	Sance	Humidity :	54 %
Test Result:	PASS	Test Date :	December 06, 2016

Channel frequency (MHz)	20dB Down BW(kHz)
2404	2748
2441	2163
2478	3021

Lowest Channel




Date: 6.DEC.2016 10:49:10

Middle Channel



Date: 6.DEC.2016 10:52:08

Highest Channel



Date: 6.DEC.2016 10:44:29



6. Band Edge

6.1 Measurement Procedure

Same as Radiated Emission Test.

6.2 Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

6.3 Measurement Results

Operation Mode:	TX Mode	Test Date :	December 16, 2016
Temperature :	21 °C	Humidity :	55 %
Test Result:	PASS	Test By:	Sance
Measured Distance:	3m		

Freq. (MHz)	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
2390.000	H	52.53	39.94	8.06	60.59	48.00	74.00	54.00	-13.41	-6.00
2390.000	V	52.15	40.66	8.06	60.21	48.72	74.00	54.00	-13.79	-5.28
2483.500	H	51.07	39.25	8.36	59.43	47.61	74.00	54.00	-14.57	-6.39
2483.500	V	51.53	38.86	8.36	59.89	47.22	74.00	54.00	-14.11	-6.78

- Note:**
- (1) Emission Level= Reading Level + Factor
 - (2) Factor= Antenna Gain + Cable Loss – Amplifier Gain
 - (3) Horn antenna used for the emission over 1000MHz.

7. Antenna requirement

7.1 Measurement Procedure

According to of FCC part 15C section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

7.2 Measurement Results

The antenna is PCB antenna and no consideration of replacement, and the best case gain of the antenna is -1.0dBi. So, the antenna is consider meet the requirement.

8. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Nov. 22, 2016	Nov. 21, 2017
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Nov. 25, 2016	Nov. 24, 2017
Positioning Controller	UC	UC 3000	N/A	0~360°, 1-4m	N/A	N/A
Color Monitor	SUNSP0	SP-140A	N/A	N/A	N/A	N/A
Single Phase Power Line Filter	SAEMC	PF201A-32	110210	32A	N/A	N/A
3 Phase Power Line Filter	SAEMC	PF401A-200	110318	200A	N/A	N/A
DC Power Filter	SAEMC	PF301A-200	110245	200A	N/A	N/A
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Nov. 06, 2016	Nov. 05, 2017
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Nov. 06, 2016	Nov. 05, 2017
RF Cable	Huber+Suhner	SF-104	MY16559/4	9KHz~25GHz	Mar. 06, 2016	Mar. 05, 2017
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Nov. 06, 2016	Nov. 05, 2017
Horn Antenna	Schwarzbeck	BBHA9170	9170-372	15GHz~26.5GHz	Oct.22, 2016	Oct.21, 2017
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Nov. 04, 2016	Nov. 03, 2017
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Oct.09, 2016	Oct.08, 2017
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Aug. 31, 2016	Aug. 30, 2017
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Nov. 02, 2016	Nov. 01, 2017
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Nov. 06, 2016	Nov. 07, 2017
Temporary antenna connector	TESCOM	SS402	N/A	9KHz-25GHz	N/A	N/A

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

---End---