


Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chungli Investments (Bermuda) LTD.				Job No.	R-8412-1	
Test Sample:	310 MHz RF Remote				Paragraph:	15.231(b)	
Model No.:	R550				FCC ID:	OXYR550	
Operating Mode:	Continuously Transmitting a 310 MHz Signal						
Technician:	T.S./P.L.				Date:	February 17, 2000	
Notes:	Test Distance: 3 Meters Detector: Peak, Unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H)/Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
310	H / 1.0	X	76.3	-4.0	72.3	4121.0	58330
	H / 1.0	Y	77.5	-4.0	73.5	4731.5	
	H / 2.5	Z	72.1	-4.0	68.1	2541.0	
	V / 1.0	X	74.9	-4.0	70.9	3507.5	
	V / 2.2	Y	75.5	-4.0	71.5	3758.4	
310	V / 1.8	Z	74.0	-4.0	70.0	3162.3	58330
620	H / 1.0	X	49.9	3.2	53.1	451.9	5833
	H / 1.0	Y	52.8	3.2	56.0	631.0	
	H / 1.5	Z	51.3	3.2	54.5	530.9	
	V / 2.0	X	50.4	3.2	53.6	478.6	
	V / 2.0	Y	47.6	3.2	50.8	346.7	
620	V / 1.0	Z	49.6	3.2	52.8	436.5	5833
930	H / 1.0	X	30.0	7.4	37.4	*74.1	5833
	H / 1.0	Y	30.0	7.4	37.4	*74.1	
	H / 1.0	Z	30.0	7.4	37.4	*74.1	
	V / 1.0	X	30.0	7.4	37.4	*74.1	
	V / 1.0	Y	30.0	7.4	37.4	*74.1	
930	V / 1.0	Z	30.0	7.4	37.4	*74.1	5833
1240	H / 3.0	X	51.3	-3.8	47.5	237.1	5000
	H / 2.5	Y	54.2	-3.8	50.4	331.1	
	H / 2.5	Z	49.0	-3.8	45.2	182.0	
	V / 2.5	X	45.4	-3.8	41.6	120.2	
	V / 2.1	Y	48.0	-3.8	44.2	162.2	
1240	V / 1.0	Z	30.0	-3.8	26.2	*20.4	5000
1550	H / 1.0	X	44.8	-0.1	44.7	171.8	5000
	H / 1.0	Y	30.0	-0.1	29.9	*31.3	
	H / 1.0	Z	51.1	-0.1	51.0	354.8	
	V / 1.0	X	30.0	-0.1	29.9	*31.3	
	V / 2.2	Y	51.3	-0.1	51.2	363.1	
1550	V / 1.0	Z	30.0	-0.1	29.9	*31.3	5000
The frequency range was scanned from 30 MHz to 3.1 GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8412


Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chungli Investments (Bermuda) LTD.			Job No.	R-8412-1		
Test Sample:	310 MHz RF Remote			Paragraph:	15.231(b)		
Model No.:	R550			FCC ID:	OXYR550		
Operating Mode:	Continuously Transmitting a 310 MHz Signal						
Technician:	T.S./P.L.			Date:	February 17, 2000		
Notes:	Test Distance: 3 Meters Detector: Peak, unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Peak Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
1860	H / 1.0	X	49.3	1.6	50.9	350.8	5833
	H / 1.0	Y	40.0	1.6	41.6	*120.2	
	H / 1.0	Z	45.2	1.6	46.8	218.8	
	V / 1.0	X	40.0	1.6	41.6	*120.2	
	V / 2.0	Y	45.5	1.6	47.1	226.5	
1860	V / 1.0	Z	43.7	1.6	45.3	184.1	5833
2170	H / 2.5	X	50.6	-1.3	49.3	291.7	5833
	H / 2.8	Y	49.2	-1.3	47.9	248.3	
	H / 1.0	Z	40.0	-1.3	38.7	*86.1	
	V / 2.0	X	48.5	-1.3	47.2	229.1	
	V / 1.0	Y	50.3	-1.3	49.0	281.8	
2170	V / 1.0	Z	43.6	-1.3	42.3	130.3	5833
2480	H / 1.0	X	40.0	0.1	40.1	*101.2	5833
	H / 1.0	Y	40.0	0.1	40.1	*101.2	
	H / 1.0	Z	40.0	0.1	40.1	*101.2	
	V / 1.0	X	40.0	0.1	40.1	*101.2	
	V / 1.0	Y	40.0	0.1	40.1	*101.2	
2480	V / 1.0	Z	40.0	0.1	40.1	*101.2	5833
2790	H / 1.0	X	40.0	1.4	41.4	*117.5	5000
	H / 1.0	Y	40.0	1.4	41.4	*117.5	
	H / 1.0	Z	40.0	1.4	41.4	*117.5	
	V / 1.0	X	40.0	1.4	41.4	*117.5	
	V / 1.0	Y	40.0	1.4	41.4	*117.5	
2790	V / 1.0	Z	40.0	1.4	41.4	*117.5	5000
3100	H / 1.0	X	40.0	3.5	43.5	*149.6	5833
	H / 1.0	Y	40.0	3.5	43.5	*149.6	
	H / 1.0	Z	40.0	3.5	43.5	*149.6	
	V / 1.0	X	40.0	3.5	43.5	*149.6	
	V / 1.0	Y	40.0	3.5	43.5	*149.6	
3100	V / 1.0	Z	40.0	3.5	43.5	*149.6	5833
The frequency range was scanned from 30 MHz to 3.1 GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8412


Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chungli Investments (Bermuda) LTD.			Job No.	8412-1		
Test Sample:	310 MHz RF Remote			Paragraph:	15.231(b)		
Model No.:	R550			FCC ID:	OXYR550		
Operating Mode:	Continuously Transmitting a 310 MHz Signal						
Technician:	T.S./P.L.			Date:	February 17, 2000		
Notes:	Test Distance: 3 Meters			Duty Cycle: 25.5%			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - 11.9 dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
310	H / 1.0	X	72.3	-11.9	60.4	1047.1	5833
	H / 1.0	Y	73.5	-11.9	61.6	1202.3	
	H / 2.5	Z	68.1	-11.9	56.2	645.7	
	V / 1.0	X	70.9	-11.9	59.0	891.3	
	V / 2.2	Y	71.5	-11.9	59.6	955.0	
310	V / 1.8	Z	70.0	-11.9	58.1	803.5	5833
620	H / 1.0	X	53.1	-11.9	41.2	114.8	583.3
	H / 1.0	Y	56.0	-11.9	44.1	160.3	
	H / 1.5	Z	54.5	-11.9	42.6	134.9	
	V / 2.0	X	53.6	-11.9	41.7	121.6	
	V / 2.0	Y	50.8	-11.9	38.9	88.1	
620	V / 1.0	Z	52.8	-11.9	40.9	110.9	583.3
930	H / 1.0	X	37.4	-11.9	25.5	*18.8	583.3
	H / 1.0	Y	37.4	-11.9	25.5	*18.8	
	H / 1.0	Z	37.4	-11.9	25.5	*18.8	
	V / 1.0	X	37.4	-11.9	25.5	*18.8	
	V / 1.0	Y	37.4	-11.9	25.5	*18.8	
930	V / 1.0	Z	37.4	-11.9	25.5	*18.8	583.3
1240	H / 3.0	X	47.5	-11.9	35.6	60.3	500.0
	H / 2.5	Y	50.4	-11.9	38.5	84.1	
	H / 2.5	Z	45.2	-11.9	33.3	46.2	
	V / 2.5	X	41.6	-11.9	29.7	30.5	
	V / 2.1	Y	44.2	-11.9	32.3	41.2	
1240	V / 1.0	Z	26.2	-11.9	14.3	*5.2	500.0
1550	H / 1.0	X	44.7	-11.9	32.8	43.7	500.0
	H / 1.0	Y	29.9	-11.9	18.0	*7.9	
	H / 1.0	Z	51.0	-11.9	39.1	90.2	
	V / 1.0	X	29.9	-11.9	18.0	*7.9	
	V / 2.2	Y	51.2	-11.9	39.3	92.3	
1550	V / 1.0	Z	29.9	-11.9	18.0	*7.9	500.0
The frequency range was scanned from 30 MHz to 3.1GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8412

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Chungli Investments (Bermuda) LTD.			Job No.	8412-1		
Test Sample:	310 MHz RF Remote			Paragraph:	15.231(b)		
Model No.:	R550			FCC ID:	OXYR550		
Operating Mode:	Continuously Transmitting a 310 MHz Signal						
Technician:	T.S./P.L.			Date:	February 17, 2000		
Notes:	Test Distance: 3 Meters			Duty Cycle: 25.5%			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - 11.9 dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
1860	H / 1.0	X	50.9	-11.9	39.0	89.1	583.3
	H / 1.0	Y	41.6	-11.9	29.7	*30.5	
	H / 1.0	Z	46.8	-11.9	34.9	55.6	
	V / 1.0	X	41.6	-11.9	29.7	*30.5	
	V / 2.0	Y	47.1	-11.9	35.2	57.5	
1860	V / 1.0	Z	45.3	-11.9	33.4	46.8	583.3
2170	H / 2.5	X	49.3	-11.9	37.4	74.1	583.3
	H / 2.8	Y	47.9	-11.9	36.0	63.1	
	H / 1.0	Z	38.7	-11.9	26.8	*21.9	
	V / 2.0	X	47.2	-11.9	35.3	58.2	
	V / 1.0	Y	49.0	-11.9	37.1	71.6	
2170	V / 1.0	Z	42.3	-11.9	30.4	33.1	583.3
2480	H / 1.0	X	40.1	-11.9	28.2	*25.7	583.3
	H / 1.0	Y	40.1	-11.9	28.2	*25.7	
	H / 1.0	Z	40.1	-11.9	28.2	*25.7	
	V / 1.0	X	40.1	-11.9	28.2	*25.7	
	V / 1.0	Y	40.1	-11.9	28.2	*25.7	
2480	V / 1.0	Z	40.1	-11.9	28.2	*25.7	583.3
2790	H / 1.0	X	41.4	-11.9	29.5	*29.9	500.0
	H / 1.0	Y	41.4	-11.9	29.5	*29.9	
	H / 1.0	Z	41.4	-11.9	29.5	*29.9	
	V / 1.0	X	41.4	-11.9	29.5	*29.9	
	V / 1.0	Y	41.4	-11.9	29.5	*29.9	
2790	V / 1.0	Z	41.4	-11.9	29.5	*29.9	500.0
3100	H / 1.0	X	43.5	-11.9	31.6	*38.0	583.3
	H / 1.0	Y	43.5	-11.9	31.6	*38.0	
	H / 1.0	Z	43.5	-11.9	31.6	*38.0	
	V / 1.0	X	43.5	-11.9	31.6	*38.0	
	V / 1.0	Y	43.5	-11.9	31.6	*38.0	
3100	V / 1.0	Z	43.5	-11.9	31.6	*38.0	583.3
The frequency range was scanned from 30 MHz to 3.1GHz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=-Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-8412