

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a Toy RC X-Twin Evo operating at 2.4G Band. The EUT can be powered by DC 3.7V (1 x 3.7V rechargeable battery). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal peak radiated output power (e.i.r.p) is: 1.0dBm (tolerance: +/- 3dB).

The normal peak conducted output power is 1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 98.4 dB μ V/m at 3m in the frequency 2439MHz

The EIRP = [(FS*D) ^2 / 30] mW = 3.17dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 96.6dB μ V/m at 3m in the frequency 2475MHz

The EIRP = [(FS*D) ^2 / 30] mW = 1.37dBm

which is within the production variation.

The maximum conducted output power specified is 4dBm= 2.512mW

The source- based time-averaging conducted output power =2.512* Duty cycle mW <2.512 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.475) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 15.6522ms

Effective period of the cycle = 1.5217ms

DC =1.5217ms / 15.6522ms =0.0972 or 9.72%