

## TEST REPORT

Report No.: HK11051168-1

**Silverlit Toys Manufactory Limited**

Application  
For  
Certification

(Original Grant)

**(FCC ID: OYK-TX00024G-1104)**

Transceiver

Prepared and Checked by:

Approved by:

Signed On File  
Kung Wing Cheong, Steven  
Assistant Engineer

---

Chan Chi Hung, Terry  
Assistant Supervisor  
Date: June 28, 2011

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

---

---

## INTERTEK TESTING SERVICES

---

---

### GENERAL INFORMATION

**SILVERLIT TOYS MANUFACTORY LIMITED  
MODEL: 82333**

**FCC ID: OYK-TX00024G-1104**

Grantee:	Silverlit Toys Manufactory Limited
Grantee Address:	Room 1701-1703, World Trade Centre, 280 Gloucester Road, Causeway Bay, Hong Kong.
Contact Person:	Edmond Chan
Tel:	29162284
Fax:	29162984
e-mail:	edmond@silverlit.com
Manufacturer:	N/A
Manufacturer Address:	N/A
Brand Name:	N/A
Model:	82333
Additional Model:	82335, 82338
Type of EUT:	Transciever
Description of EUT:	3D Twister/ 2X Twisters
Serial Number:	N/A
FCC ID :	OYK-TX00024G-1104
Date of Sample Submitted:	May 18, 2011
Date of Test:	May 23, 2011
Report No.:	HK11051168-1
Report Date:	June 28, 2011
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

---

---

## INTERTEK TESTING SERVICES

---

---

### SUMMARY OF TEST RESULT

**SILVERLIT TOYS MANUFACTORY LIMITED**

**MODEL: 82333**

**FCC ID: OYK-TX00024G-1104**

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies Separation	15.247(e) / RSS-210 A8.1	N/A
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of Hopping Frequency	15.247(e) / RSS-210 A8.1	N/A
Antenn Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
RF Exposure Compliance	15.247(i) / RSS-Gen 5.5	N/A
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 7.2.2	N/A
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(a) / RSS-210 A1.1.1	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(e) / RSS-210 A1.1.5	N/A
Transmitter Field Strength and Bandwidth Requirement	15.239 / RSS-210 A2.8	N/A
Transmitter Field Strength and Bandwidth Requirement	15.249 / RSS-210 A2.9	Pass
Transmitter Field Strength and Bandwidth Requirement	15.235 / RSS-310 3.9	N/A
Receiver / Digital Device Radiated Emissions	15.109 / ICES-003	N/A
Digital Device Conducted Emissions	15.107 / ICES-003	N/A

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

1.0	<b><u>General Description</u></b> .....	1
1.1	Product Description .....	1
1.2	Related Submittal(s) Grants.....	1
1.3	Test Methodology.....	1
1.4	Test Facility .....	1
2.0	<b><u>System Test Configuration</u></b> .....	2
2.1	Justification .....	2
2.2	EUT Exercising Software.....	2
2.3	Special Accessories .....	2
2.4	Equipment Modification .....	2
2.5	Measurement Uncertainty.....	2
2.6	Support Equipment List and Description .....	3
3.0	<b><u>Emission Results</u></b> .....	3
3.1	Field Strength Calculation.....	3
3.2	Radiated Emission Configuration Photograph.....	4
3.3	Radiated Emission Data .....	4
4.0	<b><u>Equipment Photographs</u></b> .....	7
5.0	<b><u>Product Labelling</u></b> .....	7
6.0	<b><u>Technical Specifications</u></b> .....	7
7.0	<b><u>Instruction Manual</u></b> .....	7
8.0	<b><u>Miscellaneous Information</u></b> .....	7
8.1	Measured Bandwidth.....	7
8.2	Discussion Pulse Desensitivity .....	8
8.3	Calculation of Average Factor.....	8
8.4	Emissions Test Procedures .....	9
9.0	<b><u>Equipment List</u></b> .....	10

---

# INTERTEK TESTING SERVICES

---

## 1.0 General Description

### 1.1 Product Description

The equipment under test (EUT) is a 2.4GHz RF transceiver (Controller) for a corresponding RC Car, which is operating from 2402MHz to 2478MHz. The EUT is powered by 4 x 1.5V AA size batteries. The EUT has three switches (POWER ON/OFF switch x 1, FLIPPING SYS ON/OFF x 1, Hi. GEAR/Low. GEAR switch x 1), a control stick, a control wheel and a charging cable. The POWER ON/OFF switch is used to switch on/off the controller. The FLIPPING SYS ON/OFF is used to switch on/off the function of motor. The Hi. GEAR/Low. GEAR switch is used to adjust the speed of car. The control stick is used to control the corresponding RC car moving forward and backward. The control wheel is used to control the corresponding RC car turning left and right directions. When the ON/OFF switch is switched to ON mode and the charging cable connected to the corresponding RC car, it could be charged the internal battery inside the corresponding RC car.

The Model: 82335 and 82338 are the same as the Model: 82333 in hardware aspect. The difference in item number only.

Antenna Type : Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

### 1.2 Related Submittal(s) Grants

The Certification procedure of transceiver (Car) for this transceiver (with FCC ID: OYK-FCC82333-01) is being processed as the same time of this application.

### 1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

---

---

## INTERTEK TESTING SERVICES

---

---

### 2.0 System Test Configuration

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The EUT was powered by a new 4 x 1.5V AA size batteries during test.

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emission at and above 30 MHz, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data report in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Equipment Modification

Any modifications installed previous to testing by Silverlit Toys Manufactory Limited will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

#### 2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.6 Support Equipment List and Description

N/A.

## INTERTEK TESTING SERVICES

---

---

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where              FS = Field Strength in dB $\mu$ V/m  
                      RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V  
                      CF = Cable Attenuation Factor in dB  
                      AF = Antenna Factor in dB  
                      AG = Amplifier Gain in dB  
                      AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where              FS = Field Strength in dB $\mu$ V/m  
                      RR = RA - AG - AV in dB $\mu$ V  
                      LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

RA = 52.0 dB $\mu$ V/m  
AF = 7.4 dB    RR = 18.0 dB $\mu$ V  
CF = 1.6 dB    LF = 9.0 dB  
AG = 29.0 dB  
AV = 5.0 dB  
FS = RR + LF  
FS = 18 + 9 = 27 dB $\mu$ V/m

Level in  $\mu$ V/m = Common Antilogarithm [(27 dB $\mu$ V/m)/20] = 22.4  $\mu$ V/m

## INTERTEK TESTING SERVICES

---

### 3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission at 2478.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 11.1 dB



## INTERTEK TESTING SERVICES

Applicant: Silverlit Toys Manufactory Limited

Date of Test: May 23, 2011

Model: 82333

Mode: Transmitting

Table 1  
**Radiated Emissions**

**Channel 00**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	105.6	33	29.4	102.0	114.0	-12.0
H	4804.000	59.5	33	34.9	61.4	74.0	-12.6
V	7206.000	56.9	33	37.9	61.8	74.0	-12.2
H	9608.000	44.7	33	40.4	52.1	74.0	-21.9
H	12010.000	45.9	33	40.5	53.4	74.0	-20.6
H	14412.000	47.6	33	40.0	54.6	74.0	-19.4

**Channel 24**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.000	105.0	33	29.4	101.4	114.0	-12.6
H	4880.000	59.7	33	34.9	61.6	74.0	-12.4
V	7320.000	56.4	33	37.9	61.3	74.0	-12.7
H	9760.000	44.8	33	40.4	52.2	74.0	-21.8
H	12200.000	46.3	33	40.5	53.8	74.0	-20.2
H	14640.000	47.6	33	40.0	54.6	74.0	-19.4

**Channel 50**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2478.000	106.5	33	29.4	102.9	114.0	-11.1
H	4956.000	59.4	33	34.9	61.3	74.0	-12.7
V	7434.000	56.6	33	37.9	61.5	74.0	-12.5
H	9912.000	44.9	33	40.4	52.3	74.0	-21.7
H	12390.000	46.2	33	40.5	53.7	74.0	-20.3
H	14868.000	47.8	33	40.0	54.8	74.0	-19.2

- NOTES:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative sign in the column shows value below limit.
  4. Horn antenna is used for the emissions over 1000MHz.

## INTERTEK TESTING SERVICES

Applicant: Silverlit Toys Manufactory Limited  
 Model: 82333  
 Mode: Transmitting

Date of Test: May 23, 2011

Table 2  
**Radiated Emissions**

**Channel 00**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	105.6	33	29.4	102.0	27.2	74.8	94.0	-19.2
H	4804.000	59.5	33	34.9	61.4	27.2	34.2	54.0	-19.8
V	7206.000	56.9	33	37.9	61.8	27.2	34.6	54.0	-19.4
H	9608.000	44.7	33	40.4	52.1	27.2	24.9	54.0	-29.1
H	12010.000	45.9	33	40.5	53.4	27.2	26.2	54.0	-27.8
H	14412.000	47.6	33	40.0	54.6	27.2	27.4	54.0	-26.6

**Channel 24**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.000	105.0	33	29.4	101.4	27.2	74.2	94.0	-19.8
H	4880.000	59.7	33	34.9	61.6	27.2	34.4	54.0	-19.6
V	7320.000	56.4	33	37.9	61.3	27.2	34.1	54.0	-19.9
H	9760.000	44.8	33	40.4	52.2	27.2	25.0	54.0	-29.0
H	12200.000	46.3	33	40.5	53.8	27.2	26.6	54.0	-27.4
H	14640.000	47.6	33	38.4	54.6	27.2	27.4	54.0	-26.6

**Channel 50**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2478.000	106.5	33	29.4	102.9	27.2	75.7	94.0	-18.3
H	4956.000	59.4	33	34.9	61.3	27.2	34.1	54.0	-19.9
V	7434.000	56.6	33	37.9	61.5	27.2	34.3	54.0	-19.7
H	9912.000	44.9	33	40.4	52.3	27.2	25.1	54.0	-28.9
H	12390.000	46.2	33	40.5	53.7	27.2	26.5	54.0	-27.5
H	14868.000	47.8	33	38.4	54.8	27.2	27.6	54.0	-26.4

- NOTES:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative sign in the column shows value below limit.
  4. Horn antenna is used for the emissions over 1000MHz.

---

---

## INTERTEK TESTING SERVICES

---

---

### 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

### 8.0 **Miscellaneous Information**

This miscellaneous information includes details of the measured bandwidth, the test procedure and calculation of factors such as pulse desensitization and averaging factor.

#### 8.1 **Measured Bandwidth**

From the following plots, they show that the fundamental emissions are confined in the specified band (2400 MHz to 2483.5 MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C 63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

## INTERTEK TESTING SERVICES

---

For electronic filing, the above plots are saved with filename: be.pdf

### Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

Lower bandedge

Resultant field strength = Fundamental emissions (peak value) - delta from the plot  
= 102.00dB $\mu$ V/m – 37.80dB = 64.20dB $\mu$ V/m

Resultant field strength = Fundamental emissions (peak value) - delta from the plot - Average Factor  
= 102.00dB $\mu$ V/m – 37.80dB – 27.20dB = 37.00dB $\mu$ V/m

Upper bandedge

Resultant field strength = Fundamental emissions (peak value) - delta from the plot  
= 102.90dB $\mu$ V/m – 48.61dB = 54.29dB $\mu$ V/m

Resultant field strength = Fundamental emissions (peak value) - delta from the plot - Average Factor  
= 102.90dB $\mu$ V/m – 48.61dB – 27.20dB = 27.09dB $\mu$ V/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB $\mu$ V/m (Peak Limit) and 54dB $\mu$ V/m (Average Limit).

**8.2 Discussion of Pulse Desensitization**

The effective period ( $T_{\text{eff}}$ ) was approximately 228  $\mu\text{s}$  for a digital "1" bit, as shown in the plots of Exhibit 8.3. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

**8.3 Calculation of Average Factor**

Averaging factor in dB =  $20 \log (\text{duty cycle})$

The specification for output field strengths in accordance with the FCC rules specify measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

A plot of the worst-case duty cycle as detected in this manner are saved with filename: af.pdf

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100 ms

Effective period of the cycle =  $228 \mu\text{s} \times 19 = 4.332 \text{ ms}$

DC =  $4.332 / 100 \text{ ms} = 0.04332$

Therefore, the averaging factor is found by  $20 \log_{10} 0.04332 = -27.2 \text{ dB}$

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

## INTERTEK TESTING SERVICES

### 9.0 Equipment List

#### Radiated Emissions Test

Equipment	EMI Test Receiver	Log Periodic Antenna	Biconical Antenna
Registration No.	EW-2500	EW-0446	EW-0954
Manufacturer	ROHDESCHWARZ	EMCO	EMCO
Model No.	ESCI	3146	3104C
Calibration Date	Jan 25, 2011	Apr 26, 2010	Apr 14, 2010
Calibration Due Date	Jan 25, 2012	Oct 26, 2011	Oct 14, 2011

Equipment	Spectrum Analyzer	RF Amplifiers (100MHz to 12GHz) 2 Pieces	Double Ridged Guide Antenna
Registration No.	EW-2188	EW-1779	EW-1015
Manufacturer	AGILENTTECH	MITEQ	EMCO
Model No.	E4407B	AMF-4D-001120-34- 13P	3115
Calibration Date	Dec 27, 2010	Jul 30, 2010	Feb 09, 2010
Calibration Due Date	Dec 31, 2011	Aug 01, 2011	Aug 09, 2011

Equipment	14m Double Shield RF Cable (20MHz - 6GHz)	14m Double Shield RF Cable (9kHz - 6GHz)	High Pass Filter 3GHz to 12GHz (2 Pieces)
Registration No.	EW-2528	EW-2375	EW-1835
Manufacturer	RADIALL	RADIALL	KLMICROWAVE
Model No.	nm / br5d / sma 14m	n m/br56/bnc m 14m	11SH10-3000/ T12000-0/OP
Calibration Date	Dec 14, 2010	Sep 11, 2010	Nov 07, 2010
Calibration Due Date	Dec 14, 2011	Sep 12, 2011	Nov 08, 2011

Equipment	14m RF High Frequency Cable (1 - 18)GHz		
Registration No.	EW-2552		
Manufacturer	RADIALL		
Model No.	SHF5M sma m - sma m ra		
Calibration Date	Sep 02, 2010		
Calibration Due Date	Sep 03, 2011		