



TEST REPORT No: (5212)135-1953

TEST REPORT

To:	SILVERLIT TOYS MANUFACTORY LIMITED	To:	-
Attn:	Mr. Edmond Chan	Attn:	-
Address:	17 th Floor World Trade Centre, 280 Gloucester Road, Causeway Bay, Hong Kong	Address:	-
Fax:	28348797	Fax:	-
E-mail:	edmond@silverlit.com	E-mail:	-
Folder No.:	ITM-12MA118MTHS-B-A		
Factory name:	--		
Location:	--		
Product:	2.4G Sky Dagger Model No.: 84613		
	Sample No:	HK120306/025	
	Test date:	March 20, 2012 to April 5, 2012	
	Test Requested:	FCC Part 15 - 2011	
	Test Method:	ANSI C63.4 - 2009	
	FCC ID:	OYK-TX0002G4-1203	
The results given in this report are related to the tested specimen of the described electrical apparatus.			
CONCLUSION: The submitted sample was found to <u>COMPLY</u> with requirement of FCC Part 15 Subpart C.			
Authorized Signature:			
			
Reviewed by: Keith Yeung		Approved by: Steven Tsang	
Date: May 16, 2012		Date: May 16, 2012	



TEST REPORT No: (5212)135-1953
Test Result Summary

EMISSION TEST			
Test requirement: FCC Part 15 - 2011			
Test Condition	Test Method	Test Result	
		Pass	Failed
Radiated Emission Test, 9kHz to 40GHz	ANSI C63.4	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Report Revision & Sample Re-submit History:

--



TEST REPORT No: (5212)135-1953

Location of the test laboratory

Radiated and Conducted emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. An Open Area Test Site and Full Anechoic Chamber (FCC Listed Site, Registration No. 642151) are set up for investigation and located at :

BUREAU VERITAS HONG KONG LIMITED, EMC CENTRE

No. 2106-2107, 21/F., Westin Centre,
26 Hung To Road,
Kwun Tong, Kowloon,
Hong Kong

List of measuring equipment

Radiated Emission

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATION DUE
EMI TEST RECEIVER	R&S	ESCI	100379	05-SEP-2012
LOOP ANTENNA	ETS-LINDGREN	6502	00102266	12-MAY-2012
BILOG ANTENNA	SCHAFFNER	CBL6112D	25229	01-AUG-2012
OPEN AREA TEST SITE	BVCPS	N/A	N/A	07-JUL-2012
ANECHOIC CHAMBER	ALBATROSS	M-CDC	80374004499B	25-OCT-2012
COAXIAL CABLE	SUHNER	N/A	N/A	18-SEP-2012

Remarks:-

N/A : Not Applicable or Not Available

The measurement instrumentation uncertainty would be taking into consideration on each of the test result

TEST REPORT No: (5212)135-1953

Equipment Under Test [EUT]

Description of Sample:

Model Name: 2.4G Sky Dagger
Model Number: 84613
Rating: Helicopter: 3.7Vd.c. ("rechargeable battery" x 1) /
Remote: 6Vd.c. ("AA" size battery x 4) /
117Va.c, 60Hz (computer)

Description of EUT Operation:

The Equipment Under Test (EUT) is a **SILVERLIT TOYS MANUFACTORY LIMITED** of Remote Control Transceiver. It is a 1 switch, 1 button and 2 sticks transceiver and operating at 2402MHz to 2477.5MHz. The lowest, middle and highest frequencies were tested and the results are shown in the report. The EUT transmit while buttons is being pressed or sticks are being pushed or pulled, Modulation by IC, and type is FHSS.

The transmitter has different control:

1. ON/OFF switch – ON/OFF control
2. LIGHT button – light ON/OFF control
3. Left stick – control upward and downward
4. Right stick – control direction

Antenna Requirement (Section 15.203)

The EUT is use of a permanently antenna. It is soldered on the PCB. The antenna is not replaceable or user serviceable. The requirements of S15.203 are met. There are no deviations or exceptions to the specifications.



TEST REPORT No: (5212)135-1953

Radiated Emissions (Fundamental)

Test Requirement: FCC Part 15 Section 15.249
 Test Method: ANSI C63.4
 Test Date(s): 2012-03-20
 Temperature: 22.0 °C
 Humidity: 65.0 %
 Atmospheric Pressure: 100.7 kPa
 Mode of Operation: Transmission mode
 Tested Voltage: Remote: 6Vd.c. ("AA" size battery x 4)


Test Procedure:

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

Location: The Roof, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Test Setup: Open Area Test Site





TEST REPORT No: (5212)135-1953

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.249]:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission (Average) [mV/m]	Field Strength of Harmonics Emission (Average) [μV/m]
2400-2483.5	50	500

Measurement Data

Test Result of (Transmission mode, Lowest frequency): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
2402.00	H	-5.2	74.7	114.0	-39.3
2402.00	V	-5.2	81.9	114.0	-32.1

Detection mode: # Average

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
2402.00	H	-5.2	**58.2	94.0	-35.8
2402.00	V	-5.2	**65.4	94.0	-28.6

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = $20\text{Log}(0.15) = -16.5\text{dB}$.

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz
VBW = 1MHz



TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Transmission mode, Middle frequency): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
2440.00	H	-4.6	73.0	114.0	-41.0
2440.00	V	-4.6	81.6	114.0	-32.4

Detection mode: # Average

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
2440.00	H	-4.6	**56.5	94.0	-37.5
2440.00	V	-4.6	**65.1	94.0	-28.9

Test Result of (Transmission mode, Highest frequency): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
2477.50	H	-4.3	69.7	114.0	-44.3
2477.50	V	-4.3	80.8	114.0	-33.2

Detection mode: # Average

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
2477.50	H	-4.3	**53.2	94.0	-40.8
2477.50	V	-4.3	**64.3	94.0	-29.7

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = 20Log(0.15) = -16.5dB.

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz

VBW = 1MHz



TEST REPORT No: (5212)135-1953

Radiated Emissions (Spurious Emission)

Test Requirement: FCC Part 15 Section 15.249
 Test Method: ANSI C63.4
 Test Date(s): 2012-03-20
 Temperature: 22.0 °C
 Humidity: 65.0 %
 Atmospheric Pressure: 100.7 kPa
 Mode of Operation: Transmission mode
 Tested Voltage: Remote: 6Vd.c. ("AA" size battery x 4)

Measurement Data

Test Result of (Transmission mode, Lowest frequency): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
4804.00	H	5.5	52.7	74.0	-21.3
7206.00	H	12.4	52.9	74.0	-21.1
9608.00	H	15.1	53.2	74.0	-20.8
12010.00	H	17.5	51.7	74.0	-22.3
14412.00	H	22.1	51.2	74.0	-22.8
16814.00	H	30.8	56.4	74.0	-17.6
19216.00	H	31.8	57.5	74.0	-16.5
21618.00	H	32.3	52.6	74.0	-21.4
24020.00	H	33.7	54.4	74.0	-19.6
26422.00	H	34.6	57.5	74.0	-16.5

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz
 VBW = 1MHz



TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Transmission mode, Lowest frequency): **PASS**

Detection mode: **Peak**

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4804.00	V	5.5	52.9	74.0	-21.1
7206.00	V	12.4	52.4	74.0	-21.6
9608.00	V	15.1	53.1	74.0	-20.9
12010.00	V	17.5	52.4	74.0	-21.6
14412.00	V	22.1	51.5	74.0	-22.5
16814.00	V	30.8	56.8	74.0	-17.2
19216.00	V	31.8	58.4	74.0	-15.6
21618.00	V	32.3	52.2	74.0	-21.8
24020.00	V	33.7	53.6	74.0	-20.4
26422.00	V	34.6	56.5	74.0	-17.5

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz
VBW = 1MHz



**BUREAU
VERITAS**

TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Transmission mode, Lowest frequency): PASS

Detection mode: #Average

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4804.00	H	5.5	**36.2	54.0	-17.8
7206.00	H	12.4	**36.4	54.0	-17.6
9608.00	H	15.1	**36.7	54.0	-17.3
12010.00	H	17.5	**35.2	54.0	-18.8
14412.00	H	22.1	**34.7	54.0	-19.3
16814.00	H	30.8	**39.9	54.0	-14.1
19216.00	H	31.8	**41.0	54.0	-13.0
21618.00	H	32.3	**36.1	54.0	-17.9
24020.00	H	33.7	**37.9	54.0	-16.1
26422.00	H	34.6	**41.0	54.0	-13.0

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4804.00	V	5.5	**36.4	54.0	-17.6
7206.00	V	12.4	**35.9	54.0	-18.1
9608.00	V	15.1	**36.6	54.0	-17.4
12010.00	V	17.5	**35.9	54.0	-18.1
14412.00	V	22.1	**35.0	54.0	-19.0
16814.00	V	30.8	**40.3	54.0	-13.7
19216.00	V	31.8	**41.9	54.0	-12.1
21618.00	V	32.3	**35.7	54.0	-18.3
24020.00	V	33.7	**37.1	54.0	-16.9
26422.00	V	34.6	**40.0	54.0	-14.0

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = 20Log(0.15) = -16.5dB.

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz
VBW = 1MHz

**BUREAU VERITAS HONG KONG LIMITED –
Kowloon Bay Office
1/F Pacific Trade Centre,
2 Kai Hing Road, Kowloon Bay,
Kowloon, HONG KONG**
Tel: +852 2331 0888
Fax: +852 2331 0889
www.cps.bureauveritas.com

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Transmission mode, Middle frequency): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4880.00	H	5.7	49.3	74.0	-24.7
7320.00	H	13.9	54.7	74.0	-19.3
9760.00	H	14.0	52.8	74.0	-21.2
12200.00	H	18.6	53.2	74.0	-20.8
14640.00	H	23.2	52.6	74.0	-21.4
17080.00	H	31.2	58.7	74.0	-15.3
19520.00	H	32.0	57.4	74.0	-16.6
21960.00	H	33.5	53.9	74.0	-20.1
24400.00	H	34.1	54.6	74.0	-19.4
26840.00	H	35.2	56.9	74.0	-17.1

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB \square V/m)	Limit at 3m (dB \square V/m)	Margin (dB)
4880.00	V	5.7	51.2	74.0	-22.8
7320.00	V	13.9	55.7	74.0	-18.3
9760.00	V	14.0	53.5	74.0	-20.5
12200.00	V	18.6	52.6	74.0	-21.4
14640.00	V	23.2	51.7	74.0	-22.3
17080.00	V	31.2	58.2	74.0	-15.8
19520.00	V	32.0	58.0	74.0	-16.0
21960.00	V	33.5	54.2	74.0	-19.8
24400.00	V	34.1	54.8	74.0	-19.2
26840.00	V	35.2	56.2	74.0	-17.8

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz
VBW = 1MHz



**BUREAU
VERITAS**

TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Transmission mode, Middle frequency): PASS

Detection mode: #Average

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4880.00	H	5.7	**32.8	54.0	-21.2
7320.00	H	13.9	**38.2	54.0	-15.8
9760.00	H	14.0	**36.3	54.0	-17.7
12200.00	H	18.6	**36.7	54.0	-17.3
14640.00	H	23.2	**36.1	54.0	-17.9
17080.00	H	31.2	**42.2	54.0	-11.8
19520.00	H	32.0	**40.9	54.0	-13.1
21960.00	H	33.5	**37.4	54.0	-16.6
24400.00	H	34.1	**38.1	54.0	-15.9
26840.00	H	35.2	**40.4	54.0	-13.6

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4880.00	V	5.7	**34.7	54.0	-19.3
7320.00	V	13.9	**39.2	54.0	-14.8
9760.00	V	14.0	**37.0	54.0	-17.0
12200.00	V	18.6	**36.1	54.0	-17.9
14640.00	V	23.2	**35.2	54.0	-18.8
17080.00	V	31.2	**41.7	54.0	-12.3
19520.00	V	32.0	**41.5	54.0	-12.5
21960.00	V	33.5	**37.7	54.0	-16.3
24400.00	V	34.1	**38.3	54.0	-15.7
26840.00	V	35.2	**39.7	54.0	-14.3

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

** Duty Cycle Correction = $20\text{Log}(0.15) = -16.5\text{dB}$.

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz
VBW = 1MHz

BUREAU VERITAS HONG KONG LIMITED –
Kowloon Bay Office
1/F Pacific Trade Centre,
2 Kai Hing Road, Kowloon Bay,
Kowloon, HONG KONG
Tel: +852 2331 0888
Fax: +852 2331 0889
www.cps.bureauveritas.com

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Transmission mode, Highest frequency): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4955.00	H	5.7	50.3	74.0	-23.7
7432.50	H	14.7	55.4	74.0	-18.6
9910.00	H	12.9	52.1	74.0	-21.9
12387.50	H	19.5	53.8	74.0	-20.2
14865.00	H	25.1	55.7	74.0	-18.3
17342.50	H	33.4	58.2	74.0	-15.8
19820.00	H	34.7	60.4	74.0	-13.6
22297.50	H	35.6	55.7	74.0	-18.3
24775.00	H	36.8	58.1	74.0	-15.9
27252.50	H	37.5	59.5	74.0	-14.5

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4955.00	V	5.7	49.5	74.0	-24.5
7432.50	V	14.7	57.1	74.0	-16.9
9910.00	V	12.9	52.4	74.0	-21.6
12387.50	V	19.5	53.4	74.0	-20.6
14865.00	V	25.1	55.2	74.0	-18.8
17342.50	V	33.4	59.5	74.0	-14.5
19820.00	V	34.7	61.5	74.0	-12.5
22297.50	V	35.6	55.3	74.0	-18.7
24775.00	V	36.8	58.1	74.0	-15.9
27252.50	V	37.5	58.7	74.0	-15.3

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz
VBW = 1MHz



**BUREAU
VERITAS**

TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Transmission mode, Highest frequency): PASS

Detection mode: #Average

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4955.00	H	5.7	**33.8	54.0	-20.2
7432.50	H	14.7	**38.9	54.0	-15.1
9910.00	H	12.9	**35.6	54.0	-18.4
12387.50	H	19.5	**37.3	54.0	-16.7
14865.00	H	25.1	**39.2	54.0	-14.8
17342.50	H	33.4	**41.7	54.0	-12.3
19820.00	H	34.7	**43.9	54.0	-10.1
22297.50	H	35.6	**39.2	54.0	-14.8
24775.00	H	36.8	**41.6	54.0	-12.4
27252.50	H	37.5	**43.0	54.0	-11.0

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
4955.00	V	5.7	**33.0	54.0	-21.0
7432.50	V	14.7	**40.6	54.0	-13.4
9910.00	V	12.9	**35.9	54.0	-18.1
12387.50	V	19.5	**36.9	54.0	-17.1
14865.00	V	25.1	**38.7	54.0	-15.3
17342.50	V	33.4	**43.0	54.0	-11.0
19820.00	V	34.7	**45.0	54.0	-9.0
22297.50	V	35.6	**38.8	54.0	-15.2
24775.00	V	36.8	**41.6	54.0	-12.4
27252.50	V	37.5	**42.2	54.0	-11.8

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = $20\text{Log}(0.15) = -16.5\text{dB}$.

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 1MHz
VBW = 1MHz

BUREAU VERITAS HONG KONG LIMITED –
Kowloon Bay Office
1/F Pacific Trade Centre,
2 Kai Hing Road, Kowloon Bay,
Kowloon, HONG KONG
Tel: +852 2331 0888
Fax: +852 2331 0889
www.cps.bureauveritas.com

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TEST REPORT No: (5212)135-1953

Radiated Emissions (30MHz – 2.4GHz)

Test Requirement: FCC Part 15 Section 15.209
Test Method: ANSI C63.4
Test Date(s): 2012-04-03
Temperature: 22.0 °C
Humidity: 62.0 %
Atmospheric Pressure: 100.9 kPa
Mode of Operation: On mode and Charge mode
Tested Voltage: Remote: 6Vd.c. ("AA" size battery x 4) /
Helicopter: 3.7Vd.c. ("rechargeable battery" x 1) /
117Va.c, 60Hz (computer)

Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [μ V/m]
1.705-30	300
30-88	100
88-216	150
216-960	200
Above960	500



TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (On mode, battery operated): PASS

Detection mode: Quasi-Peak

Frequency (MHz)	Polarity (H/V)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
49.72	H	29.2	40.0	-10.8
72.48	H	25.4	40.0	-14.6
160.00	H	23.7	43.5	-19.8
225.04	H	21.6	46.0	-24.4
398.28	H	29.1	46.0	-16.9
531.80	H	28.6	46.0	-17.4

Frequency (MHz)	Polarity (H/V)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
39.96	V	29.6	40.0	-10.4
62.36	V	26.4	40.0	-13.6
219.88	V	20.2	46.0	-25.8
324.76	V	24.5	46.0	-21.5
392.36	V	25.7	46.0	-20.3
492.72	V	28.6	46.0	-17.4

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 120KHz
VBW = 120KHz



TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Charge mode, battery operated): PASS

Detection mode: Quasi-Peak

Frequency (MHz)	Polarity (H/V)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
45.08	H	29.2	40.0	-10.8
122.80	H	21.3	43.5	-22.2
176.00	H	22.5	43.5	-21.0
240.04	H	22.3	46.0	-23.7
332.68	H	24.5	46.0	-21.5
410.32	H	26.7	46.0	-19.3

Frequency (MHz)	Polarity (H/V)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
63.48	V	26.7	40.0	-13.3
131.52	V	20.3	43.5	-23.2
162.32	V	21.2	43.5	-22.3
204.36	V	20.9	43.5	-22.6
270.88	V	22.8	46.0	-23.2
.375.75	V	25.6	46.0	-20.4

Note: Field Strength includes Antenna Factor and Cable Loss.



TEST REPORT No: (5212)135-1953

Measurement Data

Test Result of (Charge mode, computer operated): PASS

Detection mode: Quasi-Peak

Frequency (MHz)	Polarity (H/V)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
50.96	H	24.5	40.0	-15.5
128.80	H	26.2	43.5	-17.3
141.28	H	27.0	43.5	-16.5
164.08	H	28.9	43.5	-14.6
177.36	H	29.6	43.5	-13.9
212.92	H	28.3	43.5	-15.2

Frequency (MHz)	Polarity (H/V)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
44.60	V	26.1	40.0	-13.9
83.28	V	23.2	40.0	-16.8
146.04	V	24.7	43.5	-18.8
157.96	V	26.5	43.5	-17.0
175.84	V	25.8	43.5	-17.7
180.52	V	26.2	43.5	-17.3

Note: Field Strength includes Antenna Factor and Cable Loss.



TEST REPORT No: (5212)135-1953

Frequency range of Fundamental Emission

Test Requirement: FCC 47 CFR 15.249
Test Method: ANSI C63.4:2009 (Section 13.1.7)
Test Date(s): 2012-03-20
Temperature: 28.0 °C
Humidity: 71.0 %
Atmospheric Pressure: 100.5 kPa
Mode of Operation: Transmission mode
Tested Voltage: Remote: 6Vd.c. ("AA" size battery x 4)

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Limits for Frequency range of Fundamental Emission:

Frequency [MHz]	FCC Limits [MHz]
2402.00 – 2477.50	2400 – 2483.5




BUREAU VERITAS

TEST REPORT No: (5212)135-1953


Measurement Data :

Test Result of Frequency Range of Fundamental Emission: PASS
Lowest Frequency – 2402.00MHz



Date: 20.MAR.2012 14:51:53

Test Result of 26dB Bandwidth of Fundamental Emission: PASS
Lowest Frequency – 2402.00MHz




Date: 20.MAR.2012 14:49:10

TEST REPORT No: (5212)135-1953


Measurement Data :

**Test Result of Frequency Range of Fundamental Emission: PASS
Highest Frequency – 2477.50MHz**



Date: 20.MAR.2012 14:56:32

**Test Result of 26dB Bandwidth of Fundamental Emission: PASS
Highest Frequency – 2477.50MHz**



Date: 20.MAR.2012 14:56:06



TEST REPORT No: (5212)135-1953

Duty Cycle Correction During 100msec:

Each function key sends a different series of characters, but each packet period (100msec) never exceeds a series of 25 pulses (0.6msec). Assuming any combination of short and long pulses maybe obtained due to encoding the worst case transmit duty cycle would be considered (25×0.6) per 100msec = 15% duty cycle.

Remarks:

Duty Cycle Correction = $20\text{Log}(0.15) = -16.5\text{dB}$

The following figures [Figure A] show the characteristics of the pulse train for one of these functions.




BUREAU VERITAS

TEST REPORT No: (5212)135-1953

Measurement Data :

Figure A [Pulse Train]



Date: 20.MAR.2012 14:50:51



**BUREAU
VERITAS**

TEST REPORT No: (5212)135-1953

Photographs of EUT

Front View of the product



Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View





**BUREAU
VERITAS**

TEST REPORT No: (5212)135-1953

Inner Circuit Top View



Inner Circuit Bottom View



Battery Compartment



Battery Cover





**BUREAU
VERITAS**

TEST REPORT No: (5212)135-1953

Measurement of Radiated Emission Test Set Up



******* End of Report *******