

FCC Part 15

Subpart D Change Report

of

E.U.T. : US-EN Telephone Answering
Machine (Base Station FP)

MODEL : CD360, CD360 Duo, CD360 Trio,
CD360 Quattro
CD365, CD365 Duo, CD365 Trio,
CD365 Quattro

FCC ID. : OYMCD365

for

APPLICANT : Philips Consumer Electronics B.V.

ADDRESS : B.U. Accessories Building SBP6 PO Box 80002

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN

NO. 34. LIN 5. DINGFU TSUEN, LINKOU SHIANG

TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

TEL : (02)26023052 FAX: (02)26010910

http : // www.etc.org.tw; e-mail : emc@etc.org.tw

Report Number : 08-12-RBF-140-01

TEST REPORT CERTIFICATION

Applicant : Philips Consumer Electronics B.V.
B.U. Accessories Building SBP6 PO Box 80002

Manufacturer : Huiyang CCT Telecommunications Products Co. Ltd.
CCT Technology Park, San He Economic Developmental
Zone, Huiyang District, Huizhou City, Guangdong Province, PRC

Description of EUT


- a) Type of EUT : US-EN Telephone Answering Machine (Base Station FP)
- b) Trade Name : Philips
- c) Model No. : CD360, CD360 Duo, CD360 Trio, CD360 Quattro
CD365, CD365 Duo, CD365 Trio, CD365 Quattro
- d) Power Supply :
Adaptor (Model No.: M901.0170U)
I/P: 120Vac 60Hz 0.1A; O/P: 6Vac 500mA
Adaptor (Model No.: DM-SC060058)
I/P: 120Vac 60Hz 0.1A; O/P: 6Vac 0-0.58A
- e) Frequency Range : 1921.536~1928.448MHz

Regulation Applied : FCC Rules and Regulations Part 15 Subpart D (2008)

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.17-2006/ ANSI C63.4-2003, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.
2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

Issued Date : Mar. 16, 2009

Test Engineer : 
(Falcon Shi)

Approve & Authorized Signer : 
Will Yauo, Manager
EMC Dept. II of ELECTRONICS
TESTING CENTER, TAIWAN

Table of Contents	Page
1 GENERAL INFORMATION	1
1.1 Testing Laboratory	1
1.2 Client Information	1
1.3 Manufacturer	1
2 TEST INFORMATION	2
2.1 Descriptino of Tested Device(s)	2
2.2 Test Environment	2
3 TEST REPORT SUMMARY	3
3.1 Test Summary	3
3.2 Devices for Tested System	3
4 TEST SETUP	4
4.1 Frequency and Timing Measurements	4
4.2 Conducted Emission Tests	4
4.3 Radiated Emission Tests	5
4.4 Power Line Conducted Tests	5
5 TEST EQUIPMENT LIST	6
6 TEST RESULT	7
6.1 Corrdination with fixed microwave	7
6.2 Cross Reference	8
6.3 Labeling Requirements	9
6.4 Power Line Conducted Emissions	10
6.5 Antenna Requirement	31
6.6 digital Modulation Techniques	31
6.7 Peak Power Output	32
6.8 Power Spectral Density	37
6.9 Antenna Gain	42
6.10 Automatic discontinuation of transmission	42
6.11 Safety exposure levels	43
6.12 Emission Bandwidth B	44
6.13 Emissions inside and outside the subband	49
6.14 Frame period and jitter	74
6.15 Carrier frequency stability	80

1 GENERAL INFORMATION

1.1 Testing Laboratory

Name : Electronics Testing Center, Taiwan
Address : No. 34, Lin 5, Dingfu Tsuen, Linkou Shiang, Taipei County,
Taiwan, 24442, R.O.C.
Telephone : 886-2-26023052
Fax : 886-2-26010910
NVLAP lab registration# : 200133-0
IC OATS registration# : 2949A-1

1.2 Client Information

Name : Philips Consumer Electronics B.V.
Address : B.U. Accessories Building SBP6 PO Box 80002
Telephone : +31402736589
Contact person : Karel Rysman

1.3 Manufacturer

Name : Huiyang CCT Telecommunications Products Co. Ltd.
Address : CCT Technology Park, San He Economic Developmental Zone,
Huiyang District, Huizhou City, Guangdong Province, PRC

2 TEST INFORMATION

2.1 Descriptino of Tested Device(s)

The tested equipment is a DECT base station which complies with ETSI EN 300175. The frequencies have been reprogrammed to comply with the FCC requirements to an Isochronous UPCS device after FCC Part 15D.

The EUT is a responding device as described in ANSI C63.17 and is designed to operate together with a DECT handset, which is then the initiating device.

Frequency Channel	Frequency	Test Frequency
CH4	1928.448 MHz	F _L
CH3	1926.720 MHz	-
CH2	1924.992 MHz	-
CH1	1923.264 MHz	-
CH0	1921.536 MHz	F _H

2.2 Test Environment

Normal test condition

Temperature:	20 – 25 °C
Relative humidty:	55 – 75%

Extreme test condition (declared by manufacture)

Please see the manufacturer declaration form.

3 TEST REPORT SUMMARY

3.1 Test Summary

Requirement	FCC Paragraph #	Required	Customer Declaration	Test Pass
Coordination with fixed microwave	15.307(b)	■	■	☐
Cross Reference	15.309(b)	☐	☐	☐
Labeling requirements	15.311 15.19(a)(3)	■	■	☐
Power line Conducted Emission	15.315 , 15.207	■	☐	■
Antenna Requirement	15.317, 15.203	■	■	☐
Digital Modulation Techniques	15.319(b)	■	■	☐
Peak transmit Power	15.319(c)	■	☐	■
Power spectral Density	15.319(d)	■	☐	■
Antenna gain	15.319(e)	■	■	☐
Automatic discontinuation of transmission	15.319(f)	■	■	☐
Safety exposure levels	15.319(i)	■	☐	■
Emission Bandwidth	15.323(a)	■	☐	■
Emissions inside and outside the subband	15.323(d)	■	☐	■
Frame period and jitter	15.323(e)	■	☐	■
Carrier frequency stability	15.323(f)	■	☐	■

3.2 Devices for Tested System


All measurements are traceable to national standards.

The tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR47 Part 15, Paragraph 15.232 for Isochronous UPCS Devices and Industry Canada RSS-213 Issue 2.

The conducted test methods have been in accordance with ANSI C63.17-2006 Draft where applicable. Radiated tests were conducted in accordance with ANSI C63.4-2003.

4 TEST SETUP


4.1 Frequency and Timing Measurements



Test Set-up 1

This setup is used for measuring Frame stability, Jitter, Carrier frequency stability at normal and extremet temperatures.


4.2 Conducted Emission Tests



Test Set-up 2

This setup is used for all conducted emission tests.


4.3 Radiated Emission Tests



Test Set-up 3

This test setup is used for all radiated emissions tests. For frequencies below 30 MHz the measuring distance is 10 m, for all toher frequencies it is 3m. Emissions above 1 GHz were measured with the Spectrum Analyzer, Horn Antenna and the preamplifier after the antenna.

4.4 Power Line Conducted Tests



Test Set-up 4

5 TEST EQUIPMENT LIST

To facilitate inclusion on each page of the test equipment used for related test, each item of test equipment and ancillaries are identified (numbered) by the Test Laboratory.

Equipment	Manufacturer	Model No.	Next Cal. Due
Test Receiver	Rohde & Schwarz	ESCS 30	2010/01/25
Amplifier	HP	8447D	2009/05/16
Bi-Log Antenna	Schaffner	CBL 6111C	2009/06/05
Log-periodic Antenna	EMCO	3146	2009/10/08
Biconical Antenna	EMCO	3110	2009/09/16
EMI Test Receiver	Rohde & Schwarz	ESCI	2009/12/26
Spectrum	R&S	FSP3	2009/12/26
Signal generator	HP	8656B	2009/12/12
Double Ridged Antenna	EMCO	3115	2009/05/14
Amplifier	HP	8449B	2009/12/05
Amplifier	HP	83051A	2009/05/23
Spectrum	R&S	FSP40	2009/09/11
CTS60 DIGITAL RADIO TEST	R&S	CTS60	2009/12/25
Line Impedance Stabilization network	EMCO	3850/2	2009/05/27
Line Impedance Stabilization network	Rohde & Schwarz	ESH2-Z5	2009/09/20
Monitor	IBM	E54	N.C.R.
Printer	HP	LaserJet 1000	N.C.R.
Shielded Room	Riken	----	N.C.R.
Computer	Acer	Veriton	N.C.R.

6 TEST RESULT

6.1 Corrdination with fixed microwave

6.1.1 Standard Applicable

FCC 15.307 (b)

Each application for certification of equipment operating under the provisions of this Subpart must be accompanied by an affidavit from UTAM, Inc. certifying that the applicant is a participating member of UTAM, Inc. In the event a grantee fails to fulfill the obligations attendant to participation in UTAM, Inc., the Commission may invoke administrative sanctions as necessary to preclude continued marketing and installation of devices covered by the grant of certification, including but not limited to revoking certification.

Result

The affidavit from UTAM, Inc. is included in the documentation supplied by the applicant:

☒ **Yes**

☐ **No**

6.2 Cross Reference

6.2.1 Standard Applicable

15.309(b)

The requirements of Subpart D apply only to the radio transmitter contained in the PCS device. Other aspects of the operation of a PCS device may be subject to requirements contained elsewhere in this Chapter. In particular, a PCS device that includes digital circuitry not directly associated with the radio transmitter also is subject to the requirements for unintentional radiators in Subpart B.

15.109(a)

For unintentional device, according to FCC §15.109(a), the field strength of radiated emissions from unintentional except for class A digital device radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated μ V/m	Radiated dB μ V/m
30 - 88	3	100	40.0
88 - 216	3	150	43.5
216 - 960	3	200	46.0
Above 960	3	500	54.0

6.2.2 Test Results

This requirement is not applicable because test sample do not included digital circuitry which is not directly associated with the radio transmitter	☒
For test results according to FCC 15 subpart B, see the EMC report as attached	☐
For test results according to FCC 15 subpart B, see the measurement data as follow	☐
This requirement is covered by results of power line conducted emission test according to FCC 15.315	☐

6.3 Labeling Requirements

6.3.1 Standard Applicable

FCC 15.19

The FCC Identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is too small:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipments.

6.3.2 Result

See separate documents showing the label design and the placement of the label on the EUT.

6.4 Power Line Conducted Emissions

6.4.1 Standard Applicable

15.315

An unlicensed PCS device that is designed to connected to the public utility (AC) power line must meet the limites specified in Section 15.207.

15.207(a)

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

* Decreases with the logarithm of the frequency

6.4.2 Measurement procedure

ANSI C63.4-2003 using 50 μ H/50 ohms LISN.

6.4.3 Test Results: Complies

Measurement Data: See attached graph, (Peak detector)

Highest measured value (L1 and L2):

All emissions were below the QP and Average limits when measured with Peak detector.

A. Model No.: CD365(with TAD function)**Adaptor : DM-SC060058**Operation Mode : Base Charging & Stand byNeutralTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.173	39.7	----	0.2	39.9	----	64.8	54.8	-24.9	----
0.185	42.2	----	0.2	42.4	----	64.3	54.3	-21.9	----
0.232	31.7	----	0.2	31.9	----	62.4	52.4	-30.5	----
0.259	32.1	----	0.2	32.3	----	61.5	51.5	-29.1	----
0.275	34.7	----	0.2	34.9	----	61.0	51.0	-26.0	----
0.376	29.3	----	0.3	29.6	----	58.4	48.4	-28.8	----


Operation Mode : Base Charging & Stand byLineTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.282	37.2	----	0.2	37.4	----	60.8	50.8	-23.3	----
0.368	33.5	----	0.3	33.8	----	58.5	48.5	-24.8	----
0.548	34.3	----	0.3	34.6	----	56.0	46.0	-21.4	----
0.556	36.6	----	0.3	36.9	----	56.0	46.0	-19.1	----
0.571	34.8	----	0.3	35.1	----	56.0	46.0	-20.9	----
0.830	35.4	----	0.3	35.7	----	56.0	46.0	-20.3	----


Note :

1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----“ means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.

Mode: Base Charging & Stand by Neutral



Mode: Base Charging & Stand by Line



Operation Mode : Base On LineNeutralTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.196	35.6	----	0.2	35.8	----	63.8	53.8	-28.0	----
0.212	31.1	----	0.2	31.3	----	63.1	53.1	-31.8	----
0.267	31.3	----	0.2	31.5	----	61.2	51.2	-29.7	----
0.466	26.2	----	0.3	26.5	----	56.6	46.6	-30.1	----
0.544	26.6	----	0.3	26.9	----	56.0	46.0	-29.1	----
0.579	25.1	----	0.3	25.4	----	56.0	46.0	-30.6	----


Operation Mode : Base On LineLineTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.306	28.1	----	0.3	28.4	----	60.1	50.1	-31.7	----
0.368	33.5	----	0.3	33.8	----	58.5	48.5	-24.8	----
0.521	30.5	----	0.3	30.8	----	56.0	46.0	-25.2	----
0.536	34.1	----	0.3	34.4	----	56.0	46.0	-21.6	----
0.556	36.5	----	0.3	36.8	----	56.0	46.0	-19.2	----
0.692	28.5	----	0.3	28.8	----	56.0	46.0	-27.2	----


Note :

1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----“ means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.

Mode: Base On Line Neutral



Mode: Base On Line Line



B. Model No.: CD365(with TAD function)**Adaptor : M901.0170U**Operation Mode : Base Charging & Stand byNeutralTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.165	34.9	----	0.2	35.1	----	65.2	55.2	-30.1	----
0.177	33.7	----	0.2	33.9	----	64.6	54.6	-30.7	----
0.192	32.5	----	0.2	32.7	----	63.9	53.9	-31.2	----
0.235	30.4	----	0.2	30.6	----	62.3	52.3	-31.7	----
2.442	23.6	----	0.5	24.1	----	56.0	46.0	-31.9	----
2.575	22.9	----	0.5	23.4	----	56.0	46.0	-32.6	----


Operation Mode : Base Charging & Stand byLineTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.154	37.4	----	0.2	37.6	----	65.8	55.8	-28.2	----
0.181	34.6	----	0.2	34.8	----	64.4	54.4	-29.6	----
1.372	24.7	----	0.4	25.1	----	56.0	46.0	-30.9	----
2.532	25.5	----	0.5	26.0	----	56.0	46.0	-30.0	----
2.669	23.9	----	0.5	24.4	----	56.0	46.0	-31.6	----
4.638	21.5	----	0.6	22.1	----	56.0	46.0	-33.9	----


Note :

1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----“ means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.

Mode: Base Charging & Stand by Neutral



Mode: Base Charging & Stand by Line



Operation Mode : Base On LineNeutralTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.157	31.9	----	0.2	32.1	----	65.6	55.6	-33.5	----
0.173	30.5	----	0.2	30.7	----	64.8	54.8	-34.1	----
0.189	32.7	----	0.2	32.9	----	64.1	54.1	-31.2	----
0.232	28.2	----	0.2	28.4	----	62.4	52.4	-34.0	----
2.427	20.2	----	0.5	20.7	----	56.0	46.0	-35.3	----
2.564	19.1	----	0.5	19.6	----	56.0	46.0	-36.4	----

Operation Mode : Base On LineLineTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %


Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.192	29.5	----	0.2	29.7	----	63.9	53.9	-34.2	----
1.302	19.5	----	0.4	19.9	----	56.0	46.0	-36.1	----
2.458	22.6	----	0.5	23.1	----	56.0	46.0	-32.9	----
2.485	22.1	----	0.5	22.6	----	56.0	46.0	-33.4	----
2.618	21.0	----	0.5	21.5	----	56.0	46.0	-34.5	----
2.888	20.2	----	0.5	20.7	----	56.0	46.0	-35.3	----

Note :

1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----” means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.


Mode: Base On Line

Neutral



Mode: Base On Line

Line



C. Model No.: CD360(without TAD function)**Adaptor : DM-SC060058**Operation Mode : Base Charging & Stand byNeutralTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.173	37.3	----	0.2	37.5	----	64.8	54.8	-27.3	----
0.275	32.7	----	0.2	32.9	----	61.0	51.0	-28.0	----
0.392	25.7	----	0.3	26.0	----	58.0	48.0	-32.0	----
0.552	26.7	----	0.3	27.0	----	56.0	46.0	-29.0	----
0.583	26.7	----	0.3	27.0	----	56.0	46.0	-29.0	----
0.591	25.9	----	0.3	26.2	----	56.0	46.0	-29.8	----


Operation Mode : Base Charging & Stand byLineTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.181	40.1	----	0.2	40.3	----	64.4	54.4	-24.1	----
0.267	34.5	----	0.2	34.7	----	61.2	51.2	-26.5	----
0.353	32.6	----	0.3	32.9	----	58.9	48.9	-26.0	----
0.536	32.4	----	0.3	32.7	----	56.0	46.0	-23.3	----
0.544	33.5	----	0.3	33.8	----	56.0	46.0	-22.2	----
0.564	34.9	----	0.3	35.2	----	56.0	46.0	-20.8	----


Note :

1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----“ means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.

Mode: Base Charging & Stand by Neutral



Mode: Base Charging & Stand by Line



Operation Mode : Base On LineNeutralTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.181	37.9	----	0.2	38.1	----	64.4	54.4	-26.3	----
0.251	26.9	----	0.2	27.1	----	61.7	51.7	-34.6	----
0.267	31.7	----	0.2	31.9	----	61.2	51.2	-29.3	----
0.466	24.6	----	0.3	24.9	----	56.6	46.6	-31.7	----
0.583	24.4	----	0.3	24.7	----	56.0	46.0	-31.3	----
0.614	23.4	----	0.3	23.7	----	56.0	46.0	-32.3	----

Operation Mode : Base On LineLineTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %


Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.376	31.7	----	0.3	32.0	----	58.4	48.4	-26.4	----
0.552	33.2	----	0.3	33.5	----	56.0	46.0	-22.5	----
0.564	33.8	----	0.3	34.1	----	56.0	46.0	-21.9	----
0.571	31.3	----	0.3	31.6	----	56.0	46.0	-24.4	----
0.735	27.4	----	0.3	27.7	----	56.0	46.0	-28.3	----
4.306	23.5	----	0.6	24.1	----	56.0	46.0	-31.9	----

Note :

1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----“ means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.


Mode: Base On Line

Neutral



Mode: Base On Line

Line



D. Model No.: CD360(without TAD function)**Adaptor : M901.0170U**Operation Mode : Base Charging & Stand byNeutralTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.161	33.1	----	0.2	33.3	----	65.4	55.4	-32.1	----
0.173	31.9	----	0.2	32.1	----	64.8	54.8	-32.7	----
0.189	33.8	----	0.2	34.0	----	64.1	54.1	-30.1	----
0.232	29.2	----	0.2	29.4	----	62.4	52.4	-33.0	----
2.415	22.2	----	0.5	22.7	----	56.0	46.0	-33.3	----
2.525	21.4	----	0.5	21.9	----	56.0	46.0	-34.1	----


Operation Mode : Base Charging & Stand byLineTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.150	35.3	----	0.2	35.5	----	66.0	56.0	-30.5	----
2.415	24.1	----	0.5	24.6	----	56.0	46.0	-31.4	----
2.442	24.2	----	0.5	24.7	----	56.0	46.0	-31.3	----
2.552	23.8	----	0.5	24.3	----	56.0	46.0	-31.7	----
2.685	21.4	----	0.5	21.9	----	56.0	46.0	-34.1	----
4.357	21.3	----	0.6	21.9	----	56.0	46.0	-34.1	----


Note :

1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----“ means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.

Mode: Base Charging & Stand by Neutral



Mode: Base Charging & Stand by Line



Operation Mode : Base On LineNeutralTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %

Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.150	31.1	----	0.2	31.3	----	66.0	56.0	-34.7	----
0.157	30.5	----	0.2	30.7	----	65.6	55.6	-34.9	----
0.185	31.7	----	0.2	31.9	----	64.3	54.3	-32.4	----
0.216	23.6	----	0.2	23.8	----	63.0	53.0	-39.2	----
2.388	18.6	----	0.5	19.1	----	56.0	46.0	-36.9	----
2.521	17.1	----	0.5	17.6	----	56.0	46.0	-38.4	----

Operation Mode : Base On LineLineTest Date : Feb. 01, 2009Temperature : 18 °CHumidity : 58 %


Frequency (MHz)	Meter Reading (dB μ V)		Factor (dB)	Result (dB μ V)		Limit (dB μ V)		Margin (dB μ V)	
	Q.P	AVG		Q.P	AVG	Q.P	AVG	Q.P	AVG
0.153	31.1	----	0.2	31.3	----	65.8	55.8	-34.5	----
2.282	20.3	----	0.5	20.8	----	56.0	46.0	-35.2	----
2.310	20.2	----	0.5	20.7	----	56.0	46.0	-35.3	----
2.442	21.2	----	0.5	21.7	----	56.0	46.0	-34.3	----
2.552	20.1	----	0.5	20.6	----	56.0	46.0	-35.4	----
2.884	20.2	----	0.5	20.7	----	56.0	46.0	-35.3	----

Note :

1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----“ means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.


Mode: Base On Line

Neutral



Mode: Base On Line


Line




6.4.4 Photos of Conduction Measuring Setup


A. Model No.: CD365(with TAD function)





B. Model No.: CD360(without TAD function)





6.5 Antenna Requirement

6.5.1 Standard Applicable

FCC 15.317, 15.203

Does the EUT have detachable antenna?

☐ Yes

☒ No

If detachable, is the antenna connector non-standard?

☐ Yes

☐ No

The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connects.

6.6 digital Modulation Techniques

6.6.1 Standard Applicable

FCC 15.319(b)

All transmissions must use only digital modulation techniques.

6.6.2 Result: Meets the requirement

Please see the declaration provided by applicant

6.7 Peak Power Output

6.7.1 Standard Applicable

FCC 15.319(c)(f)

Peak transmit power shall not exceed 100 microwatts multiplie by the square root of the emission bandwidth in Hz.

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

6.7.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 6.1.2

6.7.3 Test Results: Complies

Measurement Data:

A. Model No.: CD365(with TAD function)

Channel	Frequency (MHz)	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (mw)	FCC Limit (dBm)
F _L	1921.400	16.4	43.65	20.82
F _H	1928.790	16.5	44.67	20.84

B. Model No.: CD360(with out TAD function)


Channel	Frequency (MHz)	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (mw)	FCC Limit (dBm)
F _L	1921.340	16.34	43.05	20.82
F _H	1928.550	16.25	42.17	20.85

Limit:

Peak Transmit Power = 100 uW x $\sqrt{\text{BW}}$


BW = Emission Bandwidth in Hz.

Model No.: CD365(with TAD function)
Maximum Peak Output Power: CH F_L



Date: 1.FEB.2009 00:58:37


Maximum Peak Output Power: CH F_H



Date: 1.FEB.2009 00:50:29


Model No.: CD360(without TAD function)

Maximum Peak Output Power: CH F_L



Date: 1.FEB.2009 00:15:38

Maximum Peak Output Power: CH F_H



Date: 1.FEB.2009 00:39:52

6.8 Power Spectral Density

6.8.1 Standard Applicable

FCC 15.319(d)

Power spectral density shall not exceed 3 milliwatts in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

6.8.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 6.1.5

6.8.3 Test Results: Complies

Measurement Data:

A. CD365(with TAD function)


Channel	Frequency (MHz)	Power spectral Density (dBm)	FCC Limit (dBm)
F _L	1921.436	1.36	4.77
F _H	1928.400	0.63	4.77

B. CD360(without TAD function)

Channel	Frequency (MHz)	Power spectral Density (dBm)	FCC Limit (dBm)
F _L	1921.386	0.08	4.77
F _H	1928.160	0.61	4.77


Model No.: CD365(with TAD function)

Power Spectral Density: CH F_L



Date: 1.FEB.2009 01:00:13


Power Spectral Density: CH F_H



Date: 1.FEB.2009 00:51:39


Model No.: CD360(without TAD function)

Power Spectral Density: CH F_L



Date: 1.FEB.2009 00:17:10

Power Spectral Density: CH F_H



Date: 1.FEB.2009 00:40:55

6.9 Antenna Gain

6.9.1 Standard Applicable

FCC 15.323(e)

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

6.9.2 Results: Meets the requirement

The antenna gain value provided by manufacturer is 0 dBi.

6.10 Automatic discontinuation of transmission

6.10.1 Standard Applicable

FCC 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

6.10.2 Procedure

Please see the declaration provided by applicant.

6.10.3 Results: Meets the requirement

6.11 Safety exposure levels

6.11.1 Standard Applicable

FCC 15.319(i)

UPCS devices are subject to the radio frequency radiation exposure requirements specified in FCC parts 1.1307 (b), 2.1091 and 2.1093, as appropriate. All equipment shall be considered to operate in a “general population / uncontrolled environment. For portable devices tests according to IEEE 1528 are requested, applicable.

6.11.2 Measurement procedure

Consideration of radio frequency radiation exposure for EUT is done as

SAR test according IEEE 1528 (for PP)	☐
MPE calculation as below (for FP, Repeater)	☒

SAR test results: not applicable

MPE calculation:

The EUT is considered as a mobile device according to OET Bulletin 65, Edition –97-01. Therefore distance to human body of min. 20 cm is determined.

The limit of Power density for General Population / Uncontrolled Exposure is 1.0 mW/cm².

Formula:

$$S = \text{EIRP} / 4\pi R^2$$

Calculation:

EIRP	Radiated Power (dBm)	16.5
EIRP	Radiated Power (mW)	44.67
R	Distance (cm)	20
S	Power Density (mW/cm ²)	0.035

6.11.3 Results: Complies

6.12 Emission Bandwidth B

6.12.1 Standard Applicable

FCC 15.323(a)

The 26 dB Bandwidth B shall be larger than 50 kHz and less than 2.5 MHz.

6.12.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 6.1.3

6.12.3 Test Results: Complies

Measurement Data:

A. CD365(with TAD function)


Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
F _L	1921.550	1.46
F _H	1928.460	1.47

B. CD360(without TAD function)


Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
F _L	1921.220	1.46
F _H	1928.460	1.48

Model No.: CD365(with TAD function)

26 dB Bandwidth B: CH FL




Date: 1.FEB.2009 00:58:10

26 dB Bandwidth B: CH F_H

Date: 1.FEB.2009 00:50:04


Model No.: CD360(without TAD function)

26 dB Bandwidth B: CH FL



Date: 1.FEB.2009 00:14:45

26 dB Bandwidth B: CH F_H



Date: 1.FEB.2009 00:39:30

6.13 Emissions inside and outside the subband

6.13.1 Standard Applicable

FCC 15.323(d)

Emissions inside the subband

$B < f \leq 2B$: less than or equal to 30dB below max. permitted peak power level

$2B < f \leq 3B$: less than or equal to 50 dB below max. permitted peak power level

$3B < f \leq \text{UPCs Band Edge}$: less than or equal to 60 dB below max. permitted peak power level

Emissions outside the subband

$f \leq 1.25\text{MHz}$ outside UPCS band: $\leq -9.5\text{dBm}$

$1.25\text{MHz} \leq f \leq 2.5\text{MHz}$ outside UPCS band: $\leq -29.5\text{dBm}$

$f \geq 2.5\text{MHz}$ outside UPCS band: The EUT shall pass the test either a) or b) as follow:

a) In the region at 2.5 MHz or greater below and above the lower and upper band edges respectively, the measured emission level shall not exceed -39.5 dBm	☐
b) In the region at 2.5MHz or greater below and above the lower and upper band edges respectively, the measured emission level shall not exceed the limits of 47CFR15.209. Measurement shall be made as a radiated test.	☒

6.13.2 Measurement procedure


Measurement method according to ANSI C63.17 2006 paragraph 6.1.6

6.13.3 Results: Complies

Measurement Data:


See plots.

Model No.: CD365(with TAD function)
In-band Unwanted Emission: CH F_L



Date: 1.FEB.2009 01:03:07


In-band Unwanted Emission: CH F_H



Date: 1.FEB.2009 00:53:35


Model No.: CD360(without TAD function)

In-band Unwanted Emission: CH F_L



Date: 1.FEB.2009 00:34:51

In-band Unwanted Emission: CH F_H



Date: 1.FEB.2009 00:43:09

Out-of -band Unwanted Emission:

Out-of -band Unwanted Emission (below 1GHz)

A. Model No.: CD365(with TAD function)**Adaptor : DM-SC060058**

a)

Operation Mode : Base Charging & Stand byTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
39.180	V	42.8	-11.6	31.2	40.0	-8.8	177	1.0
45.660	V	40.7	-13.1	27.6	40.0	-12.4	66	1.0
99.660	V	45.5	-13.9	31.6	43.5	-11.9	74	1.1
110.460	V	42.9	-11.7	31.2	43.5	-12.3	89	1.1
196.860	H	35.1	-7.5	27.6	43.5	-15.9	213	1.5
267.060	H	32.1	-3.7	28.4	46.0	-17.6	59	1.5

b)

Operation Mode : Base On LineTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
31.890	V	43.1	-10.2	32.9	40.0	-7.1	83	1.0
38.100	V	43.8	-11.4	32.4	40.0	-7.6	128	1.0
106.140	V	46.8	-12.5	34.3	43.5	-9.2	136	1.1
111.540	V	44.4	-11.6	32.8	43.5	-10.7	72	1.1
120.180	V	40.5	-10.8	29.7	43.5	-13.8	134	1.0
203.610	H	33.1	-6.9	26.2	43.5	-17.3	111	1.6

Note :

1. Remark "---" means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

B. Model No.: CD365(with TAD function)**Adaptor : M901.0170U**

a)

Operation Mode : Base Charging & Stand byTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
48.090	V	40.2	-13.7	26.5	40.0	-13.5	67	1.0
130.170	V	35.5	-11.5	24.0	43.5	-19.5	27	1.0
138.540	V	34.5	-10.9	23.6	43.5	-19.9	33	1.1
247.890	H	30.4	-4.0	26.4	46.0	-19.6	82	1.6
261.660	H	31.8	-3.9	27.9	46.0	-18.1	54	1.2
283.530	V	31.1	-2.5	28.6	46.0	-17.4	133	1.2

b)

Operation Mode : Base On LineTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
31.890	V	43.7	-10.2	33.5	40.0	-6.5	111	1.8
38.370	V	45.7	-11.5	34.2	40.0	-5.8	68	1.1
46.740	V	42.3	-13.4	28.9	40.0	-11.1	93	1.1
132.060	V	37.0	-11.4	25.6	43.5	-17.9	157	1.2
270.570	H	32.8	-3.5	29.3	46.0	-16.7	67	1.5
291.900	H	32.8	-1.8	31.0	46.0	-15.0	39	1.4

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

C. Model No.: CD360(without TAD function)**Adaptor : DM-SC060058**

a)

Operation Mode : Base Charging & Stand byTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
44.850	V	48.7	-12.9	35.8	40.0	-4.2	37	1.0
82.380	V	40.6	-14.8	25.8	40.0	-14.2	65	1.0
138.540	V	39.0	-10.9	28.1	43.5	-15.4	39	1.1
281.370	V	36.7	-2.6	34.1	46.0	-11.9	21	1.6
286.500	H	36.5	-2.2	34.3	46.0	-11.7	62	1.1
295.140	V	36.3	-1.4	34.9	46.0	-11.1	214	1.2

b)

Operation Mode : Base On LineTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
38.370	V	45.4	-11.5	33.9	40.0	-6.1	158	1.0
100.740	H	42.4	-13.7	28.7	43.5	-14.8	39	1.5
108.300	V	44.9	-12.1	32.8	43.5	-10.7	21	1.1
129.090	V	38.3	-11.4	26.9	43.5	-16.6	136	1.1
209.820	V	33.4	-6.5	26.9	43.5	-16.6	37	1.0
259.770	V	37.0	-3.9	33.1	46.0	-12.9	151	1.1

Note :

1. Remark "---" means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

D. Model No.: CD360(without TAD function)**Adaptor : M901.0170U**

a)

Operation Mode : Base Charging & Stand byTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
47.010	V	40.0	-13.4	26.6	40.0	-13.4	79	1.0
122.340	V	35.1	-11.0	24.1	43.5	-19.4	32	1.1
129.900	V	36.6	-11.5	25.1	43.5	-18.4	39	1.2
234.660	H	31.9	-4.8	27.1	46.0	-18.9	72	1.4
260.580	H	32.2	-3.9	28.3	46.0	-17.7	266	1.6
284.610	V	35.3	-2.4	32.9	46.0	-13.1	254	1.1

b)

Operation Mode : Base On LineTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
31.890	V	43.4	-10.2	33.2	40.0	-6.8	24	1.0
38.370	V	46.9	-11.5	35.4	40.0	-4.6	21	1.1
135.300	V	35.2	-11.1	24.1	43.5	-19.4	39	1.1
250.050	H	31.6	-3.9	27.7	46.0	-18.3	72	1.6
275.700	V	32.5	-3.1	29.4	46.0	-16.6	83	1.2
295.140	V	31.8	-1.4	30.4	46.0	-15.6	64	1.3

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

a) CH F_LOut-of -band Unwanted Emission (above 1GHz): CH F_L**A. Model No.: CD365(with TAD function)**Operation Mode : TransmittingFundamental Frequency : 1921.560MHzTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave			
3842.283	52.5	---	54.5	---	-2.6	51.9	---	74.0	54.0	-2.1	67	1.5
5763.608	52.3	---	56.5	31.8	0.7	57.2	32.5	74.0	54.0	-16.8	72	1.8
7683.575	52.8	31.5	49.1	---	3.3	56.1	34.8	74.0	54.0	-17.9	86	1.6
9609.342	49.0	---	49.3	---	4.1	53.4	---	74.0	54.0	-0.6	54	1.7
11526.849	---	---	---	---	9.1	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Item "Margin" referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

B. Model No.: CD360(without TAD function)Operation Mode : TransmittingFundamental Frequency : 1921.560MHzTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %


Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m)		Limit @3m (dBUV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H Peak	V Ave	H Peak	V Ave		Peak	Ave	Peak	Ave			
3843.730	53.0	---	51.8	---	-2.6	50.4	---	74.0	54.0	-3.6	76	1.6
5763.570	53.5	31.8	52.5	---	0.7	54.2	32.5	74.0	54.0	-19.8	24	1.5
7686.330	55.6	32.1	50.0	---	3.3	58.9	35.4	74.0	54.0	-15.1	87	1.8
9606.233	52.8	31.8	51.0	32.1	4.1	56.9	36.2	74.0	54.0	-17.1	29	1.4
11531.190	---	---	---	---	9.1	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Item "Margin" referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.


Model No.: CD365(with TAD function)

Out-of -band Unwanted Emission: CH F_L



Date: 1.FEB.2009 01:03:35


Out-of-band Unwanted Emission: CH FL



Date: 1.FEB.2009 01:03:58


Model No.: CD360(without TAD function)

Out-of -band Unwanted Emission: CH F_L



Date: 1.FEB.2009 00:35:29

Out-of-band Unwanted Emission: CH FL



Date: 1.FEB.2009 00:35:53

b) CH F_HOut-of -band Unwanted Emission (above 1GHz): CH F_H**A. Model No.: CD365(with TAD function)**Operation Mode : TransmittingFundamental : 1928.450MHz

Frequency

Test Date : Jan. 19, 2009Temperature : 20 °CHumidity : 58 %

Frequency (MHz)	Reading (dBUV)				Factor (dB) Corr.	Result @3m (dBUV/m)		Limit @3m (dBUV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	Peak	Ave	Peak	Ave		Peak	Ave	Peak	Ave			
3856.083	52.1	---	54.0	---	-2.6	51.4	---	74.0	54.0	-2.6	84	1.5
5784.167	50.6	---	56.0	31.3	0.7	56.7	32.0	74.0	54.0	-17.3	63	1.7
7713.750	54.8	32.1	48.8	---	3.4	58.2	35.5	74.0	54.0	-15.8	92	1.7
9640.550	47.2	---	49.5	---	4.1	53.6	---	74.0	54.0	-0.4	106	1.6
11568.249	---	---	---	---	9.1	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "****" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Item "Margin" referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.


B. Model No.: CD360(without TAD function)Operation Mode : TransmittingFundamental Frequency : 1928.450MHzTest Date : Feb. 01, 2009 Temperature : 18 °C Humidity : 58 %

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	Peak	Ave	Peak	Ave		Peak	Ave	Peak	Ave			
3857.420	51.7	---	53.1	---	-2.6	50.5	---	74.0	54.0	-3.5	76	1.6
5784.520	54.5	32.6	51.3	---	0.7	55.2	33.3	74.0	54.0	-18.8	82	1.5
7713.892	57.2	33.0	50.3	---	3.4	60.6	36.4	74.0	54.0	-13.4	102	1.8
9640.730	52.1	32.1	53.3	52.3	4.1	57.4	56.4	74.0	54.0	2.4	78	1.4
11572.260	---	---	---	---	9.1	---	---	74.0	54.0	---	---	---

Note :


1. Item of margin shown in above table refer to average limit.
2. It is considered that the results of average comply with average limit when measuring data with a peak function detector meet the average limit. Mark "***" means that Peak result is meet average limit.
3. Remark "---" means that the emissions level is too low to be measured.
4. Item "Margin" referred to Average limit while there is only peak result.
5. The expanded uncertainty of the radiated emission tests is 3.53 dB.

Model No.: CD365(with TAD function)
Out-of-band Unwanted Emission: CH FH




Date: 1.FEB.2009 00:54:29

Out-of-band Unwanted Emission: CH FH




Date: 1.FEB.2009 00:54:03

Model No.: CD360(without TAD function)
Out-of -band Unwanted Emission: CH FH



Date: 1.FEB.2009 00:44:07

Out-of-band Unwanted Emission: CH FH



Date: 1.FEB.2009 00:43:38

6.13.4 Photos of Radiation Measuring Setup

A. Model No.: CD365(with TAD function)





B. Model No.: CD360(without TAD function)





6.14 Frame period and jitter

6.14.1 Standard Applicable

FCC 15.323(e)

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these subbands shall be 20 milliseconds/X where X is a positive whole number. Each device that implements time division for the purposes of maintaining a duplex connection on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 50 parts per million (ppm). Each device which further divides access in time in order to support multiple communication links on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 10 ppm. The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25 microseconds for any two consecutive transmissions. Transmissions shall be continuous in every time and spectrum window during the frame period defined for the device.

6.14.2 Measurement procedure

- Frame frequency stability ≤ 50 ppm
- TDMA frame frequency stability ≤ 10 ppm (That translates to frequency drift of 19.2 kHz/slot for 1920 MHz carrier)
- Frame jitter $\leq 25\mu\text{s}$

6.14.3 Test Results: Complies**Measurement Data****Model No.: CD365(with TAD function)**

Channel No.	Frequency (KHz/slot)		Jitter (us)	
	Drift	Limit	Result	Limit
F _L	-14	19.2	-0.00	25
F _H	-14	19.2	-0.00	25


Photos of worst-case display follow:

Model No.: CD360(without TAD function)


Channel No.	Frequency (KHz/slot)		Jitter (us)	
	Drift	Limit	Result	Limit
F _L	-9	19.2	-0.01	25
F _H	-8	19.2	-0.01	25

Photos of worst-case display follow:


Model No.: CD365(with TAD function)
Frequency Drift



TDMA Frame Jitter




Frequency Drift




TDMA Frame Jitter




Model No.: CD360(without TAD function)
Frequency Drift




TDMA Frame Jitter



Frequency Drift



TDMA Frame Jitter



6.15 Carrier frequency stability

6.15.1 Standard Applicable

FCC 15.323(f)

The frequency stability of the carrier frequency of the intentional radiator shall be maintained within ± 10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of -20°C to $+50^{\circ}\text{C}$ degrees C at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20°C . For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage.

6.15.2 Measurement Requirement

- Carrier frequency stability ≤ 10 ppm over 1 hour or interval between channel access monitoring, whichever is shorter (That translates to frequency drift of 19.2 kHz for 1920 MHz carrier)
- Carrier frequency stability over -20°C to $+50^{\circ}\text{C}$ at normal supply voltage, and over 85% to 115% of rated supply voltage (voltage variation not required for battery operated device)

6.15.3 Test Results: Complies**Measurement Data****Model No.: CD365(with TAD function)****a) Carrier Frequency Stability with Supply Voltage**

Channel No.	Frequency Offset (KHz)			Limit (KHz)
	102V (85%)	120V (Normal)	138V (115%)	
F _L	15	15	15	±19.2
F _H	14	15	15	±19.2

b) Carrier Frequency Stability with Temperature and Time

Channel No.	Frequency Offset (KHz)			Limit (KHz)
	-20 °C	20 °C	50 °C	
F _L	14	15	14	±19.2
F _H	14	15	15	±19.2

Model No.: CD360(without TAD function)**a) Carrier Frequency Stability with Supply Voltage**



Channel No.	Frequency Offset (KHz)			Limit (KHz)
	102V (85%)	120V (Normal)	138V (115%)	
F _L	11	10	10	±19.2
F _H	11	11	11	±19.2

b) Carrier Frequency Stability with Temperature and Time

Channel No.	Frequency Offset (KHz)			Limit (KHz)
	-20° C	20° C	50° C	
F _L	9	9	8	±19.2
F _H	9	9	9	±19.2

Test was conducted for duration longer than 1 hour. Photo of worst-case display follows:

Model No.: CD365(with TAD function)



Model No.: CD360(without TAD function)

