



Philips Consumer Electronics B.V.

Application
For
Certification

Bluetooth Headset

(FCC ID: OYMHB9000)

Superseded report no. HK08050497-1 dated June 30, 2008

HK08050497-1(R1)
KS/ ac
September 8, 2008

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Letter of Agency
<i>EXHIBIT 9:</i>	Confidentiality Request

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

**Philips Consumer Electronics B.V. - Model: SHB9000/00, SHB9000/05,
SHB9000/10, SHB9000/27,
SHB9000/37, SHB9000/97**

FCC ID: OYMHB9000

This report concerns (check one:) Original Grant ☒ Class II Change ☐

Equipment Type : DXX - Pt 15 Low Pwr Com. Device Tx

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until : _____
date

Company Name agrees to notify the Commission
by: _____

date

of the intended date of announcement of the product so that the grant can be issued
on that date.

Transition Rules Request per 15.37 ? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [09-20-07
Edition] Provision.

Report prepared by:

Sit Kim Wai, Ken
Intertek Testing Services Hong Kong Ltd.
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone : 852-2173-8474
Fax: 852-2741-1693

INTERTEK TESTING SERVICES

Table of Contents

1.0 General Description	6
1.1 Product Description	6
1.2 Related Submittal(s) Grants	7
1.3 Test Methodology	7
1.4 Test Facility	7
2.0 System Test Configuration	9
2.1 Justification	9
2.2 EUT Exercising Software	9
2.3 Details of EUT and Description of Peripherals	10
2.4 Measurement Uncertainty	11
2.5 Equipment Modification	11
3.0 Emission Results	13
3.1 Field Strength Calculation	14
3.2 Radiated Emission Configuration Photograph - Headset	15
3.3 Radiated Emission Data - Headset	16
3.4 Radiated Emission on the Bandedge	32
3.5 Line Conducted Configuration Photograph - Headset	33
3.6 Line Conducted Emission Data	34
3.7 Transmitter Duty Cycle Calculation	35
4.0 Equipment Photographs	37
5.0 Product Labelling	39
6.0 Technical Specifications	41
7.0 Instruction Manual	43
8.0 Letter of Agency	45
9.0 Confidentiality Request	47

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Operational Description	Technical Description	descri.pdf
Test Setup Photos	Radiated & Conducted Emission for Headset	config photos.pdf
Test Report	Emission Plot	emission.pdf
Test Report	Conducted Emission Test Result	conduct.pdf
External Photos	External Photo	external photos.pdf
Internal Photos	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location Info	Label Artwork and Location	label.pdf
Users Manual	User Manual	manual.pdf
Cover Letter	Letter of Agency	letter of agency.pdf
Cover Letter	Confidentiality Request	request.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1 GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is a Bluetooth Headset. Bluetooth module operates from 2402MHz to 2480MHz. The battery for this headset is internal and rechargeable using the 5VDC 500mA supplied power adaptor through the mini USB connector. After pairing and connecting the headset with the mobile phone, the user could listen to the music and control the music wirelessly which is played from the mobile, and the Bluetooth headset can also make and receive call from the mobile. On the other hand, without any Bluetooth support, there is an option to listen to music by using and connecting with an audio cable.

The antenna used in headset is integral, and the tested sample is a prototype.

The Model: SHB9000/05, SHB9000/10, SHB9000/27, SHB9000/37 and SHB9000/97 are the same as the Model: SHB9000/00 in hardware aspect. The difference in model number serves as marketing strategy.

The circuit description is saved with filename: descri.pdf

INTERTEK TESTING SERVICES

1.2 Related Submittal(s) Grants

This is an Application for Certification of a DXX - Part 15 Low Pwr Com. Device Tx. One Transmitter is included in this application.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

INTERTEK TESTING SERVICES

EXHIBIT 2 SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

For emissions testing, the equipment under test (EUT) was setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions. The EUT was powered by an AC adaptor 100-240VAC to 5.0VDC 500mA. Three types of same-rating adaptor were considered.

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable. The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Radiated emissions were taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

Measurements of the radiated signal level of the fundamental frequency component of the emission was performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Analyzer resolution was 100 kHz or greater for frequencies below 1000 MHz. The resolution was 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value were not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which was greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever was lower.

Determination of pulse desensitization was made according to *Hewlett Packard Application Note 150-2, Spectrum Analysis... Pulsed RF*. The effective period (τ_{eff}) was 625 μ s for Bluetooth. With the resolution bandwidth 1MHz and spectrum analyzer IF bandwidth 3 dB, the pulse desensitization factor was 0 dB.

2.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

INTERTEK TESTING SERVICES

2.3 Details of EUT and Description of Peripherals

Details of EUT:

AC adaptor (provided with the unit) were used to power the device. Its description is listed below.

- (1) An AC adaptor, 2-pin (100-240VAC to 5.0VDC 500mA, Model: CM-1AD05005/37) (Supplied by Client)
- (2) An AC adaptor, 2-pin (100-240VAC to 5.0VDC 500mA, Model: CM-1AD05005/00) (Supplied by Client)
- (3) An AC adaptor, 3-pin (100-240VAC to 5.0VDC 500mA, Model: CM-1AD05005/05) (Supplied by Client)

Description of Peripherals:

- (1) Nokia Mobile Phone, Model: 5300, IMEI: 352772015773193 (Supplied by Intertek)
- (2) 1 x USB cable A to Mini B 5-pin with 1.5 meter long (Supplied by Client)

Radiated Emission Test: (Supplied by Intertek)

- (1) Lenovo, Model: T61, S/N: L3-CF468, DoC Product
- (2) LogiTech Mouse, Model: M-UV94, S/N: LZ639AB, DoC Product
- (3) Smart-drive External 1394 HDD, Model: HD3-SU2FW, S/N: 0800261, DoC Product

Conducted Emission Test: (Supplied by Intertek)

- (1) HP Notebook, Model: NX6320, S/N: CNU6370FWN, DoC Product
- (2) LogiTech Mouse, Model: M-UV94, S/N: LZ639AB, DoC Product
- (3) Genius Modem, Model: GM56EX, S/N: ZT5505000355, DoC Product

INTERTEK TESTING SERVICES

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty test has been considered.

2.5 Equipment Modification

Any modifications installed previous to testing by Philips Consumer Electronics B.V. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Commercial & Electrical Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 2.0 of this report are confirmed by:

Confirmed by:

*Sit Kim Wai, Ken
Supervisor
Intertek Testing Services
Agent for Philips Consumer Electronics B.V.*



Signature

September 8, 2008 Date

INTERTEK TESTING SERVICES

EXHIBIT 3 EMISSION RESULTS

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

where FS = Field Strength in $\text{dB}\mu\text{V/m}$
 RA = Receiver Amplitude (including preamplifier) in $\text{dB}\mu\text{V}$
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:-

$$FS = RR + LF$$

where FS = Field Strength in $\text{dB}\mu\text{V/m}$
 $RR = RA - AG$ in $\text{dB}\mu\text{V}$
 $LF = CF + AF$ in dB

Assume a receiver reading of $52.0 \text{ dB}\mu\text{V}$ is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of $32 \text{ dB}\mu\text{V/m}$. This value in $\text{dB}\mu\text{V/m}$ was converted to its corresponding level in $\mu\text{V/m}$.

$RA = 52.0 \text{ dB}\mu\text{V}$	
$AF = 7.4 \text{ dB}$	$RR = 23.0 \text{ dB}\mu\text{V}$
$CF = 1.6 \text{ dB}$	$LF = 9.0 \text{ dB}$
$AG = 29.0 \text{ dB}$	
$FS = RR + LF$	
$FS = 23 + 9 = 32 \text{ dB}\mu\text{V/m}$	

Level in $\mu\text{V/m}$ = Common Antilogarithm $[(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph - Headset

Worst Case Radiated Emission

at 4804.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.pdf

INTERTEK TESTING SERVICES

3.3 Radiated Emission Data - Headset

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 9.2 dB margin compare with the peak limit

TEST PERSONNEL:



Tester Signature

Jess Tang, Lead Engineer
Typed/Printed Name

September 8, 2008
Date

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 0 (Standalone)

Table 1, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	99.3	33	29.4	95.7	114.0	-18.3
H	*4804.000	58.9	33	34.9	60.8	74.0	-13.2
H	7206.000	47.8	33	37.9	52.7	74.0	-21.3
H	9608.000	41.0	33	40.4	48.4	74.0	-25.6
H	*12010.000	37.2	33	40.5	44.7	74.0	-29.3

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	99.3	33	29.4	43.9	51.8	94.0	-42.2
H	*4804.000	58.9	33	34.9	43.9	16.9	54.0	-37.1
H	7206.000	47.8	33	37.9	43.9	8.8	54.0	-45.2
H	9608.000	41.0	33	40.4	43.9	4.5	54.0	-49.5
H	*12010.000	37.2	33	40.5	43.9	0.8	54.0	-53.2

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 39 (Standalone)

Table 2, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2441.000	99.0	33	29.4	95.4	114.0	-18.6
H	*4882.000	58.5	33	34.9	60.4	74.0	-13.6
H	*7323.000	47.9	33	37.9	52.8	74.0	-21.2
H	9764.000	40.7	33	40.4	48.1	74.0	-25.9
H	*12205.000	37.1	33	40.5	44.6	74.0	-29.4

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2441.000	99.0	33	29.4	43.9	51.5	94.0	-42.5
H	*4882.000	58.5	33	34.9	43.9	16.5	54.0	-37.5
H	*7323.000	47.9	33	37.9	43.9	8.9	54.0	-45.1
H	9764.000	40.7	33	40.4	43.9	4.2	54.0	-49.8
H	*12205.000	37.1	33	40.5	43.9	0.7	54.0	-53.3

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 78 (Standalone)

Table 3, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	99.0	33	29.4	95.4	114.0	-18.6
H	*4960.000	58.6	33	34.9	60.5	74.0	-13.5
H	*7440.000	47.5	33	37.9	52.4	74.0	-21.6
H	9920.000	41.1	33	40.4	48.5	74.0	-25.5
H	*12400.000	36.2	33	40.5	43.7	74.0	-30.3

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	99.0	33	29.4	43.9	51.5	94.0	-42.5
H	*4960.000	58.6	33	34.9	43.9	16.6	54.0	-37.4
H	*7440.000	47.5	33	37.9	43.9	8.5	54.0	-45.5
H	9920.000	41.1	33	40.4	43.9	4.6	54.0	-49.4
H	*12400.000	36.2	33	40.5	43.9	-0.2	54.0	-54.2

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 0 (Charging by USB)

Table 4, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	99.3	33	29.4	95.7	114.0	-18.3
H	*4804.000	62.4	33	34.9	64.3	74.0	-9.7
H	7206.000	47.8	33	37.9	52.7	74.0	-21.3
H	9608.000	42.1	33	40.4	49.5	74.0	-24.5
H	*12010.000	36.3	33	40.5	43.8	74.0	-30.2

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	99.3	33	29.4	43.9	51.8	94.0	-42.2
H	*4804.000	62.4	33	34.9	43.9	20.4	54.0	-33.6
H	7206.000	47.8	33	37.9	43.9	8.8	54.0	-45.2
H	9608.000	42.1	33	40.4	43.9	5.6	54.0	-48.4
H	*12010.000	36.3	33	40.5	43.9	-0.1	54.0	-54.1

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 39 (Charging by USB)

Table 5, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2441.000	99.0	33	29.4	95.4	114.0	-18.6
H	*4882.000	61.9	33	34.9	63.8	74.0	-10.2
H	*7323.000	47.7	33	37.9	52.6	74.0	-21.4
H	9764.000	42.0	33	40.4	49.4	74.0	-24.6
H	*12205.000	36.0	33	40.5	43.5	74.0	-30.5

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2441.000	99.0	33	29.4	43.9	51.5	94.0	-42.5
H	*4882.000	61.9	33	34.9	43.9	19.9	54.0	-34.1
H	*7323.000	47.7	33	37.9	43.9	8.7	54.0	-45.3
H	9764.000	42.0	33	40.4	43.9	5.5	54.0	-48.5
H	*12205.000	36.0	33	40.5	43.9	-0.4	54.0	-54.4

NOTES: 1. Peak detector is used for the emission measurement.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

* Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 78 (Charging by USB)

Table 6, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	98.5	33	29.4	94.9	114.0	-19.1
H	*4960.000	61.7	33	34.9	63.6	74.0	-10.4
H	*7440.000	47.2	33	37.9	52.1	74.0	-21.9
H	9920.000	41.6	33	40.4	49.0	74.0	-25.0
H	*12400.000	35.5	33	40.5	43.0	74.0	-31.0

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	98.5	33	29.4	43.9	51.0	94.0	-43.0
H	*4960.000	61.7	33	34.9	43.9	19.7	54.0	-34.3
H	*7440.000	47.2	33	37.9	43.9	8.2	54.0	-45.8
H	9920.000	41.6	33	40.4	43.9	5.1	54.0	-48.9
H	*12400.000	35.5	33	40.5	43.9	-0.9	54.0	-54.9

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 0 (Charging by /37 2-pin adaptor)

Table 7, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	100.0	33	29.4	96.4	114.0	-17.6
H	*4804.000	62.4	33	34.9	64.3	74.0	-9.7
H	7206.000	48.5	33	37.9	53.4	74.0	-20.6
H	9608.000	42.1	33	40.4	49.5	74.0	-24.5
H	*12010.000	36.4	33	40.5	43.9	74.0	-30.1

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	100.0	33	29.4	43.9	52.5	94.0	-41.5
H	*4804.000	62.4	33	34.9	43.9	20.4	54.0	-33.6
H	7206.000	48.5	33	37.9	43.9	9.5	54.0	-44.5
H	9608.000	42.1	33	40.4	43.9	5.6	54.0	-48.4
H	*12010.000	36.4	33	40.5	43.9	0.0	54.0	-54.0

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V. Date of Test: May 15-June 28, 2008
 Model: SHB9000/00
 Mode : TX-Channel 39 (Charging by /37 2-pin adaptor)

Table 8, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2441.000	99.9	33	29.4	96.3	114.0	-17.7
H	*4882.000	62.1	33	34.9	64.0	74.0	-10.0
H	*7323.000	48.3	33	37.9	53.2	74.0	-20.8
H	9764.000	42.4	33	40.4	49.8	74.0	-24.2
H	*12205.000	36.2	33	40.5	43.7	74.0	-30.3

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2441.000	99.9	33	29.4	43.9	52.4	94.0	-41.6
H	*4882.000	62.1	33	34.9	43.9	20.1	54.0	-33.9
H	*7323.000	48.3	33	37.9	43.9	9.3	54.0	-44.7
H	9764.000	42.4	33	40.4	43.9	5.9	54.0	-48.1
H	*12205.000	36.2	33	40.5	43.9	-0.2	54.0	-54.2

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V. Date of Test: May 15-June 28, 2008
 Model: SHB9000/00
 Mode : TX-Channel 78 (Charging by /37 2-pin adaptor)

Table 9, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	99.7	33	29.4	96.1	114.0	-17.9
H	*4960.000	61.9	33	34.9	63.8	74.0	-10.2
H	*7440.000	47.9	33	37.9	52.8	74.0	-21.2
H	9920.000	42.1	33	40.4	49.5	74.0	-24.5
H	*12400.000	35.7	33	40.5	43.2	74.0	-30.8

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	99.7	33	29.4	43.9	52.2	94.0	-41.8
H	*4960.000	61.9	33	34.9	43.9	19.9	54.0	-34.1
H	*7440.000	47.9	33	37.9	43.9	8.9	54.0	-45.1
H	9920.000	42.1	33	40.4	43.9	5.6	54.0	-48.4
H	*12400.000	35.7	33	40.5	43.9	-0.7	54.0	-54.7

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 0 (Charging by /00 2-pin adaptor)

Table 10, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	100.1	33	29.4	96.5	114.0	-17.5
H	*4804.000	62.3	33	34.9	64.2	74.0	-9.8
H	7206.000	48.1	33	37.9	53.0	74.0	-21.0
H	9608.000	42.4	33	40.4	49.8	74.0	-24.2
H	*12010.000	36.1	33	40.5	43.6	74.0	-30.4

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2402.000	100.1	33	29.4	43.9	52.6	94.0	-41.4
H	*4804.000	62.3	33	34.9	43.9	20.3	54.0	-33.7
H	7206.000	48.1	33	37.9	43.9	9.1	54.0	-44.9
H	9608.000	42.4	33	40.4	43.9	5.9	54.0	-48.1
H	*12010.000	36.1	33	40.5	43.9	-0.3	54.0	-54.3

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V. Date of Test: May 15-June 28, 2008
 Model: SHB9000/00
 Mode : TX-Channel 39 (Charging by /00 2-pin adaptor)

Table 11, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2441.000	100.0	33	29.4	96.4	114.0	-17.6
H	*4882.000	62.1	33	34.9	64.0	74.0	-10.0
H	*7323.000	48.2	33	37.9	53.1	74.0	-20.9
H	9764.000	42.2	33	40.4	49.6	74.0	-24.4
H	*12205.000	36.0	33	40.5	43.5	74.0	-30.5

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2441.000	100.0	33	29.4	43.9	52.5	94.0	-41.5
H	*4882.000	62.1	33	34.9	43.9	20.1	54.0	-33.9
H	*7323.000	48.2	33	37.9	43.9	9.2	54.0	-44.8
H	9764.000	42.2	33	40.4	43.9	5.7	54.0	-48.3
H	*12205.000	36.0	33	40.5	43.9	-0.4	54.0	-54.4

NOTES: 1. Peak detector is used for the emission measurement.

2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

* Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 78 (Charging by /00 2-pin adaptor)

Table 12, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	99.9	33	29.4	96.3	114.0	-17.7
H	*4960.000	61.9	33	34.9	63.8	74.0	-10.2
H	*7440.000	48.1	33	37.9	53.0	74.0	-21.0
H	9920.000	42.0	33	40.4	49.4	74.0	-24.6
H	*12400.000	35.9	33	40.5	43.4	74.0	-30.6

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2480.000	99.9	33	29.4	43.9	52.4	94.0	-41.6
H	*4960.000	61.9	33	34.9	43.9	19.9	54.0	-34.1
H	*7440.000	48.1	33	37.9	43.9	9.1	54.0	-44.9
H	9920.000	42.0	33	40.4	43.9	5.5	54.0	-48.5
H	*12400.000	35.9	33	40.5	43.9	-0.5	54.0	-54.5

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V. Date of Test: May 15-June 28, 2008
 Model: SHB9000/00
 Mode : TX-Channel 0 (Charging by /05 3-pin adaptor)

Table 13, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2402.000	100.1	33	29.4	96.5	114.0	-17.5
H	*4804.000	62.9	33	34.9	64.8	74.0	-9.2
H	7206.000	48.7	33	37.9	53.6	74.0	-20.4
H	9608.000	42.0	33	40.4	49.4	74.0	-24.6
H	*12010.000	35.6	33	40.5	43.1	74.0	-30.9

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2402.000	100.1	33	29.4	43.9	52.6	94.0	-41.4
H	*4804.000	62.9	33	34.9	43.9	20.9	54.0	-33.1
H	7206.000	48.7	33	37.9	43.9	9.7	54.0	-44.3
H	9608.000	42.0	33	40.4	43.9	5.5	54.0	-48.5
H	*12010.000	35.6	33	40.5	43.9	-0.8	54.0	-54.8

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.

Date of Test: May 15-June 28, 2008

Model: SHB9000/00

Mode : TX-Channel 39 (Charging by /05 3-pin adaptor)

Table 14, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	2441.000	99.9	33	29.4	96.3	114.0	-17.7
H	*4882.000	62.8	33	34.9	64.7	74.0	-9.3
H	*7323.000	48.3	33	37.9	53.2	74.0	-20.8
H	9764.000	41.9	33	40.4	49.3	74.0	-24.7
H	*12205.000	35.5	33	40.5	43.0	74.0	-31.0

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	2441.000	99.9	33	29.4	43.9	52.4	94.0	-41.6
H	*4882.000	62.8	33	34.9	43.9	20.8	54.0	-33.2
H	*7323.000	48.3	33	37.9	43.9	9.3	54.0	-44.7
H	9764.000	41.9	33	40.4	43.9	5.4	54.0	-48.6
H	*12205.000	35.5	33	40.5	43.9	-0.9	54.0	-54.9

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V. Date of Test: May 15-June 28, 2008
 Model: SHB9000/00
 Mode : TX-Channel 78 (Charging by /05 3-pin adaptor)

Table 15, Headset

Radiated Emissions Pursuant to FCC Part 15 Section 15.249(a) Requirements

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	99.6	33	29.4	96.0	114.0	-18.0
H	*4960.000	62.3	33	34.9	64.2	74.0	-9.8
H	*7440.000	47.9	33	37.9	52.8	74.0	-21.2
H	9920.000	41.6	33	40.4	49.0	74.0	-25.0
H	*12400.000	35.3	33	40.5	42.8	74.0	-31.2

Polarization	Frequency	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2480.000	99.6	33	29.4	43.9	52.1	94.0	-41.9
H	*4960.000	62.3	33	34.9	43.9	20.3	54.0	-33.7
H	*7440.000	47.9	33	37.9	43.9	8.9	54.0	-45.1
H	9920.000	41.6	33	40.4	43.9	5.1	54.0	-48.9
H	*12400.000	35.3	33	40.5	43.9	-1.1	54.0	-55.1

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

3.4 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz and 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

Please refer to the following plots for radiated emission on the bandedge:

Plot H1A*: Headset - Low Channel Emissions

Plot H1B**: Headset - High Channel Emissions

For electronic filing, the above plots are saved with filename: emission.pdf

* Bandedge compliance is determined by applying marker-delta method, i.e.

Peak Resultant: Resultant field strength = Fundamental emissions - delta from the plot
= 96.5dB μ V/m - 35.14dB
= 61.36dB μ V/m

Average Resultant: Resultant field strength = Fundamental emissions - delta from the plot
= 52.6dB μ V/m - 35.14dB
= 17.46dB μ V/m

** Bandedge compliance is determined by applying marker-delta method, i.e.

Peak Resultant: Resultant field strength = Fundamental emissions - delta from the plot
= 96.3dB μ V/m - 50.02dB
= 46.28dB μ V/m

Average Resultant: Resultant field strength = Fundamental emissions - delta from the plot
= 52.4dB μ V/m - 50.02dB
= 2.38dB μ V/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 54dB μ V/m for average limit and 74dB μ V/m for peak limit.

Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

3.5 Line Conducted Configuration Photograph - Headset

Worst Case Line-Conducted Configuration

at 1.495 MHz

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.pdf

INTERTEK TESTING SERVICES

3.6 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by 8.4 dB margin compare with the average limit

For electronic filing, the conducted emission test result is saved with filename: conduct.pdf

TEST PERSONNEL:



Tester Signature

Jess Tang, Lead Engineer
Typed/Printed Name

September 8, 2008
Date

INTERTEK TESTING SERVICES

Company: Philips Consumer Electronics B.V.
Model: SHB9000/00

Date of Test: May 15-June 28, 2008

3.7 Transmitter Duty Cycle Calculation , FCC Rule 15.35(b, c)

Based on the Bluetooth Specification Version 2.1 + EDR, transmitter ON time is independent of the packet type (DH1, DH3 and DH5) and packet length (single-slot and multi-slot). The maximum transmitter ON time for the Bluetooth is 625 μ s.

Each TX and RX time slot is 625 μ s in length. A TDD scheme is used where master and slave alternately transmit. For one period for a pseudo-random hopping through all 79 RF channels, it takes: $79 \times (0.625 \times 2)\text{ms} = 98.75\text{ms}$.

Therefore,

$$\begin{aligned}\text{Average Factor (AF) of Bluetooth in dB} &= 20 \log_{10} (0.625/98.75) \text{ dB} \\ &= 20 \log_{10} (0.00633) \text{ dB} \\ &= -43.9\text{dB}\end{aligned}$$

INTERTEK TESTING SERVICES

EXHIBIT 4 EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf

INTERTEK TESTING SERVICES

EXHIBIT 5 PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf

INTERTEK TESTING SERVICES

EXHIBIT 6 TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

INTERTEK TESTING SERVICES

EXHIBIT 7 INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf

The required FCC Information to the User is stated on P.5 of the Instruction Manual.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 8 LETTER OF AGENCY

INTERTEK TESTING SERVICES

8.0 Letter of Agency

For electronic filing, a letter of agency is saved with filename: letter of agency.pdf

INTERTEK TESTING SERVICES

EXHIBIT 9 CONFIDENTIALITY REQUEST

INTERTEK TESTING SERVICES

9.0 Confidentiality Request

For electronic filing, a preliminary copy of the Confidentiality Request is saved with filename: request.pdf