

FCC EVALUATION REPORT FOR CERTIFICATION

Manufacturer: Ohsung Electronics Co., Ltd.

#141 Gongdan-dong, Gumi-si, Gyeongbuk,

Republic of Korea

Attn: Mr. Jae-Gyun, Kim / TEAM LEADER OF

HARDWARE DIVISION

Date of Issue: April 29, 2016

Order Number: GETEC-C1-16-215

Test Report Number: GETEC-E3-16-025

Test Site: GUMI UNIVERSITY EMC CENTER

(Test firm Registration Number: 269701)

FCC ID. : OZ5URC-UR2DTA

Applicant : Ohsung Electronics Co., Ltd.

Rule Part(s) : FCC Part 15 Subpart C-Intentional Radiator § 15.247

Test Method : ANSI C63.10 (2013)

Equipment Class : Digital Transmission System(DTS)

EUT Type : Remote controller

Type of Authority : Certification

Model Name : UR2-DTA-RFTW

Trade Mark : UNIVERSAL Remote Control

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10 (2013)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the vest of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Reviewed by,

Soon Hoon

Soon-Hoon Jeong, Senior Engineer
GUMI UNIVERSITY EMC CENTER

Jae-Hoon Jeong

Jae-Hoon Jeong, Technical Manager
GUMI UNIVERSITY EMC CENTER



CONTENTS

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
3. PRODUCT INFORMATION	6
3.1 DESCRIPTION OF EUT.....	6
3.2 DEFINITION OF MODELS.....	6
3.3 SUPPORT EQUIPMENT / CABLES USED	7
3.4 MODIFICATION ITEM(S).....	7
4. ANTENNA REQUIREMENT - §15.203	8
4.1 DESCRIPTION OF ANTENNA.....	8
5. DESCRIPTION OF TESTS.....	8
5.1 TEST CONDITION.....	8
6. DUTY CYCLE CORRECTION.....	9
6.1 OPERATING ENVIRONMENT	9
6.2 TEST SET-UP	9
6.3 TEST EQUIPMENT USED.....	9
6.4 TEST RESULT OF DUTY CYCLE.....	9
7. SUMMARY OF TEST RESULTS	10
8. 6 DB BANDWIDTH MEASUREMENT	11
8.1 OPERATING ENVIRONMENT	11
8.2 TEST SET-UP (LAYOUT)	11
8.3 LIMIT	11
8.4 TEST EQUIPMENT USED.....	11
8.5 TEST TEST PROCEDURE	11
8.6 TEST RESULT	12
9. CONDUCTED MAXIMUM PEAK OUTPUT POWER MEASUREMENT	14
9.1 OPERATING ENVIRONMENT	14
9.2 TEST SET-UP (LAYOUT)	14
9.3 LIMIT	14
9.4 TEST EQUIPMENT USED.....	14
9.5 TEST PROCEDURE	14
9.6 TEST RESULT	14
10. POWER SPECTRAL DENSITY MEASUREMENT.....	15
10.1 OPERATING ENVIRONMENT	15
10.2 TEST SET-UP (LAYOUT)	15
10.3 LIMIT	15
10.4 TEST EQUIPMENT USED.....	15
10.5 TEST PROCEDURE	15
10.6 TEST RESULT	16





11. CONDUCTED SPURIOUS EMISSION & OUT OF BAND EMISSION	18
11.1 OPERATING ENVIRONMENT.....	18
11.2 TEST SET-UP (LAY-OUT).....	18
11.3 LIMIT	18
11.4 TEST EQUIPMENT USED	18
11.5 TEST PROCEDURE.....	18
11.6 TEST RESULT	19
12. AC POWER LINE CONDUCTED EMISSION	22
12.1 OPERATING ENVIRONMENT	23
12.2 TEST SET-UP	23
12.3 MEASUREMENT UNCERTAINTY.....	23
12.4 LIMIT	24
12.5 TEST EQUIPMENT USED.....	24
12.6 TEST DATA FOR CONDUCTED EMISSION	24
13. RADIATED SPURIOUS & RESTRICTED BAND EDGE EMISSION.....	25
13.1 OPERATING ENVIRONMENT	26
13.2 TEST SET-UP.....	26
13.3 MEASUREMENT UNCERTAINTY	26
13.4 LIMIT	27
13.5 TEST EQUIPMENT USED.....	27
13.6 TEST DATA FOR RADIATED SPURIOUS EMISSION.....	28
13.7 TEST DATA FOR RADIATED RESTRICTED BAND EDGE EMISSION	33
14. SAMPLE CALCULATIONS.....	34
14.1 EXAMPLE 1 :	34
14.2 EXAMPLE 2 :	34
15. RECOMMENDATION & CONCLUSION.....	35
APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – LABELLING	
APPENDIX C – BLOCK DIAGRAM	
APPENDIX D – SCHEMATIC DIAGRAM	
APPENDIX E – TEST SETUP PHOTOGRAPH	
APPENDIX F – EXTERNAL PHOTOGRAPH	
APPENDIX G – INTERNAL PHOTOGRAPH	
APPENDIX H – USER’S MANUAL	
APPENDIX I – OPERATIONAL DESCRIPTION	
APPENDIX J – ANTENNA SPECIFICATION	
APPENDIX K – PART LIST	
APPENDIX L – RF EXPOSURE EVALUATION	





Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: Ohsung Electronics Co., Ltd.

Applicant Address: #141 Gongdan-dong, Gumi-si, Gyeongbuk, Republic of Korea

Manufacturer: Ohsung Electronics Co., Ltd.

Manufacturer Address: #141 Gongdan-dong, Gumi-si, Gyeongbuk, Republic of Korea

Contact Person: Mr. Jae-Gyun, Kim /TEAM LEADER OF HARDWARE DIVISION

Telephone Number: +82-54-461-7035

Fax Number: +82-54-461-8368

- **FCC ID.** OZ5URC-UR2DTA
- **Equipment Class** Digital Transmission System (DTS)
- **EUT Type** Remote controller
- **Model Name** UR2-DTA-RFTW
- **Rule Part(s)** FCC Part 15 Subpart C-Intentional Radiator § 15.247
- **Test Method** ANSI C63.10 (2013)
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.10 (2013), KDB558074 D01 DTS Meas Guidance v03r05(April 8,2016)
- **Dates of Test** April 15 ~ 20, 2016
- **Place of Test** GUMI UNIVERSITY EMC CENTER (FCC Test firm Registration No.: 269701)
37 Yaeun-ro, Gumi-si, Gyeongsangbuk-do, 730-711, Republic of Korea
- **Test Report Number** GETEC-E3-16-025
- **Dates of Issue** April 29, 2016

EUT Type: Remote controller

FCC ID.: OZ5URC-UR2DTA





2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2009) was used in determining radiated and conducted emissions emanating from **Ohsung Electronics Co., Ltd. Remote Controller (Model name: UR2-DTA-RFTW)**

These measurement tests were conducted at **GUMI UNIVERSITY EMC CENTER**.

The site address is 37 Yaeun-ro, Gumi-si, Gyeongsangbuk-do, 730-711, Gyeongnam 641-713, Korea

This test site is one of the highest point of Gumi 1 college at about 200 kilometers away from Seoul city and 40 kilometers away from Daeje city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.10 (2013)




Fig 1. The map above shows the Gumi University in vicinity area.





3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **Ohsung Electronics Co., Ltd. Remote controller (Model Name: UR2-DTA-RFTW) FCC ID.: OZ5URC-UR2DTA**

- Equipment	: RF Remote Control
- Model name	: UR2-DTA-RFTW
- Brand name	: UNIVERSAL Remote Control
- Serial number	: Proto type
- Electrical Rating	: DC 3.0 V(Battery)
- Manufacturer	: Ohsung electronics Co., Ltd.
- Channel Separations	: 25 MHz
- Type of Modulation	: O-QPSK
- Modulation Technology	: DSSS
- Transfer rate	: 250 kbps
- Frequency range	: 2 425 MHz ~ 2475 MHz
- Number of channel	: 3
- Antenna Type	: PCB printed antenna
- Type of chain	: One
- Antenna specification	: Manufacturer : Ohsung Electronics Co., Ltd. Antenna type : PCB printed antenna Peak Gain : 1.69 dBi
- Hardware version	: PBAFA1319B
- Software version	: V0.032

3.2 Definition of models

-None.





3.3 Support Equipment / Cables used

3.3.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
None.	-	-	S/N: None. FCC ID.: N/A.

See "Appendix E – Test Setup Photographs" for actual system test set-up

3.3.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
None.	-	-	S/N: - FCC ID.: -

3.3.3 Used Cable(s)

Cable Name	Condition	Description
None.	-	-

3.4 Modification Item(s)

- None





4. Antenna Requirement - §15.203

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the applicant can be used with the device. The use of permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with this requirement.

4.1 Description of Antenna

The **Ohsung Electronics Co., Ltd. Remote controller.** comply with the requirement of §15.203 with a built-in PCB printed antenna permanently attached to the transmitter.

5. Description of tests

5.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency: DC 3 V
- Operating condition during the test(s) :
 - . Continuous RF transmitting mode with maximum RF output power.
 - . The RF transmitting signal is DSSS modulation signal.

Operating channel frequency and moderation technology

Mode	Available channel	Type of Modulation	Data rate (kbps)
IEEE 802.15.4	15, 20, 25	O-QPSK	250

※ Frequency List

Channel No.	Frequency(MHz)
15	2425
20	2450
25	2475





6. Duty Cycle Correction

6.1 Operating Environment

Temperature : 22.0 °C
 Relative humidity : 34.2 % R.H.

6.2 Test Set-up

The spectrum analyzer was set to Zero span and the video triggered to collect the pulse train of the modulation. Calculations of the duty cycle correction factor were obtained from time data provided by the plots.

6.3 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP	Rohde & Schwarz	EMI Test Receiver	101431	Jan. 04, 2017
■ - 8493C	Agilent	6 dB Attenuator	59907	Apr. 26, 2016

6.4 Test result of Duty Cycle


- Test Date : Apr. 20, 2016
- Reference Standard : Part 15 Subpart C, Sec. 15.231 (a)(1)
- Operating Condition : RF transmitting mode
- Spectrum Resolution Bandwidth (6 dB) : 1MHz

Calculation of duty cycle

- Total width of pulse train: 1.352 ms
- Duty Cycle (%): $1.352 \text{ ms} / 15.055 \text{ ms} = 0.0898 \times 100 = 8.98 \%$
- Duty Cycle (dB): $20 \log x (1.352/15.055) = -20.93 \text{ dB}$

Frequency	Total width of ON-Time	Duty Cycle (%)	Duty Cycle (dB)
2 450 MHz	1.352 ms	8.98 %	-20.93 dB

Duty Cycle Plot on Configuration : Middle channel (2 450 MHz)



EUT Type: Remote controller

FCC ID.: OZ5URC-UR2DTA





7. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Result
§15.247(a)(2)	6 dB Bandwidth	Pass
§15.247(b)(3)	Conducted Maximum Peak Output Power	Pass
§15.247(e)	Power Spectral Density	Pass
§15.247(d)	Conducted Out of Band Emission Emissions	Pass
§15.207(a)	AC Power line Conducted Emissions	N/A ¹⁾
§15.205, 15.209	Radiated Spurious Emissions	Pass
§15.247(d), 15.205, 15.209	Radiated Restricted Band Edge	Pass

Note)

1) The EUT is supplied power from battery. Therefore the test was not applicable.






8. 6 dB Bandwidth Measurement

8.1 Operating environment

Temperature : 23.1 °C
 Relative Humidity : 37.3 % R.H.

8.2 Test Set-up (Layout)



8.3 Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

8.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP	Rohde & Schwarz	Spectrum Analyzer	101431	Jan. 04, 2017
■ - 8493C	Agilent	6 dB Attenuator	59907	Apr. 26. 2016

8.5 Test Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.






8.6 Test result

- Test Date : April 20, 2016
- Reference Standard : Part 15 Subpart C, Sec. 15.247(a)(2)
- Test Procedure(s) : ANSI C63.10 (2013), KDB558074 D01 DTS Meas Guidance v03r05(April 8,2016)
- Operating Condition : RF transmitting mode (Low: 2 425 MHz, Middle: 2 450 MHz, High: 2 475 MHz)
- Power Source : DC 3 V

Frequency (MHz)	6 dB Bandwidth (MHz)	Min. Limit (kHz)	Result
2 425	1.68	500	Complies
2 450	1.60	500	Complies
2 475	1.44	500	Complies

6 dB Bandwidth Plot on Configuration : Lowest channel (2 425 MHz)




Date: 20.APR.2016 10:53:43






6 dB Bandwidth Plot on Configuration : Middle channel (2 450 MHz)



Date: 20.APR.2016 10:57:43

6 dB Bandwidth Plot on Configuration : Highest channel (2 475 MHz)



Date: 20.APR.2016 10:58:48






9. Conducted Maximum Peak Output Power Measurement

9.1 Operating environment

Temperature : 23.4 °C
 Relative Humidity : 37.7 % R.H.

9.2 Test Set-up (Layout)



9.3 Limit

For systems using digital modulation in the (2 400~2 483.5) MHz, the limit for peak output power is 30 dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

9.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - NRV-Z32	Rohde & Schwarz	Peak Power sensor	100049	Jan. 05, 2017
■ - NRVD	Rohde & Schwarz	Dual Channel Power Meter	837794/048	Apr. 24, 2016
■ - NRP-Z51	Rohde & Schwarz	Power sensor	1138.0005.02	Jan. 05, 2017

9.5 Test Procedure

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

9.6 Test Result

- Test Date : April 20, 2016
- Reference Standard : Part 15 Subpart C, Sec. 15.247(a)(2)
- Test Procedure(s) : ANSI C63.10 (2013), KDB558074 D01 DTS Meas Guidance v03r05(April 8,2016)
- Operating Condition : RF transmitting mode (Low: 2 425 MHz, Middle: 2 450 MHz, High: 2 475 MHz)
- Power Source : DC 3 V

Frequency (MHz)	Average Conducted Power ¹⁾ (dBm)	Peak Conducted Power (dBm)	Max. Limit (dBm)	Result
2 425	6.69	6.87	30.00	Complies
2 450	6.54	6.71	30.00	Complies
2 475	6.39	6.55	30.00	Complies

Note: 1) The Average output power is reference data for RF Exposure.






10. Power Spectral Density Measurement

10.1 Operating Environment

Temperature : 23.8 °C
 Relative Humidity : 37.1 % R.H.

10.2 Test Set-up (Layout)



10.3 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

10.4 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP	Rohde & Schwarz	Spectrum Analyzer	101431	Jan. 04, 2017
■ - 8493C	Agilent	6 dB Attenuator	59907	Apr. 26. 2016

10.5 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to 3 kHz
- Set the VBW to 10 kHz
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.






10.6 Test Result

- Test Date : April 20, 2016
- Reference Standard : Part 15 Subpart C, Sec. 15.247(e)
- Test Procedure(s) : ANSI C63.10 (2013), KDB558074 D01 DTS Meas Guidance v03r05(April 8,2016)
- Operating Condition : RF transmitting mode (Low: 2 425 MHz, Middle: 2 450 MHz, High: 2 475 MHz)
- Power Source : DC 3 V

Frequency	PSD (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
2 425 MHz	-7.60	8.00	Complies
2 450 MHz	-7.85	8.00	Complies
2 475 MHz	-8.08	8.00	Complies

Power Density Plot on configuration : Lowest channel (2 425 MHz)




Date: 20.APR.2016 11:05:57






Power Density Plot on configuration : Middle channel (2 450 MHz)



Date: 20.APR.2016 11:05:11

Power Density Plot on configuration : Highest channel (2 475 MHz)



Date: 20.APR.2016 11:04:28






11. Conducted Spurious Emission & Out of Band Emission

11.1 Operating environment

Temperature : 23.2 °C
 Relative Humidity : 36.5 % R.H.

11.2 Test set-up (Lay-out)



11.3 Limit

Below -20 dB of the highest emission level of operating band (in 100 kHz resolution band width)

11.4 Test equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - FSP	Rohde & Schwarz	Spectrum Analyzer	101431	Jan. 30, 2017
■ - 8493C	Agilent	6 dB Attenuator	59907	Apr. 26, 2016

11.5 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to 3 kHz
- Set the VBW to 10 kHz
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.





11.6 Test Result

- Test Date : April 20, 2016
- Reference standard : Part 15 Subpart C, Sec. 15.247(e)
- Test Procedure(s) : ANSI C63.10 (2013), KDB558074 D01 DTS Meas Guidance v03r05(April 8,2016)
- Operating condition : RF transmitting mode (Low: 2 425 MHz, Middle: 2 450 MHz, High: 2 475 MHz)
- Power Source : DC 3 V


Conducted Spurious Emission

Operating Frequency	Spurious (dBc)	Limits (dBc)	Result
2425	-41.86	-20.00	Complies
2450	-40.92		Complies
2475	-40.06		Complies

Conducted Out of Band(Band Edge) Emission

Operating Frequency	Band Edge (dBc)	Limits (dBc)	Result
2425	-49.04	-20.00	Complies
2475	-47.39		Complies

Conducted spurious Emission Plot on Configuration : Lowest channel (2 425 MHz)




Date: 20.APR.2016 13:53:11






Conducted spurious Emission Plot on Configuration : Middle channel (2 450 MHz)



Date: 20.APR.2016 13:55:43

Conducted spurious Emission Plot on Configuration : Highest channel (2 475 MHz)




Date: 20.APR.2016 13:57:20






Low Band Edge Plot on Configuration : Lowest channel (2 425 MHz)



Date: 20.APR.2016 14:23:57

High Band Edge Plot on Configuration : Highest channel (2 475 MHz)



Date: 20.APR.2016 14:27:34





12. AC Power line Conducted emission

-Test Description

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (Test firm Registration Number: 269701)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ENV216) and the support equipment is powered from the Rohde & Schwarz LISN (ENV216). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCI).

Exploratory measurements were conducted to identify the highest emission by operating the EUT in a range of typical modes of operation, cable positions, system configuration and arrangement.

Based on exploratory measurements, the final measurements were conducted at the worst test conditions.

Exploratory measurements were scanned using Peak mode of EMI Test receiver from 150 kHz to 30 MHz with 20 ms sweep time. The final measurements were measured with Quasi-Peak and Average mode.

The bandwidth of EMI Test Receiver was set to 9 kHz. Interface cables were connected to the available interface ports of the test unit. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.




Fig 2. Impedance of LISN





12.1 Operating Environment

Temperature : - °C
 Relative Humidity : - % R.H.

12.2 Test Set-up

The conducted emission measurements were performed in the shielded room.
 The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN & ISN.
 AMN is bonded on horizontal reference ground plane.
 The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

12.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement.”
 The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 3.94 dB	Confidence level of approximately 95 % ($k = 2$)
Conducted emission (150 kHz ~ 30 MHz)	± 3.43 dB	Confidence level of approximately 95 % ($k = 2$)





12.4 Limit

RFI Conducted	FCC Limit(dBµV/m) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

12.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
<input type="checkbox"/> - ESCI	Rohde & Schwarz	EMI test receiver	100237	Apr 23. 2016
<input type="checkbox"/> - ENV216	Rohde & Schwarz	LISN	100172	Apr 23. 2016
<input type="checkbox"/> - ENV216	Rohde & Schwarz	LISN	100173	Apr 23. 2016
<input type="checkbox"/> - ISN T8	TESEQ. GmbH	ISN	24568	Apr 27. 2016

12.6 Test data for Conducted Emission

- Test Date :
 - Reference Standard :
 - Test Procedure(s) :
 - Operating Condition :
 - Frequency rage :
 - Comment : Not applicable
- ※ The EUT is supplied power from battery. Therefore this test was not applicable.





13. Radiated Spurious & Restricted Band Edge Emission

Exploratory Radiated measurements were conducted at the 3m semi anechoic chamber in order to identify the highest emission by operating the EUT in a range of typical modes of operation, cable positions, system configuration and arrangement.

Based on exploratory measurements, the final measurements were conducted at the worst test conditions.

Final measurements of below 1GHz were made at 3m or 10 m Chamber that complies with CISPR 16/ANSI C63.10. Above 1GHz final measurements were conducted at the 3m Chamber only.

For measurements above 1GHz, the bottom side of 3m chamber was installed with absorbers in order to meet SVSWR Limit.

Exploratory measurements were scanned using Peak mode of EMI Test receiver and final measurements were measured with Quasi-Peak mode (Below 1GHz) and Peak & Average mode (Above 1GHz).

The measurements were performed by rotating the EUT 360° and adjusting the receive antenna height from 1.0 m to 4.0 m. All frequencies were investigated in both horizontal and vertical antenna polarity.




Fig 3. Dimensions of test site (Below 1GHz)




Fig 4. Dimensions of test site (Above 1GHz)





13.1 Operating environment

Temperature : 19.6 °C
 Relative humidity : 42.5 % R.H.

13.2 Test set-up

A preliminary and final measurement was at 3 m anechoic chamber.

The EUT was placed on a non-conducting table.

For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane.

For emission measurements above 1 GHz, the table height is 1.5 m above the reference ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

13.3 Measurement uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test items(Anechoic Chamber)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 4.66 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 4.65 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 4.91 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 4.88 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (1 000 MHz ~ 6 000 MHz, 3 m, V/H)	± 5.32 dB	Confidence level of approximately 95 % ($k = 2$)
Radiated emission (6 000 MHz ~ 18 000 MHz, 3 m, V/H)	± 5.45 dB	Confidence level of approximately 95 % ($k = 2$)





13.4 Limit

20 dB in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2 400/F (kHz)	300
0.490 ~ 1.705	2 400/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

13.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESIB26	Rohde & Schwarz	EMI Test Receiver	830482/010	Apr. 18, 2017
■ - HFH2-Z2	Rohde & Schwarz	Loop Antenna	100041	Dec. 21, 2017
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3099	Aug. 03. 2017
■ - BBHA9120D	Schwarzbeck	Horn Antenna	207	Mar. 15. 2018
■ - 3160-09	Schwarzbeck	Horn Antenna	LM3981	Nov. 29. 2017
■ - MCU066	maturo GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM 4.0	maturo GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800-25-10P-44	MITEQ	Preamplifier	1258943	Jan. 05. 2017
■ - SCU-F1826-G47-BZ42-CSS	BONN Elektronik	Preamplifier	10003	Jan. 12. 2017






13.6 Test data for Radiated Spurious Emission

- Test Date : April 15~16, 2016
- Reference Standard : Part 15 Subpart C, Sec. 15.247(d)
- Measuring Distance : 3 m
- Spectrum Resolution : 120 kHz / 1 MHz / 10 Hz / 100 kHz
 Bandwidth(6 dB)
- Detector mode : Quasi Peak detector mode / Peak detector mode / Average detector mode
- Power Source : DC 3.0 V
- Note : Through three orthogonal axes were investigated and the worst case is report


Radiated Spurious Emission (9 kHz to 30 MHz): Middle channel (2 450 MHz)

Frequency (MHz)	Measurement Level						Limit (dBµV/m)		Margin (dB)		Positioning System			
	Reading Value (dBµV/m)		AF (dB/m)	AMP / CL (dB)	Duty Cycle collection (dB)	Test Result (dBµV/m)					Pol. (H/V)	Height (cm)	Angle (°)	
	Peak	Average				Peak	Average	Peak	Average					
The emission level was not found														





Radiated Spurious Emission (30 MHz to 1 000 MHz): Middle channel (2 450 MHz)



Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
30.560000	16.93	40.00	23.07	1000.0	120.000	125.0	V	349.0	12.6
40.119439	18.55	40.00	21.45	1000.0	120.000	107.0	V	180.0	12.9
47.974990	33.46	40.00	6.54	1000.0	120.000	106.0	V	132.0	13.3
57.134429	26.79	40.00	13.21	1000.0	120.000	120.0	V	10.0	12.8
69.677756	17.59	40.00	22.41	1000.0	120.000	111.0	V	294.0	11.5
103.067736	17.86	43.50	25.64	1000.0	120.000	125.0	V	32.0	11.4





Radiated Spurious Emission (1 GHz to 25 GHz): Lowest channel (2 425 MHz)

Frequency (MHz)	Measurement Level					Limit (dBµV/m)		Margin (dB)		Positioning System				
	Reading Value (dBµV/m)		AF	AMP / CL	Duty Cycle collection					Test Result (dBµV/m)		Pol.	Height	Angle
	Peak	Average	(dB/m)	(dB)	(dB)	Peak	Average	Peak	Average	(H/V)	(cm)	(°)		
4848.87	64.34	-	30.77	-34.67	-20.93	60.44	39.51	74.00	54.00	13.56	14.49	H	157	214
7273.34	61.01	-	35.87	-31.08	-20.93	65.80	44.87	74.00	54.00	8.20	9.13	H	100	352
9702.21	56.24	-	38.31	-26.79	-20.93	67.76	46.83	74.00	54.00	6.24	7.17	V	110	260
12127.88	47.12	-	38.88	-26.14	-20.93	59.86	38.93	74.00	54.00	14.14	15.07	H	106	336
14553.09	46.84	-	43.29	-25.37	-20.93	64.76	43.83	74.00	54.00	9.24	10.17	V	219	78



Note:

Emission level (dBµV/m) = 20 log × Emission level (µV/m).

Corrected reading: Antenna factor + Cable loss + Preamplifier gain + High Pass Filter + Read value = Test result

Duty cycle collection (dB) : 20log(dwell time / 100ms or T) dB = -20.93 dB


Pol.: H(Horizontal), V(Vertical)





Radiated Spurious Emission (1 GHz to 25 GHz): Middle channel (2 450 MHz)

Frequency (MHz)	Measurement Level						Limit (dBµV/m)		Margin (dB)		Positioning System			
	Reading Value (dBµV/m)		AF	AMP / CL	Duty Cycle collection	Test Result (dBµV/m)		Peak	Average	Peak	Average	Pol. (H/V)	Height (cm)	Angle (°)
	Peak	Average	(dB/m)	(dB)	(dB)	Peak	Average							
4898.99	65.73	-	30.84	-34.51	-20.93	62.06	41.13	74.00	54.00	11.94	12.87	H	166	149
7351.52	60.39	-	36.02	-30.92	-20.93	65.49	44.56	74.00	54.00	8.51	9.44	H	100	274
9797.99	55.68	-	38.41	-26.63	-20.93	67.46	46.53	74.00	54.00	6.54	7.47	H	100	240
12247.32	52.29	-	38.70	-26.13	-20.93	64.86	43.93	74.00	54.00	9.14	10.07	H	175	192
14703.39	50.51	-	43.06	-25.31	-20.93	68.26	47.33	74.00	54.00	5.74	6.67	H	125	145



Note:

Emission level (dBµV/m) = 20 log × Emission level (µV/m).

Corrected reading: Antenna factor + Cable loss + Preamplifier gain + High Pass Filter + Read value = Test result

Duty cycle collection (dB) : 20log(dwell time / 100ms or T) dB = -20.93 dB


Pol.: H(Horizontal), V(Vertical)





Radiated Spurious Emission (1 GHz to 25 GHz): Highest channel (2 475 MHz)

Frequency (MHz)	Measurement Level						Limit (dBμV/m)		Margin (dB)		Positioning System			
	Reading Value (dBμV/m)		AF	AMP / CL	Duty Cycle collection	Test Result (dBμV/m)		Peak	Average	Peak	Average	Pol. (H/V)	Height (cm)	Angle (°)
	Peak	Average	(dB/m)	(dB)	(dB)	Peak	Average							
4949.00	64.34	-	30.91	-34.50	-20.93	60.75	39.82	74.00	54.00	13.25	14.18	H	200	218
7426.44	62.56	-	36.17	-30.77	-20.93	67.96	47.03	74.00	54.00	6.04	6.97	V	100	229
9897.83	56.11	-	38.50	-26.45	-20.93	68.16	47.23	74.00	54.00	5.84	6.77	V	106	260
12377.56	49.00	-	38.51	-26.13	-20.93	61.38	40.45	74.00	54.00	12.62	13.55	H	113	2
14859.35	41.37	-	42.81	-25.24	-20.93	58.94	38.01	74.00	54.00	15.06	15.99	V	184	86



Note:

Emission level (dBμV/m) = 20 log × Emission level (μV/m).

Corrected reading: Antenna factor + Cable loss + Preamplifier gain + High Pass Filter + Read value = Test result

Duty cycle collection (dB) : 20log(dwell time / 100ms or T) dB = -20.93 dB

Pol.: H(Horizontal), V(Vertical)





13.7 Test data for Radiated Restricted Band Edge Emission

- Test Date : April 15~16, 2016
- Reference Standard : Part 15 Subpart C, Sec. 15.247(d)
- Measuring Distance : 3 m
- Spectrum Resolution : 120 kHz / 1 MHz / 10 Hz / 100 kHz
 Bandwidth(6 dB)
- Detector mode : Quasi Peak detector mode / Peak detector mode / Average detector mode
- Power Source : DC 3.0 V
- Note : Through three orthogonal axes were investigated and the worst case is report

Lowest channel (2 425 MHz)

Frequency (MHz)	Measurement Level							Limit (dBμV/m)		Margin (dB)		Positioning System		
	Reading Value (dBμV/m)		AF	AMP / CL	Duty Cycle collection	Test Result (dBμV/m)						Pol.	Height	Angle
	Peak	Average	(dB/m)	(dB)	(dB)	Peak	Average	Peak	Average	Peak	Average	(H/V)	(cm)	(°)
2361.46	62.04	-	26.82	-36.98	-20.93	51.88	30.95	74.00	54.00	22.12	23.05	H	152	41

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBμV/m) = 20 log × Emission level (μV/m).

Corrected reading: Antenna factor + Cable loss + Preamplifier gain + High Pass Filter + Read value = Test result

Duty cycle collection (dB) : 20log × (dwell time / 100ms or T) dB = -20.93 dB

Pol.: H(Horizontal), V(Vertical)

Highest channel (2 475 MHz)

Frequency (MHz)	Measurement Level							Limit (dBμV/m)		Margin (dB)		Positioning System		
	Reading Value (dBμV/m)		AF	AMP / CL	Duty Cycle collection	Test Result (dBμV/m)						Pol.	Height	Angle
	Peak	Average	(dB/m)	(dB)	(dB)	Peak	Average	Peak	Average	Peak	Average	(H/V)	(cm)	(°)
2483.50	69.74	-	27.21	-36.95	-20.93	60.00	39.07	74.00	54.00	14.00	14.93	H	197	86

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBμV/m) = 20 log × Emission level (μV/m).

Corrected reading: Antenna factor + Cable loss + Preamplifier gain + High Pass Filter + Read value = Test result

Duty cycle collection (dB) : 20log × (dwell time / 100ms or T) dB = -20.93 dB

Pol.: H(Horizontal), V(Vertical)






14. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

14.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dBμV
Reading	= 39.2 dBμV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dBμV - 39.2 dBμV
	= 8.8 dB



14.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB$\mu\text{V}/\text{m}$
Reading	= 31.0 dBμV
Antenna Factor + Cable Loss	= 5.8 dB
Total	= 36.8 dB$\mu\text{V}/\text{m}$
Margin	= 40.0 dB$\mu\text{V}/\text{m}$ - 36.8 dB$\mu\text{V}/\text{m}$
	= 3.2 dB





15. Recommendation & Conclusion

The data collected shows that the **Ohsung Electronics Co., Ltd. Remote controller (Model Name: UR2-DTA-RFTW)** was complies with §15.247 of the FCC Rules.

- The end -

