



AT&T Wireless Services, Inc.

Fixed Wireless Services
P.O. Box 97059
Redmond, WA 98073-9759

Base Station (B1.8 PCS) FCC Type Acceptance Application

© 1995-2001 AT&T Wireless
All rights reserved.

For additional copies of this document, please contact:

AT&T Wireless
P.O. Box 97059
Redmond, WA 98073-9759
Telephone: 425-702-2767
Ask for [Base Station \(B1.8 PCS\) FCC Type Acceptance Application or 12761](#)

Contents

Contents	iii
List of Figures	ix
List of Tables	xv

Chapter 1 Attestation Statements

Chapter 2 Block Diagrams

2.1 Block Diagrams	20
2.2 Clock Frequencies	25

Chapter 3 Cover Letters

3.1 FWAN PCS Base Station—System-Dependent Products	32
---	----

Chapter 4 External Photographs

4.1 External Photographs	34
--------------------------------	----

Chapter 5 ID Label/Location Information

5.1 ID Label	40
5.2 Location Information	41

Chapter 6 Internal Photographs

6.1 Internal Photographs of FWAN PCS B1.8 Base Station Digital Cards	44
6.1.1 Digital Shelf	44

6.1.2	Network Interface Circuit Pack PCA	46
6.1.3	WP PCA	48
6.1.4	BCP PCA	50
6.1.5	SBC PCA	52
6.1.6	SMP PCA	54
6.2	Internal Photographs of the FWAN PCS B1.8 Base Station RF Modules	56
6.2.1	Photographs of the Transceiver Module Unit	58
6.2.2	Photographs of the Power Supply	62
6.2.3	Photographs of the Duplexer	63

Chapter 7 Operational Description

7.1	System Overview	66
7.1.1	FWAN PCS General Description	66
7.1.2	FWAN PCS Network Elements Overview	66
7.1.3	Wireless Network Elements Deployment	68
7.1.4	FWAN PCS Airlink Profile	69
7.1.5	FWAN PCS Telephony Functions	69
7.1.6	FWAN PCS FAX/Modem VF Traffic Functions	72
7.1.7	FWAN PCS High-Speed-Data Functions	72
7.1.8	HSD Medium Access	72
7.2	Airlink Overview	74
7.2.1	FWAN PCS Physical Layer Overview	74
7.2.1.1	Services Provided by the Physical Layer	75
7.2.1.2	Associated Control Channel Functional Description ...	75
7.2.1.3	FWAN PCS Voice Traffic Channel (VTch) Functional Description	75
7.2.1.4	FWAN PCS Network Access Channel (NAC) Functional Description	76
7.2.1.5	BC Definition	76
7.2.1.6	CLC Definition	77
7.2.1.7	UCAC Definition	77
7.2.1.8	SCAC Definition	77
7.2.1.9	FWAN PCS Data Traffic Channel (DTch) Definition	78
7.2.2	FWAN PCS Datalink Layer Overview	78
7.2.2.1	FWAN PCS Implementation of OFDM	80
7.2.2.2	FWAN PCS Datalink Layer Resource Allocation	82
7.2.2.3	FWAN PCS High-Speed-Data Services	83
7.2.2.4	FWAN PCS Data Traffic Channel (DTch) Definition	84
7.2.2.5	High-Speed Data Medium Access Control	84

7.3 Network Synchronization	85
-----------------------------------	----

Chapter 8 Parts List/Tune Up Information

8.1 Parts List	88
8.2 Tuning Procedures	106
8.3 Limiting Base Station RF Power Output	106
8.3.1 Applicable FCC Rules	106
8.3.2 Overview of the FWAN Linear Power Amplifier (LPA)	106

Chapter 9 RF Exposure Information

9.1 RF Human Exposure	108
9.1.1 Applicable FCC Rules	108
9.1.2 FWAN PCS Test Configuration	108

Chapter 10 Schematics

10.1 Subband Management Processor (SMP) Circuit Pack Schematics ..	110
10.2 Network Interface Controller (NIC) Circuit Pack Schematics	148
10.3 Base Control Processor (BCP) Circuit Pack Schematics	200
10.4 Waveform Processor (WP) Circuit Pack Schematics	282
10.5 Subband Controller (SBC) Circuit Pack Schematics	394
10.6 Transceiver (XCVR) and RF Subsystem Circuit Pack Schematics ..	503
10.6.1 Transceiver	503
10.6.2 Receiver	511
10.7 GPS and Synchronization Block (GPS/SYNC) Circuit Pack Schematics ..	532

Chapter 11 Test Reports

11.1 Test Methodology	542
11.1.1 Introduction	542
11.1.2 Base Station Frequency Stability vs. Temperature	542
11.1.2.1 Applicable FCC Rules Parts	542
11.1.2.2 Overview	542
11.1.2.3 Test Methodology	543
11.1.3 Base Station Frequency Stability vs. Input Voltage	544
11.1.3.1 Applicable FCC Rules Parts	544
11.1.3.2 Overview	545
11.1.3.3 Test Methodology	545

11.1.4	Base Station Occupied Bandwidth	546
11.1.4.1	Applicable FCC Rule Parts	546
11.1.4.2	Overview	546
11.1.4.3	Test Methodology	547
11.1.5	Modulation Characterization	549
11.1.5.1	Applicable FCC Rules	549
11.1.5.2	Overview	549
11.1.5.3	Test Methodology	551
11.1.6	RF Output Power	553
11.1.6.1	Applicable FCC Rules	553
11.1.6.2	Overview	553
11.1.6.3	Test Methodology	554
11.1.7	Spurious Emissions at the Antenna Terminal	555
11.1.7.1	Applicable FCC Rules	555
11.1.7.2	Overview	556
11.1.7.3	Test Methodology	557
11.1.8	Radiated Emissions	559
11.1.8.1	Applicable FCC Rule	559
11.1.8.2	Overview	559
11.1.8.3	Test Methodology	560
11.1.8.4	Equipment Settings for 30 - 1000 MHz Band	561
11.1.8.5	Measurement Parameters for 30 - 1000 MHz Band	561
11.1.8.6	Antenna Factors for 30 - 1000 MHz Band	562
11.1.8.7	Cable Factors	564
11.1.8.8	Equipment Settings for 1000 - 3500 MHz Band	565
11.1.8.9	Measurement Parameters for 1000 - 3500 MHz Band	566
11.1.8.10	Antenna Factors for 1000 - 3500 MHz Band	567
11.2	RF Characterization Test Results	568
11.2.1	Test Equipment List	568
11.2.2	Base Station RF Frequency Stability vs. Temperature	568
11.2.2.1	Results Summary	568
11.2.3	Base Station Frequency Stability vs. Input Voltage	570
11.2.3.1	Results Summary	570
11.2.4	Base Station Occupied Bandwidth	573
11.2.4.1	Applicable FCC Rule Parts	573
11.2.4.2	Test Configuration	574
11.2.4.3	Test Summary	574
11.2.5	Modulation Characterization	575
11.2.5.1	Applicable FCC Rules	575
11.2.5.2	Test Configuration	575

11.2.5.3	Results Summary	575
11.2.6	RF Output Power	585
11.2.6.1	Applicable FCC Rules	585
11.2.6.2	Test Configuration	585
11.2.6.3	Results Summary	585
11.2.7	Spurious Emissions at the Antenna Terminal	587
11.2.7.1	Applicable FCC Rules	587
11.2.7.2	Test Configuration	588
11.2.7.3	Results Summary	588
11.3	Electromagnetic Compatibility Test Results	596
11.3.1	Introduction	596
11.3.2	Equipment List	596
11.3.3	List of Equipment Under Test	597
11.3.4	EMC Test Results	598
11.3.4.1	Radiated Emissions	598
11.3.4.2	Test Results	599
11.3.4.3	Radiated to Conducted Spurious Emissions	609

Chapter 12 Test Setup Photos

12.1	Radiated Emissions Test Setup	612
12.2	Parts Comprising Equipment Under Test (EUT)	614
12.2.1	List of Equipment Under Test	614
12.3	EUT Test Configuration Photos	615
12.4	Testing Facility and Location	617

Chapter 13 Users Manuals

List of Figures

Figure 2.1	B1.8 RF PCS Clock Block Diagram	20
Figure 2.2	1.544MHz TTL Square -- Backplane	21
Figure 2.3	6.66Hz/16.384MHz TTL Square -- Backplane	21
Figure 2.4	10MHz Sine Wave -- Backplane	22
Figure 2.5	32MHz/2.666KHz/250KHz LVDS Square -- Backplane	22
Figure 2.6	3.2MHz/32MHz TTL Square -- Backplane	23
Figure 2.7	Redundant 3.2MHz/32MHz TTL Square -- Backplane	23
Figure 4.1	Front Corner View of the FWAN PCS Base Station	34
Figure 4.2	Open Doors Front View of FWAN PCS Base Station	35
Figure 4.3	Open Panels Back View of the FWAN PCS Base Station	36
Figure 4.4	Back View of the FWAN PCS Base Station	37
Figure 5.1	Sample FCC ID Label	40
Figure 5.2	FCC Compliance Label—Possible Exterior Location, RF Cabinet Back ..	41
Figure 6.1	Overview of the FWAN PCS B1.8 Base Station Digital Cabinet	44
Figure 6.2	View of the Lowermost Shelf and Under-Space of the FWAN PCS B1.8 Base Station Digital Cabinet	45
Figure 6.3	Network Interface Circuit Pack PCA	46
Figure 6.4	Bottom of the Network Interface Circuit Pack PCA	47
Figure 6.5	WP PCA	48
Figure 6.6	Bottom of WP PCA	49
Figure 6.7	BCP PCA	50
Figure 6.8	Bottom of BCP PCA	51
Figure 6.9	SBC PCA	52
Figure 6.10	Bottom of SBC PCA	53
Figure 6.11	SMP PCA	54
Figure 6.12	Bottom of SMP PCA	55
Figure 6.13	Overview of the FWAN PCS B1.8 Base Station	56
Figure 6.14	View of the Lower Portion of the FWAN PCS B1.8 Base Station Cabinet ..	57

Figure 6.15	Transceiver Module — Right Side View	58
Figure 6.16	Transceiver Module - Left Side View	59
Figure 6.17	Transceiver	60
Figure 6.18	Transceiver Bottom	61
Figure 6.19	Power Supply	62
Figure 6.20	Power Supply Back	62
Figure 6.21	Duplexer Top View	63
Figure 6.22	Duplexer Side View	64
Figure 7.1	FWAN PCS Telephony Architecture	67
Figure 7.2	FWAN PCS OSI Model	69
Figure 7.3	FWAN PCS Airlink Protocol Profile	70
Figure 7.4	FWAN PCS Telephony Processing	71
Figure 7.5	FWAN PCS HSD Architecture	72
Figure 7.6	HSD Logical Channel Relationships	73
Figure 7.7	FWAN PCS OSI Model	74
Figure 7.8	NAC Logical Channel Timing Relationships	78
Figure 7.9	Illustration of OFDM Burst Parameters	79
Figure 7.10	OFDM Time-Domain Waveform Generation	80
Figure 7.11	FWAN PCS Subband Allocation	80
Figure 7.12	FWAN PCS FDMA Structure	81
Figure 7.13	FWAN PCS TDMA Framing Structure	81
Figure 7.14	FWAN PCS Datalink Layer Resource Matrix	83
Figure 7.15	RSP Definitions	85
Figure 11.1	Base Station Synchronization Card Frequency Stability vs. Temperature Test Configuration.	544
Figure 11.2	Base Station Synchronization Card Frequency Stability vs. Input Voltage Test Configuration	546
Figure 11.3	Time Keyed RSP Structure	547
Figure 11.4	Base Station Occupied Bandwidth Test Configuration	548
Figure 11.5	Modulation Characterization Test Configuration	551
Figure 11.6	Base Station Output Power Test Configuration.	555
Figure 11.7	Base Station Conducted Power Spectral Mask	557
Figure 11.8	Spectral Purity Test Configuration	559
Figure 11.9	Test Equipment Configuration	560
Figure 11.10	Base Station Synchronization Card Frequency Stability vs. Temperature, GPS Locked Mode	569
Figure 11.11	Base Station Synchronization Card Frequency Stability vs. Temperature, GPS Holdover Mode	569
Figure 11.12	Base Station Synchronization Card Frequency Stability vs. Temperature, GPS	

Free-Run Mode	570
Figure 11.13 Base Station Synchronization Card Frequency Stability vs. Input Voltage, GPS Locked Mode	571
Figure 11.14 Base Station Synchronization Card Frequency Stability vs. Input Voltage, GPS Holdover Mode	572
Figure 11.15 Base Station Synchronization Card Frequency Stability vs. Input Voltage, GPS Free-Run Mode	573
Figure 11.16 Base Station 99% Occupied Bandwidth While Transmitting Simulcast Remote Synchronization Pilots	574
Figure 11.17 Voice Channel Power vs. Frequency, 99.0% Occupied BW, and Time-Domain Average Burst Power	576
Figure 11.18 Voice Channel CCDF.	576
Figure 11.19 High-Speed Data Traffic Channel Power vs. Frequency, 99.0% Occupied BW, and Time-Domain Average Burst Power.	577
Figure 11.20 High-Speed Data Traffic Channel CCDF	578
Figure 11.21 High Speed Data Control Channel Power vs. Frequency, 99.0% Occupied Bandwidth, and Time-Domain Average Power	579
Figure 11.22 High Speed Data Control Channel CCDF.	579
Figure 11.23 NAC Channel Power vs. Frequency, 99.0% Occupied BW, and Time-Domain Average Power.	580
Figure 11.24 NAC Channel CCDF	581
Figure 11.25 Time-Keyed Remote Synchronization Pilots Power vs. Frequency, 99.0% Occupied Bandwidth, and Time-Domain Average Burst Power	582
Figure 11.26 Time-Keyed Remote Synchronization Pilots CCDF	582
Figure 11.27 Simulcast Remote Synchronization Pilots Power vs. Frequency, 99.0% Occupied Bandwidth, and Time-Domain Average Burst Power.	583
Figure 11.28 Simulcast Remote Synchronization Pilots CCDF.	584
Figure 11.29 Time-Domain Power Envelope, Average Power.	586
Figure 11.30 Time-Domain Power Envelope, Peak Power at < 99.0% Occurrence. . .	586
Figure 11.31 Time-Domain Power Envelope, Peak/Average Ratio at < 99.0% Occurrence	587
Figure 11.32 1MHz Band-Power Between 1945.5 and 1946.5 MHz.	589
Figure 11.33 Maximum Lower Guard Band Spurious Power, Measured in a 1MHz Resolution BW. Marker Indicates Edge of Subband	589
Figure 11.34 Spectral Purity from 1937MHz to 1944MHz, with Spurious Power Measured in a 1MHz Band-Power, Marker Centered on 1938.8MHz Denoting Spurious Emissions.	590
Figure 11.35 Spectral Purity from 1937MHz to 1944MHz, with Spurious Power Measured in a 1MHz Band-Power, Marker Centered on 1937.6MHz Denoting Spurious Emissions	590
Figure 11.36 Spectral Purity from 1930MHz to 1937MHz, with Spurious Power Measured in a 1MHz Band-Power.	591

Figure 11.37	Spectral Purity from 1924MHz to 1931MHz, with Spurious Power Measured in a 1MHz Band-Power, Marker Centered on 1930MHz Denoting Spurious Emissions	591
Figure 11.38	1MHz Band-Power Between 1948.5 and 1949.5MHz.	592
Figure 11.39	Maximum Upper Guard Band Spurious Power with Band Power Markers Centered on 1950.5 MHz Indicating Guard Band	592
Figure 11.40	Spectral Purity from 1951MHz to 1958MHz, with Spurious Power Measured in a 1MHz Band-Power, Marker Centered on 1952.2 MHz Denoting Spurious Emissions.	593
Figure 11.41	Spectral Purity from 1951MHz to 1958MHz, with Spurious Power Measured in a 1MHz Band-Power, Marker Centered on 1955 MHz Denoting Spurious Emissions	593
Figure 11.42	Spectral Purity from 1958MHz to 1965MHz, with Spurious Power Measured in a 1MHz Band-Power, Marker Centered on 1961.8 MHz Denoting Spurious Emissions	594
Figure 11.43	Three-Meter Chamber Ambient	598
Figure 11.44	30-1000MHz, 15 Calls on Single TDMA Slot.	600
Figure 11.45	1000MHz-35000MHz Emissions Scan, 15 Calls on Single TDMA Slot ...	601
Figure 11.46	3.5GHz-18.0GHz @1m Antenna Height Emissions Scan, Vertical Polarization, 15 Calls Same TDMA	602
Figure 11.47	3.5 GHz-18.0 GHz @1m Antenna Height Emissions Scan, Horizontal Polarization, 15 Calls Same TDMA	603
Figure 11.48	3.5 GHz- 18.0 GHz @1.5m Antenna Height Emissions Scan, Vertical Polarization, 15 Calls, Same TDMA Slot	604
Figure 11.49	3.5 GHz-18.0 GHz @ 1.5m Antenna Height Emissions Scan, Horizontal Polarization, 15 Calls Same TDMA	605
Figure 11.50	18 GHz-26.5 GHz @ 1 m Antenna Height Emissions Scan, Vertical Polarization, 15 Calls Same TDMA	606
Figure 11.51	18 GHz-26.5 GHz @ 1 m Antenna Height Emissions Scan, Horizontal Polarization, 15 Calls Same TDMA	607
Figure 11.52	18 GHz-26.5 GHz @ 1.5 m Antenna Height Emissions Scan, Vertical Polarization, 15 Calls Same TDMA	608
Figure 11.53	18 GHz-26.5 GHz @ 1.5 m Antenna Height Emissions Scan, Horizontal Polarization, 15 Calls Same TDMA	609
Figure 12.1	Radiated Emissions Test Setup	613
Figure 12.2	Base, Configuration, Doors Open—Front View	615
Figure 12.3	Base Configuration, Doors Closed—Side View	615
Figure 12.4	Base Configuration, Doors Closed—Rear Side View	616
Figure 12.5	Base Configuration, Rear Panels Removed—Rear View	616
Figure 12.6	3-Meter Shield Room Control Room	617
Figure 12.7	3-Meter Control Room	618
Figure 12.8	3-Meter Control Chamber Access Panel Penetration.	619

Figure 12.9 T1 Fiber Optic Lines	620
Figure 12.10 RU Test Rack	621
Figure 12.11 Setup of the 16 Remote Units	622
Figure 12.12 HP 84300A E62 Microwave Intentional Radiator System	623
Figure 12.13 Radiated Emission 30MHz - 1GHz Test Setup	624

List of Tables

Table 2.1	Digital Components	23
Table 2.2	RF Components	24
Table 2.3	Power Supply Components	24
Table 2.4	Clock Frequencies	25
Table 7.1	FWAN PCS Reference Architecture - Interface Definitions	67
Table 7.2	NAC Logical Channel Summary	76
Table 7.3	Basic FWAN PCS OFDM Parameters	82
Table 7.4	Basic Data Service Allocation	83
Table 8.1	List of FWAN PCS Base Station Active Components	88
Table 11.1	PWAN Interface Definitions	542
Table 11.2	Hewlett-Packard Type 89451A Radio Personality Configuration Parameters (Time Capture Mode)	548
Table 11.3	Hewlett-Packard 89441A Modulation Characterization Test Parameters (Real-Time Measurement Mode)	549
Table 11.4	Hewlett-Packard 89441A Modulation Characterization Test Parameters (Time Capture Mode)	550
Table 11.5	Hewlett-Packard 89441A RF Power Test Parameters	553
Table 11.6	Hewlett-Packard 89441A Spectral Purity Test Configuration Parameters	556
Table 11.7	Antenna Correction Factors — 30 - 1000MHz	562
Table 11.8	Cable Correction Factors	564
Table 11.9	Antenna Correction Factors — 1000 - 6000 MHz	567
Table 11.10	Test Equipment	568
Table 11.11	Base Station Synchronization Card Frequency Stability vs. Temperature Summary	570
Table 11.12	Base Station Synchronization Card Frequency Stability vs. Input Voltage Summary	573
Table 11.13	Occupied Bandwidth Test Result Summary	574
Table 11.14	Logical Channel Characterization Test Results Summary	584
Table 11.15	RF Output Power Characteristics	587

Table 11.16	Base Station In-Band and Out-Of-Band Power Summary	594
Table 11.17	Emissions Test Equipment	596
Table 11.18	Network Components	597
Table 11.19	FCC Radiated Emission Limits for Class A Devices at Three Meters	598
Table 12.1	EUT List	614


Chapter 1 Attestation Statements

AT&T Wireless Group
Fixed Wireless Services
PO Box 97059
Redmond, WA 98073-9759
425-702-2500

Federal Communications Commission
Attn.: Product Type Approval Department
7435 Oakland Mills Rd.
Columbia, MD 21046

To FCC Examiner:

The AT&T Wireless Services Base Station (B1.8) PCS has been tested in accordance with the requirements contained in the appropriate Commission regulations. To the best of our knowledge, these tests were performed using measurement procedures consistent with industry or Commission standards and demonstrate that the equipment complies with the appropriate standards. Each unit manufactured, imported or marketed as defined in the Commission's regulations, will conform to the samples(s) tested within the variation that can be expected due to the quantity produced and testing on a statistical basis. The test results and conclusions that accompany the Type Acceptance Application and test report are certified to be true and correct, having been taken personally or under the supervision of the undersigned individuals.




Date: 12/17/01


Mitchell Phillipi
EMC Engineer
AT&T Wireless Services


Keith Peavler
Manager, Hardware Platforms
AT&T Wireless Services

Date: 12/17/01


Arun Naidu
Director, Hardware Development
AT&T Wireless Services

Date: 12/17/01


John Saw
Vice President, Engineering and Chief Engineer
AT&T Wireless Services

Date: 12/19/01