



**FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of**

**Mad Catz, Inc.**

**Mad Catz F.R.E.Q.9 Wireless Headset**

**Model Number: 43401R**

**FCC ID: P25D2434011101AR**

Prepared for : Mad Catz, Inc.  
7480 Mission Valley Road, Suite 101, San Diego,  
California, 92108, USA

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F14168  
Date of Test : Feb.18~Mar.19, 2014  
Date of Report : Sep.24, 2014

**TABLE OF CONTENTS**

| <u>Description</u>  | <u>Page</u> |
|---|-------------|
| <b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>                | <b>1-1</b>  |
| 1.1. Description of Standards and Results.....                  | 1-1         |
| <b>2. GENERAL INFORMATION.....</b>                              | <b>2-1</b>  |
| 2.1. Description of Device (EUT).....                           | 2-1         |
| 2.2. Tested Supporting System Details .....                     | 2-2         |
| 2.3. Block Diagram of Test Setup.....                           | 2-2         |
| 2.4. Test information .....                                     | 2-2         |
| 2.5. Test Facility.....   | 2-3         |
| 2.6. Measurement Uncertainty (95% confidence levels, k=2) ..... | 2-3         |
| <b>3. POWER LINE CONDUCTED EMISSION MEASUREMENT.....</b>        | <b>3-1</b>  |
| 3.1. Test Equipment .....                                       | 3-1         |
| 3.2. Block Diagram of Test Setup.....                           | 3-1         |
| 3.3. Power Line Conducted Emission Test Limits.....             | 3-1         |
| 3.4. Configuration of EUT on Test .....                         | 3-1         |
| 3.5. Operating Condition of EUT.....                            | 3-2         |
| 3.6. Test Procedure.....  | 3-2         |
| 3.7. Conducted Emission at Mains Terminals Test Results .....   | 3-2         |
| <b>4. RADIATED EMISSION MEASUREMENT .....</b>                   | <b>4-1</b>  |
| 4.1. Test Equipment .....                                       | 4-1         |
| 4.2. Block Diagram of Test Setup.....                           | 4-2         |
| 4.3. Radiated Emission Limit Standard: FCC 15.247 .....         | 4-3         |
| 4.4. EUT Configuration on Test.....                             | 4-3         |
| 4.5. Operating Condition of EUT.....                            | 4-3         |
| 4.6. Test Procedure.....  | 4-3         |
| 4.7. Radiated Emission Test Results .....                       | 4-4         |
| <b>5. CONDUCTED SPURIOUS EMISSIONS .....</b>                    | <b>5-1</b>  |
| 5.1. Test Equipment .....                                       | 5-1         |
| 5.2. Limit.....   | 5-1         |
| 5.3. Test Procedure.....  | 5-1         |
| 5.4. Test result.....   | 5-1         |
| <b>6. CARRIER FREQUENCY SEPARATION TEST .....</b>               | <b>6-1</b>  |
| 6.1. Test Equipment .....                                       | 6-1         |
| 6.2. Limit.....   | 6-1         |
| 6.3. Test Results .....   | 6-1         |
| <b>7. 20 DB BANDWIDTH TEST .....</b>                            | <b>7-1</b>  |
| 7.1. Test Equipment .....                                       | 7-1         |
| 7.2. Limit.....   | 7-1         |
| 7.3. Test Results .....   | 7-1         |
| <b>8. NUMBER OF HOPPING FREQUENCY TEST.....</b>                 | <b>8-1</b>  |
| 8.1. Test Equipment .....                                       | 8-1         |
| 8.2. Limit.....   | 8-1         |
| 8.3. Test Results .....   | 8-1         |
| <b>9. DWELL TIME.....</b>                                       | <b>9-1</b>  |
| 9.1. Test Equipment .....                                       | 9-1         |

|            |  |             |
|------------|--|-------------|
| 9.2.       | Limit.....   | 9-1         |
| 9.3.       | Test Results .....                                 | 9-1         |
| <b>10.</b> | <b>MAXIMUM PEAK OUTPUT POWER TEST.....</b>         | <b>10-1</b> |
| 10.1.      | Test Equipment .....                               | 10-1        |
| 10.2.      | Limit.....   | 10-1        |
| 10.3.      | Test Procedure.....                                | 10-1        |
| 10.4.      | Test Results .....                                 | 10-2        |
| <b>11.</b> | <b>BAND EDGE COMPLIANCE TEST .....</b>             | <b>11-1</b> |
| 11.1.      | Test Equipment .....                               | 11-1        |
| 11.2.      | Limit.....   | 11-1        |
| 11.3.      | Test Produce .....                                 | 11-1        |
| 11.4.      | Test Results .....                                 | 11-1        |
| <b>12.</b> | <b>DEVIATION TO TEST SPECIFICATIONS .....</b>      | <b>12-1</b> |
| <b>13.</b> | <b>PHOTOGRAPH OF TEST.....</b>                     | <b>13-1</b> |
| 13.1.      | Photos of Power Line Conducted Emission Test ..... | 13-1        |
| 13.2.      | Photos of Radiated Emission Test.....              | 13-2        |
| <b>14.</b> | <b>PHOTOS OF THE EUT .....</b>                     | <b>14-1</b> |





FCC ID:P25D2434011101AR

TEST REPORT CERTIFICATION

Applicant : Mad Catz, Inc.  
 Manufacturer : Mad Catz, Inc.  
 EUT Description : Mad Catz F.R.E.Q.9 Wireless Headset  
 FCC ID : P25D2434011101AR  
 (A) MODEL NO. : 43401R  
 (B) SERIAL NO. : N/A  
 (C)TEST VOLTAGE : DC 5V From PC Input AC 120V/60Hz

Tested for comply with:  
 FCC Rules and Regulations Part 15 Subpart C: 2013  
 Test procedure used:  
 ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Feb.18~Mar.19, 2014 Report of date: Sep.24, 2014

Prepared by : Lisa Liang Reviewed by : [Signature]  
 Lisa Liang / Assistant Sunny Lu / Assistant Manager

信華科技(深圳)有限公司  
 Audix Technology (Shenzhen) Co., Ltd.  
 EMC 部門報告專用章  
 Stamp only for EMC Dept. Report  
 Signature: David Jin 9.24

Approved & Authorized Signer : David Jin / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

| EMISSION                                   |  |         |
|--|--|---------|
| Description of Test Item                   | Standard   | Results |
| Power Line Conducted Emission Test         | FCC Part 15: 15.207<br>ANSI C63.10 :2009<br>ANSI C63.4 :2003                           | PASS    |
| Radiated Emission Test                     | FCC Part 15: 15.209<br>FCC Part 15: 15.247(d)<br>ANSI C63.10 :2009<br>ANSI C63.4 :2003 | PASS    |
| Conducted Spurious Emissions               | FCC Part 15: 15.247(a)(1)<br>ANSI C63.10 :2009   | PASS    |
| Carrier Frequency Separation Test          | FCC Part 15: 15.247(a)(1)<br>ANSI C63.10 :2009   | PASS    |
| 20dB Bandwidth Test                        | FCC Part 15: 15.215<br>ANSI C63.10 :2009   | PASS    |
| Number Of Hopping Frequency Test           | FCC Part 15: 15.247(a)(1)(iii)<br>ANSI C63.10 :2009                                    | PASS    |
| Dwell Time Test                            | FCC Part 15: 15.247(a)(1)(iii)<br>ANSI C63.10 :2009                                    | PASS    |
| Maximum Peak Output Power Test             | FCC Part 15: 15.247(b)(1)\<br>ANSI C63.10 :2009  | PASS    |
| Band Edge Compliance Test                  | FCC Part 15: 15.247(d)<br>ANSI C63.10 :2009  | PASS    |
| N/A is an abbreviation for Not Applicable. |  |         |

## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)


|  |   |
|--|---|
| Product Name                           | : Mad Catz F.R.E.Q.9 Wireless Headset   |
| Model Number                           | : 43401R  |
| FCC ID                                 | : P25D2434011101AR  |
| Radio                                  | : Buletooth3.0+EDR  |
| Operation frequency                    | : 2402MHz-2480MHz   |
| Antenna                                | : Integrated PCB Antenna, 0.251711dBi PK gain   |
| Modulation                             | : GFSK, $\pi/4$ DQPSK, 8-DPSK   |
| Applicant                              | : Mad Catz, Inc.<br>7480 Mission Valley Road, Suite 101, San Diego,<br>California, 92108, USA |
| Manufacturer                           | : Mad Catz, Inc.<br>7480 Mission Valley Road, Suite 101, San Diego,<br>California, 92108, USA |
| USB Cable                              | : Unshielded, Detachable, 1.0m  |
| Optical Cable                          | : Unshielded, Detachable, 1.0m  |
| Audio Cable                            | : Unshielded, Detachable, 1.0m  |
| Xbox 360 Digital Optical Adapter Cable | : Unshielded, Detachable, 23cm  |
| 3.5mm to Dual Phone Lead Cable         | : Unshielded, Detachable, 1.0m  |
| Micro USB Charge Cable                 | : Unshielded, Detachable, 1.0m  |
| Xbox 360 3.5mm to 2.5mm Chat Lead      | : Unshielded, Detachable, 1.0m  |
| Date of Test                           | : Feb.18~Mar.19, 2014   |
| Date of Receipt                        | : Feb.17, 2014  |
| Sample Type                            | : Prototype production  |



### 2.2. Tested Supporting System Details

| No. | Description | ACS No.  | Manufacturer | Model    | Serial Number | Approved type  |
|-----|-------------|--|--------------|----------|---------------|--|
| 1.  | Notebook    | N/A  | DELL         | PP09S    | N/A           | <input checked="" type="checkbox"/> FCC DoC<br><input checked="" type="checkbox"/> BSMI ID: R41108 |
|     |             | Power Cord: Unshielded, Detachable, 1.8m<br>Power Adapter: Manufacturer: DELL, M/N: LA65NS1-00<br>Cable: Unshielded, Detachable, 4.0m(Bond one ferrite core) |              |          |               |  |
| 2.  | DVD Player  | ACS-EMC-DVD01  | DENON        | DVD-3910 | 4098400342E   | <input type="checkbox"/> FCC ID<br><input type="checkbox"/> BSMI ID                                |
|     |             | Data Cable: Shielded, Detachable, 1.8m<br>Power Cord: Unshielded, Detachable, 1.8m   |              |          |               |  |

### 2.3. Block Diagram of Test Setup



**(EUT: Mad Catz F.R.E.Q.9 Wireless Headset)**

### 2.4. Test information

The test software “bluesuite.exe” was used to control EUT work in Continuous TX mode, and select test channel.

| Tested mode, channel, and data rate information |                  |              |                 |
|---|------------------|--------------|-----------------|
| Mode  | data rate (Mbps) | Channel      | Frequency (MHz) |
| Tx Mode<br>GFSK<br>modulation                   | 1                | Low :CH 0    | 2402            |
|   | 1                | Middle: CH39 | 2441            |
|   | 1                | High: CH78   | 2480            |
| Tx Mode<br>8-DPSK<br>modulation                 | 3                | Low :CH 0    | 2402            |
|   | 3                | Middle: CH39 | 2441            |
|   | 3                | High: CH78   | 2480            |

Note:  $\pi/4$ DQPSK modulation is same type modulation with 8-DPSK, and according exploratory test, 8-DPSK will have worse emissions, so the final test were only performed with GFSK and 8-DPSK modulation.

**2.5. Test Facility**

Site Description

Name of Firm : Audix Technology (Shenzhen) Co., Ltd.  
 No. 6, Ke Feng Rd., 52 Block, Shenzhen  
 Science & Industrial Park, Nantou,  
 Shenzhen, Guangdong, China

3m Anechoic Chamber : Certificated by FCC, USA  
 Registration Number: 90454  
 Valid Date: Feb.22, 2015

3m & 10m Anechoic Chamber : Certificated by FCC, USA  
 Registration Number: 794232  
 Valid Date: Oct.31, 2015

EMC Lab. : Certificated by Industry Canada  
 Registration Number: IC 5183A-1  
 Valid Date: May.14, 2017

Certificated by DAkkS, Germany  
 Registration No: D-PL-12151-01-00  
 Valid Date: Dec.15, 2016

Accredited by NVLAP, USA  
 NVLAP Code: 200372-0  
 Valid Date: Mar.31, 2015

**2.6. Measurement Uncertainty (95% confidence levels, k=2)**

| Test Item  | Uncertainty                     |
|--|---------------------------------|
| Uncertainty for Conduction emission test in No. 1 Conduction       | 3.10 dB(150KHz to 30MHz)        |
| Uncertainty for Radiation Emission test in 3m chamber              | 3.22 dB(30~200MHz, Polarize: H) |
|  | 3.23 dB(30~200MHz, Polarize: V) |
|  | 3.49 dB(200M~1GHz, Polarize: H) |
|  | 3.39 dB(200M~1GHz, Polarize: V) |
| Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz) | 4.97dB (1~6GHz, Distance: 3m)   |
|  | 4.99dB (6~18GHz, Distance: 3m)  |
| Uncertainty for Radiated Spurious Emission test in RF chamber      | 3.57 dB                         |
| Uncertainty for Conduction Spurious emission test                  | 2.00 dB                         |
| Uncertainty for Output power test                                  | 0.73 dB                         |
| Uncertainty for Bandwidth test                                     | 83 kHz                          |
| Uncertainty for DC power test                                      | 0.038 %                         |
| Uncertainty for test site temperature and humidity                 | 0.6°C                           |
|  | 3%                              |




### 3. POWER LINE CONDUCTED EMISSION MEASUREMENT

#### 3.1. Test Equipment

| Item | Equipment         | Manufacturer    | Model No. | Serial No.    | Last Cal.  | Cal. Interval |
|------|-------------------|-----------------|-----------|---------------|------------|---------------|
| 1.   | 1# Shielding Room | AUDIX           | N/A       | N/A           | Apr.18,13  | 1 Year        |
| 2.   | Test Receiver     | Rohde & Schwarz | ESHS10    | 838693/001    | Oct.31, 13 | 1 Year        |
| 3.   | L.I.S.N.#1        | Rohde & Schwarz | ESH2-Z5   | 100429        | Jan.22, 14 | 1 Year        |
| 4.   | L.I.S.N.#3        | Kyoritsu        | KNW-242C  | 8-1920-1      | May.08, 13 | 1 Year        |
| 5.   | Terminator        | Hubersuhner     | 50Ω       | No. 1         | May.08, 13 | 1 Year        |
| 6.   | Terminator        | Hubersuhner     | 50Ω       | No. 2         | May.08, 13 | 1 Year        |
| 7.   | RF Cable          | Hubersuhner     | RG58      | 0100.6954.20# | Jan.22, 14 | 1 Year        |
| 8.   | Coaxial Switch    | Anritsu         | MP59B     | M50564        | May.08, 13 | 1 Year        |
| 9.   | Pulse Limiter     | Rohde & Schwarz | ESH3-Z2   | 101838        | Jan.22, 14 | 1 Year        |
| 10.  | Oscilloscope      | Tektronix       | TDS3052B  | B026036       | May.16, 13 | 1 Year        |

#### 3.2. Block Diagram of Test Setup



▨ :50Ω Terminator

#### 3.3. Power Line Conducted Emission Test Limits

| Frequency       | Maximum RF Line Voltage    |                         |
|-----------------|----------------------------|-------------------------|
|                 | Quasi-Peak Level<br>dB(μV) | Average Level<br>dB(μV) |
| 150kHz ~ 500kHz | 66 ~ 56*                   | 56 ~ 46*                |
| 500kHz ~ 5MHz   | 56                         | 46                      |
| 5MHz ~ 30MHz    | 60                         | 50                      |

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

#### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

##### 3.4.1. Mad Catz F.R.E.Q.9 Wireless Headset (EUT)

Model Number : 43401R

Serial Number : N/A

### 3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT and simulator as shown as Section 3.2.
- 3.5.2. Turn on the power of all equipment.
- 3.5.3. Let the EUT work in test mode (TX Mode) and measure it.

### 3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4-2009 on conducted Emission test.

The bandwidth of test receiver (R&S TEST RECEIVER ESHS10) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked. The test result are reported on Section 3.7.

### 3.7. Conducted Emission at Mains Terminals Test Results


**PASS.** (All emissions not reported below are too low against the prescribed limits.)



Site no :1#conduction Data No :4  
 Dis./Ant. :\*\* 2013 ESH2-25 LINE  
 Limit :FCC PART 15 C  
 Env./Ins. :25.5\*C/53% Engineer :Eric  
 EUT :Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating :DC 5V From PC  
 Test Mode :Tx Mode  
 M/N:43401R

| No | Freq (MHz) | ISN Factor (dB) | Cable Loss (dB) | Reading (dBUV) | Emission Level (dBUV) | Limits (dBUV) | Margin (dB) | Remark |
|----|------------|-----------------|-----------------|----------------|-----------------------|---------------|-------------|--------|
| 1  | 0.28630    | 0.15            | 0.01            | 40.18          | 40.34                 | 60.63         | 20.29       | QP     |
| 2  | 0.49673    | 0.16            | 0.02            | 35.17          | 35.35                 | 56.05         | 20.70       | QP     |
| 3  | 0.89441    | 0.18            | 0.03            | 32.33          | 32.54                 | 56.00         | 23.46       | QP     |
| 4  | 2.794      | 0.25            | 0.05            | 31.12          | 31.42                 | 56.00         | 24.58       | QP     |
| 5  | 4.622      | 0.31            | 0.07            | 32.10          | 32.48                 | 56.00         | 23.52       | QP     |
| 6  | 5.805      | 0.36            | 0.07            | 35.01          | 35.44                 | 60.00         | 24.56       | QP     |

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Site no :1#conduction Data No :3  
 Dis./Ant. \*\*: 2013 ESH2-Z5 NEUTRAL  
 Limit :FCC PART 15 C  
 Env./Ins. :25.5\*C/53% Engineer :Eric  
 EUT :Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating :DC 5V From PC  
 Test Mode :Tx Mode  
 M/N:43401R

| No | Freq (MHz) | ISN Factor (dB) | Cable Loss (dB) | Reading (dBuV) | Emission Level (dBuV) | Limits (dBuV) | Margin (dB) | Remark |
|----|------------|-----------------|-----------------|----------------|-----------------------|---------------|-------------|--------|
| 1  | 0.29554    | 0.20            | 0.01            | 38.81          | 39.02                 | 60.37         | 21.35       | QP     |
| 2  | 0.49150    | 0.23            | 0.02            | 32.15          | 32.40                 | 56.14         | 23.74       | QP     |
| 3  | 0.91357    | 0.26            | 0.03            | 32.47          | 32.76                 | 56.00         | 23.24       | QP     |
| 4  | 1.487      | 0.26            | 0.03            | 30.68          | 30.97                 | 56.00         | 25.03       | QP     |
| 5  | 2.839      | 0.28            | 0.05            | 32.50          | 32.83                 | 56.00         | 23.17       | QP     |
| 6  | 3.964      | 0.31            | 0.06            | 35.03          | 35.40                 | 56.00         | 20.60       | QP     |

Remarks: 1.Emission Level=ISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION MEASUREMENT

### 4.1. Test Equipment

Frequency rang: 30~1000MHz

| Item | Equipment      | Manufacturer    | Model No. | Serial No.         | Last Cal.  | Cal. Interval |
|------|----------------|-----------------|-----------|--------------------|------------|---------------|
| 1    | 3#Chamber      | AUDIX           | N/A       | N/A                | Nov.24, 13 | 1 Year        |
| 2    | EMI Spectrum   | Agilent         | E4407B    | MY41440292         | May.08, 13 | 1 Year        |
| 3    | Test Receiver  | Rohde & Schwarz | ESVS10    | 834468/011         | May.08, 13 | 1 Year        |
| 4    | Amplifier      | HP              | 8447D     | 2648A04738         | May.08, 13 | 1 Year        |
| 5    | Bilog Antenna  | TESEQ           | CBL6112D  | 35375              | May.30, 13 | 1 Year        |
| 6    | RF Cable       | MIYAZAKI        | CFD400-NL | 3# Chamber<br>No.1 | May.08, 13 | 1 Year        |
| 7    | Coaxial Switch | Anritsu         | MP59B     | M74389             | May.08, 13 | 1 Year        |


Frequency rang: above 1000MHz

| Item | Equipment         | Manufacturer | Model No.   | Serial No. | Last Cal.  | Cal. Interval |
|------|-------------------|--------------|-------------|------------|------------|---------------|
| 1    | Spectrum Analyzer | Agilent      | E4407B      | MY41440292 | May.08, 13 | 1 Year        |
| 2    | Horn Antenna      | EMCO         | 3115        | 9510-4580  | May.28, 13 | 1 Year        |
| 3    | Amplifier         | Agilent      | 8449B       | 3008A00863 | May.08, 13 | 1 Year        |
| 4    | RF Cable          | Hubersuhner  | SUCOFLEX106 | 77980/6    | May.08, 13 | 1 Year        |
| 5    | RF Cable          | Hubersuhner  | SUCOFLEX106 | 77977/6    | May.08, 13 | 1 Year        |
| 6    | Horn Antenna      | EMCO         | 3116        | 00060089   | Aug.28, 13 | 1 Year        |




### 4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



#### 4.3. Radiated Emission Limit Standard: FCC 15.247

| FREQUENCY<br>MHz | DISTANCE<br>Meters | FIELD STRENGTHS LIMIT   |                                   |
|------------------|--------------------|---|-----------------------------------|
|                  |                    | $\mu\text{V}/\text{m}$  | $\text{dB}(\mu\text{V})/\text{m}$ |
| 30 ~ 88          | 3                  | 100   | 40.0                              |
| 88 ~ 216         | 3                  | 150   | 43.5                              |
| 216 ~ 960        | 3                  | 200   | 46.0                              |
| 960 ~ 1000       | 3                  | 500   | 54.0                              |
| Above 1000MHz    | 3                  | 74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak)<br>54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average) |                                   |

Remark : (1) Emission level  $\text{dB}\mu\text{V} = 20 \log$  Emission level  $\mu\text{V}/\text{m}$

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
- (4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

#### 4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

##### 4.4.1. Mad Catz F.R.E.Q.9 Wireless Headset (EUT)

Model Number : 43401R  
Serial Number : N/A

#### 4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT and simulator as shown as Section 4.2.
- 4.5.2. Turned on the power of all equipment.
- 4.5.3. Let EUT work in Tx mode.

#### 4.6. Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2009 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.



#### 4.7.Radiated Emission Test Results


**PASS.**

All the emissions from 30MHz to 25GHz were comply with the 15.247 Limit.

Note: The duty cycle factor for calculate average level is 9.11dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit.

Duty cycle:  $0.4383\text{ms} / 1.247\text{ms} * 100\% = 35\%$   
 Duty cycle factor =  $20\log (1/\text{duty cycle}) = 9.11$






Note: The Dwell time less than 100ms.




Frequency: 30MHz~1GHz



Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/34% Engineer : Donjon  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power rating : DC 5V From PC  
 Test Mode : Tx Mode  
 M/N:43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 30.000      | 20.10              | 0.83            | 3.68           | 24.61                   | 40.00           | 15.39       | QP     |
| 2   | 172.590     | 10.07              | 1.69            | 15.26          | 27.02                   | 43.50           | 16.48       | QP     |
| 3   | 184.230     | 9.60               | 1.73            | 15.72          | 27.05                   | 43.50           | 16.45       | QP     |
| 4   | 382.110     | 15.94              | 2.41            | 6.49           | 24.84                   | 46.00           | 21.16       | QP     |
| 5   | 776.900     | 20.60              | 3.54            | 2.48           | 26.62                   | 46.00           | 19.38       | QP     |
| 6   | 897.180     | 21.54              | 3.92            | 5.79           | 31.25                   | 46.00           | 14.75       | QP     |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2013 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 24°C/34% Engineer : Donjon  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power rating : DC 5V From PC  
 Test Mode : Tx Mode  
 M/N:43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 34.850      | 17.09              | 0.92            | 8.84           | 26.85                   | 40.00           | 13.15       | QP     |
| 2   | 57.160      | 7.07               | 1.22            | 17.12          | 25.41                   | 40.00           | 14.59       | QP     |
| 3   | 144.460     | 11.65              | 1.58            | 14.26          | 27.49                   | 43.50           | 16.01       | QP     |
| 4   | 626.550     | 19.53              | 3.11            | 2.83           | 25.47                   | 46.00           | 20.53       | QP     |
| 5   | 776.900     | 20.60              | 3.54            | 4.52           | 28.66                   | 46.00           | 17.34       | QP     |
| 6   | 935.980     | 21.82              | 4.04            | 2.97           | 28.83                   | 46.00           | 17.17       | QP     |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency: 1GHz~18GHz

Data: 1 File: G:\2014 Report\Mad Catz\ACS2014H009.EM6 (32) Date: 2014-02-26




Site no. : 3m Chamber Data no. : 1  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : GFSK 2402MHz Tx  
M/N : 43401R



Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2402MHz Tx  
 M/N : 43401R


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2402.000    | 28.18              | 5.80            | 35.70           | 93.57          | 91.85                   | 74.00           | -17.85      | Peak   |
| 2   | 4804.000    | 32.85              | 8.56            | 35.70           | 46.18          | 51.89                   | 74.00           | 22.11       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 3  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : GFSK 2402MHz Tx  
M/N : 43401R







Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2402MHz Tx  
 M/N : 43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2402.000    | 28.18              | 5.80            | 35.70           | 90.66          | 88.94                   | 74.00           | -14.94      | Peak   |
| 2   | 4804.000    | 32.85              | 8.56            | 35.70           | 45.33          | 51.04                   | 74.00           | 22.96       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber      Data no. : 7  
Dis. / Ant. : 3m 2013 3115 (4580)      Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56%      Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : GFSK 2441MHz Tx  
M/N : 43401R




Site no. : 3m Chamber Data no. : 8  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2441MHz Tx  
 M/N : 43401R

| No. | Freq.<br>(MHz) | Ant. Cable AMP   |              |                | Emission          |                   |                    |                | Remark |
|-----|----------------|------------------|--------------|----------------|-------------------|-------------------|--------------------|----------------|--------|
|     |                | Factor<br>(dB/m) | Loss<br>(dB) | factor<br>(dB) | Reading<br>(dBuV) | Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) |        |
| 1   | 2441.000       | 28.27            | 5.86         | 35.70          | 92.65             | 91.08             | 74.00              | -17.08         | Peak   |
| 2   | 4882.000       | 32.99            | 8.64         | 35.70          | 45.70             | 51.63             | 74.00              | 22.37          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 9  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : GFSK 2441MHz Tx  
M/N : 43401R




Site no. : 3m Chamber Data no. : 10  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2441MHz Tx  
 M/N : 43401R


| No. | Freq.<br>(MHz) | Ant. Cable AMP   |              |                | Emission          |                   |                    |                | Remark |
|-----|----------------|------------------|--------------|----------------|-------------------|-------------------|--------------------|----------------|--------|
|     |                | Factor<br>(dB/m) | Loss<br>(dB) | factor<br>(dB) | Reading<br>(dBuV) | Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) |        |
| 1   | 2441.000       | 28.27            | 5.86         | 35.70          | 92.65             | 91.08             | 74.00              | -17.08         | Peak   |
| 2   | 4882.000       | 32.99            | 8.64         | 35.70          | 44.10             | 50.03             | 74.00              | 23.97          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber      Data no. : 11  
Dis. / Ant. : 3m 2013 3115 (4580)      Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56%      Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : GFSK 2480MHz Tx  
M/N : 43401R




Site no. : 3m Chamber Data no. : 12  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2480MHz Tx  
 M/N : 43401R


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2480.000    | 28.36              | 5.91            | 35.70           | 84.63          | 83.20                   | 74.00           | -9.20       | Peak   |
| 2   | 4960.000    | 33.13              | 8.72            | 35.70           | 43.85          | 50.00                   | 74.00           | 24.00       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber      Data no. : 13  
Dis. / Ant. : 3m 2013 3115 (4580)      Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56%      Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : GFSK 2480MHz Tx  
M/N : 43401R




Site no. : 3m Chamber Data no. : 14  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2480MHz Tx  
 M/N : 43401R

| No. | Freq.<br>(MHz) | Ant. Cable AMP   |              |                | Emission          |                   |                    |                | Remark |
|-----|----------------|------------------|--------------|----------------|-------------------|-------------------|--------------------|----------------|--------|
|     |                | Factor<br>(dB/m) | Loss<br>(dB) | factor<br>(dB) | Reading<br>(dBuV) | Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) |        |
| 1   | 2480.000       | 28.36            | 5.91         | 35.70          | 88.93             | 87.50             | 74.00              | -13.50         | Peak   |
| 2   | 4960.000       | 33.13            | 8.72         | 35.70          | 46.63             | 52.78             | 74.00              | 21.22          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.




Site no. : 3m Chamber      Data no. : 17  
Dis. / Ant. : 3m 2013 3115 (4580)      Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56%      Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : 8-DPSK 2402MHz Tx  
M/N : 43401R



Site no. : 3m Chamber Data no. : 18  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2402MHz Tx  
 M/N : 43401R


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2402.000    | 28.18              | 5.80            | 35.70           | 85.63          | 83.91                   | 74.00           | -9.91       | Peak   |
| 2   | 4804.000    | 32.85              | 8.56            | 35.70           | 44.64          | 50.35                   | 74.00           | 23.65       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 19  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : 8-DPSK 2402MHz Tx  
M/N : 43401R






Site no. : 3m Chamber Data no. : 20  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2402MHz Tx  
 M/N : 43401R


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2402.000    | 28.18              | 5.80            | 35.70           | 92.54          | 90.82                   | 74.00           | -16.82      | Peak   |
| 2   | 4804.000    | 32.85              | 8.56            | 35.70           | 47.86          | 53.57                   | 74.00           | 20.43       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber      Data no. : 23  
Dis. / Ant. : 3m 2013 3115 (4580)      Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56%      Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : 8-DPSK 2441MHz Tx  
M/N : 43401R







Site no. : 3m Chamber Data no. : 24  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2441MHz Tx  
 M/N : 43401R

| No. | Freq.<br>(MHz) | Ant. Cable AMP   |              |                | Emission          |                   |                    |                | Remark |
|-----|----------------|------------------|--------------|----------------|-------------------|-------------------|--------------------|----------------|--------|
|     |                | Factor<br>(dB/m) | Loss<br>(dB) | factor<br>(dB) | Reading<br>(dBuV) | Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) |        |
| 1   | 2441.000       | 28.27            | 5.86         | 35.70          | 86.52             | 84.95             | 74.00              | -10.95         | Peak   |
| 2   | 4882.000       | 32.99            | 8.64         | 35.70          | 45.17             | 51.10             | 74.00              | 22.90          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



Site no. : 3m Chamber Data no. : 25  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : 8-DPSK 2441MHz Tx  
M/N : 43401R




Site no. : 3m Chamber Data no. : 26  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2441MHz Tx  
 M/N : 43401R


| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBUV) | Emission Level (dBUV/m) | Limits (dBUV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2441.000    | 28.27              | 5.86            | 35.70           | 91.86          | 90.29                   | 74.00           | -16.29      | Peak   |
| 2   | 4882.000    | 32.99              | 8.64            | 35.70           | 48.45          | 54.38                   | 74.00           | 19.62       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

| Frequency (MHz) | Peak level (dBUV/m) | Duty cycle factor (dB) | AV level (dBUV/m) | Limit(dBUV/m) | Conclusion |
|-----------------|---------------------|------------------------|-------------------|---------------|------------|
| 4882            | 54.38               | 9.11                   | 45.27             | 54            | Pass       |



Site no. : 3m Chamber      Data no. : 27  
Dis. / Ant. : 3m 2013 3115 (4580)      Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56%      Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : 8-DPSK 2480MHz Tx  
M/N : 43401R




Site no. : 3m Chamber Data no. : 28  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2480MHz Tx  
 M/N : 43401R


| No. | Freq.<br>(MHz) | Ant. Cable AMP   |              |                | Emission          |                   |                    |                | Remark |
|-----|----------------|------------------|--------------|----------------|-------------------|-------------------|--------------------|----------------|--------|
|     |                | Factor<br>(dB/m) | Loss<br>(dB) | factor<br>(dB) | Reading<br>(dBUV) | Level<br>(dBUV/m) | Limits<br>(dBUV/m) | Margin<br>(dB) |        |
| 1   | 2480.000       | 28.36            | 5.91         | 35.70          | 84.96             | 83.53             | 74.00              | -9.53          | Peak   |
| 2   | 4960.000       | 33.13            | 8.72         | 35.70          | 46.81             | 52.96             | 74.00              | 21.04          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.





Site no. : 3m Chamber Data no. : 29  
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 24°C/56% Engineer : Leo-Li  
EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
Power Rating : DC 5V From PC  
Test Mode : 8-DPSK 2480MHz Tx  
M/N : 43401R



Site no. : 3m Chamber Data no. : 30  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2480MHz Tx  
 M/N : 43401R

| No. | Freq.<br>(MHz) | Ant. Cable AMP   |              |                | Emission          |                   |                    |                | Remark |
|-----|----------------|------------------|--------------|----------------|-------------------|-------------------|--------------------|----------------|--------|
|     |                | Factor<br>(dB/m) | Loss<br>(dB) | factor<br>(dB) | Reading<br>(dBuV) | Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) |        |
| 1   | 2480.000       | 28.36            | 5.91         | 35.70          | 82.36             | 80.93             | 74.00              | -6.93          | Peak   |
| 2   | 4960.000       | 33.13            | 8.72         | 35.70          | 44.20             | 50.35             | 74.00              | 23.65          | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading  
 -Amp Factor  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



## 5. CONDUCTED SPURIOUS EMISSIONS

### 5.1. Test Equipment

| Item | Equipment  | Manufacturer | Model No.   | Serial No. | Last Cal.  | Cal. Interval |
|------|------------|--------------|-------------|------------|------------|---------------|
| 1.   | Spectrum   | Agilent      | N9030A      | MY51380221 | Oct.31, 13 | 1Year         |
| 2.   | Attenuator | Agilent      | 8491B       | MY39262165 | May.08,13  | 1 Year        |
| 3.   | RF Cable   | Hubersuhner  | SUCOFLEX102 | 28618/2    | May.08,13  | 1 Year        |

### 5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.



### 5.3. Test Procedure



The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.

### 5.4. Test result

**PASS** (The testing data was attached in the next pages.)



**GFSK**  
2402MHz









2441MHz








2480MHz













8-DPSK  
2402MHz













2441MHz









2480MHz









## 6. CARRIER FREQUENCY SEPARATION TEST

### 6.1. Test Equipment

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal.  | Cal. Interval |
|------|-----------|--------------|-----------|------------|------------|---------------|
| 1    | Spectrum  | Agilent      | N9030A    | MY51380221 | Oct.31, 13 | 1Year         |

### 6.2. Limit

Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 6.3. Test Results.

|  |                         |                           |
|--|-------------------------|---------------------------|
| EUT: Mad Catz F.R.E.9 Wireless Headset |                         |                           |
| M/N: 43401R                            |                         |                           |
| Test date: 2014-03-19                  | Pressure: 101.2±1.0 kpa | Humidity: 53.8±3.0%       |
| Tested by: Leo-Li                      | Test site: RF Site      | Temperature : 24 .4±0.6°C |

| Test Mode | Channel separation | Conclusion |
|-----------|--------------------|------------|
| 8-DPSK    | 1.0MHz             | PASS       |
| GFSK      | 1.0MHz             | PASS       |



## 7. 20 DB BANDWIDTH TEST

### 7.1. Test Equipment

| Item | Equipment        | Manufacturer | Model No.   | Serial No. | Last Cal.  | Cal. Interval |
|------|------------------|--------------|-------------|------------|------------|---------------|
| 1.   | Spectrum         | Agilent      | E4446A      | US44300459 | May.08, 13 | 1 Year        |
| 2.   | Attenuator(20dB) | Agilent      | 8491B       | MY39262165 | May.08, 13 | 1 Year        |
| 3.   | RF Cable         | Hubersuhner  | SUCOFLEX102 | 28620/2    | May.08, 13 | 1 Year        |

### 7.2. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 7.3. Test Results


|  |                         |                           |
|--|-------------------------|---------------------------|
| EUT: Mad Catz F.R.E.9 Wireless Headset |                         |                           |
| M/N: 43401R                            |                         |                           |
| Test date: 2014-03-19                  | Pressure: 101.2±1.0 kpa | Humidity: 53.8±3.0%       |
| Tested by: Leo-Li                      | Test site: RF Site      | Temperature : 24 .4±0.6°C |

| Cable loss: 1.0 dB |          | Attenuator loss: 20 dB |             |
|--------------------|----------|------------------------|-------------|
| Test Mode          | CH (MHz) | 20dB bandwidth (KHz)   | Limit (KHz) |
| GFSK               | 2402     | 827.643                | N/A         |
|                    | 2441     | 830.176                | N/A         |
|                    | 2480     | 834.335                | N/A         |
| 8-DPSK             | 2402     | 1204                   | N/A         |
|                    | 2441     | 1205                   | N/A         |
|                    | 2480     | 1208                   | N/A         |


Conclusion : PASS

**GFSK**


Test Frequency: 2402MHz



Test Frequency: 2441MHz




Test Frequency: 2480MHz




8-DPSK

Test Frequency: 2402MHz






Test Frequency: 2441MHz



Test Frequency: 2480MHz



## 8. NUMBER OF HOPPING FREQUENCY TEST

### 8.1. Test Equipment

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal.  | Cal. Interval |
|------|-----------|--------------|-----------|------------|------------|---------------|
| 1    | Spectrum  | Agilent      | N9030A    | MY51380221 | Oct.31, 13 | 1Year         |



### 8.2. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

### 8.3. Test Results

|  |                         |                          |
|--|-------------------------|--------------------------|
| EUT: Mad Catz F.R.E.9 Wireless Headset |                         |                          |
| M/N: 43401R                            |                         |                          |
| Test date: 2014-03-19                  | Pressure: 101.2±1.0 kpa | Humidity: 53.8±3.0%      |
| Tested by: Leo-Li                      | Test site: RF Site      | Temperature : 24.4±0.6°C |

| Test Mode | Number of channel | Limit | Conclusion |
|-----------|-------------------|-------|------------|
| 8-DPSK    | 79                | ≥15   | PASS       |
| GFSK      | 79                | ≥15   | PASS       |



## 9. DWELL TIME

### 9.1. Test Equipment

| Item | Equipment         | Manufacturer | Model No. | Serial No. | Last Cal.  | Cal. Interval |
|------|-------------------|--------------|-----------|------------|------------|---------------|
| 1    | Spectrum Analyzer | Agilent      | E4446A    | US44300459 | May.08, 13 | 1 Year        |

### 9.2. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 9.3. Test Results



|  |                         |                          |
|--|-------------------------|--------------------------|
| EUT: Mad Catz F.R.E.9 Wireless Headset |                         |                          |
| M/N: 43401R                            |                         |                          |
| Test date: 2014-03-19                  | Pressure: 101.2±1.0 kpa | Humidity: 53.8±3.0%      |
| Tested by: Leo-Li                      | Test site: RF Site      | Temperature : 24.4±0.6°C |

| Mode   |     | dwll time   | Limit  | Conclusion |
|--------|-----|---|--------|------------|
| GFSK   | DH1 | $51\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 0.4417\text{ms} = 142.36\text{ms}$ | <400ms | PASS       |
|        | DH3 | $25\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 1.7\text{ms} = 268.6\text{ms}$     | <400ms | PASS       |
|        | DH5 | $17\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 3.025\text{ms} = 325.006\text{ms}$ | <400ms | PASS       |
| 8-DPSK | DH1 | $50\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 0.455\text{ms} = 143.78\text{ms}$  | <400ms | PASS       |
|        | DH3 | $26\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 1.735\text{ms} = 285.09\text{ms}$  | <400ms | PASS       |
|        | DH5 | $17\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 3.033\text{ms} = 325.86\text{ms}$  | <400ms | PASS       |

Note: All the lower levels were signal from receiver's, and should not considered in here.



**Test Mode: GFSK**

**DH1**









DH3





DH5





**Test Mode: 8DPSK  
DH1**



DH3



DH5





## 10. MAXIMUM PEAK OUTPUT POWER TEST

### 10.1. Test Equipment

| Item | Equipment        | Manufacturer | Model No.   | Serial No. | Last Cal.  | Cal. Interval |
|------|------------------|--------------|-------------|------------|------------|---------------|
| 1.   | Spectrum         | Agilent      | E4446A      | US44300459 | May.08, 13 | 1 Year        |
| 3.   | Power meter      | Anritsu      | ML2487A     | 6K00002472 | May.08, 13 | 1 Year        |
| 4.   | Power sensor     | Anritsu      | MA2491A     | 0033005    | May.08, 13 | 1 Year        |
| 5.   | Attenuator(20dB) | Agilent      | 8491B       | MY39262165 | May.08, 13 | 1 Year        |
| 6    | RF Cable         | Hubersuhner  | SUCOFLEX102 | 28620/2    | May.08, 13 | 1 Year        |

### 10.2. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 10.3. Test Procedure

1. Connected the EUT's antenna port to power meter Via suitable attenuator.
2. Read the peak output power from power meter directly

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

## 10.4. Test Results

| EUT: Mad Catz F.R.E.Q.9 Wireless Headset |          |                         |                          |
|--|----------|-------------------------|--------------------------|
| M/N: 43401R                              |          |                         |                          |
| Test date: 2014-03-19                    |          | Pressure: 101.2±1.0 kpa | Humidity: 54.3±3.0%      |
| Tested by: Eric                          |          | Test site: RF site      | Temperature: 25.1±0.6 °C |
| Cable loss: 1.0 dB                       |          | Attenuator loss: 20 dB  |                          |
| Test Mode                                | CH (MHz) | Peak output Power (dBm) | Limit (dBm)              |
| GFSK                                     | 2402     | 5.15                    | 30                       |
|  | 2441     | 5.01                    | 30                       |
|  | 2480     | 5.35                    | 30                       |
| 8-DPSK                                   | 2402     | 4.42                    | 30                       |
|  | 2441     | 4.68                    | 30                       |
|  | 2480     | 4.17                    | 30                       |
| Conclusion: PASS                         |          |                         |                          |

## 11. BAND EDGE COMPLIANCE TEST

### 11.1. Test Equipment

| Item | Equipment    | Manufacturer | Model No.   | Serial No. | Last Cal.  | Cal. Interval |
|------|--------------|--------------|-------------|------------|------------|---------------|
| 1.   | Spectrum     | Agilent      | E4446A      | US44300459 | May.08, 13 | 1 Year        |
| 2.   | Amp          | HP           | 8449B       | 3008A02495 | May.08, 13 | 1 Year        |
| 3.   | Horn Antenna | EMCO         | 3115        | 9510-4580  | May.28, 13 | 1 Year        |
| 4.   | HF Cable     | Hubersuhner  | Sucoflex104 | 274094/4   | May.08, 13 | 1 Year        |
| 5.   | RF Cable     | Hubersuhner  | Sucoflex102 | 28618/2    | May.08,13  | 1 Year        |

### 11.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 11.3. Test Produce

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz) from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205


For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
  - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
  - (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

### 11.4. Test Results

Pass (The testing data was attached in the next pages.)


Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



Site no. : 3m Chamber Data no. : 5  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2402MHz Tx  
 M/N : 43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2367.285    | 28.11              | 5.75            | 35.70           | 49.64          | 47.80                   | 74.00           | 26.20       | Peak   |
| 2   | 2390.000    | 28.16              | 5.78            | 35.70           | 47.70          | 45.94                   | 74.00           | 28.06       | Peak   |
| 3   | 2400.000    | 28.18              | 5.80            | 35.70           | 56.00          | 54.28                   | 74.00           | 19.72       | Peak   |
| 4   | 2402.150    | 28.18              | 5.80            | 35.70           | 90.19          | 88.47                   | 74.00           | -14.47      | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 6  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2402MHz Tx  
 M/N : 43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2314.275    | 27.99              | 5.67            | 35.70           | 50.53          | 48.49                   | 74.00           | 25.51       | Peak   |
| 2   | 2390.000    | 28.16              | 5.78            | 35.70           | 47.76          | 46.00                   | 74.00           | 28.00       | Peak   |
| 3   | 2400.000    | 28.18              | 5.80            | 35.70           | 60.55          | 58.83                   | 74.00           | 15.17       | Peak   |
| 4   | 2402.150    | 28.18              | 5.80            | 35.70           | 93.98          | 92.26                   | 74.00           | -18.26      | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 15  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2480MHz Tx  
 M/N : 43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2479.970    | 28.36              | 5.91            | 35.70           | 88.43          | 87.00                   | 74.00           | -13.00      | Peak   |
| 2   | 2483.500    | 28.36              | 5.92            | 35.70           | 47.71          | 46.29                   | 74.00           | 27.71       | Peak   |
| 3   | 2495.414    | 28.39              | 5.94            | 35.70           | 50.21          | 48.84                   | 74.00           | 25.16       | Peak   |
| 4   | 2500.000    | 28.40              | 5.94            | 35.70           | 47.81          | 46.45                   | 74.00           | 27.55       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 16  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : GFSK 2480MHz Tx  
 M/N : 43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2479.805    | 28.36              | 5.91            | 35.70           | 83.42          | 81.99                   | 74.00           | -7.99       | Peak   |
| 2   | 2483.500    | 28.36              | 5.92            | 35.70           | 47.52          | 46.10                   | 74.00           | 27.90       | Peak   |
| 3   | 2489.606    | 28.38              | 5.93            | 35.70           | 49.53          | 48.14                   | 74.00           | 25.86       | Peak   |
| 4   | 2500.000    | 28.40              | 5.94            | 35.70           | 49.01          | 47.65                   | 74.00           | 26.35       | Peak   |


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 21  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2402MHz Tx  
 M/N : 43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2338.500    | 28.04              | 5.71            | 35.70           | 49.80          | 47.85                   | 74.00           | 26.15       | Peak   |
| 2   | 2390.000    | 28.16              | 5.78            | 35.70           | 48.25          | 46.49                   | 74.00           | 27.51       | Peak   |
| 3   | 2400.000    | 28.18              | 5.80            | 35.70           | 59.43          | 57.71                   | 74.00           | 16.29       | Peak   |
| 4   | 2401.960    | 28.18              | 5.80            | 35.70           | 92.07          | 90.35                   | 74.00           | -16.35      | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber  
 Dis. / Ant. : 3m 2013 3115 (4580)  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56%  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2402MHz Tx  
 M/N : 43401R  
 Data no. : 22  
 Ant. pol. : HORIZONTAL  
 Engineer : Leo-Li

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2346.765    | 28.06              | 5.72            | 35.70           | 49.74          | 47.82                   | 74.00           | 26.18       | Peak   |
| 2   | 2390.000    | 28.16              | 5.78            | 35.70           | 48.49          | 46.73                   | 74.00           | 27.27       | Peak   |
| 3   | 2400.000    | 28.18              | 5.80            | 35.70           | 51.33          | 49.61                   | 74.00           | 24.39       | Peak   |
| 4   | 2402.150    | 28.18              | 5.80            | 35.70           | 85.01          | 83.29                   | 74.00           | -9.29       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 31  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2480MHz Tx  
 M/N : 43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2479.904    | 28.36              | 5.91            | 35.70           | 82.15          | 80.72                   | 74.00           | -6.72       | Peak   |
| 2   | 2483.500    | 28.36              | 5.92            | 35.70           | 48.53          | 47.11                   | 74.00           | 26.89       | Peak   |
| 3   | 2487.989    | 28.37              | 5.93            | 35.70           | 49.41          | 48.01                   | 74.00           | 25.99       | Peak   |
| 4   | 2500.000    | 28.40              | 5.94            | 35.70           | 48.15          | 46.79                   | 74.00           | 27.21       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.





Site no. : 3m Chamber Data no. : 32  
 Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 24°C/56% Engineer : Leo-Li  
 EUT : Mad Catz F.R.E.Q.9 Wireless Headset  
 Power Rating : DC 5V From PC  
 Test Mode : 8-DPSK 2480MHz Tx  
 M/N : 43401R

| No. | Freq. (MHz) | Ant. Factor (dB/m) | Cable Loss (dB) | AMP factor (dB) | Reading (dBuV) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Remark |
|-----|-------------|--------------------|-----------------|-----------------|----------------|-------------------------|-----------------|-------------|--------|
| 1   | 2480.135    | 28.36              | 5.91            | 35.70           | 84.49          | 83.06                   | 74.00           | -9.06       | Peak   |
| 2   | 2483.500    | 28.36              | 5.92            | 35.70           | 47.25          | 45.83                   | 74.00           | 28.17       | Peak   |
| 3   | 2491.256    | 28.38              | 5.93            | 35.70           | 50.13          | 48.74                   | 74.00           | 25.26       | Peak   |
| 4   | 2500.000    | 28.40              | 5.94            | 35.70           | 47.26          | 45.90                   | 74.00           | 28.10       | Peak   |

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

## **12.DEVIATION TO TEST SPECIFICATIONS**

[NONE]