



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/">http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our regligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



# **Table of Contents**

Rel	ease Control Record	. 3
1	Certificate of Conformity	. 4
2	RF Exposure	. 5
2	<ol> <li>Limits for Maximum Permissible Exposure (MPE)</li> <li>MPE Calculation Formula</li> <li>Classification</li> </ol>	. 5
3	Calculation Result of Maximum Density Power	. 5



# **Release Control Record**

Issue No.	Description	Date Issued
MFBEIH-WTW-P22090333	Original release	Oct. 17, 2022

#### 1 **Certificate of Conformity**

Product:	CBRS Doorbell Camera
Brand:	Sercomm, MosoLabs
Test Model:	DBC965
Sample Status:	Engineering sample
Applicant:	Sercomm Corp.
Test Date:	Sep. 16 ~ Sep. 17, 2022
FCC Rule Part:	FCC Part 2 (Section 2.1091)
Standards:	KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: <u>Celine Chou</u>, Date: Oct. 17, 2022 Celine Chou / Senior Specialist

Approved by :

Jeremy Lin, Date: Oct. 17, 2022

Jeremy Lin / Project Engineer



## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

## 2.2 MPE Calculation Formula

 $\begin{array}{l} \mathsf{Pd} = (\mathsf{Pout}^*\mathsf{G}) \: / \: (4^*\mathsf{pi}^*\mathsf{r}^2) \\ \mathsf{where} \\ \mathsf{Pd} = \mathsf{power} \: \mathsf{density} \: \mathsf{in} \: \mathsf{mW}/\mathsf{cm}^2 \\ \mathsf{Pout} = \mathsf{output} \: \mathsf{power} \: \mathsf{to} \: \mathsf{antenna} \: \mathsf{in} \: \mathsf{mW} \\ \mathsf{G} = \mathsf{gain} \: \mathsf{of} \: \mathsf{antenna} \: \mathsf{in} \: \mathsf{linear} \: \mathsf{scale} \\ \mathsf{pi} = 3.1416 \\ \mathsf{r} \: \mathsf{e} \: \mathsf{distance} \: \mathsf{between} \: \mathsf{observation} \: \mathsf{point} \: \mathsf{and} \: \mathsf{center} \: \mathsf{of} \: \mathsf{the} \: \mathsf{radiator} \: \mathsf{in} \: \mathsf{cm} \end{array}$ 

## 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

### 3 Calculation Result of Maximum Density Power

Function	Frequency Band	EIRP	Distance	Power Density	Limit
	(MHz)	(dBm)	(cm)	(mW/cm <sup>2</sup> )	(mW/cm²)
LTE Band 48	3555-3695	22.15	20	0.033	1

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

---- END ----