

1.1. Test Result of RF Exposure Evaluation

- . Product: 802.11g Wireless ADSL Router
- . Test Item: RF Exposure Evaluation Data
- . Test site: OATSI-SD
- . Test Mode: Normal Operation

1.1.1. Antenna Gain

The maximum Gain is 1.8 dBi.

1.1.2. EUT Operation condition

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

1.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Test Mode1: Modulation Standard: IEEE 802.11b(11Mbps)

Test Date: Nov. 12, 2007 Temperature: 25 Humidity: 62%

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density (S) (mW/cm ²) |
|---------|-------------------------|-------------------------------|---|
| 01 | 2412 | 18.16 | 0.020 |
| 06 | 2437 | 18.13 | 0.020 |
| 11 | 2462 | 18.09 | 0.019 |

Test Mode1: Modulation Standard: IEEE 802.11g(54Mbps)

Test Date: Nov. 12, 2007 Temperature: 25 Humidity: 62%

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density (S) (mW/cm ²) |
|---------|-------------------------|-------------------------------|---|
| 01 | 2412 | 14.03 | 0.008 |
| 06 | 2437 | 14.07 | 0.008 |
| 11 | 2462 | 13.95 | 0.007 |

Test Mode2: Modulation Standard: IEEE 802.11b(11Mbps)

Test Date: Nov. 12, 2007 Temperature: 25 Humidity: 62%

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density (S) (mW/cm ²) |
|---------|-------------------------|-------------------------------|---|
| 01 | 2412 | 18.14 | 0.020 |
| 06 | 2437 | 17.08 | 0.015 |
| 11 | 2462 | 16.35 | 0.013 |

Test Mode2: Modulation Standard: IEEE 802.11g(54Mbps)

Test Date: Nov. 12, 2007

Temperature: 25

Humidity: 62%

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density (S) (mW/cm ²) |
|---------|-------------------------|-------------------------------|---|
| 01 | 2412 | 14.16 | 0.008 |
| 06 | 2437 | 12.88 | 0.006 |
| 11 | 2462 | 12.19 | 0.005 |

The MPE is calculated as $0.020 \text{ mW} / \text{cm}^2 < \text{limit } 1 \text{ mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

For 2412-2462 MHz, the EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.