| | 1 | 2 | 2 | 3 | | | 4 | | | 5 | | |
|-------------|----------------------|--------------|--|---|--|-------|--------|----------|----------|---|--------------------|----|
| | Scale/1:1 | | | | | | 1 (訂正) | | | | | |
| | Unit/mm | | | | | | | | | | | |
| | DO NOT SCALE DRAWING | | | | | | | | | | | |
| А | | | | | | | | | | | | |
| $ ^{\sim} $ | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | Model No: | | | | | | | | | |
| | | | Serial No: | | | | | | | | | |
| | | | WAN MAC: | | | | | | | | | |
| | | | LAN MAC: | | | | | | | | | |
| | | | EUI: | | | | | | | | | |
| В | | | Input: 12VDC === 1A FCC ID: P27NA403 | Polarity: ⊝ ⊙ ⊕ | | | | | | | | |
| | | | This device complies with Part 1 Operation is subject to the follow (1) this device may not cause ha (2) this device must accept any i including interference that may | 5 of the FCC Rules. ving two conditions: | | | | | | | | |
| | | | | | | | | | | | | |
| | | | Made in Taiwan | ant C C | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | — | | | | | | | | | | | |
| | | Black | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| С | Note | | | | | | | | | | | |
| | 1.材 | 質: 50#白色Myla | ar,上霧P | | | | | | | | | |
| | 2.背 | 壓克力膠 | | | | | | | | | | |
| | | 寸/印刷:如圖示 | | | | | | | | | | |
| | | 差:+/- 0.2mm | | | | | | | | | | |
| | | 料件使用之材料 | 佰 な A RoH | \$ | | | | | | | | |
| | 0:4 | 们们反内之物们 | · · · · · · · · · · · · · · · · · · · | 0 | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | DONOTSCALEDRAWING | | | | | | | | | | | |
| D | | | | | | MODEL | NA403 | NAME | 消銀龍/中 | 性 | SCALE | / |
| | | | | | | DSN | | part. No | 932YN41 | | · · | OF |
| | | | | | | СНК | | MATERIAL | /0211141 | | REV. | |
| | | | | | | APV | | | | | | |
| | USED | | | | | FILE | | J. | SESCOW | | REV. DATE 2010.07. | 23 |
| | | | | | | | 1 | | | | | |

