

FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Wireless P/T Network Camera

Model: RC8230xxxxxxx (x= 0~9, A~Z, Blank or any Character)

Trade Name: SerComm, AT&T

Issued to

SerComm Corporation 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C.

Issued by

Compliance Certification Services Inc. No.11, Wu-Gong 6th Rd., Wugu Industrial Park, New Taipei City 248, Taiwan (R.O.C.) http://www.ccsrf.com service@ccsrf.com Issued Date: April 24, 2012



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



Revision History

	Issue		Effect	
Rev.	Date	Revisions	Page	Revised By
00	April 24, 2012	Initial Issue	ALL	Eunice Shem



TABLE OF CONTENTS

1. T	EST RESULT CERTIFICATION	4
2. E	CUT DESCRIPTION	5
3. T	EST METHODOLOGY	6
3.1	EUT CONFIGURATION	6
3.2	EUT EXERCISE	6
3.3	GENERAL TEST PROCEDURES	6
3.4	FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
3.5	DESCRIPTION OF TEST MODES	8
4. II	NSTRUMENT CALIBRATION	9
4.1	MEASURING INSTRUMENT CALIBRATION	9
4.2	MEASUREMENT EQUIPMENT USED	9
4.3	MEASUREMENT UNCERTAINTY	
5. F	ACILITIES AND ACCREDITATIONS	11
5.1	FACILITIES	
5.2	EQUIPMENT	
5.3	TABLE OF ACCREDITATIONS AND LISTINGS	
6. S	ETUP OF EQUIPMENT UNDER TEST	13
6.1	SETUP CONFIGURATION OF EUT	
6.2	SUPPORT EQUIPMENT	13
7. F	CC PART 15.247 REQUIREMENTS	14
7.1	6DB BANDWIDTH	14
7.2	PEAK POWER	25
7.3	BAND EDGES MEASUREMENT	
7.4	PEAK POWER SPECTRAL DENSITY	60
7.5	SPURIOUS EMISSIONS	72
7.6	RADIATED EMISSIONS	
7.7	POWERLINE CONDUCTED EMISSIONS	
APPE	ENDIX I RADIO FREQUENCY EXPOSURE	
APPE	ENDIX II PHOTOGRAPHS OF TEST SETUP	
APPI	ENDIX 1 - PHOTOGRAPHS OF EUT	



1. TEST RESULT CERTIFICATION

Date of Test:	March 30 ~ April 23, 2012	
Model Number: $RC8230xxxxxxxx (x=0~9, A~Z, Blank or any Character)$		
Trade Name:	SerComm, AT&T	
Equipment Under Test:	Wireless P/T Network Camera	
Applicant:	SerComm Corporation 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C	

ATTEICADEE STANDARDS				
STANDARD	TEST RESULT			
FCC 47 CFR Part 15 Subpart C	No non-compliance noted			

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

woon Lin

Jason Lin Section Manager Compliance Certification Services Inc.

Gira Lo

Gina Lo Section Manager Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	Wireless P/T Network Camera		
Trade Name	SerComm, AT&T		
Model Number	RC8230xxxxxxx (x= 0~9, A~Z, Blank or any Character)		
Model Discrepancy	All the above models are identical except for the designation of model numbers. The suffix of x ($x = 0 \sim 9$, $A \sim Z$, Blank or any Character) on model number is just for marketing purpose only.		
Received Date	March 23, 2012		
1. Brand: Sunny / Model: SYS1381-1212-W2 I/P: 100-240V, 50-60Hz, 0.5A MAX O/P: 12V, 1.0A 2. Brand: LEADER / Model: MU12-G120100-A1 I/P: 100-240V, 50-60Hz, 0.5A O/P: 12V, 1.0A 3. Brand: DVE / Model: DSA-12PFE-12 BUS I/P: 100-120V, 50-60Hz, 0.3A O/P: 12V, 1.4			
Frequency Range	$2412 \sim 2462 \text{ MHz}$		
Transmit Power	IEEE 802.11b mode: 19.96 dBm IEEE 802.11g mode: 25.75 dBm IEEE 802.11n HT 20 MHz mode: 26.38 dBm IEEE 802.11n HT 40 MHz mode: 25.25 dBm		
Modulation Technique	IEEE 802.11b mode: DSSS IEEE 802.11g mode: OFDM IEEE 802.11n HT 20 MHz mode: OFDM IEEE 802.11n HT 40 MHz mode: OFDM		
Number of Channels	IEEE 802.11b/g mode: 11 Channels IEEE 802.11n HT 20 MHz mode: 11 Channels IEEE 802.11n HT 40 MHz mode: 7 Channels		
Antenna Specification	Interference Interference fication 1. PCB Antenna / Gain: 2.68 dBi 2. Dipole Antenna / Gain: 2.27 dBi MIMO: Total ANT=10*LOG(((10^(2.68/20)+10^(2.27/20))^2)/2)= 5.49		

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: <u>P27RC8230</u> filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

	MHz	MHz	MHz	GHz
	0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
	¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
	2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
	4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
	4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
	4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
	6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
	6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
	6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
	8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
	8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
	8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
	8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
	12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
1	2.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
1	2.57675 - 12.57725	240 - 285	3600 - 4400	(²)
	13.36 - 13.41	322 - 335.4		

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT (model: RC8230) comes with three types of power adapter (SYS1381-1212-W2 / MU12-G120100-A1 / DSA-12PFE-12 BUS) for sale. After the preliminary test, the power adapter MU12-G120100-A1 was found to emit the worst emissions and therefore had been tested under operating condition.

The EUT is a 2x2 configuration spatial MIMO (2Tx & 2Rx) without beam forming function that operate in double TX chains and double RX chains. The 2x2 configuration is implemented with two outside TX & RX chains (Chain 0 and 1).

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

IEEE 802.11b mode:

Channel Low (2412MHz), Channel Mid (2442MHz) and Channel High (2462MHz) with 1Mbps data rate and cyclic delay diversity were chosen for full testing.

IEEE 802.11g mode:

Channel Low (2412MHz), Channel Mid (2442MHz) and Channel High (2462MHz) with 6Mbps data rate and cyclic delay diversity were chosen for full testing.

IEEE 802.11n HT 20 MHz mode:

Channel Low (2412MHz), Channel Mid (2442MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

IEEE 802.11n HT 40 MHz mode:

Channel Low (2422MHz), Channel Mid (2442MHz) and Channel High (2452MHz) with 13.5Mbps data rate were chosen for full testing.



4. INSTRUMENT CALIBRATION

4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year and Loop Antenna is scheduled for calibration once three years.

Conducted Emissions Test Site						
Name of Equipment Manufacturer Model Serial Number Calibration						
Spectrum Analyzer	Agilent	E4446A	MY43360131	03/16/2013		
Power Meter	Anritsu	ML2495A	1012009	04/27/2012		
Power Sensor	Anritsu	MA2411B	0917072	04/27/2012		

Wugu 966 Chamber A					
Name of Equipment	Manufacturer	anufacturer Model		Calibration Due	
Spectrum Analyzer	Agilent	E4446A	US42510252	11/02/2012	
EMI Test Receiver	R&S	ESCI	100064	02/16/2013	
Pre-Amplifier	Mini-Circults	ZFL-1000LN	SF350700823	01/12/2013	
Pre-Amplifier	Pre-Amplifier MITEQ AFS44-00102650 42-10P-44		1415367	11/19/2012	
Bilog Antenna	Sunol Sciences	JB3	A030105	10/03/2012	
Horn Antenna	EMCO	3117	00055165	01/11/2013	
Horn Antenna	EMCO	3116	00026370	10/12/2012	
Loop Antenna	EMCO	6502	8905/2356	06/10/2013	
Turn Table	CCS	CC-T-1F	N/A	N.C.R	
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	
Controller	CCS	CC-C-1F	N/A	N.C.R	
Site NSA	CCS	N/A	N/A	12/25/2012	
Test S/W	EZ-EMC (CCS-3A1RE)				

Conducted Emission room # A						
Name of Equipment	Manufacturer Model		Serial Number	Calibration Due		
TEST RECEIVER	R&S	ESCI	101201	09/05/2012		
LISN (EUT)	SCHWARZBECK	NSLK 8127	8127527	12/13/2012		
LISN	SCHWARZBECK	NSLK 8127	8127526	12/13/2012		
BNC CABLE	EMCI	5Dr	BNC A6	12/07/2012		
THERMO- HYGRO METER	TECPEL	DTM-303	NO.3	11/21/2012		



4.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
Powerline Conducted Emission	+/- 1.0717
3M Semi Anechoic Chamber / 30M~200M	+/- 4.0138
3M Semi Anechoic Chamber / 200M~1000M	+/- 3.9483
3M Semi Anechoic Chamber / 1G~8G	+/- 2.5975
3M Semi Anechoic Chamber / 8G~18G	+/- 2.6112
3M Semi Anechoic Chamber / 18G~26G	+/- 2.7389
3M Semi Anechoic Chamber / 26G~40G	+/- 2.9683

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

Remark: The Powerline Conducted test items was tested at Compliance Certification Services Inc. (Hsintien Lab.) The test equipments were listed in page 9 and the test data, please refer page 84-85.

No.11, Wu-Gong 6th Rd., Wugu Industrial Park, New Taipei City 248, Taiwan (R.O.C.)
Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

No.81-1, Lane 210, Bade 2nd Rd., Lujhu Township, Taoyuan County 33841, TAIWAN, R.O.C.

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."



5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3M Semi Anechoic Chamber (FCC MRA: TW1039) to perform FCC Part 15 measurements	FCC MRA: TW1039
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12,2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method -47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	Testing Laboratory 1309
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 2324G-1 / IC 2324G-2) to perform	Canada IC 2324G-1 IC 2324G-2

* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No	Equipment	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1	Microphone	KOKA	DM-514P	N/A	N/A	Shielded, 4.3 m	N/A
2	Notebook PC (Remote)	DELL	PP19L	GK102 A00	QDS-BRCM1021	LAN Cable: Unshielded, 10m Line Cable: Unshielded, 1.0m	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

Remark:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



7. FCC PART 15.247 REQUIREMENTS

7.1 6DB BANDWIDTH

LIMIT

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. Set the RBW = 1% of the emission bandwidth, $VBW \ge 3 \times RBW$, Detector = Peak, Trace mode = max hold, Sweep = auto couple. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

TEST RESULTS

No non-compliance noted.



<u>Test Data</u>

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	10.27		PASS
Mid	2442	10.30	>500	PASS
High	2462	10.30		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.43		PASS
Mid	2442	16.43	>500	PASS
High	2462	16.53		PASS

Test mode: IEEE 802.11n HT 20 MHz mode / Chain 0

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.77		PASS
Mid	2442	17.77	>500	PASS
High	2462	17.73		PASS

Test mode: IEEE 802.11n HT 20 MHz mode / Chain 1

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.67		PASS
Mid	2442	17.80	>500	PASS
High	2462	17.40		PASS

Test mode: IEEE 802.11n HT 40 MHz mode / Chain 0

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2422	36.40		PASS
Mid	2442	36.47	>500	PASS
High	2452	36.53		PASS

Test mode: IEEE 802.11n HT 40 MHz mode / Chain 1

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2422	36.47		PASS
Mid	2442	36.53	>500	PASS
High	2452	36.47		PASS



Test Plot

IEEE 802.11b mode

6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)





6dB Bandwidth (CH High)



IEEE 802.11g mode

6dB Bandwidth (CH Low)





6dB Bandwidth (CH Mid)



6dB Bandwidth (CH High)





IEEE 802.11n HT 20 MHz mode / Chain 0

6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)

- 🔆 🔺	gilent 18:1	1:46 Apr	11,2012					RТ		
									∆ Mkr2	17.77 MHz
Ref 20	dBm		#Att	ten 20 dB						0.63 dB
#Peak										
Log										
10	28	Cara	<u> </u>	mm	m	mm	June	-	apresent and the second	~~~~~
dB/	Ŷ									Ŷ
Offst										
17.1										
dB										
DI										
-2.5										
dBm										
LqAv										
V1 S2										
Center	2.442 00 (GHz							S	pan 20 MHz
#Res B'	W 180 kHz	z		#	VBW 560 I	kHz		Sw	eep 1 ms	; (601 pts)
Marker	r Trac	e Ty	pe	XA	loxis		Amplitu	de		
1	(1)	Fre	≥q	2.443 87	GHz		3.52 dB	m		
2R	(1)	Fre	≥q	2.433 10)GHz		-4.96 dBr	m D		
24	(1)	FIG	2 q	17.75	/ WINZ		0.03 0	0		



6dB Bandwidth (CH High)



IEEE 802.11n HT 20 MHz mode / Chain 1

6dB Bandwidth (CH Low)





6dB Bandwidth (CH Mid)



6dB Bandwidth (CH High)





IEEE 802.11n HT 40 MHz mode / Chain 0

6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)





6dB Bandwidth (CH High)



IEEE 802.11n HT 40 MHz mode / Chain 1

6dB Bandwidth (CH Low)





6dB Bandwidth (CH Mid)



6dB Bandwidth (CH High)





7.2 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. According to \$15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
- 2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. Set the RBW = 1MHz, VBW = 3MHz, Detector = Peak, Trace mode = max hold, Sweep = auto couple. Record the max reading. Repeat the above procedure until the measurements for all frequencies are completed.



<u>Test Data</u>

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	19.52	0.0895		PASS
Mid	2442	19.96	0.0991	1.00	PASS
High	2462	18.51	0.0710		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	25.75	0.3758		PASS
Mid	2442	25.03	0.3184	1.00	PASS
High	2462	25.26	0.3357		PASS

Test mode: IEEE 802.11n HT 20 MHz mode

Channel	Frequency (MHz)	Chain 0 Output Power (dBm)	Chain 1 Output Power (dBm)	Total Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	24.11	20.78	25.77	0.3773		PASS
Mid	2442	24.31	22.16	26.38	0.4342	1.00	PASS
High	2462	23.82	22.13	26.07	0.4043		PASS

Test mode: IEEE 802.11n HT 40 MHz mode

Channel	Frequency (MHz)	Chain 0 Output Power (dBm)	Chain 1 Output Power (dBm)	Total Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2422	20.75	17.64	22.48	0.1769		PASS
Mid	2442	23.05	21.24	25.25	0.3349	1.00	PASS
High	2452	19.61	17.03	21.52	0.1419		PASS

Remark: Total Output Power (w) = Chain 0 (10^{OUtput} Power /10)/1000) + Chain 1 (10^{OUtput} Power /10)/1000)



Test Plot

IEEE 802.11b mode

Peak Power (CH Low)



Peak Power (CH Mid)

🔆 Agilent 20:22:52 Apr 18, 2012

R T





-53.05 dBm/Hz



Peak Power (CH High)



IEEE 802.11g mode

Peak Power (CH Low)





Peak Power (CH Mid)



Peak Power (CH High)





IEEE 802.11n HT 20 MHz mode / Chain 0

Peak Power (CH Low)





24.11 dBm /20.0000 MHz

Peak Power (CH Mid)

🔆 Agilent 20:19:31 Apr 18, 2012

R T

-48.90 dBm/Hz

R T





-48.70 dBm/Hz

Rev. 00



Peak Power (CH High)



IEEE 802.11n HT 20 MHz mode / Chain 1

Peak Power (CH Low)





Peak Power (CH Mid)



Peak Power (CH High)





IEEE 802.11n HT 40 MHz mode / Chain 0

Peak Power (CH Low)



Peak Power (CH Mid)





Peak Power (CH High)



IEEE 802.11n HT 40 MHz mode / Chain 1

Peak Power (CH Low)





Peak Power (CH Mid)



Peak Power (CH High)





7.3 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration

For Radiated



For Conducted




TEST PROCEDURE

For Radiated

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

For Conducted

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 300 kHz. The video bandwidth is set to 300 kHz.

TEST RESULTS

Refer to attach spectrum analyzer data chart.



Band Edges (IEEE 802.11b mode / CH Low)





Detector mode: Peak







Band Edges (IEEE 802.11b mode / CH High)





Detector mode: Peak







Band Edges (IEEE 802.11g mode / CH Low)





Detector mode: Peak







Band Edges (IEEE 802.11g mode / CH High)





Detector mode: Peak







Band Edges (IEEE 802.11n HT 20 MHz mode / CH Low)

Detector mode: Peak

Polarity: Vertical





Offst 6 ďВ DL 54.0

LgAv

M1 S2 \$3 FC A AA £(f): FTun Swp







Band Edges (IEEE 802.11n HT 20 MHz mode / CH High)

Detector mode: Peak

Polarity: Vertical





Detector mode: Peak







Band Edges (IEEE 802.11n HT 40 MHz mode / CH Low)

Detector mode: Peak

Polarity: Vertical





Detector mode: Peak







Band Edges (IEEE 802.11n HT 40 MHz mode / CH High)

Detector mode: Peak

Polarity: Vertical





🔆 Agilent

Detector mode: Peak







Test Plot

Conducted Band Edges (IEEE 802.11b mode / CH Low)



Conducted Band Edges (IEEE 802.11b mode / CH High)





Т 🔆 Agilent 19:13:34 Apr 23, 2012 R Mkr1 2.413 2 GHz Ref 20 dBm Atten 20 dB 11.07 dBm #Peak ¢ Log 10 dB/ Offst Š. 16.6 5 M dB DL -8.9 Marrier J∿# dBm LgAv V1 S2 Stop 2.420 0 GHz Start 2.310 0 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 10.52 ms (601 pts) Marker Trace Type X Axis Amplitude 2.413 2 GHz 2.390 0 GHz 11.07 dBm -27.98 dBm 1 (1) Freq 2 (1) Freq -16.47 dBm 3 (1)Freq 2.400 0 GHz

Conducted Band Edges (IEEE 802.11g mode / CH Low)

Conducted Band Edges (IEEE 802.11g mode / CH High)





Conducted Band Edges (IEEE 802.11n HT 20 MHz mode / CH Low / Chain 0)

Conducted Band Edges (IEEE 802.11n HT 20 MHz mode / CH High / Chain 0)





Conducted Band Edges (IEEE 802.11n HT 20 MHz mode / CH Low / Chain 1)

Conducted Band Edges (IEEE 802.11n HT 20 MHz mode / CH High / Chain 1)





Conducted Band Edges (IEEE 802.11n HT 40 MHz mode / CH Low / Chain 0)

Conducted Band Edges (IEEE 802.11n HT 40 MHz mode / CH High / Chain 0)





Conducted Band Edges (IEEE 802.11n HT 40 MHz mode / CH Low / Chain 1)

Conducted Band Edges (IEEE 802.11n HT 40 MHz mode / CH High / Chain 1)





7.4 PEAK POWER SPECTRAL DENSITY

LIMIT

- 1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
- 2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. Set the RBW = 100 kHz, VBW = 300 kHz, Span > 5% of the bandwidth, Detector = peak, Trace mode = max hold, Sweep = auto couple. Record the maximum reading. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted.



<u>Test Data</u>

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	5.29		PASS
Mid	2442	5.08	8.00	PASS
High	2462	4.21		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	1.43		PASS
Mid	2442	2.09	8.00	PASS
High	2462	1.82		PASS

Test mode: IEEE 802.11n HT 20 MHz mode

Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-3.02	-3.49	-0.24		PASS
Mid	2442	-3.47	-2.36	0.13	8.00	PASS
High	2462	-3.00	-1.66	0.73		PASS

Test mode: IEEE 802.11n HT 40 MHz mode

Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	PPSD (dBm)	Limit (dBm)	Result
Low	2422	-7.41	-9.93	-5.48		PASS
Mid	2442	-2.03	-5.93	-0.55	8.00	PASS
High	2452	-7.08	-8.66	-4.79		PASS

Remark: Total PPSD (dBm) = $10*LOG(10^{(Chain 0 PPSD / 10)}+10^{(Chain 1 PPSD / 10)})$



Test Plot

IEEE 802.11b mode

PPSD (CH Low)





PPSD (CH High)





IEEE 802.11g mode

PPSD (CH Low)





PPSD (CH High)





IEEE 802.11n HT 20 MHz mode / Chain 0

PPSD (CH Low)





PPSD (CH High)





PPSD (CH Mid)



PPSD (CH High)





IEEE 802.11n HT 40 MHz mode / Chain 0

PPSD (CH Low)





PPSD (CH High)





PPSD (CH Mid)



Sweep 3.84 ms (601 pts)



7.5 SPURIOUS EMISSIONS

7.5.1 Conducted Measurement

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. Set the RBW=100 kHz and VBW= 300 kHz. Investigate the frequency from 30 MHz to 26 GHz with L, M and H channels separately.

TEST RESULTS

No non-compliance noted.


<u>Test Plot</u>

IEEE 802.11b mode

CH Low



CH Mid





CH High



IEEE 802.11g mode

CH Low





CH Mid



CH High





IEEE 802.11n HT 20 MHz mode / Chain 0

CH Low



CH Mid





CH High



IEEE 802.11n HT 20 MHz mode / Chain 1

CH Low





CH Mid



CH High





IEEE 802.11n HT 40 MHz mode / Chain 0

CH Low



CH Mid





CH High



IEEE 802.11n HT 40 MHz mode / Chain 1

CH Low





CH Mid



CH High





7.6 RADIATED EMISSIONS

LIMIT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (µV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54



Test Configuration

$9 \text{kHz} \sim 30 \text{MHz}$







Above 1 GHz





TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS

No non-compliance noted.



Below 1GHz

Operation Mode:	Normal Link	Test Date:	April 6, 2012
Temperature:	25°C	Tested by:	Sehni Hu
Humidity:	50% RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
59.10	70.20	-34.07	36.13	40.00	-3.87	QP	V
81.73	62.80	-33.43	29.37	40.00	-10.63	QP	V
249.87	71.72	-28.43	43.29	46.00	-2.71	QP	V
474.58	64.10	-22.54	41.56	46.00	-4.44	QP	V
500.45	64.95	-22.22	42.73	46.00	-3.27	QP	V
524.70	61.84	-21.92	39.92	46.00	-6.08	Peak	V
123.77	59.14	-27.79	31.35	43.50	-12.15	Peak	Н
249.87	73.85	-28.43	45.42	46.00	-0.58	QP	Н
299.98	61.67	-26.38	35.29	46.00	-10.71	Peak	Н
350.10	60.43	-25.20	35.23	46.00	-10.77	Peak	Н
474.58	59.98	-22.54	37.44	46.00	-8.56	Peak	Н
749.42	58.15	-18.12	40.04	46.00	-5.96	Peak	Н

- 1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz)
- 2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
- 3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 4. Margin(dB) = Result(dBuV/m) Limit(dBuV/m).



Above 1 GHz

Operation Mode:	TX / IEEE 802.11b / CH Low
Temperature:	23°C

Temperature:

Humidity: 50 % RH

Test Date: April 12, 2012 Tested by: Sehni Hu Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1523.33	55.84		-10.31	45.53		74.00	54.00	-8.47	Peak	V
3216.67	50.29		-1.60	48.69		74.00	54.00	-5.31	Peak	V
4825.00	49.01	44.55	2.61	51.62	47.16	74.00	54.00	-6.84	AVG	V
N/A										
1646.67	55.52		-9.06	46.46		74.00	54.00	-7.54	Peak	Н
3216.67	48.57		-1.60	46.97		74.00	54.00	-7.03	Peak	Н
4825.00	48.18	43.58	2.61	50.79	46.19	74.00	54.00	-7.81	AVG	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- Average test would be performed if the peak result were greater than the average limit 3. or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) - Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11b / CH Mid

23°C

Temperature:

Humidity: 50 % RH

Test Date: April 12, 2012 Tested by: Sehni Hu Polarity: Ver. / Hor.

·							·			
Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1806.67	55.62		-7.43	48.19		74.00	54.00	-5.81	Peak	V
4883.33	49.00	44.56	2.73	51.73	47.29	74.00	54.00	-6.71	AVG	V
N/A										
									1	
1713.33	55.89		-8.38	47.51		74.00	54.00	-6.49	Peak	Н
N/A										
n 1		•	•	•	•	•	•	•	•	•

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- *3.* Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Operation Mode: TX / IEEE 802.11b / CH High

23°C

Temperature:

Humidity: 50 % RH

Test Date: April 12, 2012 Tested by: Sehni Hu Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
2356.67	57.64	43.57	-4.46	53.18	39.11	74.00	54.00	-14.89	AVG	V
4925.00	48.77	43.58	2.81	51.58	46.39	74.00	54.00	-7.61	AVG	V
N/A										
1890.00	56.63		-6 59	50.04		74.00	54.00	-3.96	Peak	Н
4925.00	47.61		2.81	50.42		74.00	54.00	-3.58	Peak	н
N/A	77.01		2.01	50.42		74.00	54.00	-5.50	TCak	- 11
11/71										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH Low

23°C

Temperature:

Humidity: 50 % RH

Test Date: April 12, 2012 Tested by: Sehni Hu

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1733.33	56.23		-8.18	48.05		74.00	54.00	-5.95	Peak	V
2360.00	60.02	51.55	-4.44	55.57	47.11	74.00	54.00	-6.89	AVG	V
2463.33	63.24	53.01	-4.02	59.22	48.99	74.00	54.00	-5.01	AVG	V
3216.67	50.46		-1.60	48.86		74.00	54.00	-5.14	Peak	V
N/A										
1700.00	5(21		7 71	40.61		74.00	54.00	5 20	Deal	TT
1/80.00	36.31		-/./1	48.61		/4.00	54.00	-5.39	Реак	Н
2463.33	57.85	46.73	-4.02	53.83	42.71	74.00	54.00	-11.29	AVG	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH Mid

23°C

Temperature:

Humidity: 50 % RH

Test Date: April 12, 2012 Tested by: Sehni Hu

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1640.00	55.05		-9.13	45.92		74.00	54.00	-8.08	Peak	V
2373.33	59.50	49.45	-4.39	55.11	45.06	74.00	54.00	-8.94	AVG	V
2493.33	61.20	50.69	-3.90	57.31	46.79	74.00	54.00	-7.21	AVG	V
4883.33	48.03		2.73	50.75		74.00	54.00	-3.25	Peak	V
N/A										
1890.00	56.22		-6.59	49.63		74.00	54.00	-4.37	Peak	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH High

23°C

Temperature:

Humidity: 50 % RH

Test Date: April 12, 2012 Tested by: Sehni Hu Polarity: Ver. / Hor.

Reading Reading Correction Result Result Limit Limit Frequency Margin Ant. Pol. Remark (Peak) (Peak) (Average) Factor (Peak) (Average) (Average) (MHz) (dB) (H/V) (dBuV) (dBuV) (dB/m) dBuV/m) (dBuV/m) (dBuV/m) (dBuV/m) V 1483.33 56.51 -10.57 45.95 74.00 54.00 -8.05 Peak ___ 2516.67 -6.89 AVG V 60.36 50.92 -3.81 56.54 47.11 74.00 54.00 3283.33 49.29 -1.42 47.87 74.00 54.00 -6.13 Peak V ------N/A 1683.33 55.58 -8.69 46.90 ---74.00 54.00 -7.10 Peak Η 7383.33 AVG 47.61 34.53 7.20 54.82 41.73 74.00 54.00 -12.27Η N/A

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- *3.* Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Operation Mode: TX / IEEE 802.11n HT 20 MHz mode / CH Low Test Date: April 12, 2012

Temperature: 23°C

Tested by: Sehni Hu

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1683.33	55.74		-8.69	47.06		74.00	54.00	-6.94	Peak	V
2360.00	62.02	53.31	-4.44	57.58	48.87	74.00	54.00	-5.13	AVG	V
2463.33	63.88	53.20	-4.02	59.86	49.18	74.00	54.00	-4.82	AVG	V
4825.00	53.91	42.19	2.61	56.52	44.80	74.00	54.00	-9.20	AVG	V
N/A										
1893.33	57.36		-6.55	50.80		74.00	54.00	-3.20	Peak	Н
2463.33	57.80	46.77	-4.02	53.78	42.75	74.00	54.00	-11.25	AVG	Н
4825.00	54.66	43.69	2.61	57.27	46.30	74.00	54.00	-7.70	AVG	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- *3.* Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Humidity:

Operation Mode: TX / IEEE 802.11n HT 20 MHz mode / CH Mid Te

Test Date: April 12, 2012

Temperature: 23°C

50 % RH

Tested by: Sehni Hu Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1490.00	57.00		-10.56	46.44		74.00	54.00	-7.56	Peak	V
2390.00	62.81	54.19	-4.32	58.49	49.87	74.00	54.00	-4.13	AVG	V
2493.33	62.27	53.06	-3.90	58.37	49.16	74.00	54.00	-4.84	AVG	V
4883.33	54.23	44.66	2.73	56.95	47.39	74.00	54.00	-6.61	AVG	V
N/A										
1486.67	56.53		-10.56	45.97		74.00	54.00	-8.03	Peak	Н
2390.00	59.40	49.87	-4.32	55.08	45 55	74.00	54.00	-8.45	AVG	н
4992.22	55.40	47.22	2.72	59.00	50.05	74.00	54.00	2.05	AVC	11
4885.55	55.49	47.32	2.73	58.21	50.05	/4.00	54.00	-3.95	AVG	Н
7316.67	46.65	38.97	7.23	53.88	46.20	74.00	54.00	-7.80	AVG	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Operation Mode: TX / IEEE 802.11n HT 20 MHz mode / CH High Test Date: April 12, 2012

Temperature: 23°C

Tested by: Sehni Hu

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1776.67	55.48		-7.74	47.74		74.00	54.00	-6.26	Peak	V
2513.33	62.28	52.30	-3.82	58.45	48.48	74.00	54.00	-5.52	AVG	V
4925.00	51.93	44.78	2.81	54.74	47.59	74.00	54.00	-6.41	AVG	V
N/A										
2340.00	57.28	42.36	-4.53	52.75	37.83	74.00	54.00	-16.17	AVG	Н
4925.00	51.14	42.68	2.81	53.95	45.49	74.00	54.00	-8.51	AVG	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- *3.* Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Operation Mode:	TX / IEEE 802.11n HT 40 MHz mode / CH Low	Test Date:	April 12, 2012
Temperature:	23°C	Tested by:	Sehni Hu
Humidity:	50 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1906.67	55.13		-6.42	48.71		74.00	54.00	-5.29	Peak	V
2513.33	58.68	46.91	-3.82	54.86	43.09	74.00	54.00	-10.91	AVG	V
N/A										
1680.00	56.15		-8.72	47.42		74.00	54.00	-6.58	Peak	Н
4858.33	49.00	38.47	2.68	51.68	41.15	74.00	54.00	-12.85	AVG	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Operation Mode:	TX / IEEE 802.11n HT 40 MHz mode / CH Mid	Test Date:	April 12, 2012
Temperature:	23°C	Tested by:	Sehni Hu
Humidity:	50 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1683.33	56.08		-8.69	47.40		74.00	54.00	-6.60	Peak	V
4866.67	52.14	46.25	2.69	54.83	48.94	74.00	54.00	-5.06	AVG	V
N/A										
1680.00	54.50		-8.72	45.78		74.00	54.00	-8.22	Peak	Н
4891.67	54.10	40.12	2.74	56.85	42.86	74.00	54.00	-11.14	AVG	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



Operation Mode:	TX / IEEE 802.11n HT 40 MHz mode / CH High	Test Date:	April 12, 2012
Temperature:	23°C	Tested by:	Sehni Hu
Humidity:	50 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1830.00	56.07		-7.20	48.88		74.00	54.00	-5.12	Peak	V
N/A										
									1	
1663.33	55.80		-8.89	46.91		74.00	54.00	-7.09	Peak	Н
N/A										

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin(dB) = Remark result(dBuV/m) Average limit(dBuV/m).



7.7 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to \$15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range	Limits (dBµV)					
(IVIIIZ)	Quasi-peak	Average				
0.15 to 0.50	66 to 56*	56 to 46*				
0.50 to 5	56	46				
5 to 30	60	50				

* Decreases with the logarithm of the frequency.

Test Configuration

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

TEST PROCEDURE

- 1. The EUT was placed on a table, which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

<u>Test Data</u>

Operation Mode:	Normal Link	Test Date:	March 30, 2012
Temperature:	22°C	Tested by:	Howard Pang
Humidity:	55% RH		

Frequency	Reading	Factor	Result	Limit	Margin	Detector	Note
(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)		
0.1539	44.89	10.07	54.96	65.78	-10.82	QP	L1
0.1539	27.68	10.07	37.75	55.78	-18.03	AVG	L1
0.1700	43.10	10.05	53.15	64.96	-11.81	QP	L1
0.1700	28.02	10.05	38.07	54.96	-16.89	AVG	L1
0.1819	42.70	10.03	52.73	64.39	-11.66	QP	L1
0.1824	26.55	10.03	36.58	54.37	-17.79	AVG	L1
0.1924	26.65	10.02	36.67	53.93	-17.26	AVG	L1
0.1940	40.80	10.02	50.82	63.86	-13.04	QP	L1
0.2220	37.70	10.01	47.71	62.74	-15.03	QP	L1
0.2220	24.86	10.01	34.87	52.74	-17.87	AVG	L1
0.2540	36.40	10.02	46.42	61.62	-15.20	QP	L1
0.2540	29.32	10.02	39.34	51.62	-12.28	AVG	L1
0.1700	44.36	10.05	54.41	64.96	-10.55	QP	L2
0.1700	25.08	10.05	35.13	54.96	-19.83	AVG	L2
0.1940	42.11	10.02	52.13	63.86	-11.73	QP	L2
0.1940	23.70	10.02	33.72	53.86	-20.14	AVG	L2
0.2020	41.09	10.01	51.10	63.52	-12.42	QP	L2
0.2020	23.43	10.01	33.44	53.52	-20.08	AVG	L2
0.2300	39.36	10.01	49.37	62.45	-13.08	QP	L2
0.2300	23.75	10.01	33.76	52.45	-18.69	AVG	L2
0.2620	36.25	10.02	46.27	61.36	-15.09	QP	L2
0.2620	23.89	10.02	33.91	51.36	-17.45	AVG	L2
4.4299	36.30	10.29	46.59	56.00	-9.41	QP	L2
4.4299	17.92	10.29	28.21	46.00	-17.79	AVG	L2
29.8620	32.40	11.21	43.61	60.00	-16.39	QP	L2
29.8620	31.06	11.21	42.27	50.00	-7.73	AVG	L2

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
- 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
- 3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10 kHz; the IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9 kHz;
- 4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)



Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)

