	BUREAU VERITAS		
	RF Exposure Report		
Report No.:	SA200612D19		
FCC ID:	P27SCE5151CVZ		
Test Model:	SCE5151C-B261		
Series Model:	SCE5151C-B261xxxxxx (the 2nd x should be "blank" or "-", or A to Z; the first and the rest x could be 0 to 9, A to Z, "blank", or "-" or "/", for marketing purpose)		
Received Date:	Jun. 12, 2020		
Test Date:	Jun. 20 to Aug. 12, 2020		
Issued Date:	Aug. 13, 2020		
Applicant:	Sercomm Corp.		
Address:	8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C. (NanKang Software Park)		
Issued By:	: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Lin Kou Laboratories		
Lab Address:	: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan		
Test Location:	: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan		
FCC Registration /			
Designation Number:	/88550 / 1 00003		
	TAF Testing Laboratory 2021		
	copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted is report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this		

In this report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



Table of Contents

Relea	ase Control Record	. 3
1	Certificate of Conformity	. 4
2	RF Exposure	5
2.1	Limits For Maximum Permissible Exposure (MPE)	. 5
2.2	MPE Calculation Formula	. 5
2.3	Classification	. 5
	Antenna Gain	
2.5	Calculation Result of Maximum Conducted Power	5



Release Control Record

Issue No.	Description	Date Issued
SA200612D19	Original release.	Aug. 13, 2020



1 **Certificate of Conformity**

Product:	Bridgewater 5G mmWave Femto cell
Brand:	Verizon, Sercomm
Test Model:	SCE5151C-B261
Series Model:	SCE5151C-B261xxxxxx (the 2nd x should be "blank" or "-", or A to Z; the first and the rest x could be 0 to 9, A to Z, "blank", or "-" or "/", for marketing purpose)
Sample Status:	Engineering sample
Applicant:	Sercomm Corp.
Test Date:	Jun. 20 to Aug. 12, 2020
Standards:	FCC Part 2 (Section 2.1091)
	IEEE C95.3 -2002
References Test Guidance:	KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

elva Chen

Date: Aug. 13, 2020

Aug. 13, 2020

Date:

Celia Chen / Supervisor

Approved by :

Rex Lai / Associate Technical Manager



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f²)*	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$Pd = (Pout^{*}G) / (4^{*}pi^{*}r^{2})$

where

 $Pd = power density in mW/cm^2$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 72cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Frequency Band (MHz)	uency Band (MHz) Antenna Type		Antenna Gain (dBi)
27500~28350	27500~28350 Patch Array		22.5

Note: The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.5 Calculation Result of Maximum Conducted Power

Frequency Band	EIRP	Distance	Power Density	Limit
(MHz)	(dBm)	(cm)	(mW/cm ²)	(mW/cm²)
27500~28350	48.05	72	0.9798	1

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---